City of Coral Gables Planning and Zoning Staff Recommendation				
Applicant:	USRE Holdings, LLC			
Application:	Conditional Use Review of a Planned Area Development (PAD) and Mixed Use (MXD) Site Plan Review			
Property:	Columbus Center (1 Alhambra Plaza and 100 Alhambra Circle)			
Public Hearing - Dates/Time/ Location:	Planning and Zoning Board June 11, 2014, 6:00 – 9:00 p.m., City Commission Chambers, City Hall, 405 Biltmore Way, Coral Gables, Florida, 33134			

Application Request.

Review of a Planned Area Development (PAD) and mixed use site plan review for the project referred to as the "Columbus Center", as follows:

- An Ordinance of the City Commission of Coral Gables, Florida requesting review of a Planned Area Development (PAD) pursuant to Zoning Code Article 3, "Development Review", Division 5, "Planned Area Development (PAD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for severability, repealer, codification and an effective date. (Legal description on file at the City)
- 2. A Resolution of the City Commission of Coral Gables, Florida requesting mixed use site plan review pursuant to Zoning Code Article 4, "Zoning Districts", Division 2, "Overlay and Special Purpose Districts", Section 4-201, "Mixed Use District (MXD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for an effective date. (Legal description on file at the City)

PADs and mixed use site plans require review by the Planning and Zoning Board and City Commission. City Commission Review of a PAD requires Commission review at two (2) public hearings (via Ordinance). Approval of a mixed use site plan requires review at one (1) public hearing (via Resolution).

### Summary of Application.

USRE Holdings, LLC (hereinafter referred to as "Applicant"), has submitted an application (hereinafter referred to as the "Application") for review of a Planned Area Development (PAD) and mixed use site plan review for consideration at public hearings pursuant to and in accordance with the City of Coral Gables Zoning Code Planned Area Development (PAD) and Mixed Use District (MXD) provisions, and the Comprehensive Plan (CP) Mixed Use District (MXD) provisions. The Application package submitted by the Applicant is provided as Attachment A.

This property is located within the City's Central Business District (CBD), on the northwest corner of the intersection of Alhambra Plaza and Douglas Road. Minorca Avenue is the northern boundary of the CBD and borders the project site on the north. The existing Columbus Center development, which was constructed in 1990, is a 14 story commercial office building located at 1 Alhambra. The existing Columbus Center building is referred to as "Phase 1" of the PAD and within this Staff report. The existing Columbus Center building was approved "as-of-right" and did not require review at public hearings. However, prior to the approval of the project, the vacation of a portion of the public alleyway that bisected the block and the project site was necessary, and a substitute alleyway easement required as a condition of the approval of the vacation. That substitute alleyway easement was provided and currently exists along the northwest boundary of the property.

The Applicant has acquired the existing adjacent vacant parcel of land that is approximately 0.7 acres in size and located on the north side of the remaining public alleyway between the substitute alleyway easement and the historically designated La Palma Hotel to the west. The Applicant proposes to construct Columbus Center "Phase 2" on the existing vacant parcel. Phase 2 will encroach over the substitute alleyway easement provided as part of the existing Columbus Center development. Columbus Center Phase 2 will be a physically separate building from Columbus Center Phase 1, and will consist of an 18 story structure containing primarily multi-family residential units. Phase 2 will include 200 multi-family residential units, 3,400 sq. ft. of retail space, 2,060 sq. ft. of office space and 387 parking spaces. Phase 1, being the existing Columbus Center building, will remain essentially unchanged as a result of this proposal.

The Applicant requests that both Phase 1 and 2 (existing and proposed project) be reviewed as a single development, and has submitted Application for review of a Planned Area Development (PAD) and mixed use site plan review in order to allow the project to proceed as proposed. The Applicant has also indicated that a reduction in the required minimum nineteen (19) foot height of the substitute alleyway and minor reconfiguration are required to accommodate the proposed Columbus Phase 2 project, but that the location of the existing easement would remain the same.

The MXD site plan review is necessary for the existing commercial office building and the proposed primarily multi-family residential building to be reviewed as a mixed use project in their totality. The residential component would otherwise not be permitted. The proposed PAD is required to allow for: 1) the encroachment of Phase 2 onto the existing Columbus Center site; 2) two buildings on a single building/project site; 3) transfer of unused FAR (building square footage) from Columbus Center Phase 1

(existing building) to Columbus Center Phase 2 (proposed building); and, 4) provide relief from setback requirements that would otherwise be required. The Applicant is proposing to transfer approximately 148,000 sq. ft. from Phase 1 to Phase 2. The review of Phase 1 and Phase 2 as a single proposed project also allows for flexibility for shared open space and amenities between both phases of the project.



# Aerial with 45 degree Building Perspective (from Google Maps)

The property is bounded by Minorca Avenue (north), Alhambra Plaza (south), Douglas Road (east) and Alhambra Circle (west), as shown on the following location map and aerial photo:



#### Lot, Block and Section Location Map

Aerial



City of Coral Gables Planning Division

# Site Data and Project Timeline.

#### Site Data and Surrounding Uses

The following tables provide the subject property's designations and surrounding land uses:

Comprehensive Plan Map designation	"Commercial High-Rise Intensity"
Zoning Map designation	Commercial (C)
Within Central Business District	Yes
Within a designated Mixed-Use Overlay District (MXOD)	No
Mediterranean Architectural District (citywide)	Yes
Within Coral Gables Redevelopment Infill District (GRID)	Yes

#### **Existing Property Designations**

#### Surrounding Land Uses

Location	Existing Land Uses	CP Designations	Zoning Designations
North	Mid-rise mixed use	"Commercial Mid-Rise	Commercial (C) and
	building and 4 story	Intensity" and "Residential	Multi-Family 2 (MF2)
	multi-family building	Multi-Family Medium Density"	
South	Hyatt Regency Hotel	"Commercial High-Rise	Commercial (C)
	(mid and high-rise)	Intensity"	
East	City of Miami	City of Miami	City of Miami
West	Historic La Palma Hotel	"Commercial Mid-Rise	Commercial (C)
	and high-rise 121	Intensity" and "Commercial	
	Alhambra Tower	Mid-Rise Intensity"	

There are no changes proposed to the property's existing land use or zoning designations, as illustrated in the following maps:





### City Review Timeline

The proposal has undergone the following City reviews:

Type of Review	Date	Result of Review
Development Review Committee	08.30.13	Comments provided to Applicant
Board of Architects	05.08.14	Preliminary approval and approval of Mediterranean architectural bonuses
Planning and Zoning Board	06.11.14	TBD
City Commission (1 <sup>st</sup> reading – receipt of TDRs)	07.22.14	TBD
City Commission (2 <sup>nd</sup> reading – MXD site plan and receipt of TDRs)	TBD	ТВО

#### Proposed Mixed Use Project.

#### Legislative History

The commercial office project referred to as the "Columbus Center" (1 Alhambra Plaza) was approved in 1990. The project was approved "as-of-right" and did not require review at public hearings. However, prior to the approval of the project, the vacation of a portion of the public alleyway that bisected the block was required. The approval was conditioned on the provision of a substitute easement to serve as

an alleyway and provide for circulation and public access, and including conditions of approval that were required to be satisfied before the vacation became effective. The following ordinance vacating the public alleyway was approved (a copy of the ordinance is provided as Attachment B):

1. Ordinance No. 2854 (adopted 06.27.1989) – Approved vacation conditioned on the provision of a substitute alleyway easement and conditions of approval.

### Applicant's Proposal – PAD and Mixed Use Project

The Application package submitted by the Applicant includes the following (see Attachment A):

- 1) Statement of Use/Letter of Intent;
- 2) Planning Division Application;
- 3) Photographs of Property;
- 4) Plat and Survey of Property;
- 5) Aerial Photographs;
- 6) 3-D Perspective Views;
- 7) Architectural Drawings

(including City's Preliminary Zoning Analysis and Applicant's responses);

- 8) Background Information;
- 9) Concurrency Information;
- 10) Traffic Study.

#### Mediterranean Architectural Style

The proposed project received preliminary approval and approval of Mediterranean architectural bonuses from the Board of Architects on 05.08.14.

A Preliminary Zoning Analysis (PZA) was prepared by Planning and Zoning Division Staff and that PZA and the Applicant's responses are included in the Application package provided as Attachment A. A summary of the project is provided in the Applicant's Zoning Information Sheet submitted with the Application and is presented in the following tables.

#### Site plan information:

		Existing	Proposed	
Туре	Permitted	(Phase 1)	(Phase 2)	Total Project
Total site area	145,225 sq. ft.	112,945 sq. ft.	32,280 sq. ft.	145,225 sq. ft.
	(3.3 acres)	(2.6 acres)	(0.7 acres)	(3.3 acres)
3.5 FAR x total site area (with		395,307 sq. ft.	112,980 sq. ft.	508,287sq. ft.
Mediterranean bonuses)				
Total square footage of		247,392 sq. ft.	232,968 sq. ft.	480,360sq. ft.
proposed project		(2.2 FAR)	(7.2 FAR)	(3.3 FAR)
Retail square footage		0 sq. ft.	3,400 sq. ft.	3,400 sq. ft.

#### Staff Recommendation

Columbus Center – PAD and MXD Site Plan Review

		Existing	Proposed	
Туре	Permitted	(Phase 1)	(Phase 2)	Total Project
Office square footage		247,392 sq. ft.	2,060 sq. ft.	249,452 sq. ft.
Residential units	No limitation	N/A	200 units	200 units
	on units per		(268 units per	(61 units per
	acre within		acre)	acre)
	CBD			
Building height (with	Up to 190'-6"	161'-10"	190'-0"	190'-0"
Mediterranean bonuses)				
Number of floors	No limitation	Existing	Complies	Complies
	up to 150'-0",			
	max. 3 floors			
	above 150'-0"			
Residential unit mix:				
Studio				12 units
One bedroom	54 units			
Two bedroom	118 units			
Three bedroom				36 units

Setbacks (Phase 2):

Туре	Required*	Proposed (Phase 2)
Front (Alhambra Circle)	0 ft.	Complies
Interior Street (Minorca Avenue)	0 ft.	Complies
Interior side	0 ft.	Complies
Rear (abutting public alleyway)	0 ft.	Complies

\* Setback relief may be awarded for MXD projects approved for Mediterranean style design bonuses.

Landscaping (Phase 1):

Location	Required	Total Project
Landscape open space (on-site)	7,771 sq. ft.	9,250 sq. ft.
– minimum 20% of property area required for a PAD		
Landscape open space (rights-of-way)	Must meet City	Required to
	Streetscape Master	comply with
	Plan requirements	Zoning Code
		requirements at
		time of permit

#### Staff Recommendation

#### Parking:

On-site Parking					
Uses	Required	Existing (Phase 1)	Proposed (Phase 2)	Total Project	
Retail	14 spaces	0 spaces	14 spaces	14 spaces	
Offices	836 spaces	859 spaces	7 spaces	866 spaces	
Residential units	366 spaces	0 spaces	366 spaces	366 spaces	
Total off-street parking spaces	1,216 spaces	859 spaces	387 spaces	1,246 spaces	
Additional off-street parking provided				30 spaces	

There is no net loss of any on-street parking resulting from this project according to the site plan submitted. However, if any loss of on-street parking that occurs due to the construction of this project that has not been anticipated, the Applicant, property owner(s), its successors or assigns, shall be required to reimburse those costs in accordance with City requirements.

The Applicant's proposed site plans, ground floor plan, public realm/landscape plan, and building elevations are provided on the following pages:



**Overall Site Plan** 



#### **Overall Ground Floor Plan**



#### Pedestrial Circulation (Phase I)

#### **North Elevation**





#### South Elevation

# Findings of Fact.

This section of the Report presents City Staff's evaluation of the Application and Findings of Fact. The City's responsibility is to review the Application for consistency with the City's Comprehensive Plan (CP) Goals, Objectives and Policies, compliance with the Zoning Code and other applicable portions of the City Code.

#### Findings of Fact- Planned Area Development

Planned Area Development (PAD) Purpose and Objectives

The stated purpose of the Zoning Code's PAD provisions is to encourage the construction of Planned Area Developments (PAD) by providing greater opportunity for construction of quality development on tracts and/or parcels of land through the use of flexible guidelines which allow the integration of a variety of land uses and densities in one development. Zoning Code Section 3-501 states that a proposed PAD project must comply with the following:

- 1. Allow opportunities for more creative and imaginative development than generally possible under the strict applications of these regulations so that new development may provide substantial additional public benefit.
- 2. Encourage enhancement and preservation of lands which are unique or of outstanding scenic, environmental, cultural and historical significance.
- 3. Provide an alternative for more efficient use and, safer networks of streets, promoting greater opportunities for public and private open space, and recreation areas and enforce and maintain neighborhood and community identity.
- 4. Encourage harmonious and coordinated development of the site, through the use of a variety of architectural solutions to promote Mediterranean architectural attributes, promoting variations in bulk and massing, preservation of natural features, scenic areas, community facilities, reduce land utilization for roads and separate pedestrian and vehicular circulation systems and promote urban design amenities.
- 5. Require the application of professional planning and design techniques to achieve overall coordinated development eliminating the negative impacts of unplanned and piecemeal developments likely to result from rigid adherence to the standards found elsewhere in these regulations.

*Staff comments:* The Applicant's plans comply with the purpose and applicability for a PAD set out in Zoning Code Section 3-501 as specified in the evaluation presented in Staff's report and the following findings of fact. The requirements and performance standards set out in the Zoning Code for a PAD have been evaluated and are provided in the Zoning Analysis prepared by the Planning Division (see Attachment C). That analysis and compliance with the purpose and applicability for a PAD indicate that the proposal satisfies the Code's requirements for a PAD project.

Section 3-503 of the Zoning Code states the required findings for a proposed PAD project is as follows:

The Planning and Zoning Board shall recommend to the City Commission the approval, approval with modifications, or denial of the plan for the proposed PAD and shall include not only conclusions but also findings

of fact related to the specific proposal and shall set forth with particularity in what respects the proposal would or would not be in the public interest. These findings shall include, but shall not be limited to the following:

A. In what respects the proposed plan is or is not consistent with the stated purpose and intent of the PAD regulations.

*Staff comments:* The Applicant's plans comply with the purpose and applicability for a PAD set out in Zoning Code Section 3-501 as specified in the evaluation presented in Staff's report and the following findings of fact. The requirements and performance standards set out in Zoning Code for a PAD have been evaluated and are provided in the Preliminary Zoning Analysis prepared by the Planning and Zoning Division (see Attachment C). That analysis and compliance with the purpose and applicability for a PAD indicate that the proposal satisfies the Code's requirements for a PAD project.

B. The extent to which the proposed plan departs from the zoning and subdivision regulations otherwise applicable to the subject property, including but not limited to density, size, area, bulk and use, and the reasons why such departures are or are not deemed to be in the public interest.

*Staff comments:* Mixed use site plan review is necessary for the existing commercial office building and the proposed primarily multi-family residential building to be reviewed as a mixed use project in their totality. The residential component would otherwise not be permitted. The proposed PAD is required to allow for the encroachment of Phase 2 onto the existing Columbus Center site, allow two buildings on a single building/project site, allow for the transfer of unused FAR (building square footage) from Columbus Center Phase 1 (existing building) to Columbus Center Phase 2 (proposed building) and to provide relief from setback requirements that would otherwise be required. The proposed mixed use project is similar and consistent with previous mixed use projects approved within the CBD and along the North Ponce corridor. Adding residential dwelling units into the area will provide additional economic support for the surrounding commercial and retail uses. This development is consistent with the underlying zoning and subdivision regulations and it will not adversely or unreasonably affect the use of other adjoining, adjacent and contiguous properties in the area.

C. The extent to which the proposed plan meets the requirements and standards of the PAD regulations.

*Staff comments:* A Zoning Analysis was prepared by Planning Division Staff to determine compliance with applicable provisions and requirements within the Zoning Code for a proposed PAD and mixed use (MXD) site plan. The analysis indicates that the proposed project meets the applicable provisions and requirements within the Zoning Code, and is included Attachment C.

D. The physical design of the proposed PAD and the manner in which said design does or does not make adequate provision for public services, provide adequate control over vehicular traffic, provide for and protect designated common open areas, and further the amenities of light and air, recreation and visual enjoyment.

*Staff comments:* All vehicular parking for the project and service access is within the confines of the building, and is physically separated from pedestrian circulation around the perimeter of the project.

The project's ground floor pedestrian amenities enhance the redevelopment of the area. The project will be required to underground all overhead utilities. In addition, the proposal includes public realm improvements (i.e., under and over story landscaping, pedestrian benches, bicycle racks, waste receptacles, etc.) that will provide amenities for pedestrians.

*E.* The compatibility of the proposed PAD with the adjacent properties and neighborhood as well as the current neighborhood context including current uses.

*Staff comments:* The planned redevelopment of this property as a mixed use project is compatible and complies with the intent of the Zoning Code mixed use and PAD requirements and performance standards. The proposed project height and massing is consistent with surrounding CBD properties, and potential future height of the mid-rise multi-family apartment properties located to the north of the project site. The proposal is consistent with the property's underlying "Commercial, High-Rise Intensity" land use and Commercial (C) zoning designations.

*F.* The desirability of the proposed PAD to physical development of the entire community.

*Staff comments:* The redevelopment of this property as a mixed use project fulfills the objective of the City to attract mixed use developments to the CBD and the creation of a pedestrian oriented urban environment. The introduction of residential dwelling units will provide the economic support for the surrounding commercial and retail uses. The subject property is located within the CBD which allows and encourages the development of mixed use projects. The project is similar and complimentary to existing mixed use projects in the CBD. This is the second phase of an existing high-rise commercial development, and will provide a residential component which was not included in the first phase of the development.

*G.* The conformity of the proposed PAD with the goals and objectives and Future Land Use Maps of the City of Coral Gables Comprehensive Plan.

*Staff comments:* The property's existing "Commercial High-Rise Intensity" land use designation is the appropriate designation for the proposed high-rise mixed use project. As concluded in this report, this Application is "consistent" with the CP's Goals, Objectives and Policies with the recommended conditions of approval and site plan provisions incorporated by the Applicant which address the City's objectives for encouraging mixed use development in the Central Business District (CBD).

# Findings of Fact- Mixed Use Site Plan

#### Mixed Use District (MXD) Purpose and Objectives

The current MXD Zoning Code provisions were adopted by Ordinance No. 2004-04 on 01.13.04 and subsequently revised and readopted as a part of the comprehensive Zoning Code rewrite. The MXD was created as a "voluntary" overlay zoning designation that is supplemental to the underlying zoning designations and other applicable City regulations. Property owners who choose to develop under these regulations and secure site plan approval are regulated by the underlying zoning district, Zoning Code and Comprehensive Plan.

Section 4-201 of the Zoning Code states the purpose of the MXD district is as follows:

- 1. Provide the method by which tracts of land may be developed as a planned unified project rather than on a lot-by-lot basis as provided for in the City's other regulations.
- 2. Provide for residential uses at higher densities in exchange for public realm improvements.
- 3. Provide maximum design freedom by permitting property owners an opportunity to more fully utilize the physical characteristics of the site through modified development regulations and the planned mixing of uses.
- 4. Require that property within the District will be developed through a unified design providing continuity among the various elements causing a better environment.
- 5. Create a diversity of uses within walking distance, including but not limited to: residential, offices, workplaces, neighborhood commercial, and public open spaces.
- 6. By organizing appropriate building densities, public transit will be further strengthened as an alternative to the use of private vehicles.
- 7. Provide a strong emphasis on aesthetics and architectural design through the use of the regulations and the planned mixing of uses to establish identity, diversity and focus to promote a pedestrian friendly environment.

*Staff comments:* The compliance of the Applicant's plans with the MXD requirements and performance standards set out in the Zoning Code have been evaluated and is provided in the Zoning Analysis prepared by the Planning Division included with the Application package provided as Attachment C. That analysis and the Applicant's responses indicate that the proposal satisfies the Code's requirements for a mixed use project.

#### Site Plan Review Criteria

Section 3-406 of the Zoning Code states that the Planning and Zoning Board shall review applications for conditional use (site plan review) and provide a recommendation to the City Commission whether they should grant approval, grant approval subject to specific conditions or deny the application. The Planning and Zoning Division, Planning and Zoning Board and City Commission may recommend such conditions to an approval that are necessary to ensure compliance with the standards set forth in Section 3-408.

The Applicant's plans have been compared to the site plan review criteria set out in Zoning Code Section 3-408 as follows:

A. "The proposed conditional use is consistent with and furthers the goals, objectives and policies of the Comprehensive Land Use Plan and furthers the purposes of these regulations and other City ordinances and actions designed to implement the Plan."

*Staff comments:* As concluded in this report, this Application is "consistent" with the CP's Goals, Objectives and Policies with the recommended conditions of approval and site plan provisions incorporated by the Applicant which address the City's objectives for encouraging mixed use development in the Central Business District (CBD).

*B. "The available use to which the property may be put is appropriate to the property that is subject to the proposed conditional use and compatible with existing and planned uses in the area".* 

*Staff comments:* The subject property is located within the CBD which allows and encourages the development of mixed use projects. The project is similar and complimentary to existing mixed use projects in the CBD. This is the second phase of an existing high-rise commercial development, and will provide a residential component which was not included in the first phase of the development.

*C. "The proposed conditional use does not conflict with the needs and character of the neighborhood and the City".* 

*Staff comments:* The redevelopment of this property as a mixed use project fulfills the objective of the City to attract mixed use developments to the CBD and the creation of a pedestrian oriented urban environment. The introduction of residential dwelling units will provide the economic support for the surrounding commercial and retail uses. The ground floor pedestrian amenities enhance the existing uses within the CBD. The project is required to underground all overhead utilities. In addition, the proposal includes public realm improvements (i.e., under and over story landscaping, pedestrian benches, bicycle racks, waste receptacle, etc.) that will provide amenities for pedestrians.

D. "The proposed conditional use will not adversely or unreasonably affect the use of other property in the area."

*Staff comments:* The proposed mixed use project is similar and consistent with previous mixed use projects approved within the CBD and along the North Ponce corridor. Adding residential dwelling units into the area will provide additional economic support for the surrounding commercial and retail uses. This development is consistent with the underlying CP designation and it will not adversely or unreasonably affect the use of other adjoining, adjacent and contiguous properties in the area.

E. "The proposed use is compatible with the nature, condition and development of adjacent uses, buildings and structures and will not adversely affect the adjacent uses, buildings or structures".

*Staff comments:* The planned redevelopment of this property as a mixed use project is compatible and complies with the intent of the Zoning Code Mixed Use design regulations and Comprehensive Plan Mixed Use District (MXD) provisions. The proposed project height and massing is consistent with surrounding CBD properties, and potential future height of the mid-rise multi-family apartment properties located to the north of the project site. The proposal is consistent with the property's underlying "Commercial, High-Rise Intensity" land use and Commercial (C) zoning designations.

*F. "The parcel proposed for development is adequate in size and shape to accommodate all development features."* 

*Staff comments:* The subject property is larger than the minimum 20,000 square foot size required for an individual mixed use project (not located within a designated MXD Overlay District). The

Zoning Analysis prepared by the Planning Division indicating compliance with applicable Zoning Code PAD and mixed use provisions is provided as Attachment C. That analysis and the Applicant's responses indicate that the proposal satisfies the Code's requirements for a mixed use project.

G. "The nature of the proposed development is not detrimental to the health, safety and general welfare of the community."

*Staff comments:* The project site is surrounded by properties with either commercial or multi-family zoning designations, all of which allow for mid-rise development (70'-0" as-of-right, 97'-0" with Mediterranean bonuses) or high-rise development (150'-0" as-of-right, 190'-6" with Mediterranean bonuses). The height of the project is consistent with the property's underlying "Commercial, High-Rise Intensity" land use designation. The proposed project is consistent with the stated goals and objectives for mixed use redevelopment in the CBD. The redevelopment of this property as a mixed use project fulfills the objective of the City to attract mixed use developments to the CBD and the creation of a pedestrian oriented urban environment. The project's ground floor pedestrian amenities enhance the existing and future uses surrounding the property and within the CBD.

*H.* "The design of the proposed driveways, circulation patterns and parking is well defined to promote vehicular and pedestrian circulation."

*Staff comments:* All vehicular parking for the project and service access is within the confines of the building, and is physically separated from pedestrian circulation around the perimeter of the project. The project's ground floor pedestrian amenities enhance the redevelopment of the area. The project will be required to underground all overhead utilities. In addition, the proposal includes public realm improvements (i.e., under and over story landscaping, pedestrian benches, bicycle racks, waste receptacles, etc.) that will provide amenities for pedestrians.

I. "The proposed conditional use satisfies the concurrency standards of Article 3, Division 13 and will not adversely burden public facilities, including the traffic-carrying capacities of streets, in an unreasonable or disproportionate manner".

*Staff comments:* The proposed project was reviewed for concurrency, and it was found that there is adequate infrastructure including water, sewer, open space, parks and recreation facilities available to support the project.

# Traffic Study

This property falls within the Gables Redevelopment Infill District (GRID). The City's GRID allows development within its boundaries to move forward regardless of a roadway's level of service (LOS). The City does, however, require all developments within the GRID that increase intensity/density to complete a Traffic Impact Analysis report and provide appropriate traffic mitigation to help offset the impacts.

The Public Works Department and their consultant reviewed the Applicant's proposed plans and Traffic Impact Analysis (TIA), dated September 2013 and revised May 2014, which was submitted with the

application. The Public Works Department provided the following comments, which have been included as recommended conditions of approval in this Staff report:

- 1. Prior to the issuance of the Building permit, all outstanding Traffic Study issues as identified by the Public Works Department and City's traffic consultant shall be satisfactorily resolved, subject to review and approval by the Public Works Director.
- 2. Evaluate the feasibility of having one paseo crossing the public alley (please consider the west side of the drop off access).
- 3. Ordinance No. 2854 must be amended to comply with the vertical clearance provided on the site plan.
- 4. Commission approval required for a special treatment sidewalk, decorative pavers, landscaping, irrigation, street lighting, landscaping lighting and any other encroachments into, onto, under and over the right of way. The above encroachments must be approved by City resolution and a Hold Harmless agreement must be executed.
- 5. Provide landscaping public realm and streetscape improvements in accordance with the City of Coral Gables streetscape master plan.

#### Concurrency Management

This project has been reviewed for compliance with the City's Concurrency Management program. The Concurrency Impact Statement (CIS) for the project indicates that there is adequate infrastructure available to support the project. The CIS is on file with the City and available for review.

#### Public School Concurrency Review

Pursuant to the Educational Element of the City's Comprehensive Plan, Article 3, Division 13 of the Zoning Code, and State of Florida growth management statute requirements, public school concurrency review is required prior to final Board of Architects review for all applications for development approval in order to identify and address the impacts of new residential development on the levels of service for public school facilities. For a residential development to secure a building permit, adequate school capacity must be available or scheduled to be under actual construction within three years of the final approval. If capacity is not available, the developer, school district and affected local government must work together to find a way to provide capacity before the development can proceed. A letter was received from the Miami-Dade County Public School Board dated 03.14.14 stating the proposed project had been reviewed and that the required Level of Service (LOS) standard had been met at all three school levels and that school capacity has been reserved for a period of one year. A copy of that letter is on file with the City and available for review.

#### Art in Public Places Program

The plans submitted with the Application package indicate the proposed location for public art intended to satisfy the City's Art in Public Places program. The proposed location is in the area of the existing urban plaza constructed as part of the existing Columbus center building. However, no proposed art work has been submitted or approved. The Applicant must comply with all City requirements for Art in

Public Places, which will include having the proposed artist and concept reviewed by the Arts Advisory Panel and Cultural Development Board, and Board of Architects approval before being submitted to the City Commission. This requirement has been included as a recommended condition of approval.

# Consistency Evaluation of the Comprehensive Plan (CP) Goals, Objectives and Policies

This section provides a detailed analysis of the CP providing a basis of consistency, and finds the following CP Goals, Objectives and Policies are consistent:

Ref.		Staff
No.	CP Goal, Objective and Policy	Review
1.	<b>Goal FLU-1.</b> Protect, strengthen, and enhance the City as a vibrant community ensuring that its neighborhoods, business opportunities, shopping, employment centers, cultural activities, historic value, desirable housing, open spaces, and natural resources make the City a very desirable place to work, live and play.	Complies
2.	<b>Objective FLU-1.1.</b> Preserve Coral Gables as a "placemaker" where the balance of existing and future uses is maintained to achieve a high quality living environment by encouraging compatible land uses, restoring and protecting the natural environment, and providing facilities and services which meet or exceed the minimum Level of Service (LOS) standards and meet the social and economic needs of the community through the Comprehensive Plan and Future Land Use Classifications and Map (see FLU-1: Future Land Use Map).	Complies
3.	<b>Objective FLU-1.2.</b> Efforts shall continue to be made to control blighting influences, and redevelopment shall continue to be encouraged in areas experiencing deterioration.	Complies
4.	<b>Policy FLU-1.3.3.</b> Non-residential uses designated in the Comprehensive Plan which cause significant noise, light, glare, odor, vibration, dust, hazardous conditions or industrial traffic, shall provide buffering such as landscaping, walls and setbacks, when located adjacent to or across the street from incompatible uses such as residential uses.	Complies
5.	<b>Policy FLU-1.1.5.</b> Mixed-Use land use classifications (Land use descriptions provided herein are general descriptions, refer to underlying/assigned Zoning Classification for the list of permitted uses) as presented in Table FLU-4., entitled "Mixed-Use land use".	Complies
6.	<b>Policy FLU-1.7.1.</b> Encourage effective and proper high quality development of the Central Business District, the Industrial District and the University of Miami employment centers which offer potential for local employment in proximity to protected residential neighborhoods.	Complies
7.	<ul> <li>Policy FLU-1.7.2. The City shall continue to enforce the Mediterranean architectural provisions for providing incentives for infill and redevelopment that address, at a minimum, the impact on the following issues:</li> <li>Surrounding land use compatibility.</li> </ul>	Complies

Ref.		Staff
No.	CP Goal, Objective and Policy	Review
	Historic resources.	
	Neighborhood Identity.	
	Public Facilities including roadways.	
	Intensity/Density of the use.	
	Access and parking.	
	Landscaping and buffering.	
8.	Policy FLU-1.9.1. Encourage balanced mixed use development in the central business	Complies
	district and adjoining commercial areas to promote pedestrian activity and provide	
	for specific commitments to design excellence and long term economic and cultural	
	vitality.	
9.	<b>Objective FLU-1.11.</b> Maintain a pattern of overall low density residential use with	Complies
	limited medium and high density residential uses in appropriate areas to preserve the	
	low intensity and high quality character of the residential neighborhoods.	
10.	Policy FLU-1.11.1. Maintain and enforce effective development and maintenance	Complies
	regulations through site plan review, code enforcement, and design review boards	
	and committees.	
11.	<b>Goal DES-1.</b> Maintain the City as a livable city, attractive in its setting and dynamic in	Complies
	its urban character.	
12.	<b>Objective DES-1.1.</b> Preserve and promote high quality, creative design and site	Complies
	planning that is compatible with the City's architectural heritage, surrounding	
	development, public spaces and open spaces.	
13.	<b>Policy DES-1.1.3.</b> Ensure that the design of buildings and spaces in historic areas of	Complies
	the City complements, is compatible with, does not attempt to imitate and does not	
	undermine the City's historic character.	
14.	<b>Policy DES-1.1.5.</b> Promote the development of property that achieves unified civic	Complies
	design and proper relationship between the uses of land both within zoning districts	
	and surrounding districts, by regulating, limiting and determining the location, height,	
	density, bulk and massing, access to light and air, area of yards, open space,	
15.	vegetation and use of buildings, signs and other structures. <b>Policy DES-1.1.6.</b> Maintain the character of the residential and nonresidential	Complies
15.	districts, and their peculiar suitability for particular uses.	Complies
16.	<b>Policy DES-1.2.1.</b> Continue the award of development bonuses and/or other	Complies
10.	incentives to promote Coral Gables Mediterranean design character providing for but	Complies
	not limited to the following: creative use of architecture to promote public realm	
	improvements and pedestrian amenities; provide a visual linkage between	
	contemporary architecture and the existing and new architectural fabric; encourage	
	landmark opportunities; and creation of public open spaces.	
17.	<b>Policy DES-1.2.2.</b> Require that private development and public projects are designed	Complies
±7.	consistent with the City's unique and historical Mediterranean appearance in balance	
	with contemporary architecture.	
18.	<b>Objective DES-1.3.</b> Encourage high quality signage that is attractive, appropriately	Complies
10.	located and scaled, and balances visibility with aesthetic needs.	Complics

Ref.		Staff
No.	CP Goal, Objective and Policy	Review
19.	<b>Objective HOU-1.5.</b> Support the infill of housing in association with mixed use development.	Complies
20.	<b>Policy HOU-1.5.2.</b> Encourage residential mixed use as a means of increasing housing supply within the Downtown/Central Business District/Mixed Use Development Overlay Area, thereby promoting increase in commercial and retail activity, increased use of transit, reduction of auto dependency, in association with minimizing visual and physical impacts of nearby lower density areas.	Complies
21.	<b>Objective MOB-1.1.</b> Provide solutions to mitigate and reduce the impacts of vehicular traffic on the environment, and residential streets in particular with emphasis on alternatives to the automobile including walking, bicycling, public transit and vehicle pooling.	Complies
22.	<b>Policy MOB-1.1.1.</b> Promote mixed use development to provide housing and commercial services near employment centers, thereby reducing the need to drive.	Complies
23.	<b>Policy MOB-1.1.2.</b> Encourage land use decisions that encourage infill, redevelopment and reuse of vacant or underutilized parcels that support walking, bicycling and public transit use.	Complies
24.	<b>Policy MOB-1.1.3.</b> Locate higher density development along transit corridors and near multimodal stations.	Complies
25.	<b>Policy MOB-1.1.5.</b> Improve amenities within public spaces, streets, alleys and parks to include the following improvements: seating; art; architectural elements (at street level); lighting; bicycle parking; street trees; improved pedestrian crossing with bulbouts, small curb radii, on-street parking along sidewalks, pedestrian paths and bicycle paths to encourage walking and cycling with the intent of enhancing the feeling of safety.	Complies
26.	<b>Policy MOB-1.1.8.</b> Protect residential areas from parking impacts of nearby nonresidential uses and businesses and discourage parking facilities that intrude, impact and increase traffic into adjacent residential areas.	Complies
27.	<b>Policy MOB-2.7.1.</b> The City shall, via the review of development projects and city transportation improvement projects, conserve and protect the character and livability of all residential neighborhoods by preventing the intrusion of through vehicles on local and collector streets. The City shall discourage through traffic in neighborhoods and may incorporate traffic management and calming measures including, but not limited to, signage, landscape design, traffic calming devices and roadway design.	Complies
28.	<ul> <li>Policy MOB-2.8.1. The City shall continue implementation and further strengthen the City's existing land development regulations requiring the placement of landscaping within rights-of-way to complete the following:</li> <li>Promote expansion of the City's existing tree canopy.</li> <li>Provide screening of potentially objectionable uses.</li> <li>Serve as visual and sound buffers.</li> <li>Provide a comfortable environment for pedestrian walking (walkability)/activities.</li> <li>Improve the visual attractiveness of the urban and residential areas.</li> </ul>	Complies

Ref.		Staff
No.	CP Goal, Objective and Policy	Review
29.	Policy MOB-2.8.2. The City in its development of the downtown and and/or central	Complies
	business district shall promote the installation of landscaping within the rights-of-way	
	and private properties since the urban fabric will be transformed into a significant	
	urban center as build-out continues pursuant to the established Comprehensive Plan.	

*Staff Comments:* Staff has determined the Application is "consistent" with the CP's Goals, Objectives and Policies identified herein. Compliance is achieved subject to the conditions of approval recommended by Staff and satisfaction of all applicable PAD and MXD Zoning Code and Comprehensive Plan requirements.

# Public Notification and Comments.

The Applicant completed the mandatory neighborhood meeting on 05.28.14 with notification to all property owners within 1,000 feet of the property boundary. The Zoning Code requires courtesy notification be provided to all property owners within 1,000 feet of the MXD project boundary (see below map). The notice identifies the application filed, proposed public hearing dates/times, opportunity to submit comments and location where the application file can be reviewed. A total of 1,181 notices were mailed. Public comments received shall be provided to the Board at the public hearing. A copy of the legal advertisement and courtesy notice are provided as Attachments D and E.

#### **Courtesy Notification Radius Map**



The following has been completed to solicit input and provide notice of the application:

#### **Public Notice**

Туре	Date
Applicant neighborhood meeting	05.28.14
Courtesy notification - 1,000 feet of the property	05.30.14
Posting of property	05.30.14
Legal advertisement	05.30.14
Posted agenda on City web page/City Hall	06.06.14
Posted Staff report on City web page	06.06.14

#### Staff Recommendation and Conditions of Approval.

The Planning Division based upon the complete Findings of Fact contained within this Report recommends **approval** of the following with the conditions of approval as specified herein:

- An Ordinance of the City Commission of Coral Gables, Florida requesting review of a Planned Area Development (PAD) pursuant to Zoning Code Article 3, "Development Review", Division 5, "Planned Area Development (PAD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for severability, repealer, codification, and an effective date. (Legal description on file at the City)
- 2. A Resolution of the City Commission of Coral Gables, Florida requesting mixed use site plan review pursuant to Zoning Code Article 4, "Zoning Districts", Division 2, "Overlay and Special Purpose Districts", Section 4-201, "Mixed Use District (MXD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for an effective date. (Legal description on file at the City)

#### Summary of the Basis for Approval

Consistency with the Comprehensive Plan Goals, Objective and Polices. Staff's support of the Application for PAD and mixed use site plan review is based on compliance with the Comprehensive Plan (CP) Goals, Objectives and Policies, Zoning Code and other applicable Codes as enumerated in the complete Findings of Fact presented within this Staff Report.

#### Conditions of Approval

In furtherance of the Comprehensive Plan's Goals, Objectives and Policies, Zoning Code and other applicable City provisions, the recommendation for approval of the PAD and mixed use project referred to as "Columbus Center" is subject to all of the following conditions of approval:

- 1. Application/supporting documentation. Construction of the proposed project shall be in substantial conformance with the following:
  - a. Applicant's Submittal Package dated 06.11.14 prepared by Behar-Font Partners, P.A..
  - b. Traffic Impact Analysis, dated September 2013 and revised May 2014 prepared by Kimley-Horn and Associates, Inc.
  - c. Initial Application submittal as amended via the City review process and all representations proffered by the Applicant's representatives as a part of the review of the Application at public hearings.
- 2. Restrictive covenant. Within 30 days of approval, the property owner, its successors or assigns shall submit a draft restrictive covenant for City Attorney review/approval outlining all conditions of approval as approved by the City Commission. Failure to submit the covenant within the specified

time frame shall render the approval void unless said time frame for submittal of the covenant is extended by the City Attorney after good cause as to why the time frame should be extended.

- 3. Prior to the issuance of a City Building Permit for the project, the Applicant, property owner(s), its successors or assigns, shall satisfy the following conditions:
  - a. All outstanding Traffic Study issues as identified by the Public Works Department and City's traffic consultant shall be satisfactorily resolved, subject to review and approval by the Director of Public Works.
  - b. Evaluate the feasibility of having one paseo crossing the public alley (prefer west side of the drop off access), subject to review and approval by the Director of Public Works.
  - c. Amend Ordinance No. 2854 to comply with the vertical clearance provided on the site plan, be subject to review and approval by the Fire Chief and Directors of Public Works and Public Service.
  - d. Commission approval required for a special treatment sidewalk, decorative pavers, landscaping, irrigation, street lighting, landscaping lighting and any other encroachments into, onto, under and over the right of way. The above encroachments must be approved by City resolution and a Hold Harmless agreement must be executed.
  - e. Submit plans providing landscaping, public realm and streetscape improvements in accordance with the City of Coral Gables streetscape master plan, subject to review and approval by the Directors of Public Works, Public Service and Planning and Zoning.
  - f. Construction information/contact. Provide written notice to all properties within five hundred (500) feet of the Columbus Center Phase 2 project (100 Alhambra Circle), providing a specific liaison/contact person for the project including the contact name, contact telephone number and email, to allow communication between adjacent neighbors or interested parties of construction activities, project status, potential concerns, etc.
- 4. Written notice. Provide a minimum of seventy-two (72) hour written notice to all properties within five hundred (500) feet of the Columbus Center Phase 2 project (100 Alhambra Circle) project boundaries of any proposed partial street/alley closures as a result of the project's construction activity. Complete street/alley closure shall be prohibited.
- 5. The Applicant may be permitted to re-configure the substitute alleyway required by Ordinance No. 2854, but the location of the existing easement shall remain the same. Any re-configuration of the substitute alleyway shall be subject to review and approval by the Fire Chief and Directors of Public Works and Public Service.
- 6. Prior to the issuance of a Certificate of Occupancy (CO) for the project, the Applicant, property owner, its successors or assigns shall complete the following:
  - a. Comply with all City requirements for Art in Public Places, which will include having the proposed artist and concept for the redesign of the existing plaza as a civic space with public art to be reviewed by the Arts Advisory Panel and Cultural Development Board, and Board of Architects approval before being submitted to the City Commission. The Applicant's compliance with all requirements of the Art in Public Places program shall be coordinated by the Director of Economic Sustainability.
  - b. Right-of-way and public realm improvements. Installation of all right-of-way improvements and all landscaping, public realm and streetscape improvements identified on the Applicant's approved plans, subject to review and approval by the Directors of Public Works, Public Service and Planning and Zoning. Any changes to and departures from the right-of-way and public realm improvements identified on the Applicant's approved plans and associated detail plans and

specifications via the permitting process shall be subject to review and approval by Directors of Public Works, Public Service, Planning and Parking.

b. Undergrounding of overhead utilities. In accordance with Zoning Code Article 4 "Zoning Districts", more specifically, Section 4-201, "Mixed use District (MXD)," and Article 4, "Zoning Districts," Table 1, sub-section L, "Utilities", the Applicant shall submit all necessary plans and documents, and shall complete the undergrounding of all overhead utilities along all public rights-of-way surrounding and abutting the project boundary, subject to review and approval by the Directors of Public Works, Public Service and Planning and Zoning.

#### Attachments.

- A. Applicant's Submittal Package.
- B. Ordinance No. 2854.
- C. PAD and mixed use (MXD) Zoning Analysis prepared by Planning Division dated 04.18.14, and revised on 05.30.14, evaluating compliance with Zoning Code PAD and mixed use provisions.
- D. 05.30.14 Legal notice published.
- E. 05.30.14 Courtesy notice mailed to all property owners within 1,000 feet of the project boundary.

Please visit the City's webpage at <u>www.coralgables.com</u> to view all Application plans and materials, notices, applicable public comments, minutes, etc. The complete Application and all background information also is on file and available for examination during business hours at the Planning Division, 427 Biltmore Way, Suite 201, Coral Gables, Florida, 33134.

Respectfully submitted,

Ramon Trias Director of Planning and Zoning City of Coral Gables, Florida



PLANNING AND ZONING BOARD JUNE 11,2014

# TABLE OF CONTENTS

- 1. Statement of Use / Letter of Intent
- 2. Planning Department Application
- 3. Photographs
- 4. Plat & Survey of Property
- 5. Aerial Photographs
- 6. 3D Views
- 7. Architectural Drawings
- 8. Background Ordinance No. 2854
- 9. Concurrency Information
- 10. Traffic Study Summary and Conclusions



Writer's Direct Dial: (305) 376-6061 Writer's E-Mail Address: mgarcia-serra@gunster.com

March 24, 2014

VIA HAND DELIVERY

Mr. Ramon Trias Planning & Zoning Director City of Coral Gables 427 Biltmore Way, 2<sup>nd</sup> Floor Coral Gables, Florida 33134

# Re: Columbus Center / Phase II / MXD Site Plan and PAD Application / Statement of Use

Dear Mr. Trias:

On behalf of USRE Holdings, LLC and Gables Residential (collectively, the "Applicant"), I respectfully submit this statement of use in connection with the enclosed application for Mixed Use District (MXD) Site Plan and Planned Area Development (PAD) approval (the "Application").

The Columbus Center is a 14-story mixed used building located at 1 Alhambra Plaza which was constructed "as of right" in 1990 after City Commission approval of the partial vacation of the alley which previously bisected the block. It was the first mid-rise building in the area and it provided an alternative access to the remaining public alley way as well as a public plaza on the West side of the building. Today, it is bordered by buildings of similar height and scale to the north, south, and west. While large buildings have risen across the streets surrounding Columbus Center, an approximately 0.744 acre parcel abutting Columbus Center to the northwest has remained vacant.

The Applicant proposes to fill in the vacant parcel to the northwest by completing "Phase II" of the Columbus Center (the "Project"). Phase II will consist of an 18-story mixed use building, including 200 luxury residences, 3,400 SF of retail space, 2,600 SF of office space, and 387 parking spaces. To ensure that Phase II is fully unified with the existing Columbus Center, and to allow flexibility in the provision of mixed uses, open space, and communal amenities, all without sacrificing the strong emphasis on aesthetics and architecture that the City's regulations demand, the Applicant is seeking the following approvals:

a Mixed Use District (MXD) Site Plan approval;

One Biscayne Tower 2 South Biscayne Boulevard, Suite 3400 Miami, FL 33131 p 305-376-6000 f 305-376-6010 GUNSTER.COM Fort Lauderdale | Jacksonville | Miami | Palm Beach | Stuart | Tallahassee | Tampa | The Florida Keys | Vero Beach | West Palm Beach

- a Planned Area Development (PAD) Designation approval; and
- an amendment to Ordinance No. 2854 which vacated part of the alley which previously bisected the site and provided for an alternative alley access easement.

Specifically, the requested MXD Site Plan approval will allow Phase II of the Project to incorporate residential and retail uses alongside the existing office uses of Phase I of the Columbus Center. The PAD Designation will allow the Applicant to transfer approximately 147,915 square feet of floor area from the Phase I site to the Phase II site, will provide relief from certain stepback requirements and will permit part of the new Phase II building to encroach on the Phase I site as indicated in the enclosed plans. This will grant the Applicant the necessary flexibility to provide shared open spaces and amenities between both Phases of Columbus Center even as the overall floor area permitted to be developed on the Property is unchanged. The proposed Phase II building will require a slight reconfiguration and reduction in height of the alternative alley access easement which was required for Ordinance No. 2854. A direct application will be made to the City Commission requesting this modification.

#### Benefits to the City

The Project will adhere to the City's Mediterranean architectural design standards and will advance George Merrick's vision of a residential community anchored by a dynamic commercial center. By providing a mix of complementary uses, the Project will minimize reliance on cars within the area thus helping to reduce traffic congestion. Furthermore, the Project will include an enhanced street level public realm including the installation of an arcade and pedestrian access routes on all sides of the Project as well as a greatly improved public plaza. These public realm improvements will help form a very pedestrian friendly transition between Downtown Coral Gables and the residential communities to the north and east of the Project.

#### Consistency with the Comprehensive Plan and Zoning Code Criteria

The Project will be consistent with the following Goals, Objectives, and Policies of the Comprehensive Plan:

<u>Goal FLU-1</u>. Protect, strengthen, and enhance the City of Coral Gables as a vibrant community ensuring that its neighborhoods, business opportunities, shopping, employment centers, cultural activities, historic value, desirable housing, open spaces, and natural resources make the City a very desirable place to work, live, and play.

**Objective FLU-1.1.** Preserve Coral Gables as a "placemaker" where the balance of existing and future uses is maintained to achieve a high quality living environment by encouraging compatible land uses, restoring and protecting the natural environment, and providing facilities and services which meet or exceed the minimum Level of Service (LOS) standards and meet the social and economic needs of the community through the Comprehensive Plan and Future Land Use

Classifications and Map (see FLU-1: Future Land Use Map).

<u>Policy FLU-1.1.5</u>. The general intent of the Mixed-Use land use classification is to promote a multi-faceted pedestrian friendly environment comprised of an assortment of uses, including: Residential, Retail/Commercial, Office, Industrial, and Public Open Spaces.

<u>Policy FLU-1.7.1</u>. Encourage effective and proper high quality development of the Central Business District, which offers potential for local employment in proximity to protected residential neighborhoods.

<u>Policy FLU-1.9.1</u>. Encourage balanced mixed use development in the central business district and adjoining commercial areas to promote pedestrian activity and provide for specific commitments to design excellence and long term economic and cultural vitality.

**<u>Policy FLU-1.9.2</u>**. Encourage the detailed planning of downtown, which is defined as the central business district, to establish sound economic, aesthetic, and land use principles for effective utilization of both public and private resources.

<u>Goal DES-1</u>. Maintain the City as a livable city, attractive in its setting and dynamic in its urban character.

**<u>Objective DES-1.1</u>**. Preserve and promote high quality, creative design and site planning that is compatible with the City's architectural heritage, surrounding development, public spaces and open spaces.

**<u>Policy DES-1.1.1.</u>** Promote and support George Merrick's vision consistent with the established historic and cultural fabric of the City.

<u>Policy DES-1.2.1</u>. Continue the award of development bonuses and/or other incentives to promote Coral Gables Mediterranean design character providing for but not limited to the following: creative use of architecture to promote public realm improvements and pedestrian amenities; provide a visual linkage between contemporary architecture and the existing and new architectural fabric; encourage landmark opportunities; and creation of public open spaces.

<u>Policy DES-1.1.2</u>. Provide for rigorous design guidelines, standards, and review processes via the City's Zoning Code that ensure high quality design of buildings and spaces.

<u>Policy MOB-1.1.1</u>. Promote mixed use development to provide housing and commercial services near employment centers, thereby reducing the need to drive.

<u>Policy MOB-1.1.2</u>. Encourage land use decisions that encourage infill, redevelopment and reuse of vacant or underutilized parcels that support walking, bicycling and public transit use.

**Policy MOB-1.1.3.** Locate higher density development along transit corridors and near multimodal stations.

**Policy MOB-2.8.2.** The City in its development of the downtown and central business district shall promote the installation of landscaping within the rights-of-way and private properties since the urban fabric will be transformed into a significant urban center as buildout continues pursuant to the establishes Comprehensive Plan and Map.

<u>Policy HOU-1.5.2</u>. Encourage residential mixed use as a means of increasing housing supply within the Downtown/Central Business District/Mixed Use Development Overlay Area, thereby promoting increase in commercial and retail activity, increased use of transit, reduction of auto dependency, in association with minimizing visual and physical impacts of nearby lower density areas.

Through the incorporation of responsible planning techniques like mixed land uses, pedestrian-friendly design, increased density, protected open space, and urban revitalization, the Application supports the City's goal of economic growth through sustainable development that increases its residents' quality of life.

#### Compliance with Conditional Use Standards and Criteria

We respectfully submit that this request for mixed use Site Plan approval satisfies the review criteria of Section 3-408 of the Zoning Code as follows:

A. The proposed conditional use is consistent with and furthers the goals, policies and objectives of the Comprehensive Plan and furthers the purposes of these regulations and other City ordinances and actions designed to implement the Plan.

As stated above, the development is consistent with the Comprehensive Plan and will promote the realization of the goals, objectives, and policies thereof.

B. The available use to which the property may be put is appropriate to the property that is subject to the proposed conditional use and compatible with existing and planned uses in the area.

As the site is located within the Central Business District (CBD), the proposed mixed residential and commercial use is appropriate and compatible with the adjacent pedestrian-friendly, downtown commercial district.

C. The proposed conditional use does not conflict with the needs and character of the neighborhood and the City.

On the contrary, the proposed development is both compatible and complimentary of the historical and cultural fabric of the City.

# D. The proposed conditional use will not adversely or unreasonably affect the use of other property in the area.

The Project will benefit nearby properties by enhancing property values, provide housing to new customers for local businesses, and encourage pedestrian activity with its street level retail options for residents.

# E. The proposed use is compatible with the nature, condition, and development of adjacent uses, buildings and structures and will not adversely affect the adjacent uses, buildings or structures.

As discussed herein, the Project has positive synergy with adjacent uses, buildings, and structures and will not have an adverse impact upon them.

# F. The parcel proposed for development is adequate in size and shape to accommodate all development features.

The unified design provides continuity with its adjacent neighboring sites, complimenting the skyline at the entrance to the downtown CBD district while also providing architectural design elements focused to the pedestrian scale.

# G. The nature of the proposed development is not detrimental to the health, safety and general welfare of the community.

The Project will feature the highest quality design and construction and the Applicant is sensitive to the various dimensions of development that affect the civic environment, including traffic, the landscape, streetscape, and community concerns.

# H. The design of the proposed driveways, circulation patterns and parking is well defined to promote vehicular and pedestrian circulation.

The driveways and pathways provide safe, efficient circulation for vehicles and pedestrians while creating positive aesthetic qualities. Off-street parking requirements are met for all uses in the Project.

#### I. The proposed conditional use satisfies the concurrency standards of Article 3, Division 13 and will not adversely burden public facilities, including the trafficcarrying capacities of streets, in an unreasonable or disproportionate manner.

The proposed Project complies with the City's concurrency standards as is indicated by the Concurrency Impact Statement provided as part of this submittal.
Mr. Ramon Trias March 24, 2014 Page 6

#### **Compliance with Required Findings for a PAD**

We respectfully submit that this request for PAD approval satisfies the findings required by Section 3-503 of the Code as follows:

#### A. In what respects the proposed plan is or is not consistent with the stated purpose and intent of the PAD regulations.

The Project exemplifies the Code's intent of developing economies of scale achieved through the creative planning of experienced design professionals. The development team has utilized the Code's permissive provisions to unify the Columbus Center site in a harmonious, efficient plan that embraces the City's architectural heritage and further enhances the downtown business district.

# B. The extent to which the proposed plan departs from the zoning and subdivision regulations otherwise applicable to the subject property, including but not limited to density, size, area, bulk and use, and the reasons why such departures are or are not deemed to be in the public interest.

In order to better integrate the development across the Project site, the Project employs innovative PAD provisions regarding relaxed stepback controls and the sharing of floor area among uses. This design flexibility enables the Applicant to provide better amenities and infrastructure improvements without an overreliance upon these flexible provisions, the result of which would undermine important regulatory criteria. The result is a balanced use of bulk, height, open space, and dwelling units over the entire property.

## C. The extent to which the proposed plan meets the requirements and standards of the PAD regulations.

The Project adheres faithfully to the Code's prescriptive standards, but the use of a PAD permits simultaneous control at the design stage, thus ensuring that the individual elements of the PAD work together to enhance the whole. Adherence to these requirements has guaranteed that the multiple land uses are seamlessly integrated and make efficient use of the open land.

#### D. The physical design of the proposed PAD and the manner in which said design does or does not make adequate provision for public services, provide adequate control over vehicular traffic, provide for and protect designated common open areas, and further the amenities of light and air, recreation and visual enjoyment.

The Applicant's design observes the Code's objectives concerning architectural, landscape, and streetscape elements so that the entire Project maintains a cohesive sense of place. Pedestrian connectivity is encouraged by the shaded arcades and welcoming landscaping, while the public plaza provides circulation and visually pleasing open space. Mr. Ramon Trias March 24, 2014 Page 7

# E. The compatibility of the proposed PAD with the adjacent properties and neighborhood as well as the current neighborhood context including current uses.

The Project's unified architectural style and size are aesthetically pleasant and compatible with adjacent properties. The improved design of the Columbus Center integrates recreational, living, working, and commercial facilities wholly within the PAD. Its mixture of uses adds to a diversified neighborhood concept, with pedestrian-filled pathways that enhance the character of the neighborhood.

# F. The desirability of the proposed PAD to physical development of the entire community.

Rather than conventional regulations which contain uniform standards, the PAD promotes variety in the physical development pattern of the City and offers a more desirable living environment. The development incentives provided to the Applicant offer a significant return for the City in terms of attractive new property, valuable tax revenues, increased economic activity, and opportunities for residents.

#### G. The conformity of the proposed PAD with the goals and objectives and Future Land Use Maps of the City of Coral Gables Comprehensive Plan.

As detailed in the previous section, the Columbus Center PAD is consistent with the goals and values of the City's growth management plan. The Project's integrated development fulfills the Comprehensive Plan by advancing intelligent growth and sustainability, while furthering the downtown district's reputation for high quality urban design.

Thank you for your consideration of the Application. Please contact me if you have any questions or would like to discuss the foregoing.

Sincerely, Mario German - Seeman

Mario J. Garcia-Serra

Enclosures

cc: Mr. Joseph Wilber

MIA\_ACTIVE 4168685.1



#### Application request

The undersigned applicant(s)/agent(s)/property owner(s) request City of Coral Gables consideration and review of the
following application(s) (please check all that apply):
Abandonment and Vacations
Annexation
Coral Gables Mediterranean Architectural Design Special Locational Site Plan
🗌 Comprehensive Plan Map Amendment - Small Scale
Comprehensive Plan Map Amendment - Large Scale
Comprehensive Plan Text Amendment
Conditional Use - Administrative Review
Conditional Use without Site Plan
Conditional Use with Site Plan
Development Agreement
Development of Regional Impact
Development of Regional Impact - Notice of Proposed Change
🔀 Mixed Use Site Plan
X Planned Area Development Designation and Site Plan
Planned Area Development Major Amendment
Restrictive Covenants and/or Easements
🗋 Site Plan
Separation/Establishment of a Building Site
Subdivision Review for a Tentative Plat and Variance
Transfer of Development Rights Receiving Site Plan
University Campus District Modification to the Adopted Campus Master Plan
Zoning Code Map Amendment
Coning Code Text Amendment
Other:

#### General information

100 Alhambra Cir. (Vacant Parcels at intersection of Alhambra Cir. & Minorca Av., plus Street address of the subject property: <u>1 Albambra Plz</u>)

Property/project name: Columbus Center

Legal description: Lot(s) \_\_\_\_\_ 8 through 40 plus portions of alleys as described in Exhibit A.

Block(s) 22

Section (s) Revised Coral Gables Section L

Property owner(s): USRE Holdings, LLC

Property owner(s) mailing address: USAA Real Estate Company, 9830 Colonnade Boulevard, Suite 600, San Antonio, TX 78230

Telephone:

Business 305-740-5442 Fax 305-740-5443

Other \_\_\_\_\_ Email \_\_\_\_ hailey.ghalib

@ usrealco.com

#### City of Coral Gables Planning Division Application

Applicant(s)/agent(s): Mario J. Garcia-Serra / Greenberg Traurig, PA

Applicant(s)/agent(s) mailing address: 333 SE 2nd Avenue, Miami, Florida 33131

Telephone: Business <u>305-579-0837</u>

Other \_\_\_\_\_

Fax 305-961-5837

garcia-serram

Email

@ gtlaw.com

#### Property information

Current land use classification(s): Commercial High Intensity within the Central Business District

Current zoning classification(s): Commercial within the Central Business District

Proposed land use classification(s) (if applicable): n/a

Proposed zoning classification(s) (if applicable): n/a

#### Supporting information (to be completed by Planning Staff)

A Preapplication Conference is required with the Planning Division in advance of application submittal to determine the information necessary to be filed with the application(s). Please refer to the Planning Divison Development Review Process Handbook, Section 3.0, for an explanation of each item. If necessary, attach additional sheets to application. The Planning Division reserves the right to request additional information as necessary throughout the entire review process.

X Aerial.

Affidavit providing for property owner's authorization to process application.

Annexation supporting materials.

Application fees.

Application representation and contact information.

Appraisal.

X Architectural/building elevations.

🔀 Building floor plans.

Comprehensive Plan text amendment justification.

Comprehensive Plan analysis.

Concurrency impact statement.

- Encroachments plan.
- Environmental assessment.
- Historic contextual study and/or historical significance determination.
- Landscape plan.

Lighting plan.

Massing model and/or 3D computer model.

Miami-Dade County Conflict of Interest and Code of Ethics Lobbyist form.

Ordinances, resolutions, covenants, development agreements, etc. previously granted for the property.

Parking study.

Photographs of property, adjacent uses and/or streetscape.

🗙 Plat.

**Property survey and legal description**.

#### City of Coral Gables Planning Division Application

Property owners list, notification radius map and two sets of labels.

Public Realm Improvements Plan for mixed use projects.

- Public school preliminary concurrency analysis (residential land use/zoning applications only).
- Sign master plan.

٩)

- Site plan and supporting information.
- Statement of use and/or cover letter.
- Streetscape master plan.
- Traffic accumulation assessment.
- Traffic impact statement.
- Traffic impact study.
- Traffic stacking analysis.
- Utilities consent.
- Utilities location plan.
- □ Vegetation survey.
- ☐ Video of the subject property.
- Zoning Analysis (Preliminary).
- Zoning Code text amendment justification.
- 🔀 Warranty Deed.
- Other:

#### Application submittal requirements

- 1. Hard copies. Three (3) hard copies of the entire application shall be submitted including all the items identified in the preapplication conference.
- 2. Digital media copies. Twelve (12) compact discs (CD ROMs) of the entire application including all items identified in the Preapplication Conference. Each document shall be separated into PDF files (i.e., application; site plan, landscape plan; etc.). Please include a "Table of Contents" identifying all PDF file name(s). Each PDF file size shall not exceed 10 Mb. All discs shall be labeled with the applicant(s) name, project name and date of submittal.

#### Applicant/agent/property owner affi rmation and consent

#### (I) (We) affirm and certify to all of the following:

- 1. Submission of the following:
  - a. Warranty deed/tax record as proof of ownership for all properties considered as a part of the application request; or
  - b. Authorized as the applicant(s)/agent(s) identified herein to file this application and act on behalf of all current property owner(s) and modify any valid City of Coral Gables entitlements in effect during the entire review process.
- 2. This request, application, application supporting materials and all future supporting materials complies with all provisions and regulations of the Zoning Code, Comprehensive Land Use Plan and Code of Ordinances of the City of Coral Gables unless identified and approved as a part of this application request or other previously approved applications. Applicant understands that any violation of these provisions renders the application invalid.
- 3. That all the information contained in this application and all documentation submitted herewith is true to the best of (my) (our) knowledge and belief.
- 4. Understand that the application, all attachments and fees become a part of the official records of the City of Coral Gables and are not returnable.

#### City of Coral Gables Planning Division Application

đ

- 5. Failure to provide the information necessary pursuant to the established time frames included but not limited to application submittal, submission of revised documents, etc. for review by City Staff and the designated reviewing entity may cause application to be deferred without further review until such time the requested information is submitted.
- 6. All representatives of the application have registered with and completed lobbyist forms for the City of Coral Gables City Clerk's office.
- 7. Understand that under Florida Law, all the information submitted as part of the application are public records.
- 8. Additional costs in addition to the application fees may be assessed associated with the review of applications by the City. These are costs that may be incurred by the applicant due to consultant fees paid by City to review the application. The types of reviews that could be conducted may include but are not limited to the following: property appraisals; traffic impact analyses; vegetation/environmental assessments; archeological/historic assessments; market studies; engineering studies or reports; and legal fees. Such fees will be assessed upon finalization of the City application review.

Property owner(s) signature(s):	0	Property of	owner(s) print name:	
Property owner(s) signature(s):	8	BY:US Real Esta Its sole member	LLC, a Delaware limited liability company ite Linuted Partnership, a Texas limited partnership istate Company, a Delaware corporation ar	
Property owner(s) signature(s):		Property c	owner(s) print name:	
Property owner(s) signature(s):		Property c	wner(s) print name:	
Address: USAA Real Estate Company,	9830 Colonnade Boi	Jevard, Sui	te 600, San Antonio, Texas 78230	
Telephone: 305-740-5442	Fax: 305-740-5443		Email: hailey.ghalib@usrealco.com	
NOTARIZATION				
STATE OF FLORIDA/COUNTY OF The foregoing instrument was acknowled (Signature of Notary Public - State of Flor Te	lged before me this ida) XAS	<u></u> day	of Feb. 2014 by Hailey Ghalib	
(Print, Type or Stamp Commissioned Nan		Identification	HALEY KOENIG Notary Public State of Texas My Comm. Exp. 05-21-2016	











A-0.3



3Ø

18

CONTEXT PHOTOS

COLUMBUS CENTER 100 ALHAMBRA CIRCLE CORAL GABLES, FLORIDA

DATE:02-28-14 PROJECT NO: 11-025 DRAWING NAME: SHEET NO:

A-0.3.1

6



- 20



#### LEGAL DESCRIPTION:

Lots 3, 4, 5 and 6, Block 22 of "REVISED PLAT OF CORAL GABLES SECTION L", according to the plat thereof as recorded in Plat Book 8, Page 85, of the Public Records of Miami-Dade County, Florida.

Containing 32,280 square feet (0.74 acres) more or less by calculations.

Property Address: 100 Alhambra Circle, Coral Gables, Florida

Folio No.: 03-4108-077-2010 03-4108-007-2020

#### SURVEYOR'S NOTES:

1. Last day of field work was performed on April 12, 2012.

- 2. Avino & Associates, Inc. and certifying Land Surveyor accept no responsibility for Rights—of—Way, Easements, Restrictions of Record or other matters affecting tille to lands surveyed other than those recited in current Deed and/or other instruments of record furnished by Client,
- 3. Bearings shown hereon are based on the Southwesterly Line of Lots 3, Block 22 of "REVISED PLAT OF CORAL GABLES SECTION L", according to the plat thereof as recorded in Plat Book 6, Page 85, of the Public Records of Miami-Dade County, Florida; with an assumed Bearing of N 42'54'22" W, said line to be considered a well monumented line.
- By scaled determination the subject property appears to lie in Flood Zone X, as per Federal Emergency Management Agency (FEMA) Community-Panel Number 120639, Map No. 12086C0294, Suffix L, Revised Date: 09-11-2009. An accurate Zone determination should be made by the preparer of the map, the Federal Emergency Management Agency, or the Local Government Agency having jurisdiction over such matters prior to any judgments being made from the Zone as noted. The referenced Federal Emergency Management Agency Map states in the notes to the user that 'this map is for insurance purposes only".
- 5. All Elevations shown hereon refer to National Geodetic Vertical Datum 1929 (NGVD).

Benchmark Identification: Coral Gables Benchmark: No.630 Elevation: 11.49 feet (National Geodetic Vertical Datum) Location: Galiano Street & Alhambra Plaza. PK Nail and Brass Washer in Concrete Sidewalk.

Benchmark Identification: Coral Gables Benchmark: No.517 Elevation: 9.68 feet (National Geodetic Vertical Datum) Location: Galiano Street & Madeira Avenue. PK Nail and Brass Washer in Concrete Sidewalk

6. The Survey depicted herein is not intended to show the location or existence of any Wetland or Jurisdictional areas, or areas of protected species of vegetation either natural or cultivated.

7. Any use of this Survey for purposes other than which it was intended, without written verification, will be at the user's sole risk and without liability to the surveyor. Nothing herein shall be construed to give any rights or benefits to anyone than those certified to.

8. The minimum relative distance accuracy for this type of Survey is 1 foot in 10,000 feet. The accuracy obtained by measurement and calculation of closed geometric figures was found to exceed this requirement. Well-identified features as depicted on the Survey Map were measured to an estimated horizontal positional accuracy of 1/10 foot.

-	PLOT DA	TE: 04/19/2012	© 2012 AVINO 4 AL	BOCIATES, NC. ALL REGITS RE
MARK	DATE	REVISIONS		BOUN
$\Box$				

IDARY AND TOPOGRAPHIC SURVEY 100 ALHAMBRA CIRCLE CORAL GABLES, FL 33134

ERGIER HEREDY EXPRESSLY RESERVES HIS COMPRISH & DT-ER PROPERTY RIGHTS

USRE HOLDINGS, LLC. 9830 COLONNADE BOULEVARD SUITE 600 SAN ANTONIO, TX 78230-2239



1350 S.W. 57th AVEN WEST MIAMI, FLORIDA TEL: (305) 265-5 FAX: (305) 265-50 EB # 5098 LB # 50 E-MAIL: jravino@avin



VICINITY MAP NOT TO SCALE

9. Since no other information other than what is cited in the Sources of Data were furnished, the Client is hereby advised that there may legal restrictions on the Subject Property that are not shown on the Survey Map or contained within this Report that may be found in the Public Records of Miami-Dade County, or the records of any other public and private entities as their jurisdictions may appear. The Surveyor makes no representation as to ownership or possession of the Subject Property by any entity or individual who may appear of public record

No excavation or determination was made as to how the Subject Property is served by utilities. No improvements were located, other than those shown. No underground foundations and/or improvements were located or shown hereon. This notice is required by the "Minimum Technical Standards for Land Surveying in the State of Florida," pursuant to Chapter 5J-17, Florida Administrative Code and as adopted by the Florida Board of Professional Surveyors and Mappers pursuant to Chapter 472, Florida Statutes.

Notice is hereby given that Sunshine State One Call of Florida, Inc. must be contacted at 1-800-432-4770 at least 48 hours in advance of any construction, excavation or demolition activity within, upon, abutting or adjacent to the Subject Property. This Notice is given in compliance with the "Underground" Facility Damage Prevention and Safety Act," pursuant to Chapter 556.101-111 of the Florida Statutes.

#### CERTIFIED TO:

USRE HOLDINGS, INC. LOADSTAR, INC.

#### SURVEYOR'S CERTIFICATE:

This is to certify to the herein named firm and/or persons that the "Boundary & Topographic Survey" of the herein described property is true and correct to the best of our knowledge and belief as surveyed under our direction. I further certify that this survey meets the Minimum Technical Standards Requirements as set forth in Chapter 5J-17, Florida Administrative Code, as adopted by the Florida Board of Professional Surveyors and Mappers pursuant to 472.027 Florida Statute.

NOTICE: Not valid without the signature and original raised seal of a Florida Licensed Surveyor and Mapper. Additions or deletions to Survey Maps by other than the signing party are prohibited without the written consent of the signing party.

PERTINION AND CONSIST.	ACAD FILE: BOUNDARY &	TOPO SURVEY	
NUE, SUITE 207 33144 030 133 198	SEAL	DRAWN BY: B.J.S. CHECKED BY: J.R.A. APPROVED BY: J.R.A. DATE : 04/19/2012 SCALE : 1" = 20' JOB No. : 12108.00	sheet 1
oandassociates.com	JORGE R. AVIÑO, P.E.A	22207; P.L.S.# 4996	SHEET 1 OF 1

# JIDARY & TOPOGRAPH SURVEY

#### LEGAL DESCRIPTION:

Lots 3 to 40, Block 22 of "REVISED PLAT OF CORAL GABLES SECTION L", according to the plat thereof as recorded in Plat Book 8, Page 85, of the Public Records of Miami-Dade County, Florida.

Containing 145,019 square feet (3.33 acres) more or less by calculations.

Property Address: 100 Alhambra Circle, Coral Gables, Florida

Folio No.: 03-4108-077-2010 03-4108-007-2020 03-4108-007-2210

#### SURVEYOR'S NOTES:

- 1. Last day of field work was performed on March 20, 2014.
- 2. Avino & Associates, Inc. and certifying Land Surveyor accept no responsibility for Rights-of-Way, Easements, Restrictions of Record or other matters affecting title to lands surveyed other than those recited in current Deed and/or other instruments of record furnished by Client.
- 3. Bearings shown hereon are based on the Centerline of ALHAMBRA PLAZA with an assumed Bearing of S84\*42'25"W. said line to be considered a well monumented line.
- 4. By scaled determination the subject property appears to lie in Flood Zone X, as per Federal Emergency Management Agency (FEMA) Community-Panel Number 120639, Map No. 12086C0294, Suffix L, Revised Date: 09-11-2009. An accurate Zone determination should be made by the preparer of the map, the Federal Emergency Management Agency, or the Local Government Agency having jurisdiction over such matters prior to any judgments being made from the Zone as noted. The referenced Federal Emergency Management Agency Map states in the notes to the user that "this map is for insurance purposes only".

5. All Elevations shown hereon refer to National Geodetic Vertical Datum 1929 (NGVD).

Benchmark Identification: Coral Gables Benchmark: No.630 Elevation: 11.49 feet (National Geodetic Vertical Datum) Location: Galiano Street & Alhambra Plaza. PK Nail and Brass Washer in Concrete Sidewalk.

Benchmark Identification: Coral Gables Benchmark: No.517 Elevation: 9.68 feet (National Geodetic Vertical Datum) Location: Galiano Street & Madeira Avenue. PK Nail and Brass Washer in Concrete Sidewalk.

- 6. The Survey depicted herein is not intended to show the location or existence of any Wetland or Jurisdictional areas, or areas of protected species of vegetation either natural or cultivated.
- 7. Any use of this Survey for purposes other than which it was intended, without written verification, will be at the user's sole risk and without liability to the surveyor. Nothing herein shall be construed to give any rights or benefits to anyone than those certified to.
- 8. The minimum relative distance accuracy for this type of Survey is 1 foot in 10,000 feet. The accuracy obtained by measurement and calculation of closed geometric figures was found to exceed this requirement. Well-identified features as depicted on the Survey Map were measured to an estimated horizontal positional accuracy of 1/10 foot.
- 9. Since no other information other than what is cited in the Sources of Data were furnished, the Client is hereby advised that there may legal restrictions on the Subject Property that are not shown on the Survey Map or contained within this Report that may be found in the Public Records of Miami-Dade County, or the records of any other public and private entities as their jurisdictions may appear. The Surveyor makes no representation as to ownership or possession of the Subject Property by any entity or individual who may appear of public record.

SW 13TH ST	
SW 13TH TE	-
SW 14TH ST	n
SW 15TH ST	
SW 18TH ST	
ZAMORA AV	SIT
WADERA AV	
	8
UNORCA AV	-
ALCAZAR AV	-
	ALHA
	P.
	iz iz
-	1 3
THE	ANDALUSA
-02/	Martin

#### SURVEYOR'S CERTIFICATE:

This is to certify to the herein named firm and/or persons that the "Boundary & Topographic Survey" of the herein described property is true and correct to the best of our knowledge and belief as surveyed under our direction. I further certify that this survey meets the Minimum Technical Standards Requirements as set forth in Chapter 5J-17, Florida Administrative Code, as adopted by the Florida Board of Professional Surveyors and Mappers pursuant to 472.027 Florida Statute.

NOTICE: Not valid without the signature and original raised seal of a Florida Licensed Surveyor and Mapper. Additions or deletions to Survey Maps by other than the signing party are prohibited without the written consent of the signing party.

PLOT DA	TE: 03/21/2014 @	Э эми Анно и лакослитарыс, лиц налик назаниес, секкием начаки сималыси накалие ин соминали отнам мылами нана мына мына мына и	onumes are not to be reproduced, classed, ce conso in any rort or kanen sisted by uniour free defause.	UNITEN PERVESION AND CONSIDE OF AVERO I ASSOCIATES, HIS, NOR AND THEY TO BE ASSOCIO TO ANY PARTY KITCH? PARTY AND DEVIDE AND DEVIDE PERVESION AND CONSIDE.	ACAPTALE BOUNDARY & TOPO SURVEY (BLOCK 22)
ARK DATE	REVISIONS	BOUNDARY AND TOPOGRAPHIC SURVEY 100 ALHAMBRA CIRCLE CORAL GABLES, FL 33134	USRE HOLDINGS, LLC. 9830 COLONNADE BOULEVARD SUITE 600 SAN ANTONIO, TX 78230-2239	Aviñó SASSILATES BREEZ : FANEZ : SINETORI BREEZ : FANEZ : SINETORI BREEZ : FANEZ : SINETORI	SEA     DRAWN BY: B.J.S.     SHEET       OHECKED BY: J.R.A.     APPROVED BY: J.R.A.     SHEET       APROVED BY: J.R.A.     DATE : 03/21/2014     1       SALE : 1" = 20"     JOB NO. : 12108.00     SHEET     1



NOT TO SCALE

No excavation or determination was made as to how the Subject Property is served by utilities. No improvements were located, other than those shown. No underground foundations and/or improvements were located or shown hereon. This notice is required by the "Minimum Technical Standards for Land Surveying in the State of Florida," pursuant to Chapter 5J-17, Florida Administrative Code and as adopted by the Florida Board of Professional Surveyors and Mappers pursuant to Chapter 472, Florida Statutes.

Notice is hereby given that Sunshine State One Call of Florida, Inc. must be contacted at 1-800-432-4770 at least 48 hours in advance of any construction, excavation or demolition activity within, upon, abutting or adjacent to the Subject Property. This Notice is given in compliance with the "Underground" Facility Damage Prevention and Safety Act," pursuant to Chapter 556.101-111 of the Florida Statutes.



PLOT DATE: 03/21/2014 TOPO SURVEY (BLOCK 2 CAD FILE BOUNDARY RAWN BY: B.J.S. 1350 S.W. 57TH AVENUE, SUITE 207 WEST MIAMI, FLORIDA 33144 SHEET REVISION USRE HOLDINGS, LLC. Avino CHECKED BY: J.R.A BOUNDARY AND TOPOGRAPHIC SURVEY 9830 COLONNADE BOULEVARD APPROVED BY: J.R.A. TEL: (305) 265-5030 FAX: (305) 265-5033 EB = 5098 LB = 5098 100 ALHAMBRA CIRCLE 2 DATE : 03/21/2014 & ASSOCIATES SUITE 600 SCALE : 1" = 20' CORAL GABLES, FL 33134 JOB No. 12108.00 SAN ANTONIO, TX 78230-2239 ENGNEERS . FLANERS . SLEVETORS E-MAIL: JRAVINO AVINOANDASSOCIATES.COM REAL & AVISO, PJ #22207, PL SJEMME SHEET 1 OF





NORTH EAST





NORTH WEST

EAST

AERIAL VIEWS



PROJECT NO: 11-025 DRAWING NAME: SHEET NO:







A-4.1









brawing name: sheet no: A-4.3 ARCHITECTURE

May 16, 2014

#### RE: Comments- 100 Alhambra Circle

The following is an itemized response to the comments pertaining to the above referenced project.

#### Planning and Zoning Comments:

- 1. Elevation Drawings (Sec. 3-502.D.3.c).
  - Provide elevation drawings indicating each of the following frontages for proposed (phase II) mixed-use building: Alhambra Circle, Minorca Avenue, Alhambra Plaza (view from plaza), Douglas Road (view from Phase I0, and Galiano Street (view form La Palma).
  - Include total height to top of slab and to top of roof line in all elevation drawings.

#### Please refer to Sheets A-3.0 - A-3.4 for Building Elevation.

2. Signage Plan (Sec. 3-502-D.3.h). A signage plan that complies with Zoning Code regulation as well as appropriate wayfinding signage and ATM locational signage will be provided.

#### PLANNING Please refer to Sheet A-0.9\_ Signage Floor Plan

- INTERIORS 3. Art in Public Places: Not part of this submission. Improvements of the plaza to be part of Art in Public Places submittal. By others.
  - 4. Circulation Plans (Sec. 3-502-D.3.b). Submit circulation plan for the following types of systems: pedestrian, vehicular, bicycle, and public transit (buses and trolley).

Please refer to Sheet A-0.10 Accessibility Floor Plan as well as Exhibits 3,4 and 5 created by Kimley Horn .

- Traffic Regulation devices (Sec. 3-502-D.3.q). Show all proposed traffic control devices (parking garage, arm/gates, overhead doors, etc.) on plans.
  Please refer to Sheet A-1.1\_ Ground Floor plan.
- Concurrency Impact Statement. Provide CIS indicating infrastructure is available for the project.
  Concurrency administrator cannot get it. She has already informed Planning and Zoning Director.

135 San Lorenzo Ave., Suite 610 Coral Gables, FL 33146 Tel.: 305.740.5442 Fax: 305.740.5443 E-Mail:Reception@beharfont.com Certification No. AA2451

Elevations (Sec. 4-201.F.2, No blank walls). Architectural reliefs and elements shall be provided on all sides of buildings and include similar architectural

features as to those provided on the front façade. No blank walls shall be permitted unless required pursuant to applicable Fire and Life Safety Code requirements.

#### Please refer to Sheets A-3.0 - A-3.4 for Building Elevation.

 Overhead doors (Sec. 4-201.F.9). Overhead doors shall not face or be directed towards residential properties and/ or adjacent rights-of-ways abutting residentially zoned properties. Indicate on plans that there will be no proposed overhead doors facing Minorca Ave.

Please refer to Sheet A-1.1\_ Ground Floor plan.

- Paver treatments. Paver treatments shall be included in the following locations: driveways entrances, crosswalks, and sidewalks (minimum of 25% of paving surfaces).
  Please refer to Sheet A-0.8 Mediterranean Bonus for percentages and A-1.1 Ground Floor Plan.
- Landscape open space (Sec. 3-502.C.6). Minimum required landscaped open space for a PAD shall be not less than 20%.
  Please refer to Sheet A-0.5.1 Zoning Chart for calculations and A-0.8
  Mediterranean Bonus.
- 11. Pedestrian pass-throughs/ paseo (Sec. 3-502.C.8.d). Where necessary and appropriate to enhance public pedestrian access, no block face shall have a length greater than two hundred and fifty (250) feet without a public pedestrian passageway or alley providing through access.

Please refer to Sheet A-1.0 Site plan and A-1.1 Ground Floor plan.

12. Ground floor building frontage on secondary streets (Sec. 4-201.E.11) Minimum 40% of linear ground floor building frontage shall include retail sales and service, office, or restaurant or public realm land area uses.

Please refer to sheet A-0.7 Overall Ground Floor for calculations, L-1.1 Overall Public Amenities Site Plan and ST-1.1 Public Realm Plan (Phase I)

# Kimley » Horn

May 13, 2014

Yamilet Senesplenda, P.E. City Engineer City of Coral Gables Department of Public Works 2800 SW 72<sup>nd</sup> Ave. Miami, FL 33155

#### RE: Comments – 100 Alhambra Circle, Columbus Center Phase II

The following is an itemized response to the comments pertaining to the above referenced project

#### **Public Works Comments:**

- 1. Updated traffic study shall be submitted:
  - a. New traffic counts (TMC's conducted in July are not accepted by the City).
  - b. Committed developments (33 Alhambra Circle) have to be included in the analysis.
  - c. A full updated site plan has to be included in the traffic study Appendix to better understand the traffic circulation and parking garage location.
  - d. Trip distribution does not show the trips assigned to the alley entering from and exiting to Galiano Street.

Please refer to the responses generated by John McWilliams dated May 5, 2014 and the revised traffic study submitted on May 6, 2014.

- 2. No left turn signs shall be installed at the alley exit to Galiano Street. Please refer to the revised Signage and Marking Plan (EX-3). A right turn only sign is proposed in the alley exiting to Galiano Street.
- 3. A description of the traffic circulation on the public alley as well as an appropriate way finding signage shall be provided.

Please refer to the revised Signage and Marking Plan (EX-3) for a depiction of the traffic circulation in the public alley with the appropriate signage. Please refer to the pedestrian Accessibility Floor Plan exhibit created by Behar Font.

- 4. Provide full size underground facilities master plan to the Public Works Department. Please refer to the Conceptual Utilities Plan (EX-1). There are no above ground facilities that will need to be relocated underground.
- New 6" PVC C900 laterals must be provided. The section of the sewer line must be replaced from manhole to manhole.
  The project will be serviced by two (2) 6" PVC C900 sewer laterals. The section of sewer line will be replaced as required. The existing sewer mains will be televised and copies will be submitted to the City for review.

954 535 5100

# Kimley » Horn

May 5, 2014

Ms. Yamilet Senespleda, P.E. City of Coral Gables Coral Gables, FL

#### **RE: Traffic Impact Study Response to Comments**

We have received comments provided by the City of Coral Gable's traffic engineering consultant for the 100 Alhambra Circle traffic study on April 9, 2014. It should be noted that this response to comments only includes the traffic related comments. We offer the following responses:

1. New traffic counts (TMC's conducted in July are not accepted by the City).

Response: New traffic counts were collected in April 2014. The revised traffic impact analysis has been updated to reflect the new counts and peak season factor for the two intersections that previously utilized TMC's from July.

2. Committed developments (33 Alhambra Circle) have to be included in the analysis.

Response: Per our meeting on April 23, 2014, a traffic study has not been submitted for this project. Therefore, it was not included as a committed development.

### 3. A full updated site plan has to be included in the traffic study Appendix to better understand the traffic circulation and the parking garage location.

Response: An updated site plan has been included in Appendix A of the revised traffic impact study. In addition, a signs and pavement marking plan has been included in Appendix A to better illustrate the traffic circulation and parking garage location on site.

4. Trip distribution does not show the trips assigned to the alley entering from and exiting to Galiano Street.

Response: The trip distribution has been updated to show trips assigned to the alley entering from and existing to Galiano Street. The updated trip distribution can be found in the revised traffic impact analysis.

Please contact me at (954) 535-5100 or john.mcwilliams@kimley-horn.com should you have any questions.

Sincerely,

John J. McWilliams, P.E.











# GRAPHIC SCALE IN FEET 400 n MIAMI-DADE COUNTY BUS STOP CITY OF CORAL GABLES TROLLEY STOP SHEET NUMBER PUBLIC TRANSPORTATION EX-5 EXHIBIT



ee Dispos						1	
Tree #	Height	Spread (FT)	DBH	Type	Disposition	Condition	Canopy Area
1	30	15	14"	Mahogony / Swietenia mahagoni	Remove	Poor	176,625
2			_	Schefferra actinophylla	Remove	Exotic Invasive	0
3				Schetterra actinophylia	Remove	Exotic Investive	0
4				Schefferra actinophylla	Remove	Exotic Investve	0
5				Schellerra actinophylla	Remove	Exotic Investor	6
6				Scholterra actinophylla	Romove	Exotic Investor	0
7				Schetterra actinophylla	Remove	Exotic Invisive	0
8				Schellerra actinophylla	Remove	Ecolic Investive	0
9				Schefferra actinophylla	Remove	Exotic Invasive	0
10				Schetterra actinophylla	Remove	Exotic invasive	0
11				Orad			0
12	25	10	10"	Queen Palm / Syagrus romanzoffana	Remove	Fair	78.5
13	25	10	10*	Queen Palm / Syegrus remanzoffana	Remove	Fair	78.5
14		-		Albizia jolibrizala	Remove	Exotic Investor	0
15		1	_	Albizia jusprissin	Remove	Exotic Invesive	0
10				Albizia sibbessio	Remove	Exotic Invasive	0
17				Albizia julibriasin	Remove	Exotic Invasive	0
18				Albizia ulibrissio	Remove	Exotic Investve	0
19				Albizia (ulbrissin	Remove	Exotic Invasive	¢
20	30	30	17*	Mahogony / Swietenia mahagoni	Remove	Fair	706.5
21				Areca Palm / Dypsis lutescons	Remove	Fair	0
22	30	30	17*	Mahogony / Swietenia mahagoni	Remove	Fait	706.5
23				Areco Polm / Dypsis lutescens	Remove	Fair	0
24	30	30	17*	Mahogony / Swietenia mahagoni	Remote	Fair	706.5
25	30	30	117	Mahogony / Swietenia mahagoni	Remove	Fair	706.5
26	15	10	6*	Wax Privet / Ligustrum japonicum	Bantore	Fait	78.5
27	15	10	6*	Wax Privet / Ligustrum japo/icum	Remova	Fait	78.5
	30	30	10*	Mahogony / Swietenia mahagoni	Remove	Falt	706.5
28	15	10	6*	Was Privet / Liguatrum japonicum	Remove	Falt	78.5
30	15	10	6*	Wax Privet / Liguistrum japoricum	Remove	Fair	78.5
	15	10	6*	Wax Privet / Ligustrum japoricum	Remove	Fait	78.5
31	30	30		Mahogony / Swietenia mahagoni	Remove	Fair	706.5
32			10*	Wax Privet / Liguatrum japonicum	Remove	Fair	78.5
33	15	10	67	Wax Privet / Ligustrum Japonicum	Remove	Fait	78.5
34	15	10			Remove	Fait	78.5
35	15	10	67	Wax Privet / Ligustrum japonicum	Remove	Fal	708.5
36	30	30	17"	Mahogony / Swietienia mahagoni	Remove	Fair	0
37				Deed		an order to contract	0
38	0.0		-W	Schellerra actinophylla	Remove	Exotic Investve	
39	12	6	14*	Sabel Palm / Sabel palmetto	Remove	Poor	19.625
40	12	5	14*	Sabal Palm / Sabal palmetto	Remove	Popr	19,625
41	12	5	14*	Sabal Palm / Sabal palmetto	Remove	Poor	19.625
42	25	25	30*	Sea Grape / Coccoloba uvilera	Remove	Poor	490.625
43	6	5	14*	Sabal Palm / Sabal palmetto	Remove	Poor	19.625
44				Dead			0
45				Dead			0





I

 $\geq$ 



0



	SPECIFICATIONS
	12 C.T.
_	F.Q.
	22" HT. X 10" SPR, 6"-6" CAL. MIN.
	F.G.
	8' G.W., 22' O.A. HT, MIN.
	F.G., MATCHED HTS.
RS	
	SPECIFICATIONS
	15" HT. X 15" SPR. / 15" O.C.
	3 GAL
_	15" HT, X 18" SPR /24" O.C.
	3 GAL
_	24" HT. X 24" SPR / 24" O.C.
_	3 GAL

C.
_





BEHAR·FON





0.09		5,650 8.1.
ired/ Ved	PROVIDE	D
86	4,459	- 2
	35	(31 Trees at Level 5)
	6	-
	17	-
	5	-
	10	
	50	(31 Trees at Level 5)
0	517	(475 Shrubs al Level 5)

مريكة ( هرسايين	KIM LIGHT	
TING BYMBOL ON PLAN	Specifications	
	Barry, Boost, Ward, Ward	







#### **PLANTING NOTES:**

-All plant material is to be Florida Number 1 or better pursuant to the Florida Department of Agriculture's Grades and Standards for Nursery Plants.

-All plants are to be top dressed with a minimum 3" layer of Melaleuca mulch, Eucalyptus mulch or equal.

-Planting plans shall take precedence over plant list in case of discrepancies.

-No changes are to be made without the prior consent of the Landscape Architect and Owner. Additions and or deletions to the plant material must be approved by the project engineer.

-Landscape Contractor is responsible for providing their own square footage takeoffs and field verification for 100% sod coverage for all areas specified.

- All landscape areas are to be provided with automatic sprinkler system which provide 100% coverage, and 50% overlap.

- All trees in lawn areas are to receive a 24" diameter mulched saucer at the base of the trunk.

- Trees are to be planted within parking islands after soil is brought up to grade. Deeply set root balls are not acceptable.

- Planting soil for topsoil and backfill shall be 50/50 mix, nematode free. Planting soil for annual beds to be comprised of 50% Canadian peat moss, 25% salt free coarse sand and 25% Aerolite.

- Tree and shrub pits will be supplemented with "Agriform Pells", 21 gram size with a 20-10-5 analysis, or substitute application accepted by Landscape Architect. Deliver in manufacturer's standard containers showing weight, analysis and name of manufacturer.

#### LANDSCAPE DETAILS

SCALE: NTS

#### SOD NOTES:

-Sod is to be grade "A" weed free.

-All areas marked "LAWN" shall be solid sodded with St. Augustine 'Floratam' solid sod. See limit on plan. All areas marked 'Bahia Grass' shall be solid sodded with Paspalum.

-Provide a 2" deep blanket of planting soil as described in planting notes this sheet. Prior to planting, remove stones, sticks, etc. from the sub soil surface. Excavate existing non-conforming soil as required so that the finish grade of sod is flush with adjacent pavement or top of curb as well as adjacent sod in the case of sod patching.

-Place sod on moistened soil, with edges tightly butted, in staggered rows at right angles to slopes.

-Keep edge of sod bed a minimum of 18" away from groundcover beds and 24" away from edge of shrub beds and 36" away from trees, measured from center of plant.

-Sod Shall be watered immediatley after installation to uniformily wet the soil to at least 2" below the bottom of the sod strips.

-Excavate and remove excess soil so top of sod is flush with top of curb or adjacent pavement or adjacent existing sod.

#### **GENERAL NOTES:**

-The Landscape Contractor is to locate and verify all underground and overhead utilities prior to beginning work. Contact proper utility companies and / or General Contractor prior to digging for field verification. The Owner and the Landscape Architect shall not be responsible for any damages to utility or irrigation lines (see Roadway Plans for more utility notes).

-Landscape Contractor is to verify all current drawings and check for discrepancies and bring to the attention of the Landscape Architect prior to commencing with the work.

-All unattended and unplanted tree pits are to be properly barricaded and flagged during installation.

-All planting plans are issued as directives for site layout. Any deviations, site changes, etcetera are to be brought to the attention of the Landscape Architect for clarification prior to installation.





BEHAR·FON









ELEVATED DECK (LEVEL 6): 20,190 SF

ELEVATED DECK (LEVEL 6) (PHASE 1) SCALE:NTS













PUBLIC REALM PLAN (PHASE 1411)

ST-1.0



SCALE:NTS





# COLUMBUS CENTER

100 ALHAMBRA CIRCLE CORAL GABLES, FLORIDA

ST-1.2



#### ZONING INFORMATION: CENTRAL BUSINESS DISTRICT

DEVELOPMENT STANDARDS	PHAGE I (Existing)	PHASE II (PROPOSED)	TOTAL (PHASE   &   )
SITE AREA	112,945 SQ. FT. (2.593 ACRES)	32,280 SQ. FT. (0,744 ACRES)	145,225 6Q. FT. (3.337 ACRES)
CONFIGURATION OF LANDS	LOT WIDTH: 370'-11" FT.	LOT WIDTH: 196'-5" FT.	LOT WIDTH: 567'-4" FT.
MIN, LOT WIDTH: 200 FT. MIN, LOT DEPTH: 100 FT.	LOT DEPTH: 220'-2" FT.	LOT DEPTH: 107'-11" FT.	

MIXED-USE PROJECT/ HIGH-RISE INTENSITY

MAXIMUM FAR	PHAGE 1 (EXISTING)			PHAGE II (PROPOSED)			TOTAL		
		ALLOUED/REQUIRED	PROVIDED		ALLOUED/REQUIRED	PROVIDED		ALLOUED/REQUIRED	PROVIDED
CORAL GABLES: 30 MEDITERRANEAN BONUS: 05	112,945 <i>00</i> × 3 <i>0</i> 112,945 <i>00</i> × 05	338,835 <i>00</i> 5Q. FT. 56,472 <i>50</i> 8Q. FT.		32,280 × 3.0 32,280 × 05	96 <i>840</i> 8Q. FT. 16,140 8Q. FT.		145,225 ×3ø 145,225 ×ø5	435,675 SQF.T. 72,6125 SQF.T.	
	TOTAL	395,307.00 SQ. FT.	247,392.16 SQFT	SUB-TOTAL (PHASE II) UNUSED F.A.R. PHASE I ( BY P.A.D.)	112,980 SQ. FT. 147,914.84 SQFT	232,968 5Q. FT.	TOTAL	5082875 SQ. FT,	247,392.16 8QF.T + 232,96 480,360.16 SQ
	UNUSED F.A.R (PHASE 1) Allaued F.A.R - PROVIDED F.A.R 395,30100 SQ.FT 247,392,16 SQ.FT 147,914,84 SQ.FT.		TOTAL 147,914,84 SQFT	TOTAL (PHASE II) (FAR PHA9E III UNUSED FAR PHASE I) 112,980 50. FT. + 141,914.84 50.FT. + 260,934.84 50.FT.	26 <i>0,8</i> 94,84 9QFT	. 232,968 SQ. FT.		.1	

F.A.R CALCULATIONS	PHAGE   (EXIGTING)			PHASE    (PROPOSED)		TOTAL	
	BUILDING A	BUILDING B	TOTAL		TOTAL		
BASEMENT				N/A			
GROUND			32,191.72 SQFT.		5,460 SQ. FT.		
MEZZANINE	N/A	N/A					
2ND	(FARKING)	(PARKING)		(PARKING)			
3RD	(PARKING)	(PARKING)		(PARKING)			
4†H	(PARKING)			(PARKING)			
БТН	(PARKING)	(PARKING)		(RESIDENTIAL)	17,350 SQFT.		
бтн	17,480,14 SQFT.	18,969.38 SQ.FT.	36,449.52 SQ.FT.	(RESIDENTIAL)	16,444 SQ.FT.		
НТН	17,938,84 SQFT.	18,95023 SQFT.	36,883.07 SQ.FT.	(RESIDENTIAL)	16,444 SQFT.		
8TH	17,938.84 SQFT.	17,934,81 SQFT.	35,813.65 SQ.FT.		16,444 SQFT.		
9TH	17,938,84 SQFT.	N/A	17,938.84 SQFT.	(RESIDENTIAL)	16,444 SQ.FT.		
IØTH	17,938,84 SQFT.	N/A	17,938,84 SQ.FT.	(RESIDENT(AL)	16,444 SQ.FT.		
IITH	17,938,84 6QFT.	N/A	17,938.84 SQ.FT.	(RESIDENTIAL)	16,444 SQFT.		
12TH	17,938,84 SQFT.	N/A	17,938.84 SQFT.	(RESIDENTIAL)	16,444 SQ.FT.		
ІЗТН	11,938,84 SQFT.	N/A	17,938,84 SQFT.	(RESIDENTIAL)	16,444 SQ.FT.		
14TH	16,294 SQFT.	N/A	16,294 SQ.FT.	(RESIDENTIAL)	16,444 SQFT.		
ISTH-ITTH	N/A	N/A		16,444 SQFT. X 3=49,332	49,332 SQFT.		
PENTHOUSE	N/A	N/A			12,830 SQ.FT.		
TOTAL			247,392.16 SQFT.		232,968 SQ. FT.	480,360.16 SQ. FT.	
	UNUSED F.A.R (PHASE I)		TOTAL				
	ALLOWED FAR - PROVIDED FAR. 39530700 60. FT24739216 60.FT.=147,914.84 80.FT.		147,914.84 SQFT				


		1					
DEVELOPMENT STANDARDS	PHASE   (Existing)		PH4 (PRO	ТС	TOTAL		
DENSITY (AS PER 4-201EJ3 CITY OF CORAL GABLES ZONING CODE)	- N/A		200 UNITS		200	200 UNITS	
THERE SHALL BE NO LIMITATIONS IN CBD DISTRICTS							
LANDSCAPED OPEN SPACE	REQUIRED	PROVIDED	REQUIRED	PROVIDED	REQUIRED	PROVIDE	
(AS PER 3-502/C6 CITY OF CORAL GABLES ZONING CODE) SHALL NOT BE LESS THAN 20% OF PAD SITE " REFER TO SHEET A-000 MED BONUS	2 <i>0% O</i> F 106,369 SQFT. 21,273,8 SQFT.	38,869 SQFT.	20% OF 38,856 SQF.T 7,771 SQFT.	9250 SQFT.	20% OF 145,225 6Q.F.T = 29,045 SQ.F.T.	48,119 SF	
			1				
LOT COVERAGE	REQUIRED	PROVIDED	REQUIRED	PROVIDED	REQUIRED	PROVIDE	
(AS PER 5604- B CITY OF CORAL GABLES ZONING CODE) NO MINIMUM OR MAXIMUM BUILDING LOT COVERAGE IS REQUIRED. REFER TO SHEET A-0.0 MED BONUS	NO MINIMUM OR MAXIMUM REQUIRED.	16,818 SQFT.	NO MINIMUM OR MAXIMUM REQUIRED.	36,305 SQFT.		113,183 SQF	
HEIGHT OF BUILDINGS (AS PER 5604 CITY OF CORAL GABLES ZONING CODE) MAX. HEIGHT: 1901-5"	-  61'-1©"		19Ø'-Ø"				
PARKING	PHASE   (EXISTING)		PHASE    (PROPOSED)		то	TAL S	
	REQUIRED *	PROVIDED	REQUIRED	PROVIDED	PRO	VIDED	
(AS PER 5.1429 CITY OF CORAL GABLES ZONING CODE)	I. TOTAL PROJ. AREA @ 1 SPACE/35 SQFT.	50	I. RESIDENTIAL:	e 1754NIT			

	REQUIRED *	PROVIDED	REQUIRED	PROVIDED	PROVIDED
(AS PER 51409 CITY OF CORAL GABLES ZONING CODE)	I. TOTAL PROJ. AREA © 1 SPACE/350 SQFT. 213,725 SQFT/350 SQFT.= 182 2. CARS REQUIRED FOR SOUTHERN BELL= 41		1. RESIDENTIAL: • STUDIO, I BEDROOM, 2 BEDROOMS UNITS @ 1.75/UNIT STUDIO= 12 UNITS 1 BR= 54 UNITS 2 BR= 118 UNITS TOTAL: 184 UNITS @1.75= 322	322	
	• (INFORMATION FROM ORIGINAL DRAWINGS)		• 3 BEDROOMS @ 2.25/ UNIT 3 BR= 16 UNITS TOTAL: 16 UNITS @2.25= 36	38	
			2. RETAIL PARKING (   PER 250 SQFT. ) 3,400 SQFT./250 = 13.6	14	
			3. OFFICE PARKING ( I PER 300 SQFT. ) 2,060 SQFT/300 = 686	Г	
			4. LOBBY 4 BOH 9 GF = PARKING (1 PER 300 60FT.) MAIN LOBBY 950 6F. FIRE COMAND 200 6F. MAIL ROOM 600 6F.	6	
			TOTAL: 1,750/300= 5.83		
TOTAL NUMBER OF PROVIDED PARKING SPACES	829 PARKING SPACES	859 PARKING SPACES	385 PARKING SPACES	387 PARKING SPACES	1,246 PARKING SPACES
TOTAL HC PARKING SPACES	REQUIRED	PROVIDED	REQUIRED	PROVIDED	Sec. 1
		22**	TOTAL HC PARKING SPACES 2% of lotal 385 SPACES=7.7	8''	30**
" INCLUDED IN TOTAL					
LOADING SPACES	2 LOADING SF	PACES	2 LOADING SPACES	4 LOADING SPACES	



ZONING CHART

DATE 05-16-14 PROJECT NO 11-025 DRAWING NAME SHEET NO:



SETBACKS	PHASE I (EXISTING)	)		PHAGE    Roposed)		
(A6 PER A-201E)4 CITY OF CORAL GABLE6 ZONING CODE) FRONT (ALHAMBRA CIRCLE); Ø'-Ø" UP TO 45'-Ø" IN HEIGHT IØ'-Ø" OVER 45'-Ø" IN HEIGHT	N/A		0'-0" AT BASE Balconies Struc Mass of Building	CTURE: 1'-0" TO 4'-8" 5: 6'-6" TO 9'-5"		
SIDE STREET ( MINORCA AVENUE ): 15'-@"				CTURE: 5'-0" TO 8'-0"		
INTERIOR SIDE (LA PALMA): 10'-4"	N/A N/A		MASS OF BUILDING: 13'-@" TO 15'-2" 10'-4" AT BASE BALCONIES STRUCTURE: 20'-0" TO 38'-0"			
INTERIOR SIDE (ONE COLUMBUS CENTER): 0'-0"	N/A		Ø'-6" AT BA <del>S</del> E	5: 23'-0" TO 43'-0" CTURE: 1'-10" TO 10'-5" 5: 13'-9" TO 14'-1"		
REAR ABUTTING ALLEY: Ø'-Ø"	N/A			CTURE: 23'-0" TO 72'-0" G: 27'-8" TO 80'-0"		
MIXED USE PERCENTAGES	PHASE	=   =	F	PHASE		OTAL
(A6 PER 4-201DB CITY OF CORAL GABLES	PROVID	ED	P	ROVIDED	REQUIRED	
** REFER TO SHEET A-0.7 OVERALL GROUND FLOOR	RETAIL & OFFICE:	34,730 SQFT.	RETAIL & OFFICE:	5,460 SQFT.	Min. 8% Total Saft. Total F.a.R. Phase 1411: 480,360.16 Saft. X 0.08=	
MIN. 8% TOTAL SQFT. TOTAL FAR: PHASE 1411: 480,000 SQFT. × 0.08 = 38,400 SQFT. (8%)	TOTAL:	34,730 SQFT.	TOTAL:	5,460 SQFT.	38,429 SQFT. (8%)	
GROUND FLOOR BUILDING FRONTAGE	STREET 1	NAME		ED FRONTAGE (50%)	PF	ROVIDED
(AS PER 4-201E.10 CITY OF CORAL GABLES ZONING CODE)	S.W. 37 A	VENUE	220'-9" × 05=	110'-4"	1	191'-9"
MIN. 50% OF LINEAR GROUND FLOOR BUILDING FRONTAGE SHALL INCLUDE RETAIL SALES AND SERVICE, OFFICE, OR RESTAURANT OR PUBLIC	ALHAMBRA PLAZA		634'-5" × Ø5=	317'-2"		608'-1"
REALM LAND AREA USES.	GALIANO STREET		100'-0" × 0.5= 50'-0"			68'-Ø"
	ALHAMBRA	4 CIRCLE	1Ø7'-11" × Ø.5≖	53'-11"		91'-5"
GROUND FLOOR BUILDING FRONTAGE	STREET	NAME		ED FRONTAGE (40%)	PF	ROVIDED

567'-4" X Ø.4=

226'-11"

MINORCA AVENUE

MIN. 40% OF LINEAR GROUND FLOOR BUILDING FRONTAGE SHALL INCLUDE RETAIL SALES AND SERVICE, OFFICE, OR RESTAURANT OR PUBLIC REALM LAND AREA USES.

·· REFER TO SHEET A-0.7 OVERALL GROUND FLOOR





PORTION OF PHASE II OVERLAPPING WITH PHASE I



MIXED USE PERCENTAGES REQUIREMENT AS PER 4-20105 CITY OF CORAL GABLES ZONING CODE	REQUIRED	PROVIDED	
8% OF BUILDING SQUARE FOOTAGE		Commercial Area: Phase 1	
TOTAL FAR. PHASE   4 1: 497,4 1 8QFT. X 008= 39,793 SQFT.		RETAIL 4 OFFI	CE: 34,730 6QFT.
		TOTAL:	34,730 SQFT.
		PHAGE II RETAIL 4 OFFI	CE: 5,460 SQFT
		TOTAL:	5,460 6QFT.
	39,793 SQFT. (8%)	TOTAL PHASE I 4 II	40,190 60,FT,

6TREET	REQUIRED		PROVIDED
SUL 37 AVENUE	220'-9" × 0.5=	11@"-4"	191-9"
ALHAMBRA PLAZA	634'-5" × 0.5=	317'-2"	608'-1"
GALIANO STREET	100'-0" × 0.5=	50'-0"	68'-0"
ALHAMBRA CIRCLE	107'-11" × 05=	53'-11"	9l'-5"
SECONDARY STREET			
	PEOUPED		

ŜTREET	REQUIRED FRONTAGE = 40%	PROVIDED	
MINORCA AVENUE	567'-4" × 0.4•	226*-11"	255'-5"

LEGEND	
	PHASE I 411
-	PLAZA
$\langle \rangle \rangle$	PORTION OF PHASE II OVERLAPPING WITH PHASE
	RETAIL AND OFFICE AREA
	LOBBY AREA



A-0.7

OVERALL GROUND FLOOR SCALE:NTS



			A REGA	
	PLAZA	PHASE    38,856 SF	TOTAL 145,225 OF	ě
⊃ 345 <del>8</del> F		LOT AREA PHAGE I UGED IN PHAGE II = 6516 GF PHAGE II LOT AREA = 32280 GF		
		36,305 SF	113,183 5#	
EL 6):	15,8TI SF	RECREATIONAL FLOOR: 9250 5	48,119 SF	DATE:05-10-11 PROJECT NO: 11-025
		2,395 SF	13,2Ø1 <del>S</del> F	DRAWING NAME
-		ARCADE: 3,668 SF	15,699 9F	SHEET NO
		PASEO: 1283 SF		A-0.8
AN	EAN	N BONUS		

SCALE: NTS

1,41



NOTE: REFER BUILDING ELEVATIONS FOR SIGNS LOCATIONS





NOT PART OF THIS SUBMISSION: IMPROVEMENTS TO BE BE PART OF ART IN PUBLIC PLACES SUBMITTAL



DRAWING NAME

A-0.10

BEHAR·FON

TLUR

ERTUBEHAR

Or

-----

CIRCLE 100 ALHAMBRA CORAL GABLES, I







SCALE: 3/32"=1'-@"



SECOND FLOOR PARKING SCALE: 3/32"=1'-@"









SCALE: 3/32"=1'-@"













OF FLORID AR14339 ROBERT BEHAR AR NO

BEHAR·FONT

COLUMBUS CENTER 100 ALHAMBRA CIRCLE CORAL GABLES, FLORIDA





A-3.2



# COLUMBUS CENTER 100 ALMAMBRA CIRCLE CORAL GABLES, FLORIDA





CALE:NTS





DOUGLAS ROAD ELEVATION SCALE:NTS



#### ORDINANCE NO. 2854

AN ORDINANCE VACATING PORTION OF ALLEY RUNNING EAST/WEST WHICH IS BOUNDED ON THE EAST BY THE SOUTHERLY PROLONGATION OF THE EAST LINE OF LOT 15 AND IS BOUNDED ON THE WEST BY THE SOUTHERLY PROLONGATION OF THE WEST LINE OF LOT 7; AND ALL OF THAT PORTION OF THE ALLEY RUNNING NORTH/SOUTH WHICH IS BOUNDED ON THE NORTH BY THE EASTERLY PROLONGATION OF THE NORTH LINE OF LOT 11 AND BOUNDED ON THE SOUTH BY THE EAS-TERLY PROLONGATION OF THE SOUTH LINE OF LOT **11**, ALL IN BLOCK 22 OF THE "REVISED PLAT OF CORAL GABLES SECTION L", ACCOR-DING TO THE PLAT THEREOF AS RECORDED IN PLAT BOOK 8 AT PAGE 85 OF THE PUBLIC RECORDS OF DADE **COUNTY**, FLORIDA; PROVIDING FOR SUBSTITUTE EASEMENT FOR ALLEY PURPOSES; SETTING FORTH TERMS AND CONDITIONS; PROVIDING EFFECTIVE DATE THIRTY DAYS FROM JUNE 27, 1989; AND REPEALING ALL ORDINANCES INCONSIS-TENT HEREWITH.

WHEREAS, the purpose of this ordinance is to vacate a portion of alley running East/West and all of that portion of alley running North/South lying in Block 22 of the "Revised Plat of Coral Gables Section L", more particularly described hereinafter in Section 1; to provide for substitute easement for public alley purposes as described in Section 2, and

WHEREAS, the Street and Alley Vacation Committee at a meeting held on May 4, 1989, recommended the vacation of such alley, and

BEG2

WHEREAS, the City Commission held a public hearing on May 23, 1989, to consider the vacation of said alley at which hearing all interested persons were afforded the opportunity to be heard, and

WHEREAS, it is felt that the vacation of said alley and the provisions of the substitute easement are in the interest of public health, safety, order, convenience, comfort, prosperity and general welfare,

NOW, THEREFORE, BE IT ORDAINED BY THE COMMISSION OF THE CITY OF CORAL GABLES:

SECTION 1. That a portion of alley running East/West which is bounded on the East by the Southerly prolongation of the East line of Lot 15 and is bounded on the West by the Southerly prolongations of the West line of Lot 7, and all of that portion of alley running North/South which is bounded on the North by the Easterly prolongation of the North line of Lot 11 and bounded on the South by the Easterly prolongation of the South line of Lot 11, all in Block 22, of the "Revised Plat of Coral Gables Section L" (Minorca Avenue and Douglas Road) shall be and it is hereby vacated, abandoned and discontinued for the purpose for which it was dedicated to public use subject to the terms and conditions as set forth hereinafter.

SECTION 2. That the Owner of record, by proper instrument, shall grant an easement to the City of Coral Gables and any and all applicable utility companies for substitute alley purposes to be used for utility purposes including storm and sanitary sewers and for use as a passageway for City vehicles and the general public. Said easement being legally described as follows:

> Begin at the Southwest corner of Lot 7, Block 22, of the "REVISED PLAT OF CORAL GABLES SECTION L" according to the plat thereof as recorded in Plat Book 8 at Page 85 of the Public Records of Dade County, Florida; thence run North 50' 03' 53" East for a distance of 23.01 feet to a point; thence run North 10' 08' 25" East along a line parallel with the West line of said Lot 7 for a distance of 107.00 feet more or less to a Point of Intersection with the North line of said Lot 7, said point being a point on a circular curve concave to the North; thence run along said circular curve to the left having a radius of 290.18 feet through a central angle of 03' 57' 51" for an arc distance of 20.08 feet, and a chord which bears South

> > Page 1 of 3, Ord. No. 2854

84' 44' 25" East to a point on a line; thence run South 10' 08' 26" West along a line parallel with the West line of said Lot 7 for a distance of 140.45 feet to a Point of Intersection with the South right-of-way line of the 20 feet East-West Alley in said Block 22; thence run South 89' 59' 20" West along the South right-of-way line of the said 20 feet East-West Alley for a distance of 35.32 feet to a Point of Intersection with the Southerly projection of the West line of said Lot 7; thence run North 10' 08' 26" East for a distance of 20.32 feet to the Point of Beginning; containing 3,236 square feet, more or less.

SECTION 3. That the easement described hereinabove in Section 2 shall be constructed in accordance with the specifications of the Public Works Department of the City of Coral Gables and the plans for such construction shall be submitted to and shall be subject to approval by the Public Works Department. The permits and inspections for such construction shall be handled in the same manner as the paving for streets and alleys.

SECTION 4. That the City of Coral Gables shall have the right to exercise the same control over the easement described hereinabove in Section 2 as if the same were a dedicated alley and the acceptance and approval of such easement shall in no way relieve the applicant from complying with any and all regulations pertaining to alleys including but not limited to the building, zoning and other applicable regulations.

SECTION 5. That the easement described hereinabove in Section 2 shall at all times be kept free and clear of any and all encroachments and obstructions, including but not limited to motor vehicles, trucks, trailers, debris, stoops, waste containers, and the like, and the City shall have the authority to monitor and enforce the same.

SECTION 6. That a vertical clearance of nineteen (19) feet extending the full length and width of the easement shall be provided above the easement described hereinabove in Section 2. That the Owner shall be able to construct foundations and footings underneath the roadway to be constructed in the easement area, provided that such footings and foundations do not interfere with any storm and sanitary sewers to be installed in the easement area.

SECTION 7. When and if required by the Public Works Department, the easement described hereinabove in Section 2 shall be provided with lighting fixtures which will provide an average level of illumination of two (2) footcandles of lighting over all of the area of the easement, but at no point shall there be less than one (1) footcandle of light. The cost of installing and maintaining the lighting fixtures and lights shall be borne by the applicant. Should the applicant fail to maintain the lighting system to the level of proper illumination and should the applicant fail to correct such deficiency within a period of thirty (30) days upon notification by the City, then the City Manager shall proceed to have such condition remedied and the cost thereof shall be a lien against the property to the same extent and character as are the liens for special assessments or improvements and with the same penalties and with the same rights of collection, foreclosure, sale and forfeiture as obtained in the case of liens for special improvements.

SECTION 8. That the Owner shall be held responsible for the maintenance and repair of the easement described hereinabove in Section 2 and should the Public Works Department, upon inspection, determine that the easement is in disrepair, it shall notify the Owner and if the Owner fails to repair said easement within a period of thirty (30) days, then the City Manager shall proceed to have such condition remedied and the cost thereof shall be a lien against the property to the same extent and character as are the liens for special assessments or improvements and with the same penalties and with the same rights of collection, foreclosure, sale and forfeiture as obtained in the case of liens for special improvements.

SECTION 9. That the costs of removal and/or relocation of any and all utilities, including storm and sanitary sewers, installation of any required drainage facilities, removal of curbs or abandoned concrete approaches and sidewalks, removal of any structures and the paving and construction of the substitute easement hereinabove described shall be borne by the applicant, whose action necessitates such expense.

Page 2 of 3, Ord. No. 2854

SECTION 10. That the use of the vacated property shall be limited to the same uses as to which the adjacent properties are zoned.

SECTION 11. That the reversionary rights to the portion of the alley vacated shall revert to the owners abutting on each side of the vacated alley.

SECTION 12. That the vacation of the alley shall not become effective until such time as all the existing buildings adjacent to the vacated alley have been removed and the substitute easement is conveyed and a foundation permit required for the associated project is granted.

SECTION 13. That this ordinance shall become void if said foundation permits lapse prior to the commencement of construction.

SECTION 14. That the vacation of the alley shall not become effective until such time as the seven (7) conditions - as outlined in the Preliminary Design Review Committee's Minutes of Special Meeting of Wednesday, June 7, 1989 - are met. These conditions are as follows:

- Re-study the proposed service court.
  Improve visibility of traffic entering and exiting parking ramps. Reexamine proximity of entrance/exit of parking ramp on Minorca Avenue and the wall and setback at Galiano Street parking access.
- 3. Conform building facade modifications to the Mediterranean bonus requirements as reviewed and approved by the Board of Architects.
- 4. Study by applicant of the possibility of retaining and incorporating key elements of the art deco Southern Bell Building into the new development, preferably in the proposed park.
- 5. Provide a pedestrian crosswalk across Alhambra Plaza, between the main entrances of the existing Alhambra development and the
- proposed project. 6. Provision by applicant of traffic studies by David Plummer and Associates prepared for the proposed development.
- 7. That handicapped access throughout the development be indicated on the plans, and that it meet Code requirements.

SECTION 15. That the City of Coral Gables, within thirty (30) days after the requirements of this ordinance have been satisfied, shall issue a certificate of recordable form, confirming that the requirements of the ordinance have been satisfied and that the vacation of the alley has become effective.

SECTION 16. That this ordinance shall become effective thirty (30) days from June 27, 1989.

SECTION 17. That all ordinances or parts of ordinances inconsistent or in conflict herewith shall be and they are hereby repealed insofar as there is conflict or inconsistency.

PASSED AND ADOPTED THIS TWENTY-SEVENTH DAY OF JUNE, A. D., 1989

CORRIGAN

ATTEST:

VIRGINIA L. PAUL CITY CLERK



Superintendent of Schools Alberto M. Carvalho Miami-Dade County School Board Perla Tabares Hantman, Chair Dr. Lawrence S. Feldman, Vice Chair Dr. Dorothy Bendross-Mindingall Susie V. Castillo Carlos L. Curbelo Dr. Wilbert "Tee" Holloway Dr. Martin Karp Dr. Marta Pérez Raquel A. Regalado

March 14, 2014

#### VIA ELECTRONIC MAIL

Mr. Robert Behar, Architect Behar - Font & Partners, P.A. 4533 Ponce de Leon Boulevard Coral Gables, Florida 33146

reception@beharfont.com

#### RE: PUBLIC SCHOOL CONCURRENCY DETERMINATION COLUMBUS CENTER – DR-13-08-0696 LOCATED AT 100 ALHAMBRA CIRCLE SP0314022700731 - FOLIO NO.: 0341080072020 AND 0341080072010

Dear Applicant:

Pursuant to State Statutes and the Interlocal Agreement for Public School Facility Planning, the above-referenced application was reviewed for compliance with Public School Concurrency. Accordingly, attached please find the School District's Concurrency Determination. As you will note, the applicable Level of Service (LOS) standards of 100% Florida Inventory of School Housing (FISH) have been met at the three school levels and as such, capacity has been reserved for a one year period, under Master Concurrency Number **MA0314022700731**.

The reservation term for this Site Plan will expire on **February 28, 2015**. Concurrency reservation may be extended for additional one-year periods, provided: 1) City of Coral Gables confirms the application is still valid; 2) you request an extension at least 120 days prior to the expiration date, via email address <u>concurrency@dadeschools.net</u>; and 3) the total reservation period does not exceed six years from the original effective date of this certificate.

Failure to request an extension at least 120 days prior to the expiration date will result in revocation of the reservation, and a new application must be submitted. Extensions will be granted, upon payment of the corresponding review fee and acknowledgement from the local government. The reservation period may not exceed the term of the development approval issued by the City of Coral Gables.

Should you have any questions, please feel free to contact me at 305-995-4501.

Ivan M. Rodriguez, R.A. Director I

IMR:ir L-487

Enclosure

cc: Ms. Ana Rijo-Conde Mr. Michael A. Levine Ms. Vivian G. Villaamil City of Coral Gables School Concurrency Master File

> Ana Rijo-Conde, Deputy Chief Facilities & Eco-Sustainability Officer • Planning, Design & Sustainability School Board Administration Building • 1450 N.E. 2nd Ave. • Suite 525 • Miami, FL 33132 305-995-7285 • 305-995-4760 (FAX) • arijo@dadeschools.net

	Miami Dade Co	unty Public Sc	hools				ander der gehannte
	м	iami-Dao	le County	Public S	chools		
	ă.	Concurre	ncy Manag	ement Sys	tem		
ate A	Application Number: pplication Received: f Application:	School Co SP0314	022700731 014 12:34:22	Determin Lo PM LG			
pplica ddres 1aster	ant's Name: is/Location: · Folio Number: nal Folio Number(s):	100 Alh 034108	– <u>us Center</u> <u>ambra Circle</u> 0072020 0072010, 034	1080072010,		8	
ROPO	SED # OF UNITS	<u>200</u>			*		
INGL	E-FAMILY DETACHED UNITS	5: <u>0</u>		5			
INGL	E-FAMILY ATTACHED UNITS	5: <u>0</u>					
1ULTI	FAMILY UNITS:	<u>200</u>					
onvers							
ene u		CONCURR	ENCY SERVIC				
CSA Id	Facility Name		Net Available Capacity	e Seats Required	Seats Taken	LOS Met	Source Type
5401	SUNSET EL - GEORGE CAR CORAL GABLES EL	VER EL -	166	10	10	YES	Current CSA
962	CORAL GABLES PREPARAT ACADEMY (MID COMP)	ORY	1	6	1	NO	Current CSA
962	CORAL GABLES PREPARAT ACADEMY (MID COMP)	ORY	0	5	0	NO	Current CSA Five Year Plan
6741	PONCE DE LEON MIDDLE		108	5	5	YES	Current CSA
7071	CORAL GABLES SENIOR	- 2011/0 0 12 114	-452	7	0	NO	Current CSA
7071	CORAL GABLES SENIOR		153	7	7	YES	Current CSA Five Year Plan
	Mar Carlos	ADJACE	NT SERVICE	AREA SCHOOL	S		
	*An Impact reduction o	f <u>21.13%</u> inc	luded for char	ter and magn	et schools (	Schools	of Choice).
MEET Gover	S has conducted a public sc (Concurrency Met) all ap nment's Educational Elemer ng in Miami-Dade County.	plicable LOS	Standards for	a Final Devel	opment ord	er as ad	opted in the local
Num	Der:	3140227007 B/2014 2:00:		Total Numbe Units:	20		2:00:16 DM
	1/2			Expiration Da pior: 7	ne. 2/		5 2:00:16 PM
	4 MD	CPS Administ	A	X			ithorized Signature

# **Kimley Worn**

May 5, 2014

Ms. Yamilet Senespleda, P.E. City of Coral Gables Coral Gables, FL

#### **RE: Traffic Impact Study Response to Comments**

We have received comments provided by the City of Coral Gable's traffic engineering consultant for the 100 Alhambra Circle traffic study on April 9, 2014. It should be noted that this response to comments only includes the traffic related comments. We offer the following responses:

1. New traffic counts (TMC's conducted in July are not accepted by the City).

Response: New traffic counts were collected in April 2014. The revised traffic impact analysis has been updated to reflect the new counts and peak season factor for the two intersections that previously utilized TMC's from July.

2. Committed developments (33 Alhambra Circle) have to be included in the analysis.

Response: Per our meeting on April 23, 2014, a traffic study has not been submitted for this project. Therefore, it was not included as a committed development.

3. A full updated site plan has to be included in the traffic study Appendix to better understand the traffic circulation and the parking garage location.

Response: An updated site plan has been included in Appendix A of the revised traffic impact study. In addition, a signs and pavement marking plan has been included in Appendix A to better illustrate the traffic circulation and parking garage location on site.

4. Trip distribution does not show the trips assigned to the alley entering from and exiting to Galiano Street.

Response: The trip distribution has been updated to show trips assigned to the alley entering from and existing to Galiano Street. The updated trip distribution can be found in the revised traffic impact analysis.

Please contact me at (954) 535-5100 or john.mcwilliams@kimley-horn.com should you have any questions.

Sincerely,

John J. McWilliams, P.E.

954 535 5100

# Kimley » Horn

- Provide adequate turning radius for all vehicles that would normally use the alley and the dedicated easement.
   Please refer to the Proposed Circulation Plan (EX-4) for vehicle maneuverability throughout the public alley.
- Must comply with City of Coral Gables Public Works sight distance requirements at all driveway and intersections including the alley.
   Please refer to the Circulation Plan (EX-4) for applicable site distances for all driveways and intersections per City of Coral Gables Public Works Manual.

#### Planning and Zoning Comments:

 Signage Plan (Sec. 3-505.D.3.h). Submit signage plan for review to determine compliance with Zoning Code regulations. Include in signage plan way finding signage and ATM location signage.

Please refer to Exhibit 2 and 3 for the Existing and Proposed Signage and Marking Plans. All signs, existing and proposed are depicted.

- Utilities Plan (Sec. 3-505.D.3.I) and Statement (Sec. 3-505.D.3.i). Submit utilities plan for entire PAD site. Indicate in plan that all utilities will be installed underground. Submit letters/statements from all utilities indicating their compliance with proposal.
   Please refer to the Conceptual Utility Plan (EX-1). Note No. 2 indicates all utilities will be installed underground. No overhead utilities are located on or around the site that will need to be converted to underground facilities.
- Circulation Plans (Sec. 3-505.D.3.b). Submit circulation plans for the following types of systems: pedestrian, vehicular, bicycle, and public transit (buses and trolley).
  Please refer to exhibits 3, 4 and 5 as well as Accessibility Floor Plan exhibit created by Behar Font for proposed site circulation.

Please accept the revised plans and comments for approval and if you require any additional information or further clarification please do not hesitate to contact me at 954-535-5138. Thank you for your assistance with this project.

Sincerely,

1 tolo

Kimley-Horn and Associates Christopher Falce, P.E.

Cc: Robert Behar – Behar Font

# **Revised Traffic Impact Analysis**

# **100 Alhambra Circle Coral Gables, Florida**





Revised May 2014 September 2013 043581000 Revised Traffic Impact Analysis

# 100 Alhambra Circle Coral Gables, Florida

Prepared for:

USRE Holdings, LLC Miami, Florida

Prepared by:



©2014 Kimley-Horn and Associates, Inc. Revised May 2014 September 2013 043581000

> John J. McWilliams, P.E. Florida Registration Number 62541 Kimley-Horn and Associates, Inc. 600 North Pine Island Road, Suite 450 Plantation, FL 33411



## TABLE OF CONTENTS

#### <u>Page</u>

INTRODUCTION
PROJECT TRAFFIC
Existing and Proposed Land Uses 3
Project Access 3
Trip Generation
Internal Capture Volumes 4
Pass-By Capture Volumes 4
Net New Project Trips 4
Trip Distribution and Assignment6
EXISTING TRAFFIC 10
FUTURE BACKGROUND TRAFFIC 12
Background Area Growth12
FUTURE TOTAL TRAFFIC
INTERSECTION CAPACITY ANALYSIS 17
CONCLUSIONS



## LIST OF FIGURES

#### Page

Figure 1: Site Location Map	. 2
Figure 2: Peak Hour Project Trip Distribution	. 7
Figure 3: Pass-By Trip Distribution	. 8
Figure 4: Peak Hour Trip and Pass-By Assignment	. 9
Figure 5: 2013 Existing Peak Hour Traffic	11
Figure 6: Background Peak Hour Traffic	14
Figure 7: Future Peak Hour Traffic	16

## LIST OF TABLES

#### Page

Table 1: Peak Hour Trip Generation	. 5
Table 2: Cardinal Trip Distribution	. 6
Table 3: Intersection Capacity Analysis	18

## LIST OF APPENDICES

Site Plan
Project Trip Generation
Cardinal Distribution
Traffic Data
Background Area Growth
Volume Development Worksheets
Intersection Capacity Analyses

### INTRODUCTION

USRE Holdings, LLC is proposing a mixed-use development consisting of residential and retail uses located at 100 Alhambra Circle in the City of Coral Gables. Currently, the area proposed for development is vacant. The proposed development will consist of a 188-unit high-rise apartment building and 3,000 square feet of specialty retail space. Access to the site is provided through one (1) full-access driveway along Minorca Avenue and one (1) full-access driveway along the alley on the south side of the site, accessed from Galiano Street. A project location map is included as Figure 1 and a site plan is provided in Appendix A. The project is expected to be completed by year 2017.

The roadways within the immediate vicinity of the site include Alhambra Circle, Minorca Avenue, Galiano Street, and South Douglas Road/Southwest 37<sup>th</sup> Avenue. Minorca Avenue is a two-lane undivided east-west roadway with on-street parking. Alhambra Circle is a two-lane divided roadway with on–street parking. Galiano Street is a two-lane undivided north-south roadway with on-street parking. South Douglas Road/Southwest 37<sup>th</sup> Avenue is a four-lane undivided north-south roadway.

Kimley-Horn and Associates, Inc. has completed this traffic impact analysis to assess the project's impact on the surrounding roadway network and determine if adequate capacity is available to support future traffic volumes. This report summarizes the data collection, project trip generation and distribution, and operational analyses. This report has been revised to account for the City comments dated April 9, 2014.



© 2014

Kimley-Horn and Associates, Inc. Figure 1 Site Location Map 100 Alhambra Circle Coral Gables, Florida



## **PROJECT TRAFFIC**

Project traffic used in this analysis is defined as the vehicle trips expected to be generated by the project and the distribution and assignment of that traffic over the study roadway network.

#### Existing and Proposed Land Uses

The project site is currently vacant. The proposed development will consist of a 188-unit highrise apartment building and 3,000-square-feet of specialty retail.

#### Project Access

Proposed access to the site is provided through one (1) full-access driveway along Minorca Avenue and one (1) full-access driveway along the alley on the south side of the site, accessed from Galiano Street. A site plan is provided in Appendix A.

#### Trip Generation

Trip generation calculations for the proposed development were performed using the Institute of Transportation Engineer's (ITE's) *Trip Generation*, 9<sup>th</sup> Edition. ITE Land Use Code (LUC) 222 (High-Rise Apartment) was utilized for the residential component of the proposed development and ITE LUC 826 (Specialty Retail) was utilized for the retail component. Table 1 summarizes the project's forecast trip generation for the daily, weekday A.M. and weekday P.M. peak hours of adjacent street traffic. As shown in Table 1, this project is expected to generate 57 gross trips during the A.M. peak hour and 101 gross trips during the P.M. peak hour. Detailed trip generation information is included in Appendix B.

#### Internal Capture Volumes

Internal capture is expected between the complementary land uses within a project. Internal capture trips are trips made among the on-site uses, which in the case of this project are trips between the apartment units and the proposed retail development. Internal capture trips for the project were determined based upon methodology contained in the ITE's, *Trip Generation Handbook*, 2<sup>nd</sup> Edition June 2004. The applied internal capture percentages are presented in Table 1 and detailed calculations are contained in Appendix B.

#### Pass-By Capture Volumes

A portion of the driveway volumes at the project site will be the result of new trips on the roadway network. The remainder of the driveway volumes will be trips from the adjacent traffic passing by the site (pass-by capture trips). Pass-by trips are intermediate stops on the way from an origin to a primary trip destination. Pass-by capture rates were estimated using ITE Land Use 820: Shopping Center. The pass-by percentages were determined based on information provided in the ITE's, *Trip Generation Handbook*, 2<sup>nd</sup> Edition June 2004. The pass-by capture rates expected for the redevelopment are indicated in Table 1. Detailed calculations and figures depicting pass-by project trips are contained in Appendix B.

#### Net New Project Trips

Net new project trips are equal to the gross project trips minus the internal capture, pass-by capture, and existing development trips. The net new project trips represent additional vehicles on the roadway network. As shown in Table 1, this project is expected to generate 57 net new trips during the A.M. peak hour and 87 net new trips during the P.M. peak hour.


		Т	able 1: P	eak Ho	ur Trip G	ieneratio	n					
Land Uses	ITE	Scale	Gross	Project	Trips	Inte Capt		Pass Capt	'	Net Ne	w Proje	ct Trips
	Code		Enter	Exit	Total	%	Trips	%	Trips	Enter	Exit	Total
		Weekda	ıy A.M. Pe	ak Hour	[Weekda	ıy P.M. Ped	ık Hour]					
High-Rise Apartment	222	188 d.u.	14 [44]	43 [28]	57 [72]	0.0% [4.2%]	0 [3]	0.0% [0.0%]	0 [0]	14 [42]	43 [27]	57 [69]
Specialty Retail Center	826	3,000 s.f.	(0) [13]	(0) [16]	(0) [29]	(0.0%) [10.3%]	(0) [3]	(0.0%) [34.0%]	(0) [8]	(0) [8]	(0) [10]	(0) [18]
Tot	al		(14) [57]	(43) [44]	(57) [101]	-	0 [6]	-	0 [8]	(14) [50]	(43) [37]	(57) [87]

### **Trip Distribution and Assignment**

The likely distribution of project traffic was forecasted for the trips expected to be generated by the proposed development. The trip distribution was based on a cardinal trip distribution for the project site's traffic analysis zone (TAZ 1035) obtained from interpolating the *2005 Cost Feasible Plan* and *2035 Cost Feasible Plan* travel demand model developed by the Miami-Dade Metropolitan Planning Organization. The cardinal trip distribution for TAZ 1035 interpolated for the year 2017 is provided in Table 2.

Table 2: Cardinal	Trip Distribution
Cardinal Direction	Percentage of Trips
North-Northeast	12.35%
East-Northeast	16.15%
East-Southeast	3.81%
South-Southeast	8.71%
South-Southwest	15.99%
West-Southwest	17.12%
West-Northwest	10.59%
North-Northwest	15.28%
Total	100.00%

The detailed cardinal distribution is included in Appendix C. Figure 2 and 3 present the project's trip distribution and pass-by distribution and Figure 4 presents the project's traffic assignment for the weekday A.M. and P.M. peak hours.



© 2014





## **EXISTING TRAFFIC**

A.M. peak period (7:00 to 9:00 A.M.) and P.M. peak period (4:00 to 6:00 P.M.) turning movement counts were collected on September 4, 2013 (Wednesday) at the following four intersections:

- Alhambra Circle and Galiano Street
- Alhambra Plaza and Galiano Street
- Alhambra Plaza and Douglas Road/SW 37<sup>th</sup> Avenue
- Minorca Avenue and Douglas Road/SW 37<sup>th</sup> Avenue

A.M. and P.M. peak hour turning movement counts were collected on April 24, 2014 (Thursday) at the following intersections:

- Alhambra Circle and Minorca Avenue
- Alhambra Circle and Douglas Road/SW 37<sup>th</sup> Avenue

The volumes were collected in 15-minute intervals and the peak hour was determined for each intersection. The Florida Department of Transportation (FDOT) peak season conversion factor (PSCF) was applied to the traffic counts to adjust the traffic to peak season volumes. The appropriate peak season conversion factor for the counts collected in April is 1.01 and for the counts collected in September is 1.02. The turning movement counts and FDOT peak season factor category reports are included in Appendix D. Figure 5 presents the existing turning movement volumes at the study intersections during the weekday A.M. and P.M. peak hours.





## **FUTURE BACKGROUND TRAFFIC**

Future background traffic conditions are defined as expected traffic conditions on the roadway network in the year 2017 without the construction of the proposed project. Future background traffic volumes used in the analysis are the sum of the existing traffic and an additional amount of traffic generated by growth in the study area. Figure 6 presents the year 2017 peak hour background traffic volumes during the weekday A.M. and P.M. peak hours.

### **Background Area Growth**

Future traffic growth on the transportation network was determined based upon historic growth trends at nearby FDOT traffic count stations and based upon the Miami-Dade Metropolitan Planning Organization's (MPO) projected 2005 and 2035 model network volumes. FDOT count stations referenced in this analysis include:

- Count Station #2534 located on SR 972/Coral Way, 200 feet east of SW 37th Ave.
- Count Station #0024 located on SR 953/LeJeune Road, 200 feet south of Coral Way/SR 972
- Count Station #0025 located on SR 953/LeJeune Road, 200 feet south of SW 8<sup>th</sup> St./SR 90

The FDOT historic growth rate analysis yielded a -0.45 percent (-0.45%) growth rate over the most recent ten (10) year period and a 0.22 percent (0.22%) growth rate over the most recent five (5) year period.



Additionally, the MPO 2005 and 2035 model network volumes were examined to determine the growth trend for the roadway segments near the site location. MPO model roadway segments referenced in this analysis include:

- South Douglas Road/SW 37<sup>th</sup> Avenue
- Ponce De Leon Boulevard
- Alhambra Circle

The MPO model growth rate analysis yielded a 0.72 percent (0.72%) growth rate. To provide for a conservative analysis, a 1.0 percent (1.0%) growth rate was applied annually to the existing traffic volumes to attain future (2017) background traffic conditions. The worksheets used to analyze the historic growth trends are included in Appendix E.



© 2014



### FUTURE TOTAL TRAFFIC

Future total traffic conditions are defined as the expected traffic conditions in the year 2017 after the opening of the project. Total traffic volumes considered in the analysis for this project are the sum of the year 2017 background traffic volumes and the expected project traffic volumes. Figure 7 presents the future traffic volumes for the weekday A.M. and P.M. peak hours. Volume development worksheets for the study intersections are included in Appendix F.





### **INTERSECTION CAPACITY ANALYSIS**

The operating conditions were analyzed for the study intersections. Three (3) scenarios (existing conditions, future background conditions, and future total conditions) were analyzed using *Trafficware's SYNCHRO 8.0 Software*, which applies methodologies outlined in the *Highway Capacity Manual, 2010 Edition*. Synchro worksheets for the study intersections are included in Appendix H. A summary of the intersection analyses for the A.M. and P.M. peak hours is presented in Table 3. As this table indicates, all the study intersections are expected to operate at adopted levels of service (LOS D or better) overall during the A.M. and P.M. peak hours with exception of the minor street stop-controlled eastbound approach at the intersection of Alhambra Circle and South Douglas Road/SW 37<sup>th</sup> Avenue.

The minor street stop-controlled eastbound approach at the intersection of Alhambra Circle at South Douglas Road/SW 37<sup>th</sup> Avenue is expected to operate at LOS F during the A.M. and P.M. peak hours under existing, future background, and future total conditions. This result is common during peak periods where a high traffic volume free-flowing major street intersects with a stop-controlled minor street.



	Table 3: Int	tersection Cap	acity Analysis	;		
		Overall		Approa	ch LOS	
Intersection	Traffic Control	LOS/Delay	EB	WB	NB	SB
Exist	ing Conditions (Backgro	und Conditions) [F	uture Total Condi	itions Scenario]		
		A.M. Peak Ho				
Alhambra Circle and Galiano Street	All-Way Stop-Controlled	C/16.0 (C/17.2) [C/17.8]	A/9.2 (A)/9.3 [A]/9.5	C/20.5 (C)/22.6 [C]/23.6	B/13.3 (B)/13.8 [B]/14.0	B/10.6 (B)/10.9 [B]/11.1
Alhambra Plaza and Galiano Street	Signalized <sup>(3)</sup>	B/12.0 (B/12.0) [B/12.1]	A/3.0 (A)/3.1 [A]/3.1	A/6.3 (A)/6.0 [A]/6.1	D/40.3 (D)/40.5 [D]/40.4	D/36.0 (D)/35.8 [D]/35.8
Alhambra Plaza and South Douglas Road/SW 37 <sup>th</sup> Avenue	Signalized <sup>(3)</sup>	C/26.2 (C/26.2) [C/26.2]	F/>80.0 (F)/>80.0 [F]/>80.0	F/>80.0 (F)/>80.0 [F]/>80.0	A/7.3 (A)/7.9 [A]/7.9	B/13.8 (B)/18.3 [B]/18.3
Minorca Avenue and South Douglas Road/SW 37 <sup>th</sup> Avenue	Signalized	A/5.4 (A/5.5) [A/5.8]	C/30.9 (C)/32.9 [C]/32.6	N/A	A/0.7 (A)/0.7 [A]/0.8	A/8.6 (A)/8.6 [A]/9.0
Alhambra Circle and Minorca Avenue	Two-Way Stop-Controlled	(1)	B/14.1 (B)/14.5 [B]/14.9	C/19.2 (C)/20.2 [C]/22.5	(2)	(2)
Alhambra Circle and South Douglas Road/SW 37 <sup>th</sup> Avenue	One-Way Stop-Controlled	(1)	F/>50 (F)/>50 [F]/>50	N/A	(2)	(2)
Minorca Avenue and Project Driveway	One-Way Stop-Controlled	(1)	(2)	(2)	[A]/9.9	[N/A]
Galiano Street and Alley	One-Way Stop-Controlled	(1)	[N/A]	[B]/10.7 <sup>(3)</sup>	(2)	(2)
		P.M. Peak Ho				
Alhambra Circle and Galiano Street	All-Way Stop-Controlled	C/16.5 (C/17.9) [C/19.1]	B/10.3 (B)/10.5 [B]/10.8	C/23.4 (D)/26.3 [D]/28.7	B/12.6 (B)/13.1 [B]/13.4	B/12.5 (B)/13.2 [B]/13.6
Alhambra Plaza and Galiano Street	Signalized <sup>(3)</sup>	C/26.0 (C/27.3) [C/28.4]	A/5.0 (A)/5.3 [A]/5.4	A/7.3 (A)/7.7 [A]/7.8	F/>80.0 (F)/>80.0 [F]/>80.0	C/32.4 (C)/32.0 [C]/32.0
Alhambra Plaza and South Douglas Road/SW 37 <sup>th</sup> Avenue	Signalized <sup>(3)</sup>	C/23.0 (C/23.1) [C/23.1]	F/>80.0 (F)/>80.0 [F]/>80.0	F/>80.0 (F)/>80.0 [F] />80.0	A/8.3 (A)/8.9 [A]/8.9	B/12.1 (B)/15.0 [B]/15.0
Minorca Avenue and South Douglas Road/SW 37 <sup>th</sup> Avenue	Signalized	A/5.5 (A/5.7) [A/6.1]	D/37.1 (D)/39.8 [D]/40.3	N/A	A/0.8 (A)/0.8 [A]/0.8	A/6.8 (A)/6.9 [A]/7.3
Alhambra Circle and Minorca Avenue	Two-Way Stop-Controlled	(1)	B/12.2 (B)/12.4 [B]/13.3	C/20.6 (C)/21.8 [D]/25.7	(2)	(2)
Alhambra Circle and South Douglas Road/SW 37 <sup>th</sup> Avenue	One-Way Stop-Controlled	(1)	F/>50.0 (F)/>50.0 [F]/>50.0	N/A	(2)	(2)
Minorca Avenue and Project Driveway	One-Way Stop-Controlled	(1)	(2)	(2)	[B]/10.5	[N/A]
Galiano Street and Alley	One-Way Stop-Controlled	(1)	[N/A]	[B]/10.3 <sup>(3)</sup>	(2)	(2)

Overall intersection LOS is not defined, as intersection operates under stop-control conditions. Approach operates under free-flow conditions. LOS is not defined. HCM 2010 does not provide LOS result; therefore, HCM 2000 results were provided

(2) (3)

Notes:



### CONCLUSIONS

This analysis has addressed traffic-related impacts associated with the proposed 100 Alhambra Circle mixed-use project consisting of a 188-unit high-rise apartment building and a 3,000 square-foot specialty retail store. Based on the results of the analysis, the following is concluded:

- The project is expected to generate 57 new trips during the A.M. peak hour, and 87 new trips during the P.M. peak hour.
- Intersection capacity analyses indicate that the study intersections are expected to operate at adopted levels of service (LOS D or better) during the A.M. and P.M. peak hours under all analysis conditions with exception of the minor street stop-controlled eastbound approach at the intersection of Alhambra Circle and South Douglas Road/SW 37<sup>th</sup> Avenue. The minor street stop-controlled eastbound approach at the intersection of Alhambra Circle as 20<sup>th</sup> Avenue. The minor street stop-controlled eastbound approach at the intersection of Alhambra Circle at South Douglas Road/SW 37<sup>th</sup> Avenue is expected to operate at LOS F during the A.M. and P.M. peak hours under existing, future background, and future total conditions. This result is common during peak periods where a high traffic volume free-flowing major street intersects with a stop-controlled minor street.

APPENDIX A: Site Plan







DATE: 04-19-13 PROJECT NO: 11-025 DRAWING NAME: SHEET NO:



APPENDIX B: Project Trip Generation

# **TRIP GENERATION**

#### PROPOSED AM PEAK HOUR TRIP GENERATION

	ITE TRIP GENERATI	ON CHARA	CTERIS	STICS			TIONAL BUTION		GROS VOLUM			RNAL TURE	DRI	VEWAY	TRIPS		S-BY FURE	EX	NET NEW	
	Land Use	ITE Edition	ITE Code	Scale	ITE Units	Per In	cent Out	In	Out	Total	Percent	IC Trips	In	Out	Total	Percent	PB Trips	In	Out	Total
1	High-Rise Apartment	9	222	188	du	25%	75%	14	43	57	0.0%	0	14	43	57	0.0%	0	14	43	57
2	Specialty Retail Center	9	826	3	ksf	0%	0%	0	0	0	0.0%	0	0	0	0	0.0%	0	0	0	0
3																				
4																				
5																				
6																				
7																				
8																				
9																				
10																				
1																				
12																				
13																				
14																				
15													<u> </u>							$\vdash$
	LUC						Total:	14	43	57			14	43	57			14	43	57

 LUC
 RATE/EQUATION

 222
 LN(Y) = 0.99\*LN(X)+-1.14

 826
 ASSUMED CLOSED

### PROPOSED PM PEAK HOUR TRIP GENERATION

ITE TRIP GEN	IERATION CHAR	ACTERI	STICS			TIONAL BUTION		GROS VOLUM			RNAL TURE	DRI	VEWAY	TRIPS		S-BY TURE	EX	NET NEW FERNAL T	
Land Use	ITE Edition	ITE Code	Scale	ITE Units	Per In	cent Out	In	Out	Total	Percent	IC Trips	In	Out	Total	Percent	PB Trips	In	Out	Total
1 High-Rise Apartment	9	222	188	du	61%	39%	44	28	72	4.2%	3	42	27	69	0.0%	0	42	27	69
2 Specialty Retail Center	9	826	3	ksf	44%	56%	13	16	29	10.3%	3	12	14	26	34.0%	8	8	10	18
3																			1
4																			
5																			
6																			
7																			
8																			
9																			
0																			
1																			
2																			
3																			
4																			
5																			
						Total:	57	44	101	5.9%	6	54	41	95	8.4%	8	50	37	87
<u>LUC</u> 222			EQUATION	<u>l</u>															
222		Y=0.32	2*(X)+12.3																

Y=0.32\*(X)+12.3 Y=2.4\*(X)+21.48

826

APPENDIX C: Cardinal Distribution



Image: PFECENT         11.70         13.80         5.82         5.02         13.80         22.32         15.16         15.20           Image: PFECENT         15.31         15.32         7.47         8.32         13.64         13.73         3.38         13.75         13.83         13.75         13.84         13.73         13.84         13.75         13.84         13.75         13.84         13.75         13.84         13.75         13.84         13.75         13.84         13.85	MIAMI-DADE 2005	5 DIRECTIONAL DISTRIBUT	TION SUMMAR	Y								
Image: Process of the second	OR	IGIN ZONE		CARDINA	L DIRECTI	ONS						
1000         1070         189         138 </th <th>County TAZ</th> <th>Regional TAZ</th> <th></th> <th>NNE</th> <th>ENE</th> <th>ESE</th> <th>SSE</th> <th>SSW</th> <th>wsw</th> <th>WNW</th> <th>NNW</th> <th>TOTAL</th>	County TAZ	Regional TAZ		NNE	ENE	ESE	SSE	SSW	wsw	WNW	NNW	TOTAL
Image: PFECENT         11.70         13.80         5.82         5.02         13.80         22.32         15.16         15.20           Image: PFECENT         15.31         15.32         7.47         8.32         13.64         13.73         3.38         13.75         13.83         13.75         13.84         13.73         13.84         13.75         13.84         13.75         13.84         13.75         13.84         13.75         13.84         13.75         13.84         13.85												
1010         3710         FINPS         987         948         447         786         787         480         787         481         513         153         154         154         153         154         154         153         154         154         153         154         154         153         155         155         155         155         155         155         155         150         154         153         140         156         153         140         156         153         140         156         153         140         156         156         151         150         15	1009	3709										475
Image: Product in the system of the												
1011         3711         PRCMT         188         137.         186.         138.         122.         123.         138. <t< td=""><td>1010</td><td>3710</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>5,730</td></t<>	1010	3710										5,730
Image: biolog         17.26         9.24         8.38         10.24         9.77         10.33         27.74         5.78         10.33           1013         377.13         17.87         5.78         5.76         5.71         3.10         3.73         3.78         3.78           1013         377.13         17.87         5.78         5.72         4.00         3.83         4.10         3.64         1.53         3.75           1014         377.41         17.87         5.99         5.71         4.00         5.71         5.72         4.00         2.72         8.06         4.22           1015         377.15         7.74         1.45         1.03         9.68         8.51         0.06         1.11         1.47         1.47         1.47         1.47         1.47         1.47         1.47         1.44         1.44         1.10         8.78         1.82         1.88         1.47         1.44         1.44         1.10         8.78         1.82         1.81         1.43         1.41         1.49         1.48         1.41         1.43         1.43         1.43         1.43         1.43         1.43         1.43         1.43         1.43         1.43         1.43 <td></td>												
1012         3712         IPPS         326         647         331         2447         510         544         372         713         388           1013         3713         IPPS         398         516         250         195         321         400         363         7.37         12         15         63.4         15.33         3         37.37         12         15         63.4         15.33         3         4.40         362         464         470         2.22         80.6         4.23           1014         3717         IPPS         474         649         383         360         654         652         357         647         4.41           1016         3716         IPPS         114         1497         1095         612         1256         987         7.32         168.2         899         6.33           1016         3716         IPPS         114         1497         1095         612         1256         987         7.32         168.4         149.4         110.4         149.7         149.5         127.7         133.5         142.0         153.0         110.2         110.2         110.2         110.2         110.2	1011	3711										1,777
1013         3731.31         14001         946         13.33         1401         346         140         2.67           1014         3747.31         1787         338         130         395         7.29         12         15         6.44         15.33           1016         37141         1787         599         851         400         362         464         470         222         806         4.23           1015         37151         1787         474         449         388         300         654         523         367         607         4.12           1016         37161         1787         111.4         307         1096         523         1582         898         14.73           1010         37171         1707         1204         16.73         13.24         6.84         11.03         15.78         8.39         10.37         14.48           1010         37171         1705         200         322         1040         10.277         13.13         14.04         13.03         13.13         14.14         14.14         14.04         14.04         14.04         14.04         14.04         14.04         14.04         14.04												
1013         3713         TMPS         138         516         250         132         231         135         410         232         135         648         133           1014         3714         TMPS         1398         551         430         362         464         470         622         806         4.23           1015         3715         TMPS         141.1         649         388         360         654         552         837         667         4.12           1016         3715         TMPS         11.1         1477         1275         8.69         4.40         11.08         8.08         6.33           1010         3715         TMPS         1224         16.61         13.08         11.08         8.08         8.08         1.08         8.08         1.08         8.08         1.08         8.08         1.08         8.08         1.08         8.08         1.08         1.08         8.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08         1.08	1012	3712										3,883
Image: marging state         Image: ma												
1014         3714 TRPS         599         851         410         362         464         470         272         806         4.23           1015         3715 TRPS         1415         20.1         9.88         550         153         1532         837         607         4.12           1016         2716 TRPS         1114         4477         1056         641         1256         987         723         1662         8.94           1017         3717 TRPS         900         622         353         532         1666         1656         668         683         6.33           1017         3717 TRPS         900         622         353         532         1664         1037         14.14           1018         3718 TRPS         552         777         203         315         444         307         422         666         3.67           1019         3719 TRPS         270         448         200         140         422         133         70         2.12           1010         3720 TRPS         301         474         122         134         103         1313         1313         1314         141         136         1313	1013	3713										2,674
PERCINT         14.15         20.1         9.88         8.55         10.99         11.1         6.42         19.04           1016         37116         FIPS         11.1         15.75         8.69         8.74         15.82         15.82         18.82         10.16         37316         10.82         3997         7.33         10.56         8.84         10.35         10.88         38.35         10.86         18.88         10.35         10.36         10.35         10.36         10.35         10.36         10.35         10.36         10.35         10.36         10.35         10.36												
1015         3715 [FIPS         474         649         358         360         654         652         367         647           1016         3716 [FIPS         1114         1497         1095         612         1256         987         152         894         1633         1226         683         1404         11.03         808         1858           1017         3717 [FIPS         900         823         532         1306         1057         684         693         633           1018         3718 [FIPS         552         777         28         814         337         242         666         3.67           1019         3713 [FIPS         522         713         816         11.43         10.34         633         370         242         666         3.67           1019         3719 [FIPS         200         476         124         200         404         420         860         173         370         212         131         343         1601         335         507         130         430         420         420         430         420         420         430         430         430         430         431         431	1014	3/14										4,234
PERCENT         11.5         15.7         8.69         8.74         15.87         15.82         5.91         14.73         1.62           1016         3716         FRECENT         12.45         16.73         12.24         6.84         14.04         11.03         8.06         18.58           1017         3717         FRECENT         14.2         13.06         5.57         206         16.67         10.79         14.18           1018         3718         FRECENT         15.22         777         200         315         434         397         242         666         3.67           1019         3713         FRECENT         12.02         30.9         4.81         10.43         12.43         8.60         13.43         13.83         307         2.12           PERCENT         11.80         1.85         4.44         2.60         3.83         2.61         13.83         1.61         10.33         15.64         3.00         3.00         4.73         1.15         1.15.3         1.15.9         1.15.3         1.15.9         1.15.9         1.15.9         1.15.9         1.15.9         1.15.9         1.14.8         1.16.67         1.13.3         1.15.9         1.15.9         <												
1016         3716 [PHPS         1114         1497         1105         612         122.6         927         123.6         18.58           1011         3717 [PHPS         900         828         33.3         532         1066         10.75         18.88         99         6.33           1018         3718 [PHPS         552         777         260         315         434         397         422         666         3.67           1019         3718 [PHPS         522         777         260         315         434         397         422         666         3.67           1019         3718 [PHPS         120         73         8.86         11.48         10.43         12.88         6.30         7.21         11.33         1.66         5.37         3.68         6.39         1.32         11.31         1.46         1.57         1.33         1.51         1.46         1.53         1.51         1.46         1.53         1.51         1.46         1.53         1.51         1.46         1.53         1.51         1.46         1.53         1.53         1.51         1.46         1.53         1.53         1.51         1.46         1.53         1.53         1.55         <	1015	3715										4,121
PERCENT         12.49         16.73         12.24         6.84         14.04         11.03         8.08         18.88         -           1017         3717         FIRPS         102         3718         FIRPS         522         777         250         315         434         307         14.18           1018         3718         FIRPS         522         777         250         315         434         303         421         666         3,67           1019         3718         FIRPS         270         434         200         1/4         222         273         185         370         2,12           PERCENT         1198         444         200         1/4         222         273         183         10.21         15.39         1733         1133         13.23           1020         3727         FIRPS         380         2416         659         819         1353         1531         1313         13.13         13.13         13.13         13.23         1313         13.23         13.14         14.14         14.14         14.14         14.14         14.14         14.14         14.14         14.14         14.14         14.14         14.14	1010											
1017         37.7         TRPS         900         228         35.3         321         1086         1075         684         899         6.33           1018         37.18         TRPS         552         77.7         200         315         434         397         242         666         3,67           1019         37.19         TRPS         270         434         200         174         222         723         185         37.0         2,12           1020         3720 TRPS         301         476         124         220         304         40.20         128         8.69         17.33         16.035         15.49           1020         3720 TRPS         180         7444         8.86         13.54         14.62         15.71         11.51         14.46         13.14,62         15.71         11.51         14.46         13.42         13.54         14.52         14.53         10.53         15.49         13.54         14.52         14.53         13.54         14.52         13.54         14.51         13.54         14.52         13.54         14.52         13.54         14.51         13.54         13.54         14.53         13.54         14.53         13.52	1016	3/16										8,946
PRCENT         14.2         13.0         5.77         23.9         17.13         16.67         10.79         14.18           1018         3718         RIPS         552         777         290         315         434         397         242         666         3,67           1019         3719         TMPS         270         434         200         17.4         12.23         185         3.70         2.13           1020         3720         TMPS         301         476         11.44         220         340         402         200         1389         2.51           1021         3721 <tmps< td="">         318         91.85         5.44         8.76         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.13         1.14         1.14         1.13         1.14</tmps<>												
1018         3712         TIP         250         777         290         315         434         397         242         666         3,67           1019         3719         TNPS         270         434         200         174         812         1081         6.55         1813         370         2,12           1020         3720         TNPS         301         476         124         220         304         402         226         388         8.69         17.39           1020         3720         TNPS         380         446         8.76         13.54         10.35         15.49           1021         3721         TNPS         780         4346         8.76         13.54         10.25         3131         313.13,23           1022         3722         TNPS         780         4346         30.0         353         567         423         649         10.47         578         30.0           1022         3722         TNPS         514         80.3         10.36         583         567         423         649         10.47         578         30.0           1023         3725         TNPS         514         8	1017	3717										6,339
PERCENT         15.03         22.15         7.9         8.88         11.82         10.81         6.59         18.13           1019         3719         TRPS         270         434         200         174         222         273         185         370         2,12           1020         3720         TRPS         301         476         124         220         340         402         260         389         2,51           1021         3721         TRPS         301         476         124         220         340         402         260         389         2,51           1021         3721         TRPS         1800         2416         659         819         1353         507         423         689         1047         5,78           1022         3722         TRPS         362         567         320         338         305         382         275         535         3,08           1024         3724         TRPS         514         809         142         485         640         328         428         340           1026         3725         TRPS         401         577         440         328												
1019         3719         TRIPS         270         434         200         174         722         735         185         370         2,12           1020         3720         TRIPS         301         476         124         220         340         402         260         389         2.51           1021         3721         TRIPS         1890         2446         659         819         1335         2079         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1523         1913         1435         1571         1151         14.66         1733         11021         3723         TRIPS         362         567         320         338         362         157.1         1131         156         1433         663         445         728         4,54           1024         3724         TRIPS         538         652         460         277         440         136         1103         157.7         1203         362	1018	3718										3,673
PERCENT         12.59         20.39         9.4         8.18         10.43         12.83         8.69         17.39           1020         3720 TRIPS         301         476         12.4         220         340         402         260         339         2,51           1021         3721 TRIPS         1890         2416         659         819         1353         0279         1523         1913         13,23           1022         3722 TRIPS         780         1436         310         533         567         423         689         1047         5,78           1022         3722 TRIPS         780         1436         310         533         567         423         689         1047         5,78           1023         3723 TRIPS         780         1436         848         412         475         653         450         364         426         248         424         445         75         53         3.00           1124         747         1430         805         342         275         533         3.00           1125         7420         336         442         348         141         147         143         3463 <td></td>												
1020         3720         TRIPS         301         476         12         220         330         402         260         389         2,51           1021         3721         TRIPS         1880         2416         659         819         1354         16         10.35         15.49           1022         3722         TRIPS         1880         2416         659         819         1352         2079         1523         1913         13,23           1022         3722         TRIPS         780         1436         310         553         557         423         689         1047         578           1023         3723         TRIPS         532         532         308         303         538         2075         533         300           1024         3724         TRIPS         542         654         449         421         475         663         445         228         457           1026         3725         TRIPS         538         652         460         277         437         398         633         533         370           1026         3725         TRIPS         538         652         460	1019	3719										2,128
PERCENT         11.98         19.95         4.94         8.76         13.35         16.30         15.49           1021         3721         TRIPS         18.90         2416         659         819         1935         2075         15.23         1913         13.23           1022         3722         TRIPS         780         14.36         310         533         557         423         689         1007         5,78           1023         3723         TRIPS         352         557         320         338         302         323         12,39         8.92         17.35           1024         3724         TRIPS         514         805         494         412         475         663         445         728         4,54           1024         3724         TRIPS         514         805         494         12.33         986         12.33         986         12.33         948         15.67           1026         3725         TRIPS         401         577         4497         338         363         583         3,70           1026         3726         TRIPS         135         11.75         7.04         12.12         96.63												
1021         3721         TRIPS         1890         2416         659         819         1935         2079         1522         1913         13,23           1022         3722         TRIPS         780         1436         310         553         567         423         689         1047         5,78           1023         3723         TRIPS         352         567         320         338         305         382         275         535         3,08           1023         3723         TRIPS         514         805         498         412         475         663         445         228         5,67         420         336         428         4,54           1024         3724         TRIPS         514         805         498         412         475         663         445         728         4,54           1025         3725         TRIPS         514         1318         6.65         12.33         986         12.57         123         9.63         12.57         123         9.63         12.57         123         9.63         12.58         146         4.94         12.41         12.47         12.41         9.41         14.51	1020	3720										2,512
PERCENT         14.28         18.26         4.98         6.19         14.62         15.71         11.51         14.46           1022         3722         TRIPS         780         1436         310         533         557         423         689         1047         5,78           1023         3723         TRIPS         362         557         320         338         305         322         725         535         3,00           1024         3724         TRIPS         362         557         440         9.88         12.39         8.82         1,735           1024         3724         TRIPS         514         805         498         412         475         663         445         728         4,54           1025         3725         TRIPS         1317         1037         499         228         567         420         336         428         3,40           1026         3726         TRIPS         538         652         400         376         386         353         3,70           1027         3727         TRIPS         132         11315         1230         122         163         12.18         14.64 <td></td>												
1022         3722         TRIPS         780         1436         310         533         567         423         689         1047         5,78           1023         3723         TRIPS         362         557         320         383         305         382         727         555         3,08           1024         3724         TRIPS         314         805         488         12,39         8.92         17.35           1026         3724         TRIPS         401         577         449         228         557         420         336         428         3,40           1025         3725         TRIPS         401         577         449         228         557         420         336         428         3,40           1026         3726         TRIPS         401         577         449         228         57         420         336         533         3,70           1026         3726         TRIPS         538         652         460         277         437         398         363         583         3,70           1027         3227         TRIPS         1436         11,75         7.04         1455	1021	3721										13,234
PERCENT         13.48         24.82         5.36         9.21         9.8         7.31         11.91         18.1           1023         3723         TRIPS         362         567         320         338         305         322         75         535         3,08           1024         3724         TRIPS         514         805         498         412         475         663         445         728         4,54           1025         3725         TRIPS         401         577         449         228         557         420         336         428         3,40           1025         3725         TRIPS         1021         17.73         10.97         477         473         398         363         583         ,370           1026         3726         TRIPS         1451         17.58         12.41         7.47         11.79         10.73         9.79         15.72           1027         3727         TRIPS         126         1290         1455         12.21         9.63         12.18         14.64           1028         3728         TRIPS         126         290         188         107         12.49         12.49												
1023         3723         TRIPS         362         567         320         338         305         382         275         535         3,08           1024         3724         TRIPS         514         805         498         12.39         8.92         1.7.35           1025         3725         TRIPS         401         577         449         228         567         420         366         42.8         3,40           1026         3725         TRIPS         538         652         460         277         437         398         563         533         3,70           1026         3726         TRIPS         538         652         460         277         437         398         563         533         3,70           1027         3727         TRIPS         929         1176         759         455         783         622         787         948         6,45           1028         3728         TRIPS         129         143         14.96         7.94         9.17         10.74         12.49         12.5         1.55           1028         3728         TRIPS         126         230         188         91	1022	3722										5,785
PERCENT         11.74         18.39         10.38         10.96         9.89         12.39         8.92         17.35           1024         3724         TRIP5         514         805         498         412         475         663         445         728         4,54           1025         3725         TRIP5         401         577         449         228         567         420         336         428         3,40           1026         3725         TRIP5         538         652         460         277         437         398         363         583         3,70           1026         3725         TRIP5         538         652         460         277         437         398         363         583         3,70           1027         3727         TRIP5         929         1176         759         455         783         622         787         948         6,45           1028         3727         TRIP5         12.1         12.37         204         14.96         17.074         12.12         12.18         14.62           1029         3729         TRIP5         186         232         286         287         <												
1024         3724         TRIPS         514         805         449         412         475         663         445         728         4,54           1025         3725         TRIPS         401         577         449         228         557         420         336         428         3,40           1026         3725         TRIPS         538         652         460         277         437         398         36         583         3,70           1026         3726         TRIPS         538         652         460         277         437         398         36         583         3,70           1027         3727         TRIPS         929         1176         759         455         783         662         787         948         6,45           1028         3728         TRIPS         1187         315         230         122         141         165         12.39         12.49         12.49         12.49         12.49         12.49         12.49         12.49         12.49         12.49         12.49         12.49         12.55           1028         3730         TRIPS         266         523         286         28	1023	3723	TRIPS	362	567	320	338	305	382	275	535	3,084
PERCENT         11.32         17.73         10.97         9.07         10.46         14.66         9.88         14.64           1025         3725         TRIPS         401         577         449         228         567         420         336         428         3,40           1026         3726         TRIPS         538         652         460         277         437         398         363         553         3,70           1026         3726         TRIPS         1315         17.75         124         17.47         17.9         10.73         9.79         15.72           1027         3727         TRIPS         1176         759         455         783         622         787         948         6,45           1028         3728         TRIPS         187         315         230         122         141         165         122         185         1,53           1028         3729         TRIPS         126         290         188         91         81         107         127         144         1,155           1030         3730         TRIPS         341         644         197         387         297         2			PERCENT	11.74	18.39	10.38	10.96	9.89	12.39			
1025         3725         TRIPS         401         577         449         228         567         420         336         428         3,40           PERCENT         11.77         16.94         13.18         6.65         16.65         12.33         9.86         12.57           1026         3726         TRIPS         538         652         460         277         437         398         363         583         3,70           1027         3727         TRIPS         929         1176         759         455         788         622         787         948         6,45           1028         3728         TRIPS         187         315         230         122         141         165         192         185         1,53           1028         3729         TRIPS         187         315         230         122         141         165         192         185         1,53           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,34           1031         3731         TRIPS         341         614         197         387	1024	3724	TRIPS	514	805	498	412	475	663			4,540
PERCENT         11.77         16.94         13.18         6.69         16.65         12.33         9.86         12.57           1026         3726         TRIPS         538         652         460         277         437         398         363         583         3,70           1027         3727         TRIPS         929         1176         759         455         783         662         787         948         6,455           1028         3728         TRIPS         127         20.49         14.96         7.94         9.17         10.74         12.48         14.68           1029         3729         TRIPS         126         290         188         91         81         107         12.7         145         1,153           1029         3729         TRIPS         126         290         188         91         81         107         12.7         145         1,153           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1031         3731         TRIPS         341         614         197         384 <t< td=""><td></td><td></td><td></td><td>-</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>				-								
1026         3726         TRIPS         538         652         460         277         437         398         363         583         3,70           1027         3727         TRIPS         929         11/6         758         747         11.79         10.73         9,79         15,72           1027         3727         TRIPS         929         11/6         759         743         10.73         9,78         15,72           1028         3728         TRIPS         14.38         18.21         11.75         7.04         12.12         9,63         12.18         14.66           1028         3728         TRIPS         187         315         230         122         141         165         192         185         1,53           1029         3729         TRIPS         126         290         188         91         81         107         12.7         145         1,153           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1031         3731         TRIPS         341         614         197         387 <td< td=""><td>1025</td><td>3725</td><td>TRIPS</td><td>401</td><td>577</td><td>449</td><td></td><td>567</td><td>420</td><td></td><td></td><td>3,406</td></td<>	1025	3725	TRIPS	401	577	449		567	420			3,406
PERCENT         14.51         17.58         12.41         7.47         11.79         10.73         9.79         15.72           1027         3727         TRIPS         929         1176         759         455         783         622         787         948         6.45           1028         3728         TRIPS         187         115         20         122         141         165         122         128         14.68           1028         3728         TRIPS         187         1315         220         188         91         81         107         127         145         1,15           1029         3729         TRIPS         126         209         188         7.88         7.01         9.26         111         12.55           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1032         3732         TRIPS         341         614         197         387 <td></td> <td></td> <td>PERCENT</td> <td>11.77</td> <td>16.94</td> <td>13.18</td> <td>6.69</td> <td>16.65</td> <td>12.33</td> <td>9.86</td> <td>12.57</td> <td></td>			PERCENT	11.77	16.94	13.18	6.69	16.65	12.33	9.86	12.57	
1027         3727         TRIPS         929         1176         759         455         783         622         787         948         6,455           1028         3728         TRIPS         187         315         230         122         141         165         192         185         1,53           1028         3729         TRIPS         187         315         230         122         141         165         192         185         1,53           1029         3729         TRIPS         126         290         188         91         81         107         127         145         1,15           1029         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1030         3730         TRIPS         341         614         197         387         297         250         306         405         2,79           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1033         3733         TRIPS         341         614	1026	3726	TRIPS	538	652	460	277	437	398	363	583	3,708
PERCENT         14.38         18.21         11.75         7.04         12.12         9.63         12.18         14.68           1028         3728         TRIPS         187         315         230         122         141         165         192         185         1,53           1029         3729         TRIPS         126         290         188         91         81         107         127         145         1,15           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1030         3730         TRIPS         246         127         12.3         8.83         7.84         11.3         31.45           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1032         3732         TRIPS         84         161         83         96         105         90         111         77           1033         3733         TRIPS         834         947         360         415         876         113.4         10.9			PERCENT	14.51	17.58	12.41	7.47	11.79	10.73	9.79	15.72	
1028       3728       TRIPS       187       315       230       122       141       165       192       185       1,53         1029       3729       TRIPS       126       290       188       91       81       107       12.49       12.04         1029       3729       TRIPS       126       290       188       91       81       107       12.49       145       1,15         1030       3730       TRIPS       266       523       286       287       206       183       269       314       2,33         1031       3731       TRIPS       266       523       286       287       206       183       269       314       2,33         1031       3731       TRIPS       341       614       197       387       297       250       306       455       279         1032       3732       TRIPS       88       161       88       38       96       105       90       111       77         1033       3733       TRIPS       88       161       88       38       96       105       90       111       777       6.43         1033	1027	3727	TRIPS	929	1176	759	455	783	622	787	948	6,459
PERCENT         12.17         20.49         14.96         7.94         9.17         10.74         12.49         12.04           1029         3729         TRIPS         126         290         188         91         81         107         127         145         1,15           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1031         3730         TRIPS         341         614         197         387         297         250         306         405         2,79           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1032         3732         TRIPS         84         161         197         387         297         250         306         405         2,79           1032         3733         TRIPS         84         161         13.84         10.62         8.94         10.04         14.48           1033         3733         TRIPS         834         947         360         415         876         113.4 </td <td></td> <td></td> <td>PERCENT</td> <td>14.38</td> <td>18.21</td> <td>11.75</td> <td>7.04</td> <td>12.12</td> <td>9.63</td> <td>12.18</td> <td>14.68</td> <td></td>			PERCENT	14.38	18.21	11.75	7.04	12.12	9.63	12.18	14.68	
1029       3729       TRIPS       126       290       188       91       81       107       127       145       1,15         1030       3730       TRIPS       266       523       286       287       206       183       269       314       2,33         1030       3730       TRIPS       341       614       12,25       12.3       8.83       7.84       11.53       13.45         1031       3731       TRIPS       341       614       197       387       297       250       306       405       2,79         1032       3732       TRIPS       88       161       88       38       96       105       90       111       77         1033       3733       TRIPS       884       146       88       38       96       105       90       111       77         1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1034	1028	3728	TRIPS	187	315	230	122	141	165	192	185	1,537
PERCENT         10.91         25.11         16.28         7.88         7.01         9.26         11         12.55           1030         3730         TRIPS         266         523         286         287         206         183         269         314         2,33           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1032         3732         TRIPS         88         161         88         38         96         105         90         111         77           1032         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1033         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1034         3734         TRIPS         2050         1905         665         858			PERCENT	12.17	20.49	14.96	7.94	9.17	10.74	12.49	12.04	
1030       3730       TRIPS       266       523       286       287       206       183       269       314       2,33         1031       PERCENT       11.4       22.41       12.25       12.3       8.83       7.84       11.53       13.45         1031       3731       TRIPS       341       614       197       387       297       250       306       405       2,79         1032       3732       TRIPS       88       161       88       38       96       10.5       90       111       77         1033       3733       TRIPS       884       947       360       415       876       1134       699       1007       6,34         1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1035 <t< td=""><td>1029</td><td>3729</td><td>TRIPS</td><td>126</td><td>290</td><td>188</td><td>91</td><td>81</td><td>107</td><td>127</td><td>145</td><td>1,155</td></t<>	1029	3729	TRIPS	126	290	188	91	81	107	127	145	1,155
PERCENT         11.4         22.41         12.25         12.3         8.83         7.84         11.53         13.45           1031         3731         TRIPS         341         614         197         387         297         250         306         405         2,79           1032         3732         TRIPS         88         161         88         38         96         105         90         111         77           1032         3733         TRIPS         88         141         88         38         96         105         90         111         77           1033         3733         TRIPS         834         947         360         415         876         1134         699         10077         6,34           1033         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1034         3733         TRIPS         2050         1905         665         858         2362         2953         1821         2513         15,12           1034         3735         TRIPS         1166         1323         309         755			PERCENT	10.91	25.11	16.28	7.88	7.01	9.26	11	12.55	
1031       3731       TRIPS       341       614       197       387       297       250       306       405       2,79         PERCENT       12.19       21.95       7.04       13.84       10.62       8.94       10.94       14.48         1032       3732       TRIPS       88       161       88       38       96       105       90       111       77         1033       3733       TRIPS       884       947       360       415       876       1134       699       1077       6,34         1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1035       3735       TRIPS       1166       1323       309       765       1467       1790       1112       1525       9,45         1036       3736 </td <td>1030</td> <td>3730</td> <td>TRIPS</td> <td>266</td> <td>523</td> <td>286</td> <td>287</td> <td>206</td> <td>183</td> <td>269</td> <td>314</td> <td>2,334</td>	1030	3730	TRIPS	266	523	286	287	206	183	269	314	2,334
PERCENT         12.19         21.95         7.04         13.84         10.62         8.94         10.94         14.48           1032         3732         TRIPS         88         161         88         38         96         105         90         111         77           1033         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1033         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1034         3734         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1034         3734         TRIPS         2050         1905         665         858         2362         2953         1821         2513         1512           1035         3735         TRIPS         1166         1323         309         765         1467         1952         12.04         1661           1035         3735         TRIPS         1572         1831         587         990 <t< td=""><td></td><td></td><td>PERCENT</td><td>11.4</td><td>22.41</td><td>12.25</td><td>12.3</td><td>8.83</td><td></td><td></td><td>13.45</td><td></td></t<>			PERCENT	11.4	22.41	12.25	12.3	8.83			13.45	
1032       3732       TRIPS       88       161       88       38       96       105       90       111       77         1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1034       9734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1035       9734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1035       9735       TRIPS       1166       1323       309       765       1467       1700       1112       1525       9,45         1035       9735       TRIPS       1572       1831       587       990       1663       217       1376       16,29       12,10 <td>1031</td> <td>3731</td> <td>TRIPS</td> <td>341</td> <td>614</td> <td>197</td> <td>387</td> <td>297</td> <td>250</td> <td>306</td> <td></td> <td>2,797</td>	1031	3731	TRIPS	341	614	197	387	297	250	306		2,797
PERCENT         11.33         20.72         11.33         4.89         12.36         13.51         11.58         14.29           1033         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1034         3733         TRIPS         834         947         360         415         876         1134         699         1077         6,34           1034         3734         TRIPS         2050         1905         665         858         2362         2953         1821         2513         15,12           1034         3735         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1035         3735         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1035         3735         TRIPS         1572         1831         587         990         1663         2117         1363         1495         13.55         13.64         167         1469         14.7         14.79         14.79			PERCENT	12.19	21.95	7.04	13.84	10.62	8.94	10.94	14.48	
1033       3733       TRIPS       834       947       360       415       876       1134       699       1077       6,34         1014       PERCENT       13.15       14.93       5.68       6.54       13.81       17.88       11.02       16.98         1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         1035       3735       TRIPS       1166       1323       309       765       1467       1790       1112       1525       9,45         1035       3735       TRIPS       1166       1323       309       765       1467       1790       1112       1525       9,45         1036       3735       TRIPS       1572       1831       587       990       1663       2117       1376       1609       12,10         1036       3736       TRIPS       1572       1831       587       990       1663       2117       1376       1627       1467         1037       3737       TRIPS       562       913       271       583       499       594       535       730       4,68	1032	3732	TRIPS	88	161	88	38	96	105	90	111	777
PERCENT         13.15         14.93         5.68         6.54         13.81         17.88         11.02         16.98           1034         3734         TRIPS         2050         1905         665         858         2362         2953         1821         2513         15,12           1035         3735         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1035         3735         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1036         3736         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1036         3736         TRIPS         1572         1831         587         990         1663         2117         1376         16.99         12,10           1037         3737         TRIPS         562         913         271         583         499         594         535         730         4,68           1037         3737         TRIPS         562         913 <td< td=""><td></td><td></td><td>PERCENT</td><td>11.33</td><td>20.72</td><td>11.33</td><td>4.89</td><td>12.36</td><td>13.51</td><td>11.58</td><td>14.29</td><td></td></td<>			PERCENT	11.33	20.72	11.33	4.89	12.36	13.51	11.58	14.29	
1034       3734       TRIPS       2050       1905       665       858       2362       2953       1821       2513       15,12         PERCENT       13.55       12.59       4.4       5.67       15.61       19.52       12.04       16.61         1035       3735       TRIPS       1166       1323       309       765       1467       1790       1112       1525       9,45         1036       3736       TRIPS       1166       1323       309       765       1467       1790       1112       1525       9,45         1036       3736       TRIPS       1572       1831       587       990       1663       2117       1376       1969       12,10         1036       3737       TRIPS       1572       1831       587       990       1663       2117       1376       1969       12,10         1037       ATRIPS       562       913       271       583       499       594       535       730       4,68         1037       3737       TRIPS       562       913       271       583       499       594       535       730       4,68         1038       3738	1033	3733	TRIPS	834	947	360	415	876	1134	699	1077	6,342
PERCENT         13.55         12.59         4.4         5.67         15.61         19.52         12.04         16.61           1035         3735         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1035         3735         TRIPS         1166         1323         309         765         1467         1790         1112         1525         9,45           1036         3736         TRIPS         1572         1831         587         990         1663         2117         1376         1969         12,10           1036         3737         TRIPS         152         913         271         583         499         594         535         730         4,68           1037         3737         TRIPS         562         913         271         583         499         594         535         730         4,68           1037         3737         TRIPS         562         913         271         583         499         594         535         730         4,68           1038         3738         TRIPS         1667         2198         667			PERCENT	13.15	14.93	5.68	6.54	13.81	17.88	11.02		
1035       3735       TRIPS       1166       1323       309       765       1467       1790       1112       1525       9,45         1036       PERCENT       12.33       13.99       3.27       8.09       15.51       18.93       11.76       16.13         1036       3736       TRIPS       1572       1831       587       990       1663       2117       1376       1969       12,10         1037       PERCENT       12.99       15.13       4.85       8.18       13.74       17.49       11.37       16.27         1037       3737       TRIPS       562       913       271       583       499       594       535       730       4,68         1037       3737       TRIPS       562       913       271       583       499       594       535       730       4,68         1038       3738       TRIPS       1667       2198       667       1151       1971       2001       1700       1973       13,33         1038       3738       TRIPS       1667       1122       241       391       998       796       824       961       6,04         1039       3739	1034	3734	TRIPS	2050	1905	665	858	2362	2953	1821	2513	15,127
PERCENT         12.33         13.99         3.27         8.09         15.51         18.93         11.76         16.13           1036         3736         TRIPS         1572         1831         587         990         1663         2117         1376         1969         12,10           1036         PERCENT         12.99         15.13         4.85         8.18         13.74         17.49         11.37         16.27           1037         3737         TRIPS         562         913         271         583         499         594         535         730         4,68           1037         3737         TRIPS         562         913         271         583         499         594         535         730         4,68           1038         3738         TRIPS         1677         2198         667         1151         1971         2001         1700         1973         13,33           1038         3738         TRIPS         1667         11.48         5         8.63         14.78         15         12.75         14.79           1039         9739         TRIPS         660         1172         241         391         998			PERCENT	13.55	12.59	4.4	5.67	15.61	19.52	12.04	16.61	
1036       3736       TRIPS       1572       1831       587       990       1663       2117       1376       1969       12,10         1010       PERCENT       12.99       15.13       4.85       8.18       13.74       17.49       11.37       16.27         1037       3737       TRIPS       562       913       271       583       499       594       535       730       4,68         1037       PERCENT       11.99       19.48       5.78       12.44       10.65       12.67       11.41       15.57         1038       3738       TRIPS       1677       2198       667       1151       1971       2001       1700       1973       13,33         1039       PERCENT       12.57       16.48       5       8.63       14.78       15       12.75       14.79         1039       PERCENT       12.57       16.48       5       8.63       14.78       15       12.75       14.79         1039       MPS       660       1172       241       391       998       796       824       961       6,04         1040       PERCENT       10.92       19.39       3.99       6.47 <td>1035</td> <td>3735</td> <td>TRIPS</td> <td>1166</td> <td>1323</td> <td>309</td> <td>765</td> <td>1467</td> <td>1790</td> <td>1112</td> <td>1525</td> <td>9,457</td>	1035	3735	TRIPS	1166	1323	309	765	1467	1790	1112	1525	9,457
PERCENT         12.99         15.13         4.85         8.18         13.74         17.49         11.37         16.27           1037         3737         TRIPS         562         913         271         583         499         594         535         730         4,68           1037         PERCENT         11.99         19.48         5.78         12.44         10.65         12.67         11.41         15.57           1038         3738         TRIPS         1677         2198         667         1151         1971         2001         1700         1973         13,33           1039         PERCENT         12.57         16.48         5         8.63         14.78         15         12.75         14.79           1039         3739         TRIPS         660         1172         241         391         998         796         824         961         6,04           1039         3740         TRIPS         660         1172         241         391         998         796         824         961         6,04           1040         3740         TRIPS         668         810         212         346         703         849 <td< td=""><td></td><td></td><td>PERCENT</td><td>12.33</td><td>13.99</td><td>3.27</td><td>8.09</td><td>15.51</td><td>18.93</td><td>11.76</td><td>16.13</td><td></td></td<>			PERCENT	12.33	13.99	3.27	8.09	15.51	18.93	11.76	16.13	
1037       3737       TRIPS       562       913       271       583       499       594       535       730       4,68         1010       PERCENT       11.99       19.48       5.78       12.44       10.65       12.67       11.41       15.57         1038       3738       TRIPS       1677       2198       667       1151       1971       2001       1700       1973       13,33         1039       PERCENT       12.57       16.48       5       8.63       14.78       15       12.75       14.79         1039       PERCENT       12.57       16.48       5       8.63       14.78       15       12.75       14.79         1039       3739       TRIPS       660       1172       241       391       998       796       824       961       6,04         1040       PERCENT       10.92       19.39       3.99       6.47       16.51       13.17       13.64       15.9         1040       3740       TRIPS       686       810       212       346       703       849       589       925       5,12	1036	3736	TRIPS	1572	1831	587	990	1663	2117	1376	1969	12,105
PERCENT         11.99         19.48         5.78         12.44         10.65         11.41         15.57           1038         3738         TRIPS         1677         2198         667         1151         1971         2001         1700         1973         13,33           1040         PERCENT         12.57         16.48         5         8.63         14.78         15         12.75         14.79           1039         3739         TRIPS         660         1172         241         391         998         796         824         961         6,04           1040         PERCENT         10.92         19.39         3.99         6.47         16.51         13.17         13.64         15.9           1040         3740         TRIPS         668         810         212         346         703         849         589         925         5,12			PERCENT	12.99	15.13	4.85	8.18	13.74	17.49	11.37	16.27	
PERCENT         11.99         19.48         5.78         12.44         10.65         11.41         15.57           1038         3738         TRIPS         1677         2198         667         1151         1971         2001         1700         1973         13,33           1040         PERCENT         12.57         16.48         5         8.63         14.78         15         12.75         14.79           1039         3739         TRIPS         660         1172         241         391         998         796         824         961         6,04           1040         PERCENT         10.92         19.39         3.99         6.47         16.51         13.17         13.64         15.9           1040         3740         TRIPS         668         810         212         346         703         849         589         925         5,12	1037	3737	TRIPS	562	913	271	583	499	594	535	730	4,687
1038       3738       TRIPS       1677       2198       667       1151       1971       2001       1700       1973       13,33         1038       PERCENT       12.57       16.48       5       8.63       14.78       15       12.75       14.79         1039       G3739       TRIPS       660       1172       241       391       998       796       824       961       6,04         1040       PERCENT       10.92       19.39       3.99       6.47       16.51       13.17       13.64       15.9         1040       3740       TRIPS       686       810       212       346       703       849       589       925       5,12				11.99	19.48	5.78	12.44	10.65	12.67			
PERCENT         12.57         16.48         5         8.63         14.78         15         12.75         14.79           1039         3739         TRIPS         660         1172         241         391         998         796         824         961         6,04           0         PERCENT         10.92         19.39         3.99         6,47         16.51         13.17         13.64         15.9           1040         3740         TRIPS         686         810         212         346         703         849         589         925         5,12	1038	3738		-								13,338
1039       3739       TRIPS       660       1172       241       391       998       796       824       961       6,04         1040       PERCENT       10.92       19.39       3.99       6.47       16.51       13.17       13.64       15.9         1040       3740       TRIPS       686       810       212       346       703       849       589       925       5,12				-								
PERCENT         10.92         19.39         3.99         6.47         16.51         13.17         13.64         15.9           1040         3740         TRIPS         686         810         212         346         703         849         589         925         5,12	1039	3739		-								6,043
1040 3740 TRIPS 686 810 212 346 703 849 589 925 5,12		5,00										
	1040	3740										5,120
PERCENT 13.4 15.82 4.14 6.76 13.73 16.58 11.5 18.07	10+0	5740										5,120

		UTION SUMMA	.m i				DIRECTION	s			
ORIGIN ZONE			NNE	ENE			SSW		WNW	NNW	TOTAL
		PERCENT	9.4	4	1	11.48	17.5				TOTAL
1021	3721	TRIPS	1508		-	961	1639		969		11,00
		PERCENT	13.7	18.65		8.73	14.89	14.5	8.8		
1022	3722	TRIPS	806	1178	867	885	709	813	368	1113	6,73
		PERCENT	11.96	17.48	12.87	13.13	10.52	12.06	5.46	16.52	
1023	3723	TRIPS	357	535		443	500	372	248		3,54
		PERCENT	10.07	15.09		12.49	14.1	10.49	6.99		
1024	3724	TRIPS	574		464	237	820	905	717	993	5,40
		PERCENT	10.63	12.79		4.39	15.18				
1025	3725	TRIPS	702	666		199	530	489	355		4,14
1020	2726	PERCENT	16.93	16.06		4.8	12.78	11.79	8.56		2.01
1026	3720	TRIPS PERCENT	455	506 13.28		342 8.97	570 14.96	491 12.88	390 10.23		3,81
1027	2722	TRIPS	1083	13.28		479	501	582	815		6,44
1027	5727	PERCENT	16.8			7.43	7.77	9.03			0,44
1028	3728	TRIPS	196	327	205	242	204	263	189		1,80
1020	5720	PERCENT	10.88	18.15		13.43	11.32	14.59	10.49	9.77	1,00
1029	3729	TRIPS	145	178		296	11.52	72	124		1,27
1025	5725	PERCENT	11.41	14		23.29	9.21	5.66	9.76		1,27
1030	3730	TRIPS	428			341	419	194			2,81
	0,00	PERCENT	15.19	19.38		12.11	14.87	6.89	15.19		2,0
1031	3731	TRIPS	870	918	-	228	399	207	368		3,82
		PERCENT	22.77	24.03		5.97	10.45	5.42	9.63	13.04	,
1032	3732	TRIPS	102	145		70	165	115	109		93
		PERCENT	10.86	15.44	6.39	7.45	17.57	12.25	11.61	18.42	
1033	3733	TRIPS	1006	1099	304	480	1459	1568	1024	1385	8,32
		PERCENT	12.08	13.2	3.65	5.77	17.53	18.83	12.3	16.64	
1034	3734	TRIPS	2690	3083	725	1569	4341	3521	2005	2907	20,84
		PERCENT	12.91	14.79	3.48	7.53	20.83	16.89	9.62	13.95	
1035	3735	TRIPS	1570	2456	584	1220	2118	1825	1120	1775	12,66
		PERCENT	12.39	19.39	4.61	9.63	16.72		8.84	14.01	
1036	3736	TRIPS	2038	2422	1418	2463	3716	2686	1788		18,73
		PERCENT	10.88			13.15	19.84		9.55	11.75	
1037	3737	TRIPS	635	835		506	1016	603	701	810	5,47
		PERCENT	11.6			9.24	18.55	11.01	12.8		
1038	3738	TRIPS	1920	2763		894	3242	2276	2567	3019	17,34
		PERCENT	11.07	15.93		5.16	18.7	13.12	14.8		
1039	3739	TRIPS	906	1284		385	950	1100	833		7,24
		PERCENT	12.5	17.72		5.31	13.11	15.18			
1040	3740	TRIPS	803	812	113	296	866	1189	897	1050	6,02
1041	2741	PERCENT	13.33	13.47	1.88	4.91	14.37	19.73	14.89		0.2
1041	3/41	TRIPS PERCENT	1064			587	1338	1345	810		8,2
1042	2742	TRIPS	12.96			7.15	16.29	16.38			9,20
1042	5/42	PERCENT	1341	1	1	313 3.38		1582	1383		9,20
1043	27/2	TRIPS	14.48		1	202	14.91 662	17.08 1115	14.93 952		7,8
1045	3743	PERCENT	20.99		1.55	2.57	8.43	14.2	12.12		7,0.
1044	3744	TRIPS	1153	10.91		197	730	1414	1022	1498	7,12
	5777	PERCENT	16.18			2.76	10.24				/,1/
1045	3745	TRIPS	10.10			481	1103	1394	1081	1102	8,10
1045	5745	PERCENT	13.28			5.89	13.52	17.08			0,10
1046	3746	TRIPS	958	1	1	93	797	1393	1494		7,08
1010	5,10	PERCENT	13.52	14.39		1.31	11.24	19.65	21.08		,,,,,
1047	3747	TRIPS	1411	996	-	86	305	547	729		5,2
		PERCENT	26.95			1.64	5.83	10.45	13.93		-,-
1048	3748	TRIPS	887	811	429	421	916		1029		6,6
		PERCENT	13.31	12.17	6.44	6.32	13.74	19.26	15.44	13.32	,
1049	3749	TRIPS	2208	1	1	80	306		973		7,3
		PERCENT	30.07	13.96		1.09	4.17	10.43	13.25		,-
1050	3750	TRIPS	300	139	1	15	65	149	122		1,0
		PERCENT	29.35	13.6		1.47	6.36				
1051	3751	TRIPS	644		1	17	23		325		1,9
		PERCENT	32.69	6.5	1.07	0.86	1.17	19.29	16.5	21.93	
1052	3752	TRIPS	6615	1784	1	125	997	2567	1972		17,8
		PERCENT	37.04	9.99		0.7	5.58		11.04	20.61	
1053	3753	TRIPS	1770	1039	217	32	783	841	837	1197	6,7
	-	PERCENT	26.35	15.47	3.23	0.48	11.66	12.52	12.46	17.82	
		TRIPS	1709		64	171	1313		1430		9,93

**APPENDIX D:** 

Intersection Turning Movement Counts, Peak Season Factor Category Report, and Signal Timing Data **Intersection Turning Movement Counts** 

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHCGALI Page : 1

#### ALL VEHICLES

		AVENUE			ALHAMBRA		Ξ		GALIANO				ALHAMBRA		Ξ		
Fi	rom Noi	th			From Eas	3C			From Son	ltn			FION Wes	SC		i I	
τ	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	Tota
Date 09/04	4/13																
07:00	0	8	0	4	0	2	15	6	0	1	3	6	0	0	1	0	4
07:15	0	7	0	1	0	1	17	6	0	1	5	9	0	0	0	0	4
07:30	0	15	7	5	0	3	18	12	0	8	2	12	0	0	1	0	8
07:45	0	21	4	13	0	4	34	17	0	8	8	25	0	0	1	0	13
Hr Total	0	51	11	23	0	10	84	41	0	18	18	52	0	0	3	0	31
00:80	0	27	3	17	1 0	15	54	15	1	15	11	29	0	0	1	3	19
08:15	0	38	2	9	0	24	46	48	0	17	6	30	0	0	1	0	22
08:30	0	25	4	20	0	17	47	29	0	17	12	26	0	0	0	0	19
08:45	0	6	7	30	0	13	40	22	<u> </u>	22	5	23	0	0	2	0	17
Hr Total	0	96	16	76	0	69	187	114	1	71	34	108	0	0	4	3	77
	- * BRI	SAK *															
16:00	0	18	2	6	0	15	48	14	0	2	6	13	0	3	3	6	13
	•	15	-	10	0	18	36	11	l 0	2	10	10	0	1		- 1	
16:15	0	15	8	10	1 0	10			1 0				· ·	-	3	3	12
L6:15 L6:30	0	13	8 12	25		13	46	17		0	7	19	•	0	3 6	3   5	12 16
L6:30	-				0				0		7 5	19 15	0			'	16
L6:30 L6:45	0	13	12	25	0   0	13	46	17	0   0	0			0   0	0	6	5	16 14
	0	13 23	12 9	25 22	0   0   0	13 8	46 39	17 14	0   0   0	0	5	15		0 1	6 4	5	16 <u>14</u> 57
.6:30 <u>.6:45</u> Ir Total .7:00	0	13 23 69	12 9 31	25 22 63		13 8 54	46 39 169	17 14 56	0 <u>  0</u>   0	0 <u>6</u> 10	28	15 57	0   0   0	0 1 5	6 4 16	5   0   14	16 <u>14</u> 57 26
l6:30 l6:45 Ir Total	0 0 0	13 23 69 40	12 9 31 13	25 22 63 39	0   0   0	13 8 54 28	46 39 169 41	17 <u>14</u> 56 29	0 <u>  0</u>   0	0 <u>6</u> 10 2	5 28 14	<u>15</u> 57 27	0   0   0	0 1 5 1	6 4 16 15	5   0   14   14	
.6:30 .6:45 Hr Total .7:00 .7:15	0 0 0 0 0	13 23 69 40 37	12 9 31 13 14	25 22 63 39 39	0   0   0	13 8 54 28 29	46 39 169 41 40	17 14 56 29 21	0   0   0	0 6 10 2 2	5 28 14 13	15 57 27 24	0   0   0	0 1 5 1 1	6 4 16 15 18	5   0   14   14	16 <u>14</u> 57 26 25 24
.6:30 .6:45 Hr Total .7:00 .7:15 .7:30	0 0 0 0 0 0	13 23 69 40 37 32	12 9 31 13 14 6	25 22 63 39 39 32	0   0   0   0   0   0	13 8 54 28 29 21	46 39 169 41 40 50	17 14 56 29 21 27	0   0   0   0   0   0	0 6 10 2 2 3	5 28 14 13 13	15 57 27 24 32	0   0   0   0   0   0	0 1 5 1 1 3	6 4 16 15 18 11	5   0   14   14   14   19	16 <u>14</u> 57 26 25

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

	CAZAR A	<b>AVENUE</b> th			ALHAMBRA  From Eas		E		GALIANO				ALHAMBRA		Ξ	1	
	furn							Right	   UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	Tota
te 09/04/ ak Hour A								07.00 +			 4 / 1 3						
ak start			cnutre	Incerse	08:00		eriou.	07.00 C	08:00		1/15		08:00			I	
lume	0	96	16	76	•	69	187	114		71	34	108	•	0	4	3	
rcent	0*	51%	9%	40%	0%	19%	51%	31%	0%	33%	16%	50%	0%	0%	57%	43%	
total	188				370				214				7				
ghest	08:15				08:15				08:00	)			08:00			l	
lume	0	38	2	9	0	24	46	48	1	15	11	29	0	0	1	3	
total	49				118				56				4				
F	. 96				. 78				.96				.44			-	
						AL	JCAZA	AR AV	ENUE								
		•		ο.	76		16	; .	96		0						
											34						
											114						
															•	•	0
				0	76		16	5	96		148				0		
						1											
				1		· -	0.0	1	I								
				1		1	.88		" 336							1	14
LHAMBI	RA C	IRCI	LE			1	.88	-	<sup>  </sup> 336 ··				<b>Б</b> ана [	11	4	• 1	14
LHAMBI	RA C	CIRCI	LE		 L_	1	.88	-	<sup>  </sup> 336 ··			]		11	4	• 1	14
72	2			<b>Been</b>	 L				」 <sup>  </sup> 336 · HICLE	s			•••• 	11	.4		<u></u>
72 187	2 7		LE 335	<b>Berne</b>	 	<u> </u>				S							14 87
72	2 7				 	' 1 				S			<b></b> 370	11			<u></u>
72 187 76	2 7 6					<u> </u>				S			370				<u></u>
72 187 76	2 7		335			<u> </u>				S			370			• 1	87
72 187 76	2 7 6									S			<b></b>	18	37	• 1	<u></u> .
72 187 76	2 7 6		335		3	42				S	57		■ [ 370 	18		• 1	87
72 187 76	2 7 6 0		335		3					S	57		370	18	37	• 1	87
72 187 76	2 7 6		335 0	  ] 7	3		• AI	L VE	HICLE				370 	18	37	· 1	87
72 187 76	2 7 6 0		335		3		• AI	L VE	HICLE				370 	18	37 59	· 1	87 69 96
72 18 76	2 7 6 0		335 0		3		• AI	L VE	HICLE				370 	18	37 59	· 1	87 69 96 4
72 18 76	2 7 6 0		0 4	   	3		• AI	L VE	HICLE				370 	18	37 59	· 1	87 69 96
72 18 76	2 7 6 0		335 0		3		• AI	L VE	HICLE tion 779					18 6 20	37 59 08	· 1	87 69 96 4
72 18 76	2 7 6 0		0 4	     	3		• AI	L VE	HICLE	Tota	1			18 6 20	37 59 08	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0 4 3		0 4		3		• AI	L VE	HICLE tion 779		1			18 6 20	37 59 08	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0		335 0 4 3		3		• AI	L VE ersec	HICLE tion 779 302	Tota	1 4 —	8	  ALH	18 6 20	37 59 )8 &A CI	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0 4 3		0 4		3		• AI	L VE ersec	HICLE tion 779	Tota	1	8		18 6 20	37 59 08	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0 4 3		335 0 4 3		3		• AI	L VE ersec	HICLE tion 779 302	Tota	1 4 —	8	  ALH	18 6 20	37 59 )8 &A CI	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0 4 3		335 0 4 3		3		• AI	L VE ersec	HICLE tion 779 302	Tota	1 4 —	8	  ALH	18 6 20	37 59 )8 &A CI	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0 4 3		335 0 4 3	 	3		• AI Inte	rsec	HICLE tion 779 302 72	Tota	1 4 — 34	8	ALH	18 6 20	37 59 08 2A C1	· 1	87 69 96 4
72 18 76 (0)	2 7 6 0 4 3		335 0 4 3		3		• AI	rsec	HICLE tion 779 302	Tota	1 4 —	8	  ALH	18 6 20	37 59 )8 &A CI	· 1	87 69 96 4

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHCGALI Page : 3

#### ALL VEHICLES



#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHCGALI Page : 1

#### PEDESTRIANS

	CAZAR	AVENUE			ALHAMBRA		E		GALIANO  From So 				ALHAMBR  From Wes		ιE	1	
	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Tota
Date 09/04	1/13																
07:00	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	
07:15	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	1	
07:30	0	0	0	0	0	0	0	2	0	0	0	0	0	0	0	2	
07:45	0	0	0	1	0	0	0	1	] 0	0	0	1	0	o	0	2	
Hr Total	0	0	0	l	0	0	0	6	0	0	0	1	0	0	0	6	1
08:00	0	0	0	0	0	0	0	6	0	0	0	2	0	0	0	1	
08:15	0	0	0	2	0	0	0	3	0	0	0	2	0	0	0	3	1
08:30	0	0	0	0	0	0	0	2	0	0	0	2	0	0	0	0	
08:45	0	0	0	0	0	0	0	1	0	0	0	1	1 0	0	0	0	
Hr Total	0	0	0	2	0	0	0	12	0	0	0	7	0	0	0	4	2
	+ BRI	EAK * -															
16:00	0	0	0	0	0	0	0	5	0	0	0	3	0	0	0	1	
16:15	0	0	0	0	0	0	0	0	0	0	0	1	1 0	0	0	0	
16:30	0	0	0	3	0	0	0	5	0	0	0	0	1 0	0	0	1	
16:45	0	0	0	3	0	. 0	0	0	0	0	0	0	0	0	0	0	
Hr Total	0	0	0	6	0	0	0	10	1 0	0	0	4	0	0	0	2	2
17:00	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	2	
17:15	0	0	0	2	0	0	0	0	0	0	0	0	0	0	0	0	
17:30	0	0	0	2	0	0	0	5	0	0	0	0	0	0	0	2	
17:45	0	0	0	3	0	0	0	1	0	0	0	0	0	0	0	οį	
Hr Total	0	0	0	7	0	0	0	7	0	0	0	1	0	0	0	4	1



ALHAMBRA PLAZA & GALIANO STREET CORAL GABLES, FLORIDA COUNTED BY: ROLANDO MARTINEZ SIGNALIZED

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHAGALI Page : 1

#### ALL VEHICLES

	GALIANO	STREET			ALHAMBR	A PLAZA			GALIANO	STREET			ALHAMBR	A PLAZA		 	
	From No:				From Ea				From So				From We	st		i	
	UTurn	Left	Thru	Pight	UTurn	Left	Thru	Right	UTurn	ī⇔f⊧	Thru	Right	   UTurn	Left	Thru	 Right	Total
Date 09/				5													
07:00	0	0	2	0	2	0	21	4	0	0	1	7	0	5	58	1	101
07:15	0	0	0	1	1	3	24	5	0	2	4	5	1	7	63	1	117
07:30	0	0	6	2	0	4	27	4	0	1	4	7	3	19	74	0	151
07:45	0	1	3	4	<u> </u>	2	33	17	0	3	8	9	1	24	74	1	183
Hr Total	0	1	11	7	6	9	105	30	0	6	17	28	5	55	269	3	552
08:00	0	5	8	6	2	4	34	9	0	2	22	8	1	24	90	2	217
08:15	0	2	18	3	0	7	56	13	0	7	16	9	5	30	86	2	254
08:30	0	4	19	4	3	3	60	20	0	6	15	14	5	28	86	3	270
08:45	0	3	13	3	2	4	60	14	0	4	17	9	4	21	64	3	221
Hr Total	0	14	58	16	7	18	210	56	0	19	70	40	15	103	326	10	962
	* BR	EAK * -															
16:00	0	4	8	9	0	3	47	3	0	10	11	11	4	10	67	3	190
16:15	0	4	13	13	1	4	64	6	0	11	10	13	10	7	79	2	237
16:30	0	8	12	11	0	1	62	4	0	15	12	13	7	5	79	0	229
16:45	0	4	10	7	2	3	64	2	1 0	7	14	13	6	12	61	1	206
Hr Total	0	20	43	40	3	11	237	15	0	43	47	50	27	34	286	6	862
17:00	0	5	31	26	0	1	73	8	0	13	20	13	12	13	84	6	305
17:15	0	8	29	19	1	2	58	6	0	17	18	16	7	12	69	3	265
17:30	0	7	26	22	0	3	71	3	1	15	32	36	11	10	67	2	306
17:45	0	3	25	15	1	2	57	7	<u> </u>	17	12	15	8	5	84	3	254
Hr Total	0	23	111	82	2	8	259	24	1	62	82	80	38	40	304	14	1130
*TOTAL*			223		18		811	125	! 1	130	216	198	85	232	1185	33	3506
IOIND"	U	50	223	140	; 10	40	011	125	; I	130	210	198	05	232	1192	1 22	3506

ALHAMBRA PLAZA & GALIANO STREET CORAL GABLES, FLORIDA COUNTED BY: ROLANDO MARTINEZ SIGNALIZED

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHAGALI Page : 2

GALIANO From Nor				ALHAMBRA				GALIANO				ALHAMBRA  From Wes				1
UTurn	Left			   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   Tota
ate 09/04/13 eak Hour Analys				ction for	the D	eriod.	07:00 t	0.09.00	09/04							
eak start 08:00		Encire	THEETBE	08:00		errou.	07.00 C	0 09:00 0		1/15		08:00				1
olume 0	14	58	16	•	18	210	56		. 19	70	40		103	326	10	1
ercent 0%	16%	66%	18%	,	68	72%	19%	,	15%	54%	31%		23*	728	2*	
total 88				291				129				454				
ghest 08:30	1			08:30				08:30	)			08:15				
olume O	4	19	4	3	3	60	20	0	6	15	14	5	30	86	2	
total 27				86				35				123				
IF .81				.85				.92				.92				1
					GA	LIAN	IO ST	REET				I				
			ο.	16	•	58	•	14		118 70 56						
	-			16		58				244				0		0
				<u> </u>		88	<u> </u>									
LHAMBRA I	PLAZ	J			 	88	 -	 332 ·			]		5	6		56
LHAMBRA H 19 210			<b></b>	, 				 332 · HICLE	S		J		5			
		A 245			1				S				21		. 2	56 10
19 210 16									S			291			2	
19 210		245			1				S							10
19 210 16									S			291	21	.0		
19 210 16		245		  6	99				S	67		291	21			10
19 210 16 118		245		   6	99				S	67		291 	21	.0		10
19 210 16	1	245			99	• AL	L VE	HICLE				[ 291 [	21	.0		10 25
19 210 16 118	1	245	   45		99	• AL	L VE	HICLE				 291 	21	.0		10 25 14
19 210 16 118 326	1	245	 ] 45		99	• AL	L VE	HICLE				291	21	.0	3	10 25
19 210 16 118	1	245 118 326	   45		99	• AL	L VE	HICLE				 	21 2 38	.0	3	10 25 14 26
19 210 16 118 326	1	245			99	• AL	L VE	HICLE tion 962				 	21 2 38	.0	3	10 25 14 26
19 210 16 118 326	1	245 118 326			99	• AL	L VE	HICLE	Tota	1		 	21 2 38	.0	3	10 25 14 26
19 210 16 118 326 10	1	245 118 326			99	• AL	L VE	HICLE tion 962		1		 	21 2 38	.0	3	10 25 14 26
19 210 16 118 326	1	245 118 326 10			99	• AL	st VE	HICLE tion ' 962	Tota	1 		  	21 2 38 AMBR	.0 25 30 2A PI	3	10 25 14 26
19 210 16 118 326 10	1	245 118 326			99	• AL	st VE	HICLE tion 962	Tota	1 		 	21 2 38 AMBR	.0	3	10 25 14 26
19 210 16 118 326 10	1	245 118 326 10			99	• AL	st VE	HICLE tion ' 962	Tota	1 		  	21 2 38 AMBR	.0 25 30 2A PI	3	10 25 14 26
19 210 16 118 326 10	1	245 118 326 10			99	• AL	rsec	HICLE	Tota	1 9 <u>-</u> 70		ALH	21 2 38 AMBR	.0 25 30 2 <b>A</b> PI 0	3	10 25 14 26
19 210 16 118 326 10	1	245 118 326 10			99	• AL	rsec	HICLE	Tota	1 		  	21 2 38 AMBR	.0 25 30 2A PI	3	10 25 14 26
19 210 16 118 326 10	1	245 118 326 10			99	• AL	rsec	HICLE	Tota	1 9 <u>-</u> 70		ALH	21 2 38 AMBR	.0 25 30 2 <b>A</b> PI 0	3	10 25 14 26

ALHAMBRA PLAZA & GALIANO STREET CORAL GABLES, FLORIDA COUNTED BY: ROLANDO MARTINEZ SIGNALIZED Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHAGALI Page : 3

GALIANO From Nor				ALHAMBRA  From Eas				GALIANO  From Sou				ALHAMBRA				
UTurn		Thru	Right	   UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	Tota
ate 09/04/13																
eak Hour Analys eak start 17:00		Entire	Incerse	17:00		erioù:	16:00 0	17:00		4/13		17:00			1	
olume 0	23	111	82		8	259	24		62	82	80		40	304	14	
ercent 0%	11%	51%	38%	•	3%	88%	88		28%	36%	36%		10%	77%	48	
total 216				293				225				396			Í	
.ghest 17:00	)			17:00				17:30	i i			17:00				
olume O	5	31	26	0	1	73	8	1	15	32	36	12	13	84	6	
total 62				82				84				115				
IF .87				.89				.67				.86				
					GA	LIAN	10 ST	REET								
	•		ο.	82		111		23		78 82 24						
			0	82		111		23		 184				0		0
					2	16	<u> </u>	"								
								400 -				Г				24
LHAMBRA I	PLAZ	7										ſ			-	
													2	24	-	
62						<b>.</b> .	T TTT		-				2	24	-	
63 259	1	104	-			· Al	L VE	HICLE	S		[		2	24		
259	2	104	-			· AI	L VE	HICLE	S							59
		104	_			· Al	L VE	HICLE	S		2	 293	25			59
259			- 			· Al	L VE	HICLE	S		2	 293 				59
259 82		104 	- == ]			• AI	L VE	HICLE	5			 293 	25	59	2!	59
259 82				8	00	· AI	JL VE	HICLE	5	70		 293   <del></del>	25		2!	
259 82 78				8	00	• AI	JL VE	HICLE	S	70		 293   <del></del>	25	59	2!	
259 82		78	]	1	00							 293 	25	59	2!	10
259 82 78			] ] 39	1	00		ersec	tion '				 293 	25	.0	2!	10
259 82 78		78	] ] ]	1	00			tion '				 293 	25	.0	2!	10  23 04
259 82 78 304		78	] ] 	1	00		ersec	tion '				 293  	25	.0	2!	10
259 82 78		78	] ] 	1	00		ersec 1,	tion / 130					25 1 40	59 -0 -07	2!	10  23 04
259 82 78 304		78	] ]	1	00		ersec 1,	tion '	Iota	1			25 1 40	.0	2!	10  23 04
259 82 78 304 14		78	] ]_	1	00		ersec 1,	tion / 130		1			25 1 40	59 -0 -07	2!	10  23 04
259 82 78 304		78 304 14	] ]_ ]_	1	00	Inte	ersec 1,	tion 7 130 360 -	Iota	1 5 —	 o 	ALH	25 1 40	59 .0 07 2A PI	2!	10  23 04
259 82 78 304 14		78	] ]_ ]_	1	00	Inte	ersec 1,	tion / 130	Iota	1			25 1 40	59 -0 -07	2!	10  23 04
259 82 78 304 14		78 304 14	] ]_ ]_	1	00	Inte	ersec 1,	tion 7 130 360 -	Iota	1 5 —	 o 	ALH	25 1 40	59 .0 07 2A PI	2!	10  23 04
259 82 78 304 14		78 304 14		1	00	Inte	ersec 1,	tion 7 130 360 -	Iota	1 5 —	 o 	ALH	25 1 40	59 .0 07 2A PI	2!	10  23 04
259 82 78 304 14		78 304 14	]	1	00	Inte 10 111 14	ersec 1,	tion 7 130 360 -	Iota	1 5 —	 o 	ALH	25 1 40	59 .0 07 RA PI	2!	10  23 04
259 82 78 304 14		78 304 14	]	1	00	Inte	ersec 1,	tion 7 130 - 63	Iota	1 5 — 82	 o 	ALH	25 1 40	59 .0 07 2A PI	2!	10  23 04
259 82 78 304 14		78 304 14	]	1		10 111 14  135	ersec 1,	tion 7 130 - 63  63	Iota	1 5 — 82	 o 	ALH	25 1 40	59 .0 07 RA PI	2!	10  23 04





ALHAMBRA PLAZA & SW 37TH AVENUE CORAL GABLES, FLORIDA COUNTED BY: M. CRUZ & L. PALOMINO SIGNALIZED

\_\_\_\_\_

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHA37A\_ Page : 1

#### ALL VEHICLES

	 SW 37TH	AVENUE			ALHAMBR	A PLAZA			SW 37TH	AVENUE			ALHAMBR	A PLAZA			
1	From No:	rth			From Ea	st			From So	uth			From We	st			
	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   UTurn	Left	Thru	 Right	Total
Date 09/	04/13 -																
07:00	0	1	168	11	0	7	0	1	0	16	168	2	0	24	0	22	420
07:15	0	0	185	9	0	3	5	6	0	16	181	1	0	53	2	26	487
07:30	1	2	197	17	0	0	3	10	0	17	206	3	0	41	6	20	523
07:45	0	2	232	12	0	5	5	4	0	28	230	2	4	58	2	16	600
Hr Total	1	5	782	49	0	15	13	21	0	77	785	8	4	176	10	84	2030
08:00	0	4	255	13	I 0	6	3	13	0	27	216	0	1	60	2	26	626
08:15	0	4	281	28	0	2	5	8	·	35	211	1	0	62	2	43	682
08:30	0	2	285	28	i o	4	7	1	0	44	220	4	,   0	56	0	42	693
08:45	0	2	293	21	0	1	6	7	0	42	201	2	1	44	4	31	655
Hr Total	0	12	1114	90	0	13	21	29	0	148	848	7	2	222	8	142	2656
	* BRI	EAK * -															
16:00	1	2	208	19	0	2	5	3	0	25	261	1	0	44	6	26	603
16:15	1	3	228	29	0	5	8	2	0	32	271	7	0	59	5	28	678
16:30	0	5	196	26	0	1	2	3	0	35	277	3	1	54	4	34	641
16:45	0	2	223	30	0	5	2	4	0	39	245	4	2	45	6	24	631
Hr Total	2	12	855	104	0	13	17	12	0	131	1054	15	3	202	21	112	2553
17:00	0	4	238	27	0	2	2	5	0	49	284	4	0	62	9	34	720
17:15	0	4	259	28	0	2	8	3	0	31	307	3	0	60	6	26	737
17:30	0	5	241	28	0	2	5	0	0	42	299	11	4	69	7	23	736
17:45	0	1	254	25	0	5	9	3	0	32	300	5	1	56	10	25	726
Hr Total	0	14	992	108	0	11	24	11	0	154	1190	23	5	247	32	108	2919
*TOTAL*	3	43	3743	351	0	52	75	73	0	510	3877	53	14	847	71	446	1015

ALHAMBRA PLAZA & SW 37TH AVENUE CORAL GABLES, FLORIDA COUNTED BY: M. CRUZ & L. PALOMINO SIGNALIZED

#### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHA37A\_ Page : 2

ALL	VEHICLES
-----	----------


ALHAMBRA PLAZA & SW 37TH AVENUE CORAL GABLES, FLORIDA COUNTED BY: M. CRUZ & L. PALOMINO SIGNALIZED

\_\_\_\_\_

Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

### Site Code : 00130154 Start Date: 09/04/13 File I.D. : ALHA37A\_ Page : 3

From Nor	AVENUE th			ALHAMBRA  From Eas				SW 37TH  From Sou				ALHAMBRA				
UTurn		Thru	Right	   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   Tota
te 09/04/13									<b>-</b> -							
ak Hour Analys		Entire	Interse			eriod:	16:00 t			4/13		17:00				1
ak start 17:00 lume 0	14	992	108	17:00   0	11	24	11	17:00   0	154	1190	23	•	247	32	108	1
rcent 0%	18	89%	108		24%	52%	24%		11%	87%	23 28		63%	8%	28%	
total 1114				46				1367			_	392				1
ghest 17:15	5			17:45				17:30	1			17:00				ţ
lume O	4	259	28	0	5	9	3	0	42	299	11	j 0	62	9	34	1
total 291				17				352				105				1
F .96				. 68				.97				.93				1
					SW	371	:н аv 	ENUE				1				
	•		ο.	108	•	992	2.	14		252 190 11						
				108		992	2	14	 1,	 453				0		0
					1,1	14	<u> </u>									
				L	±,±		- 2,	567 ·				г				11
LHAMBRA H	PLAZ	A		L	-,-		- 2,	567 ·				Γ	1	.1		11
	PLAZ	A			±, ±					<u> </u>	]	ſ	1	.1		11
154			-	]	±, ±			567 ·	S				]	.1		
154 24		A 286	-		±, ±				S	<u>, , , , , , , , , , , , , , , , , ,</u>		[				11 24
154			_		± / ±				S	<u> </u>	]	[ 46		.1 .2 .24		
154 24			_ 		- / -				S	<u> </u>		46				
154 24 108			- 						S			[ 46 				
154 24 108		286	]	6	78				S	11	5	[ 46 	2			24
154 24 108 252		286		6					S	11	5	[ 46 [	2			24
154 24 108		286	]			• AI	L VE	HICLE			  5 	46	2			24
154 24 108 252		286	] ] 39			• AI	L VE	HICLE			 5 	[ 46 [	2	.1		24 11 14
154 24 108 252		286	] ] 39			• AI	L VE	HICLE			 5 	46	2			24 11 14 32
154 24 108 252		286 252 32				• AI	L VE	HICLE			5		  	.1 .9		24 11 14
154 24 108 252 32		286	] ] ]_			• AI	L VE ersec 2,	HICLE tion 919			5		  	.1		24 11 14 32
154 24 108 252 32		286 252 32	]			• AI	L VE ersec 2,	HICLE tion 919 478	Tota	1			  	.1 .9	AZA	24 11 14 32
154 24 108 252 32 108		286 252 32	]			• AI	L VE ersec 2,	HICLE tion 919 478		1	5		  	.1 .9	AZA	24 11 14 32
154 24 108 252 32		286 252 32 108	] ]			• AI	L VE ersec 2, - 2,	HICLE tion 919 478	Tota 1,36	1 7 — 			  	24 .1 59 2A PI	- 	24 11 14 32
154 24 108 252 32 108		286 252 32	]			• AI	L VE ersec 2, - 2,	HICLE tion 919 478	Tota	1 7 — 			  	.1 .9	JAZA	24 11 14 32
154 24 108 252 32 108		286 252 32 108	] ] ]_			• AI	L VE ersec 2, - 2,	HICLE tion 919 478	Tota 1,36	1 7 — 			  	24 .1 59 2A PI	- 	24 11 14 32
154 24 108 252 32 108		286 252 32 108	]		78	• AI Inte	L VE	HICLE	Tota 1,36 · 1,	1 7		ALH	  	24 .1 59 2A PI	JAZA	24 11 14 32
154 24 108 252 32 108		286 252 32 108	]		78	• AI	L VE	HICLE tion 919 478	Tota 1,36 · 1,	1 7 — 			  	24 .1 59 2A PI	AZA	24 11 14 32
154 24 108 252 32 108		286 252 32 108	]		78	• AI Inte	L VE	HICLE	Tota 1,36 · 1,	1 7		ALH	  	24 .1 59 2A PI 0	- 	24 11 14 32





MINORCA AVENUE & SW 37TH AVENUE CORAL GABLES, FLORIDA COUNTED BY: MAURICE GOMEZ SIGNALIZED

\_

\_

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00130154 Start Date: 09/04/13 File I.D. : MIN037AV Page : 1

### ALL VEHICLES

		AVENUE							SW 37TH				MINORCA				
Fr	om Noi	rth			From Eas	Bt			From So	uth			From we	5 C		1	
U	Turn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	Tota
Date 09/04	/13																
07:00	0	0	174	4	0	0	0	0	1	3	189	0	0	1	0	4	37
7:15	0	0	187	8	0	0	0	0	0	4	230	0	0	0	0	2	43
7:30	0	0	210	5	0	0	0	0	0	5	253	0	0	3	0	5	48
07:45	0	0	239	12	0	0	0	0	0	14	279	0	0	3	0	5	55
Ar Total	0	0	810	29	0	0	0	0	1	26	951	0	0	7	0	16	184
8:00	0	0	269	10	0	0	0	0	0	22	271	0	0	4	0	9	58
8:15	0	0	290	13	0	0	0	0	0	19	265	0	0	2	0	14	60
8:30	0	0	300	12	0	0	0	0	0	22	252	0	0	1	0	11	59
8:45	0	0	312	12	0	0	0	0	0	22	228	0	0	2	.0	6	5
Ir Total	0	0	1171	47	0	0	0	0	0	85	1016	0	0	9	0	40	236
	* BRI	EAK *															
16:00	0	0	223	8	0	0	0	0	0	3	309	0	0	11	0	8	56
L6:15	0	0	250	4	0	0	0	0	0	11	319	0	0	7	0	11	60
L6:30	0	0	210	2	0	0	0	0	0	8	322	0	0	10	0	14	50
6:45	0	0	237	6	0	0	0	0	0	6	291	0	0	15	0	11	5
Ir Total	0	0	920	20	0	0	0	0	0	28	1241	0	0	43	0	44	22
			247	5	0	0	0	0	0	7	341	0	0	17	0	20	63
L7:00	0	0	211			^	0	0	0	11	358	0	0	18	0	30	68
	0 0	0 0	265	4	0	0											
17:00 17:15 17:30				4 8		0	0	0	0	11	356	0	0	23	0	17	67
.7:15 .7:30	0	0	265		0		0	0	0   0	11 11	356 349	0 0		23 21	0	17   25	6
7:15	0 1	0 0	265 263	8	0   0	0	-		0				0		-		

MINORCA AVENUE & SW 37TH AVENUE CORAL GABLES, FLORIDA COUNTED BY: MAURICE GOMEZ SIGNALIZED

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

### Site Code : 00130154 Start Date: 09/04/13 File I.D. : MINO37AV Page : 2

From No	AVENUE			   <del>-</del>				SW 37TH				MINORCA			ĺ	
	rth			From Eas	t			From Sou	ith			From Wes	t			
UTurn te 09/04/13 -	Left	Thru	Right	   UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	Tot
ak Hour Analy																
ak start 08:0	0			08:00				08:00				08:00			l	
ume 0	0	1171	47		0	0	0	1	85	1016	0		9	0	40	
cent 0%	0%	96%	48		0%	08	0%	•	88	92%	08		18%	0%	82%	
total 1218	F			0				1101				49   08:15			l	
jhest 08:4 .ume 0	5 0	312	12	07:00   0	0	0	0	08:00	22	271	0		2	0	14	
total 324	°,	912		0	Ũ		Ū	293		2,1	0	16	-	· ·		
.94				.0				.94				.77			ĺ	
			I		SW	371	'H AV	ENUE				I				
			ο.	47	. 1	,171	1.	o		9						
	•		0	4/		, _ / _			1	016						
									±,	0						
															•	0
			0	47	1	,171		0	1,	025				0		
					1 2	10	1	, II								
					1,2		- 2.	243 -							•	0
INORCA A	VENU	E					-,							0		•
85			_						_							
0		1 2 2				· AL	'T AE	HICLE	S							~~~~
17		132				• AL	L VE	HICLE	S						•	0
47		132				• AL	L VE	HICLE	S			 0		0	•	0
		132				• AL	L VE	HICLE	S			 0 		0	•	0
47 9		132  9	— ]			· AL	L VE	HICLE	S			 0 		0		0
-			— ]	1	81	· AL	L VE	HICLE	S		0			0	•	
9			]	1	81	· AL	L VE	HICLE	S		0	 0 			•	
		9	] ]	1	81						0 	 0 			•	0
9			] ] 49	1	81		ersec	tion '			0 	 0 		0	•	0
9 0		9	] ] 49 ]	1	81		ersec				0 	 0   ===				0
9		9 0	] ] 49 ]	1	81		ersec	tion '			0	 0   		0	•	0
9 0		9	] ] 49 	1	81		ersec 2,	tion ' 368			0			0	•	0
9 0		9 0	 49 	1	81		ersec 2,	tion ' 368 312 -	Iota	1	0			0	•	0
9 0 40		9 0	] ]	1	81		ersec 2,	tion ' 368 312 -		1	0	 0   		0	•	0
9 0		9 0	] 49 ]_	1		Inte	ersec 2, - 2,	tion ' 368 <u>312</u>	Tota 1,10	1	0			0	•	0
9 0 40		9 0 40	 	1		Inte 0 ,171	ersec 2, - 2,	tion ' 368 <u>312</u>	Iota	1	0			0	•	0
9 0 40		9 0 40	 49 	1		Inte	ersec 2, - 2,	tion ' 368 <u>312</u>	Tota 1,10	1	0			0	•	0
9 0 40		9 0 40	] 	1	1	Inte 0 ,171 40	ersec 2, 2,	tion ' 368 312 - 85	Tota 1,10 • 1,•	1 1 — 016	0	0		0	•	0
9 0 40		9 0 40	] 	1	1	Inte 0 ,171	ersec 2, 2,	tion ' 368 <u>312</u>	Tota 1,10 · 1, '	1	0			0	•	0
9 0 40		9 0 40	] 	1	1  1	Inte 0 ,171 40  ,211	ersec 2, 2,	tion ' 368 312 - 85	Tota 1,10 · 1, '	1 1 — 016	0	0		0	•	0

MINORCA AVENUE & SW 37TH AVENUE CORAL GABLES, FLORIDA COUNTED BY: MAURICE GOMEZ SIGNALIZED

----

-----

Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

### Site Code : 00130154 Start Date: 09/04/13 File I.D. : MINO37AV Page : 3

SW 37TH				1								MINORCA	AVENT		I	
From Nor				  From Eas	t			SW 37TH				From Wes				
UTurn	Left			   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	Tot
te 09/04/13 ak Hour Analys				ction for	the P	eriod:	16:00 t	o 18:00 d	on 09/04	4/13						
ak start 17:00				17:00				17:00				17:00				
lume 1	0	1027	25		0	0	0	0	40	1404	0	0	79	0	92	
rcent 0%	0%	98%	2%	0%	0%	0%	08	0%	3*	97%	0%	0 <b>%</b>	46%	0%	54%	
total 1053				0				1444				171				
ghest 17:30	)			07:00	)			17:15	5			17:15			ł	
lume 1	0	263	8	0	0	0	0	0	11	358	0	0	18	0	30	
total 272				0				369				48				
F .97				.0				.98				.89				
					SW	371	гн аv	ENUE								
			~	0.5		0.05	,	-		70						
	•		ο.	25	· • +	,027	/ ·	1	1	79 404						
									±,	-0-						
							_									0
			0	25	1	,027	7	1	1.	483				0		·
					_	,		-	-,					-		
· · · · · · · · · · · · · · · · · · ·				<u> </u>	ʻ1,0	53		"								
							- 2,	536				Г			•	0
INORCA A	VENU	E												0		
4.0														-		
						ъ т			0					-		
40		C.F.	_			• AI	L VE	HICLE	S							
0		65	-			• AI	LL VE	HICLE	S			_  _			•	0
		65				• AI	LL VE	HICLE	S			 o		0		0
0 25		65	- 			• AI	LL VE	HICLE	S			 0 1				0
0			- — 1			• AI	L VE	HICLE	S			 o 	<u>+ 1 </u>			
0 25		65 79	- 	2	36	• AI	LL VE	HICLE	S		1	 0 		0		0
0 25			_ ]	2	36	• AI	LL VE	HICLE	S		1	 0 	<u>.</u>			
0 25			_ 	2	36	• AI	L VE	HICLE	S		1	 0 		0		
0 25 79			] ] 17		36		ersec	tion		1	1	 0 		0		-
0 25 79		79	- ] 17		36		ersec	tion		1	1			0		0
0 25 79 0		79	-  17 		36		ersec			1	1			0	•	0
0 25 79		79 0	-  17 		36		ersec	tion		1	1	 0   		0		0
0 25 79 0		79	] ] 17 		36		ersec 2,	tion 668		1	1	 0 		0		0
0 25 79 0		79 0	] ] 		36		ersec 2,	tion 668 563	Tota		1	 0 [ 		0		0
0 25 79 0 92		79 0	] ]		36		ersec 2,	tion 668 563						0		0
0 25 79 0		79 0 92	] ]_ ]_		36	Inte	ersec 2, - 2,	tion 668 563	Tota 1,44	4 —				0	•	0
0 25 79 0 92		79 0	] ]			Inte	ersec 2, - 2,	tion 668 563	Tota	4 —	1			0		0
0 25 79 0 92		79 0 92	] ]			Inte	ersec 2, - 2,	tion 668 563	Tota 1,44	4 —	1			0	•	0
0 25 79 0 92		79 0 92	] ]			Inte	ersec 2, - 2,	tion 668 563	Tota 1,44	4 —	1			0	•	0
0 25 79 0 92		79 0 92	] ] ]_		1	Inte .,027 .92	ersec 2, - 2,	tion 668 563 40	Tota 1,44 • 1,•	4			·	0		0
0 25 79 0 92		79 0 92			1	Inte	ersec 2, - 2,	tion 668 563	Tota 1,44 • 1,•	4 —	1	0.		0		0
0 25 79 0 92		79 0 92	 		1  1	Inte ,027 92	ersec 2, - 2, - 2,	tion 668 563 40	Tota 1,44 • 1,•	4		0.		0		0

SW 37TH AVENUE



sustant of the second s 2030 <u>Minorca p</u> 1 A B VIV coral Gables, FLOrida September 04,2013 drawn by! mis Palomino Signalized

- - ----

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHAMINO Page : 1

### ALL VEHICLES

FI	INORCA	AVENUE			ALHAMBRI  From Eas		E		MINORCA  From So				ALHAMBRA From Wes		E		
τ	JTurn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	Total
Date 04/24	4/14																
07:00	0	1	4	2	0	2	12	1	0	1	1	1	0	2	6	5	38
07:15	0	0	2	0	0	1	24	1		3	3	0	0	5	3	16	58
07:30	0	0	4	4	2	5	34	2	0	1	5	1	0	10	5	16	89
07:45	0	0	. 5	10	0	3	46	8	0	4	7	2	•	11	9	22	127
Hr Total	0	1	15	16	2	11	116	12	0	9	16	4	0	28	23	59	312
08:00	0	1	3	19	0	1	59	10	0	7	9	4	1 0	24	9	31	177
08:15	0	2	12	40	0	3	66	10	0	4	6	0	2	26	14	23	208
08:30	0	3	11	23	0	9	72	3	0	11	14	3	0	21	10	34	214
08:45	0	0	9	20	0	4	56	2	0	9	2	1	0	5	9	22	139
Hr Total	0	6	35	102	0	17	253	25	0	31	31	8	2	76	42	110	738
	* BRE	AK *															
16:00	0	0	4	23	2	1	57	3	0	7	4	2	0	13	22	22	160
16:15	0	0	3	15	0	0	54	2	0	9	6	2	2	6	14	18	131
16:30	0	1	8	13	0	3	57	3	0	10	4	2	0	9	18	10	138
	0	0	5	13	0	4	56	0	0	16	5	0	2	16	25	14	156
16:45												~	1	44		e . 1	585
	0	1	20	64	2	8	224	8	0	42	19	6	4	44	79	64	585
1 <u>6:45</u> Hr Total 17:00	0	1 0	20 6	64 18	2	8	224 52	8	0   0	42 32	19	4		44 20	79 29	28	212
Hr Total 17:00													1				
Hr Total	0	0	6	18	1	2	52	1	0	32	18	4	1	20	29	28	212
Hr Total 17:00 17:15	0 0	0 1	6 13	18 31	1   0	2 3	52 50	1 0	0   0	32 25	18 14	4 3	1   0   1	20 7	29 20	28   22	212 189
Hr Total 17:00 17:15 17:30	0 0 0	0 1 1	6 13 8	18 31 16	1   0   0	2 3 0	52 50 45	1 0 1	0   0   0	32 25 17	18 14 17	4 3 2	1   0   1   0	20 7 20	29 20 17	28   22   17	212 189 162

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHAMINO Page : 2

							ALL V	EHICLES						5		
MINORCA From Nor				ALHAMBRA  From Eas		 E		MINORCA  From Sou				ALHAMBRA  From Wes		 E		
UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	   UTurn	Left	Thru	Right	UTurn	Left	Thru	 Right	Total
Date 04/24/14																
Peak Hour Analys		Entire	Interse			eriod:	07:00 t			4/14						
Peak start 08:00 Volume 0	6	35	102	08:00	17	253	25	08:00	31	31	8	08:00	76	42	110	
Percent 0%	4%	24%	71%	4	/ 6%	86%	8%		44%	44%	0 11%		33%	42 18%	48%	
Pk total 143				295				70				230				
Highest 08:15				08:30				08:30	ł			08:15			i	
Volume 0	2	12	40	0	9	72	3	0	11	14	3	2	26	14	23	
Hi total 54				84				28				65				
PHF .66				.88				.62				.88				
			I		MI	NORC	'A AV	ENUE								
	•		ο.	102		35	•	6		78 31 25						
																0
			0	102		35		6	-	134				0		•
								,								
		÷		L	1	43		 277 -			I					
ALHAMBRA C	IRC	LE					•	211 -				ſ	2	25	· 4	25
													_			
31						• AL	L VE	HICLES	5		<b>F</b>					
253 102	-	386											0.5	• - •	25	53
											4	295	25	د ر		
· 78																
		78		i							I				-	L7
				6	16					35	1		1	.7		
				1								L				
· 42		42	23			Tnto	~~~~~	tion r		1						
		42	23	0		ince		tion 7 738	rota.	L			5	6		6 12
			— I					/50					5	00	4	±∠ 8
· 110			-													0
	-	110										ALH	AMBR	A CI	RCLE	
			L	Г			•	232 -								
· 0							п Г	I	70	) —						
• 0		0				1 7		31		31		0		0		
		0				17 35		5 T		3 I	•	8 •		0		
						110										
														-		
						162		31		31		8		0		
					ΜΤ	งกษณ	 A AVI									
					1-1					1						

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

### Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHAMINO Page : 3

ALL	VEHICLES
-----	----------



### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHAMINO Page : 1

### PEDESTRIANS

		AVENUE			ALHAMBR		Έ		MINORCA		3		ALHAMBRA		Έ		
	From No:	rth			From Ea:	st			From So	uth			From Wes	st			
	Left	Thru	Right	Peds	   Left	Thru	Right	Peds	   Left	Thru	Right	Peds	Left	Thru	Right	Peds	Total
Date 04/	24/14 -																
07:00	0	0	0	3	0	0	0	0	1 0	0	0	1	0	0	0	0	4
07:15	0	0	0	2	0	0	ů O	0	0	õ	õ	2		ő	ů O	0	4
07:30	0	0	0	1		0	0	2	1 0	0	0	2		0	0	0	5
07:45	0	0	0	2	,	0	0	4		0	õ	1	,	0	ů 0	0	7
Hr Total	. 0	0	0	8	0	0	0	б	A	0	0	6		0	0	0	20
08:00	0	0	0	1	0	0	0	0	0	0	0	5	0	0	0	0	6
08:15	0	0	0	2	0	0	0	2	0	0	0	1	0	0	0	1	6
08:30	0	0	0	3	0	0	0	0	0	0	0	4	0	0	0	0	7
08:45	0	0	0	2	0	0	0	2	0	0	0	2	0	0	0	0	6
Hr Total	0	0	0	8	0	0	0	4	0	0	0	12	0	0	0	1	25
	* BRI	CAK * -															
16:00	* BRI 0	EAK * - 0	0	3	0	0	0	2	0	0	0		0	0	0	 0	 9
				 3 4	0   0	0	0 0	2 7	1	0 0	0	4 2	0   0	0	0	0   2	 9 15
16:00 16:15	0	0	0						0				0				
16:00	0 0	0 0	0 0	4	0	0	0	7	0	0	0	2	0	0	0	2	15
16:00 16:15 16:30 16:45	0 0 0	0 0 0	0 0 0	4 5	0	0 0	0 0	7 2	0   0   0	0 0	0 0	2 2		0 0	0 0	2   1	15 10
16:00 16:15 16:30	0 0 0	0 0 0 0	0 0 0	4 5 1	0 0 0	0 0 0	0 0 0	7 2 0	0   0   0	0 0 0	0 0 0	2 2 0	0   0   0	0 0 0	0 0 0	2   1   0	15 10 <u>1</u>
16:00 16:15 16:30 <u>16:45</u> Hr Total 17:00	0 0 0 0	0 0 0 0	0 0 0 0	4 5 1 13	0 0 0	0 0 0	0 0 0	7 2 0 11	0   0   0	0 0 0	0 0 0	2 2 0 8	0   0   0	0 0 0	0 0 0	2   1   0   3	15 10 <u>1</u> 35
16:00 16:15 16:30 <u>16:45</u> Hr Total	0 0 0 0	0 0 0 0 0	0 0 0 0	4 5 13 6 1		0 0 0 0	0 0 0 0	7 2 0 11	0   0   0	0 0 0 0	0 0 0 0	2 2 0 8		0 0 0 0	0 0 0 0	2   1   0   3   1	15 10 <u>1</u> 35 9
16:00 16:15 16:30 <u>16:45</u> Hr Total 17:00 17:15	0 0 0 0 0	0 0 0 0 0	0 0 0 0 0	4 5 1 13 6 1		0 0 0 0 0	0 0 0 0 0	7 2 0 11 1 0	0   0   0   0	0 0 0 0 0	0 0 0 0 0	2 2 0 8 1 0		0 0 0 0 0	0 0 0 0 0	2   1   0   3   1   2	15 10 <u>1</u> 35 9 3
16:00 16:15 16:30 <u>16:45</u> Hr Total 17:00 17:15 17:30	0 0 0 0 0 0 0 0 0 0	0 0 0 0 0 0 0	0 0 0 0 0 0 0	4 5 13 6 1		0 0 0 0 0 0	0 0 0 0 0 0 0	7 2 0 11 1 0 0	0   0   0   0   0   0   0	0 0 0 0 0 0	0 0 0 0 0 0 0	2 2 0 8 1 0 1		0 0 0 0 0 0	0 0 0 0 0 0 0	2   1   0   3   1   2   1	15 10 <u>1</u> 35 9 3 3

North



-----

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHA37AV Page : 1

							<i>.</i> 4	ALL V	EHICLES						Page	: : .	L
	SW 37TH			*		<u>-</u>			SW 37TH				ALHAMBR	A CIRCLI	 E		
1	From No:	rth			From Ea	st			From So	uth			From We	st			
	UTurn	Left		5	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	Total
Date 04/2	24/14 -																
07:00	0	0	192	11	0	0	0	0	0	1	161	0	0	8	0	1	374
07:15	0	0	206	24	0	0	0	0	0	0	243	0	1	2	0	5	481
07:30	0	0	253	34	0	0	0	0	0	0	232	0	0	2	0	2	523
07:45	1	0	261	52	0	0	0	0	0	0	292	0	0	12	0	3	621
Hr Total	1	0	912	121	0	0	0	0	0	1	928	0	1	24	0	11	1999
08:00	0	0	244	62	0	0	0	0	0	1	312	0	0	15	0	3	637
08:15	0	0	331	76	0	0	0	0	0	3	292	0	0	15	0	6	723
08:30	0	0	308	75	0	0	0	0	0	1	275	0	1	15	0	3	678
08:45	0	0	321	51	0	0	0	0	0	0	250	0	0	14	0	3	639
Hr Total	0	0	1204	264	0	0	0	0	0	5	1129	0	1	59	0	15	2677
	* BRI	EAK *															
16:00	0	0	263	55	0	0	0	0	0	0	302	0	0	12	0	0	632
16:15	0	0	272	56	0	0	0	0	j 0	0	308	0	0	13	0	4	653
16:30	0	0	266	61	0	0	0	0	0	0	334	0	0	12	0	6	679
16:45	00	0	293	60	0	0	0	0	0	0	312	0	0	19	0	6	690
Hr Total	0	0	1094	232	0	0	0	0	0	0	1256	0	0	56	0	16	2654
17:00	0	0	261	56	0	0	0	0	0	0	359	0	0	21	0	8	705
17:15	0	0	268	51	0	0	0	0	0	2	355	0	0	19	0	2	697
17:30	0	0	264	54	0	0	0	0	0	1	318	0	0	18	0	7	662
17:45	3	0	245	56	0	0	0	0	0	2	316	0	1	21	0	6	650
Hr Total	3	0	1038	217	0	0	0	0	0	5	1348	0	1	79	0	23	2714
*TOTAL*	4	0	4248	834	0	0			0	11	4661		3	218	0	65	1004

\_\_\_\_\_

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHA37AV Page : 2

SW 37TH AV																
From North				  From Eas	t			SW 37TH  From Sou 				ALHAMBRA  From Wes		Е		
	Left		-	UTurn			Right	UTurn	Left	Thru	Right	UTurn	Left	Thru	Right	Tota
ate 04/24/14 eak Hour Analysis							07.00 +		n 04/2/	·						
eak start 08:00	з Бу Б	SHCILE	meerse	08:00			07:00 C	08:00		1/14		08:00			1	
olume 0	0	1204	264	00.00	0	0	0	00.00	5	1129	0	1	59	0	15	
ercent 0%	0%	82%	18%	0%	0%	0%	0%		- 0%	100%	- 0%	'	79¥	0%	20%	
k total 1468				0				1134				75	-	-		
ighest 08:15				07:00				08:00				08:15			Ì	
olume O	0	331	76	0	0	0	0	0	1	312	0	0	15	0	6	
i total 407				0				313				21			1	
HF .90				.0				.91				.89			I	
					SW	371	'H AV	ENUE								
	•		ο.	264	· 1	,204	•	0	1,1	60 129 0						
	-		0	264	1	,204		0	1,3	189				0		0
					1,4	68	<u> </u>	"			,					
ALHAMBRA CI	IRCI	Ε		L			- 2,	657 -				Γ				0
														•		
5	_		_	······		· AL	L VE	HICLES	3							
0	2	269	_	]		• AL	L VE	HICLES	5							0
	2	269	_			• AL	L VE	HICLES	5			 0		0 0		0
0 264	2	269				• AL	L VE	HICLES	5			 0				0
0			- 			· Al	L VE	HICLES	5			 0 				
0 264		69 60	- 	3	44	· AL	L VE	HICLES	5		0	 o 		0		0
0 264 60			_ ] ]	3	44	• AL	L VE	HICLES	5		0	 0 				
0 264		60	]	I							0 	 0 		0		
0 264 60			] ] 75	I			rsec	tion 1			0	 0 		0 0		0
0 264 60		60		I			rsec				0	 0 		0		0
0 264 60 0		60		I			rsec	tion 1			0 	0 		0 0		0
0 264 60		60 0	-  75 	I			rsec	tion 1			0	0 		0 0		0
0 264 60 0		60	   	I			rsec 2,	tion 5 677			0	 0  		0 0		0
0 264 60 0		60 0		I			rsec 2,	tion 5 677 353 -	[ota]	L	0   	 0  		0 0		0
0 264 60 0		60 0 15	-  75  ]	I			rsec 2,	tion 5 677	[ota]	1 1 —	0   	 0   		0 0		0
0 264 60 0 15		60 0		I		Inte	rsec 2, 2,	tion 5 677	[ota]	1 1 —	0   			0 0		0
0 264 60 0 15		60 0 15		I		Inte 0 ,204	ersec 2, 2,	tion 5 677	[ota]	1 1 —	0     -	 		0 · 0 ·		0
0 264 60 0 15		60 0 15		I		Inte	ersec 2, 2,	tion 5 677	[ota]	1 1 —	0     -	 		0 · 0 ·		0
0 264 60 0 15		60 0 15		I	1	Inte 0 ,204 15	2,	tion 5	Tota .,134 1,1	1 <u> </u>	0			0		0
0 264 60 0 15		60 0 15		I	1	Inte 0 ,204	2,	tion 5 677	[ota]	1 <u> </u>	0     -			0 · 0 ·		0
0 264 60 0 15		60 0 15		I	1	Inte 0 ,204 15	2,	tion 5	Tota .,134 1,1	1 <u> </u>	0			0		0

### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

### Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHA37AV Page : 3

ALL VEHICLES	ALL	VEHICLES
--------------	-----	----------



### Traffic Survey Specialists, Inc. 624 Gardenia Terrace Delray Beach, Florida 33444 Phone (561) 272-3255

Site Code : 00140086 Start Date: 04/24/14 File I.D. : ALHA37AV Page : 1

### PEDESTRIANS

	W 37TH	AVENUE			From Ea	st			SW 37TH  From So		}		ALHAMBR		Ε		
	Left	Thru	Right	Peds	Left	Thru	Right	Peds	   Left	Thru	Right	Peds	   Left	Thru	Right	Peds	Tota
Date 04/2	4/14																
07:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	
07:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	
07:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
07:45	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
Hr Total	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5	!
00:80	0	0	0	0	0	0	0	0	0	0	0	0	1 0	0	0	0	
08:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
08:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	
08:45	0	0	0	0	0	0	0	0	0	0	0	0	0	. 0	0	0	
Hr Total	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	
	- * BRI	CAK * -						<b></b> -									
16:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	
16:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
16:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
16:45	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3	
Hr Total	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	8	i
17:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	(
17:15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	:
17:30	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	2	:
7:45	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	11	1:
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	14	1
Ir Total	Ũ																





**Peak Season Factor** 

١K	SEAS	ΟN	FACTOR	CZ	ATEGORY	REPORT	-	REPORT	TYPI	Ξ:	ALL	
	8701	ΜJ	IAMI – DAI	Σ	SOUTH							
								MC	DCF:	0	.99	

WEEK	DATES	SF	MOCF: 0.99 PSCF
			PSCF 1.00 1.01 1.03 1.02 1.01 1.00 1.02 1.00

\* PEAK SEASON

18-FEB-2014 08:46:31

830UPD

6\_8701\_PKSEASON.TXT

**Signal Timing Data** 

Print Date: 5/20/2013

Asset 5140 <u>PH 1</u> NBL

0

# **TOD Schedule Report**

for 5140: Douglas Rd&Minorca Av

ei ei						for 5140	40: Douglas Rd&Minorca Av	Av				Print Time: 10:13 AM	
		Intersection			<u>TOD</u> Schedule	Op Mode	Plan #	Cvcle	Offset	<u>TOD</u> Setting	<u>Active Active</u> PhaseBank Maximum	<u>Active</u> Maximum	
	Dougle	Douglas Rd&Minorca Av	rca Av		DOW-2		 N/A	0	0	N/A	0	0 Max 0	
			Sp	<u>Splits</u>									
	<u>PH 2</u>	<u>PH 3</u>	<u>PH 4</u>	<u>PH 5</u>	<u>9 H </u>	<u> 7 H </u>	<u>PH 8</u>						
	SBT	ı	ı		NBT	·	EBT						
	0	0	0	0	0	0	0						

Phase Bank 1 Active Phase Bank:

unknown				12345678	126-8	-26-8	-26-8	-26-8		
Last In Service Date:		Dormittod Dhacoc			Default	External Permit 0	External Permit 1	External Permit 2		
Red			0.9	0.9	0	0	0	0.9	0	0.5
<u>Yellow</u>			4	4	0	0	0	4	0	4
Max 2		2 3	5 2 - 2 - 2 5 - 7 - 7 18 - 7 - 7	- 1 20 - 20 - 20 32 - 30 - 30	0 - 0 - 0	- 0 - 0	0 - 0 - 0	- 1 20 - 20 - 20 35 - 30 - 30	0 - 0 - 0	7 4 -2.5 - 2.5 7 - 15 - 15 49 - 15 - 15
		1	7 18	20 32	-	0 0	_	20 35	0 0	15 49
<u>Max Limit</u>		2 3	- 7 - 2	0 - 20 -	- 0 - (	- 0 - (	- 0 - (	0 - 20 -	- 0 - (	- 15 -
Ext		3 1	2 - 2 5		0 - 0 - 0 0 - 0 - 0	0 - 0 - 0 0 - 0 - 0 - 0 - 0	0 - 0 - 0 0 - 0 - 0	1 - 1 2	0 - 0 - 0 0 - 0 - 0	.5 - 2.5 7
<u>Veh Ext</u>		1 2	2 -	3 1 - 1	- 0	- 0	- 0	3 1 - 1	- 0	4 -2
<u>Min Initial</u>		2 3	5 -	- 16 - 16	- 0 - 0	- 0 - 0	- 0 - 0	- 16 - 16	0 - 0 -	- 7 - 7
		1	- 0 2 -	0 16 -	- 0 0	- 0 0	- 0 0	0 16 -	- 0 0	- 6 0
<u>Don't Walk</u>		1 2 3	- 0 - 0	0 - 0 - 0	- 0 - 0	- 0 - 0	0 - 0 - 0	- 0 - 0	- 0 - 0	- 0 - 0
<u>Walk</u>	Phase Bank	1 2 3	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0
<u>Phase</u>			1 NBL	2 SBT	- د	4 -	5 -	6 NBT	- 7	8 EBT

					<b>Green Time</b>	ime						I ocal T(	l ocal TOD Schedule	
Cuelo 1	1 2	7		4		w	9	7		Ding Offcot	Offent			
Plan Lycle NBL SBT	NBL SBT -	SBT -	ı				NBT	-	EBT	KING UITSEL	<u>Urtset</u>	Time	<u>Plan</u>	DOW
1 130 7 91 0 0	7 91 0	0	0	0		0	103	0	18	0	68	0000	20	Su S
2   120 7 73 0 0	7 73 0	0	0	0		0	85	0 2	26	0	39	0000	23	M T W Th F
3   100 7 61 0 0	7 61 0	0	0	0		0	73	0 1	18	0	29	0100	23	Su
5 1 180 17 101 0 0	17 101 0	101 0	0	0		0	123	0 4	48	0	27	0115	Flash	МТWThF
6   90 7 49 0 0	7 49 0	0	0	0		0	61	0 2	20	0	70	0230	Flash	Su Su
7 180 17 111 0 0	17 111 0	111 0	0	0		0	132	0 3	38	0	52	0230	Flash Flash	M I W I D F
8 80 7 45 0 0	7 45 0	0	0	0		0	57	0 1	14	0	64	0330	riasn 20	
9 75 7 39 0 0	7 39 0	0	0	0		0	51	0 1	15	0	56	0020	70	
10 130 7 81 0 0	7 81 0	0	0	0		0	93	0 2	28	0	99		ით	
11 120 7 81 0 0	7 81 0	0	0	0		0	93	0 1	18	0	68	0030	5	МТШТЬЕ
20 75 7 36 0 0 (	7 36 0 0	0 0	0 0		Ŭ	0	48	0	18	0	38	1000	10	Su Su
23 70 7 34 0 0	7 34 0 0	0	0		9		46	0	15	0	43	1530		МТѠТһ F
												1900	ω	МТѠТҺҒ
												2100	6	МТWThF
												2200	6	Su S
												2330	23	Su M T W Th
Current Time of Day Function						Local Ti	Time of I	ime of Day Function	ction					* Settings
Settings * Day of Week	Day of Week	Day of Week			н	Time	<b>Function</b>	티		Settings *	<u>Day of Week</u>	ek	Blank - FREE -	Blank - FREE - Phase Bank 1, Max 1
TOD OUTPUTS SuM T W ThF S	SuM T W ThF S					0000	TOD O	TOD OUTPUTS	6		SuM T W ThF S	F S	Blank - Plan - P	Blank - Plan - Phase Bank 1, Max 2

No Calendar Defined/Enabled

Phase Bank 2, Max 1
 Phase Bank 2, Max 2
 Phase Bank 3, Max 1
 Phase Bank 3, Max 2
 EXTERNAL PERMIT 1
 EXTERNAL PERMIT 2
 X-PED OMIT

8 - TBA

Page 2 of 2

Print Date: 5/20/2013

## **TOD Schedule Report**

for 5169: Alhambra Plz&Galiano St

Print Date: 5/20/2013						for 5169.	for 5169: Alhambra Plz&Galiano St	o St				Print Time: 10:14 AM	
					TOD					TOD	Active	Active	
Asset		<b>Intersection</b>	-1	Sc	<u>Schedule</u>	<u>Op Mode</u>	<u>Plan #</u>	<u>Cycle</u>	<u>Offset</u>	Setting	<u>PhaseBank</u>	<u> PhaseBank Maximum</u>	
5169	Alham	Alhambra Plz&Galiano St	iliano St	DQ	DOW-2		N/A	0	0	N/A	0	Max 0	
			Spl	<u>Splits</u>									
<u>PH 1</u>	<u>PH 2</u>	<u>PH 3</u>	<u>PH 4</u>	<u>PH 5</u>	<u>9 H </u>	<u>PH 7</u>	<u>PH 8</u>						
EBL	WBT		NBT		EBT		SBT						
0	0	0	0	0	0	0	0						
1	ł		*		ſ		-						

	unknown				<u>12345678</u>	12-4-6-8	-2-4-6-8	-2-4-6-8	-2-4-6-8			
	Last In Service Date:		Dormittad Dhacae			Default	External Permit 0	External Permit 1	External Permit 2			
	Red			0	0.3	0	1.8	0	0.3	0	1.8	
	<u>Yellow</u>			3	4	0	4	0	4	0	4	
	<u>Max 2</u>		1 2 3	20 - 10 - 10	0 - 30 - 30	0 - 0 - 0	69 - 20 - 20	0 - 0 - 0	0 - 30 - 30	0 - 0 - 0	69 - 20 - 20	
	<u>Max Limit</u>		1 2 3	7 - 7 - 7   20 - 10 - 10	30 - 30 - 30		20 - 20 - 20	0 - 0 - 0	30 - 30 - 30		20 - 20 - 20	
	<u>Veh Ext</u>		1 2 3	2 - 2 - 2	1 - 1 - 1	0 - 0 - 0 0 - 0 - 0	7 2.5 -2.5 - 2.5 20 - 20 - 20 69 - 20 20	0 - 0 - 0	1 - 1 - 1	0 - 0 - 0 0 - 0 - 0	7 2.5 -2.5 - 2.5 20 - 20 - 20 69 - 20 20	
	<u>Min Initial</u>		1 2 3	5 - 2 - 2	15 - 15 - 15	0 - 0 - 0	7 - 7 - 7	0 - 0 - 0	15 - 15 - 15	0 - 0 - 0	7 - 7 - 7	
Phase Bank 1	<u>Don't Walk</u>		1 2 3	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	
	<u>Walk</u>	Phase Bank	1 2 3	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	0 - 0 - 0	
Active Phase Bank:	<u>Phase</u>			1 EBL	2 WBT	3	4 NBT	5 -	<u>6</u> EBT	7 -	8 SBT	

				•	i								
turint of		-	ç				y	0 F			Local T	Local TOD Schedule	
TOD Schedule Plan	<u>Cycle</u> E	• EBL	wbt		HBT		<b>u</b> EBT	S	T Ring Offset	<u>Offset</u>	Time	<u>Plan</u>	DOW
Ţ	90 5		54 0		18 0		62 0	18	0	29	0000	20	Su Su
2	120 5		66 0		36 0				0	85	0000	23	И Т W Тh F
3	100 5		58 0		24 0		66 0		0	65	0100	23	Su S
5	90 5		46 0		26 0		54 0	) 26	0	0	0115	21	МТWThF
9	90 5		49 0		23 0		57 0	) 23	0	46	0230	21	Su Su
7	90 5		40 0		32 0		48 0		0	73	0230	22	
8	80 5		44 0		18 0			) 18	0	47	0330	22	
6	75 5		39 0		18 0		47 0	) 18	0	53	0000	70	
10	100 5		64 0		18 0		72 0	) 18	0	18		nd	
11	120 5		69 0		33 0		77 0	33	0	97	0000		М Т М Т Б
20	75 5		39 0		18 0		47 0		0	73	1000	4 C	Su Su Su
21	70 5		44 0	) 8	0		52 0	8	0	44	1530	~	МТѠТһ Е
22	70 5		44 0		0				0	44	1900	- α	MTWThF
23	70 5		44 0	8	0		52 0		0	44	2100	6	MTWThF
											2200 2330	20 23	Su Su Su T W Th
					] ]								
Current Time of Day Function	ſ				<u> </u>	Local Tir	me of D	ime of Day Function	on				* Settings
Time Function	Settings *		<u>Day of Week</u>	<u>/eek</u>		Time	<b>Function</b>	Ę	<u>Settings *</u>	<u>*</u> Day of Week	<u>jek</u>	Blank - FREE -	Blank - FREE - Phase Bank 1, Max 1
0000 TOD OUTPUTS		SL	SuM T W ThF S	ThF S	Ó	- 0000	TOD OL	TOD OUTPUTS		SuM T W ThF S	hFS	Blank - Plan - F	Blank - Plan - Phase Bank 1, Max 2
					]						]	1 - Phase Bank 2, Max 1	< 2, Max 1
												2 - Phase Bank 2, Max 2	< 2, Max 2
											1	3 - Phase Bank	< 3, Max 1
												4 - Phase Bank 3, Max 2	< 3, Max 2
												5 - EXTERNAL PERMIT	- PERMIT 1
												6 - EXTERNAL PERMIT 2	- PERMIT 2
												7 - X-PED OMIT	T
											-		

No Calendar Defined/Enabled

8 - TBA

Print Date: 5/20/2013

Asset 3580

# **TOD Schedule Report**

for 3580: Alhambra Plz&Douglas Rd

Print Time: 9:52 AM	<u>Active</u> <u>Active</u> <u>PhaseBank</u> <u>Maximum</u>	0 Max 0				
	<u>TOD</u> <u>Setting</u>	N/A				
	<u>Cycle</u> <u>Offset</u>	0 0				
80: Alhambra Piz&Douglas Rd	Plan#	N/A		<u>PH 8</u>		0
for 3580	<u>Op Mode</u>			<u> H 1</u>	·	0
	<u>TOD</u> <u>Schedule</u>	DOW-2			NBT	0
		Rd	<u>Splits</u>	<u>PH 4 PH 5</u>	WBT -	0 0
	<u>Intersection</u>	Alhambra PIz&Douglas Rd		<u>PH3</u> I	EBT V	0
		Alhamb		<u>PH 2</u>	SBT	0

Phase Bank 1	
Active Phase Bank:	
Acti	

ł

ſ

5

<u>PH 1</u> NBL

0

Last In Servi		Permitted F		Default	External Pe	External Pe	External Pe			
Red		0	<u>ة</u>	ω	<u>ة</u>	0	<u>ة</u>	0		
<u>х</u>			1	0	0		1			
<u>Yellow</u>		с	4	4	4	0	4	0	0	
	ю	- 6	40 - 40	- 20	- 8	- 0	- 40	- 0	0 -	
<u>Max 2</u>	7	6 - 6 - 6	- 40	7 - 7 - 7 2.5 -2.5 - 2.5 17 - 17 - 17 36 - 20 - 20	18 - 8 - 8	0 - 0 - 0	- 1 - 1   40 - 40 - 40   0 - 40 - 40	0 - 0 - 0	- 0 - 0 0 - 0 - 0 - 0 - 0 - 0 - 0 - 0 -	
	-		0	36		_	0	_	0	
mit	ю	- 0 - 0 5 - 5 - 5 2 - 2 - 2 6 - 6 - 6	1 - 1 - 1 40 - 40 - 40	- 17	7 - 7 - 7 2.5 -2.5 - 2.5 5 - 5 - 5	0 - 0 - 0 0 - 0 - 0 - 0 - 0	- 40	0 - 0 - 0 0 - 0 - 0 - 0 - 0	0	
<u>Max Limit</u>	1 2 3	9	- 40	- 17	- 5	- 0	- 40	- 0	0	
Σ		9	40	17	5	0	40	0	0	
IJ	1 2 3 1 2 3 1	- 2	1	- 2.5	- 2.5	- 0	-	- 0	0 -	
<u>Veh Ext</u>	2	- 2	1	- 2.5	- 2.5	- 0	- 1	- 0	0	
>		2	-	2.5	2.5	0	1	0	0	
<u>a</u>	ю	۔ ۱	- 7	- 7	- 7	- 0	7 - 7 - 7	- 0	0 -	
Min Initial	6	- 2	- 7	- 7	- 7	- 0	- 7	- 0	0	
Mil	-	5	7	7	7		7	0	0	
<u>alk</u>	2 3	0	- 20 - 20	- 13 - 13	- 0 - 0	- 0 - 0	- 20 - 20	- 0 - 0	0 -	
n't Walk	7	0	- 20	- 13	- 0	- 0	- 20	- 0	0	
Doi	-	0	20	13	0	0	20	0	0	
ank	б	0	- 7	- 5	- 0	- 0	- 7	- 0	0 -	
<u>Walk</u> Phase Bank	6	0	- 7	- 5	- 0	- 0	- 7	- 0	- 0	
Ъh	-	0	2	5	0	0	7	0	0	
<u>ıase</u>		NBL	SBT	EBT	WBT		NBT		,	
히		-	2	<b>ო</b>	4	2 2	9	~	ω	

unknown		<u>12345678</u>	1234-6	-234-6	-234-6	-234-6	
Last In Service Date:	<b>Permitted Phases</b>		Default	External Permit 0	External Permit 1	External Permit 2	

—																			1								
adula	Plan DOW	Free Su S		Su	MTWThF	Su	MTWThF				M T W T h F	II.S.	MTWThF	M T W T h F	9 M T W T h F	ึง	Free SuMTWTh	* Settings	Blank - FREE - Phase Bank 1, Max 1	Blank - Plan - Phase Bank 1. Max 2	1 - Phase Bank 2, Max 1	2 - Phase Bank 2, Max 2	3 - Phase Bank 3, Max 1	4 - Phase Bank 3, Max 2	5 - EXTERNAL PERMIT 1	6 - EXTERNAL PERMIT 2	7 - X-PED OMIT
l ocal TOD Schedule																			Blank	Blank	1 - Ph	2 - Ph	3 - Ph	4 - Ph	5 - EX	9 - EX	7 - X-PE
	Time	0000	0000	0100	0115	0230	0230	0330	00020		0030	1000	1530	1900	2100	2200	2330		치	ŝ	ŝ	S					
	<u>Offset</u>	59	39	31	21	59	24	57	44	103	59	29	]						<u>Day of Week</u>	SuM T W ThF S	SuM T W ThF S	SuM T W ThF					
	Ring Offset	0	0	0	0	0	0	0	0	0	0	0							Settings *	2		2					
	 ∞ '	0	0	0	0	0	0	0	0	0	0	0						unction		STU	TS	JTS					
	r -	0	0	0	0	0	0	0	0	0	0	0						me of Day Function	<b>Function</b>	TOD OUTPUTS	TOD OUTPUTS	TOD OUTPUTS					
	6 NBT	80	72	62	110	52	102	42	37	82	70	37						Local Time									
Green Time	T · 5	0	0	0	0	0	0	0	0	0	0	0						Loc	Time	0000	0600	2330					
Greel	3 4 EBT WBT	13	12	7	23	7	22	7	7	12	13	7							쓌	S L	S S L	Е S					
	2 SBT EI	21		15	12 31		40	15	15	. 20	21	15							<u>Day of Week</u>	SuM T W ThF	SuM T W ThF S	1 T W Th					
	1 NBL S	72	64	54	102	44	94	34	29	74	62	29								Sul	SuN	SuN					
		130 5		100 5	180 5			80 5	75 5	130 5	120 5	75 5							Settings *	2		2					
	<u>Cycle</u>	<u> </u>									-		-					tion									
	Plan	-	2	3	5	6	7	8	6	10	11	20						Current Time of Day Function		TPUTS	TPUTS	TPUTS					
	<u>Current</u> TOD Schedule																	Time of I	Function	τορ ουτρυτs	TOD OUTPUTS	TOD OUTPUTS					
	<u>Cur</u> TOD Sc																	Current	Time								

No Calendar Defined/Enabled

APPENDIX E: Background Area Growth **SERPM Model** 

Location		Model Volumes		Growth Rate	
Location	2005	2035	Diff	(%)	
	35,650	39,059	3,409	0.32%	
S. Douglas Road/SW 37th Avenue	44,409	48,967	4,558	0.34%	
	46,983	51,773	4,790	0.34%	
Ponce De Leon Boulevard	21,995	33,241	11,246	1.70%	
Alhambra Circle	11,549	18,895	7,346	2.12%	
Amanibra Circle	20,024	28,638	8,614	1.43%	
SW 22nd Street	30,946	36,663	5,717	0.62%	
Total	211,556	257,236	45,680	0.72%	

## Growth Rate Calculations from 2005 and 2035 M-D MPO SERPM



Licensed to Kimley-Horn and Associates, Inc



Licensed to Kimley-Horn and Associates, Inc.

**FDOT Historical Data** 

## **Historical AADT Growth Rates**

Station	Location	Historic	Growth	
Number	Location	5-year	10-year	
2534	SR 972/Coral Way, 200' E of SW 37th Ave.	0.64%	0.26%	
0024	SR 953/LeJeune Road, 200' S of Coral Way/SR 972	-5.76%	-0.64%	
0025	SR 953/LeJeune Road, 200' S of S SW 8th St./SR 90	5.79%	-0.98%	
	Total	0.22%	-0.45%	

	27th Avenue
<b>TRAFFIC TRENDS</b>	oral Way 200' E. of SW 27th Avenue
	SR 972/Cora

Station #: Highway: 2008 2010 2012 2012 2012 2012 2013 2012 2014 2014	SR 972/Coral Way 200' E. of SW 27th Avenue	Way 200	' E. of SW 2	27th Avenu	e	<u></u>	County:		87	
Kear     Kear       2008     2010       2011     2011       2012     2012       2013     2012       2014     2014       Year     2014       2014     2014       2014     2014		<b>N</b>					Station #: Highway:		2534 SR 972/Coral V	Vav
Year       Year         18       2025       2032       2014         18       2025       2032       2014         Year       2014       2014       2014									1 4/ - 32 - F	
20 20 20 20 20 20 20 20 20 20 20 20 20 2								Voor		Trand**
18 2025 2032 2032 2032 2032 2032 2032 2032	Ohsenved	Count							27000	
200 2018 2025 2032 2032 2032 2032 2032 2032 2018 2018 2018 2018 2018 2018 2018 201	Fitted Curv	APP - PA				Ì		2009	38000	39100
2018 2025 2032 2032 2032 2032 2032 2032 2032		2						2010	43000	39300
20 2018 2025 2032 2032 2032 2032 2032 2032 2032								2011	42500	39600
2018 2025 2032 2032 2032 2032 2032 2032 2032								2012	36000	39800
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2018 2005 2018 2005 2005 2005 2005 2005 2005 2005 200										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2023 2025 2032 2032 2032 2032 2032 2032										
2018 2023 2032 2032 2032 2032 2032 2032 203										
2018 2025 2032 2032 2032 2032 2032 2032 2032										
2018 2023 2025 2032 2032 20 Year		-		+	+					
200	2013	2018	2023	2025	2032	2032		201	4 Opening Yea	ar Trend
			Yea	_				2014	N/A	40300
2017 N/A			5	_				2	2017 Mid-Year <sup>-</sup>	Trend
								2017	N/A	41100

\*Axle-Adjusted

43300 ts/Trends

**TRANPLAN Foreca** 

250 1.5% 0.64% 0.63% 15-Aug-13

\*\* Annual Trend Increase: Trend R-squared: Trend Annual Historic Growth Rate: Trend Growth Rate (2012 to Design Year): Printed: 1

Straight Line Growth Option

rend

Year

Design AN

20; 2026

TRAFFIC TRENDS	SR 972/Coral Way 200' E. of SW 27th Avenue
TRAFFIC	SR 972/Coral Way 200

I RAFFIC I RENUS						
SR 972/Coral Way 200' E. of SW 27th Avenue	rth Aven	ne	County:		87	
			Station #:		2534 25 077/02:21	
			пуниау.		on ar zrunar way	vay
					Traffic (ADT/AADT)	T/ADT)
nnne				Year	Count*	Trend**
Dbserved Count				2003	31500	39200
45000				2004	43500	39300
				2005	44000	39400
				2006	40500	39500
				2007	40500	39600
				2008	37000	39700
[] []				2009	38000	39800
e 20000 + 2000 - 20000				2010	43000	39900
(∧)				2011	42500	40000
				2012	36000	40100
ieO						
2000 +						
	-	-				
2003 2008 2013 2018	2023	2032	2032	201	2014 Opening Year Trend	r Trend
Year				2014	N/A	40300
				2	2017 Mid-Year T	rend
				2017	N/A	
				20;	2026 Design Year	Tr
** Annual Trend Increase:	ncrease:	106		2026	N/A	41600
Trend R-squared	squared:	0.6%		TRAN	TRANPLAN Forecasts/Trends	ts/Trends
Trend Annual Historic Growth Rate:	vth Rate:	0.26%				
Trend Growth Rate (2012 to Design Year)	jn Year): Drintad:	0.27%				
	LILLICO.					

\*Axle-Adjusted

Straight Line Growth Option

### FLORIDA DEPARTMENT OF TRANSPORTATION TRANSPORTATION STATISTICS OFFICE 2012 HISTORICAL AADT REPORT

### COUNTY: 87 - MIAMI-DADE

SITE: 2534 - SR 972/CORAL WAY, 200' E SW 37 AVENUE

YEAR	AADT	DIRECTION 1	IRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
2012	36000 C	E 18000	18000	W 18000	9.00	59.70	2.00
2011	42500 C	E 21000	21000	W 21500	9.00	58.20	3.30
2010	43000 C	E 21000	21000	W 22000	7.87	58.27	4.10
2009	38000 C	E 19000	19000	W 19000	7.98	59.96	2.90
2008	37000 C	E 17500	17500	W 19500	8.07	66.31	2.40
2007	40500 C	E 19000	19000	W 21500	7.90	63.12	1.40
2006	40500 C	E 18500	18500	W 22000	7.39	58.66	2.00
2005	44000 C	E 20000	20000	W 24000	7.70	65.70	2.40
2004	43500 C	E 22500	22500	W 21000	8.20	67.10	6.40
2003	31500 C	E 13500	13500	W 18000	8.10	72.30	4.30
2002	36500 C	E 18000	18000	W 18500	9.20	68.00	5.30
2001	34000 C	E 16500	16500	W 17500	8.20	53.50	3.90
2000	31500 C	E 15500	15500	W 16000	8.20	53.10	5.70
1999	26000 C	E 13500	13500	W 12500	9.10	52.70	6.10
1998	27000 C	E 12500	12500	W 14500	9.30	52.70	1.90
1997	28500 C	E 14000	14000	W 14500	9.10	64.50	5.20

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; X = UNKNOWN \*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

87 24 SR 953/LeJeune Road	Traffic (ADT/AADT)           Year         Count*         Trend**           2008         45000         46000           2009         43000         43400           2010         44500         40700           2011         35500         38100           2012         35500         35400	2014 Opening Year Trend 2014 N/A 30100 2017 Mid-Year Trend 2017 Mid-Year Trend 2026 Design Year Trend 2026 Design Year Trend 2026 N/A -1700 TRANPLAN Forecasts/Trends
County: Station #: Highway:	5032	
TRAFFIC TRENDS SR 953/LeJeune Road 200' E. of Coral Way/SR 972	50000 50000 400000 400000 400000 400000 5000 50000 50000 5000000 50000 5000000 500000 50000 500000 500	-30000 Tear ** Annual Trend Increase: -2,650 Trend R-squared: 76,1% Trend Annual Historic Growth Rate: -5.76% Trend Growth Rate (2012 to Design Year): -7.49% Trend Growth Rate (2012 to Design Year): -7.49% Printed: 15-Aug-13 Straight Line Growth Option
87 24 SR 953/LeJeune Road	Traffic (ADT/ADT)           Year         Traffic (ADT/ADT)           Year         Count*         Trend**           2003         37500         41800           2004         41000         41500           2005         48000         41300           2006         34000         41000           2007         42000         40700           2008         45000         40700           2009         43000         39900           2010         35500         39900           2012         35500         39400	2014 Opening Year Trend 2014 N/A 38900 2017 Mid-Year Trend 2017 N/A 38100 2026 Design Year Trend 2026 N/A 35700 TRANPLAN Forecasts/Trends
---	---	---
County: Station #: Highway:		5032
SR 972		-267 -267 -0.64% -0.67% 15-Aug-13
ENDS of Coral Way!		2013 2018 2023 Year ** Annual Trend Increase: Trend Annual Historic Growth Rate: Growth Rate (2012 to Design Year): Printed: ht Line Growth Option
TRAFFIC TRENDS SR 953/LeJeune Road 200' E. of Coral Way/SR 972	Count Count	2013 Trend Ann d Growth R
T 353/LeJeune	Observed Count	5000 5000 5000 5000 5000 5000 5000 500
Ø	Average Daily Trattic (Vehicles/Day) o	5

\*Axle-Adjusted

#### FLORIDA DEPARTMENT OF TRANSPORTATION TRANSPORTATION STATISTICS OFFICE 2012 HISTORICAL AADT REPORT

#### COUNTY: 87 - MIAMI-DADE

SITE: 0024 - SR 953/LEJEUNE RD, 200' S CORAL WAY/SR 972

YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
2012	35500 C	N 18000	s 17500	9.00	59.70	4.00
2011	35500 C	N 18000	S 17500	9.00	58.20	5.70
2010	44500 C	N 22000	S 22500	7.87	58.27	3.80
2009	43000 C	N 22500	S 20500	7.98	59.96	3.20
2008	45000 C	N 23500	S 21500	8.07	66.31	3.50
2007	42000 C	N 22000	S 20000	7.90	63.12	4.70
2006	34000 C	N 15000	S 19000	7.39	58.66	7.20
2005	48000 F	N 21500	S 26500	7.70	65.70	5.50
2004	41000 C	N 18500	S 22500	8.20	67.10	9.00
2003	37500 C	N 20000	S 17500	8.10	72.30	5.00
2002	39000 C	N 17500	S 21500	9.20	68.00	4.30
2001	39000 C	N 20500	S 18500	8.20	53.50	5.70
2000	40500 C	N 21000	S 19500	8.20	53.10	4.30
1999	49000 C	N 28000	S 21000	9.10	52.70	4.40
1998	41000 C	N 21000	S 20000	9.30	52.70	6.10
1997	35500 C	N 19500	S 16000	9.10	64.50	4.20

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; X = UNKNOWN \*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

87 25 SR 953/LeJeune Road	Traffic (ADT/AADT)           Year         Count*         Trend**           2008         35000         36300           2009         41000         38400           2010         39000         40500           2011         43000         42600           2012         44500         44700	2014 Opening Year Trend 2014 N/A 48900 2017 Mid-Year Trend 2017 N/A 55200	2026 Design Year Trend 2026 N/A 74100 TRANPLAN Forecasts/Trends *Axle-Adjusted
TRAFFIC TRENDS SR 953/LeJeune Road 200' S of SW 8th St./SR 90 Station #: Highway:	100000 10000 0000 0000 0000 0000 00000 00000 0000	0 2008 2013 2018 2023 2025 2032 2032 7032 7032 7032 7032 7032 7032	** Annual Trend Increase:       2,100         Trend Annual Historic Growth Rate:       80.2%         Trend Growth Rate (2012 to Design Year):       4.70%         Printed:       15-Aug-13         Straight Line Growth Option       15-Aug-13

87 25 SR 953/LeJeune Road	Traffic (ADT/AADT)           Year         Traffic (ADT/AADT)           2003         44000         43300           2004         48000         43300           2005         56000         42500           2006         25000         42500           2007         38500         41600           2008         35000         41200           2010         395000         40800           2011         43000         39900           2012         44500         39500	2014 Opening Year Trend 2014 N/A 38600 2017 Mid-Year Trend 2017 N/A 37300	Forecast	*Axle-Adjusted
County: Station #: Highway:				
SR 90		2032	-430 2.5% -0.98% -1.10% 15-Aug-13	
TRAFFIC TRENDS SR 953/LeJeune Road 200' S of SW 8th St./SR 90		2018 2023 Year	** Annual Trend Increase: Trend Annual Historic Growth Rate: I Growth Rate (2012 to Design Year): Printed:	
TRAFFIC TRENDS Jeune Road 200' S of SW	Pitted Count	2013	** Trend Annu Trend Growth Rat	
SR 953/Le.	Average Daily Trattic (Vehicles/Day) 50 Average Daily 10 Average Daily 10 Averag	2003		

\*Axle-Adjusted

#### FLORIDA DEPARTMENT OF TRANSPORTATION TRANSPORTATION STATISTICS OFFICE 2012 HISTORICAL AADT REPORT

#### COUNTY: 87 - MIAMI-DADE

SITE: 0025 - SR 953/LEJEUNE RD, 200' S SW 8 ST/SR 90

YEAR	AADT	DIRECTION 2	l DIREC	TION 2 *H	K FACTOR	D FACTOR	T FACTOR
2012	44500 C	N 22000	 s 22	500 <u>-</u>	9.00	59.70	4.00
2011	43000 C	N 21000	S 22	000	9.00	58.20	5.70
2010	39000 C	N 19500	S 19	500	7.87	58.27	3.80
2009	41000 C	N 21000	S 20	000	7.98	59.96	3.20
2008	35000 C	N 17000	S 18	000	8.07	66.31	3.50
2007	38500 C	N 19500	S 19	000	7.90	63.12	4.70
2006	25000 C	N 11000	S 14	000	7.39	58.66	7.20
2005	56000 F	N 28000	S 28	000	7.70	65.70	5.50
2004	48000 C	N 24000	S 24	000	8.20	67.10	9.00
2003	44000 C	N 21500	S 22	500	8.10	72.30	5.00
2002	43000 C	N 20500	S 22	500	9.20	68.00	4.30
2001	42500 C	N 20500	S 22	000	8.20	53.50	5.70
2000	62000 C	N 37500	S 24	500	8.20	53.10	4.30
1999	49000 C	N 23500	S 25	500	9.10	52.70	4.40
1998	45000 C	N 21500	S 23	500	9.30	52.70	6.10
1997	42500 C	N 21000	S 21	500	9.10	64.50	4.20

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; X = UNKNOWN \*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

# APPENDIX F: Volume Development Worksheets

Alhambra Circle and Galiano Street

September 4, 2013

0.881

0.915

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR:

"AM EXISTING TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR AM Raw Turning Movements 0 4 3 69 187 114 72 34 108 96 16 76 Peak Season Correction Factor 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 AM EXISTING CONDITIONS 0 4 70 191 116 73 35 110 98 16 78 3 "PM EXISTING TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBR SBT PM Raw Turning Movements 5 57 55 99 171 104 8 48 97 136 43 140 Peak Season Correction Factor 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 **PM EXISTING CONDITIONS** 58 56 101 174 106 49 99 139 44 143 5 8 "AM BACKGROUND TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR Years To Buildout 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 Yearly Growth Rate 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% AM BACKGROUND TRAFFIC GROWTH 5 1 0 0 0 3 8 3 1 4 4 3 AM NON-PROJECT TRAFFIC 73 199 121 76 36 114 102 17 81 0 4 3 "PM BACKGROUND TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR Years To Buildout 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 Yearly Growth Rate 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% PM BACKGROUND TRAFFIC GROWTH 0 4 7 4 0 4 6 2 2 2 2 6 PM NON-PROJECT TRAFFIC 5 60 58 105 181 110 8 51 103 145 46 149 "PROJECT DISTRUBUTION" LAND USE EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL TYPE EBU EBL SBT SBR Pass-Bv Entering Distribution Exiting Net New 9.0% 18.0% Entering Distribution 7.0% 11.0% 9.0% Exiting 5.0% "AM PROJECT TRAFFIC" LAND USE WBU WBL WBT WBR TYPE EBU EBL EBT EBR NBU NBL NBT NBR SBU SBL SBT SBR Pass - By Project 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 Trips Net New 1 2 3 3 5 4 AM TOTAL PROJECT TRAFFIC 1 0 0 2 0 3 0 0 0 3 5 4 AM TOTAL TRAFFIC 75 199 124 76 36 114 105 22 85 1 4 3 "PM PROJECT TRAFFIC" LAND USE TYPE EBU EBL EBT EBR WBU WBL WBT WBR NBL NBR SBL SBR NBU NBT SBU SBT Pass - By Project Trips Net New 5 2 9 3 4 3 PM TOTAL PROJECT TRAFFIC 5 2 9 3 4 3 PM TOTAL TRAFFIC 10 60 58 107 181 119 8 51 103 148 50 152

Alhambra Plaza and Galiano Street

September 4, 2013

0.891

0.923

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR:

"AM EXISTING TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBL SBT SBR SBU AM Raw Turning Movements 15 103 326 10 25 210 56 19 70 40 14 58 16 Peak Season Correction Factor 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 AM EXISTING CONDITIONS 15 105 333 10 26 214 57 19 71 41 14 59 16 "PM EXISTING TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBR SBT PM Raw Turning Movements 38 40 304 14 10 259 24 63 82 80 23 111 82 Peak Season Correction Factor 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 **PM EXISTING CONDITIONS** 310 14 264 64 84 82 113 84 39 41 10 24 23 "AM BACKGROUND TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR Years To Buildout 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 Yearly Growth Rate 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% AM BACKGROUND TRAFFIC GROWTH 14 2 2 1 4 0 1 9 1 3 2 1 1 AM NON-PROJECT TRAFFIC 16 109 347 27 223 59 20 74 43 15 17 10 61 "PM BACKGROUND TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR Years To Buildout 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 Yearly Growth Rate 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% PM BACKGROUND TRAFFIC GROWTH 2 2 13 0 11 1 3 3 5 3 1 3 1 PM NON-PROJECT TRAFFIC 41 43 323 15 10 275 25 67 87 85 24 118 87 "PROJECT DISTRUBUTION" LAND USE EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU TYPE EBU EBL SBL SBT SBR Pass-By Entering Distribution Exiting Net New 16.0% 7.0% Entering Distribution 7.0% Exiting "AM PROJECT TRAFFIC" EBU LAND USE WBT WBR NBU TYPE EBL EBT EBR WBU WBL NBL NBT NBR SBU SBL SBT SBR Pass - By Project 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 Trips Net New 2 1 3 AM TOTAL PROJECT TRAFFIC 0 2 0 0 0 0 0 0 0 0 3 0 1 AM TOTAL TRAFFIC 16 111 347 10 27 223 59 20 75 43 15 64 17 "PM PROJECT TRAFFIC" LAND USE TYPE EBU EBT EBR WBU WBL WBT WBR NBL NBR SBL EBL NBU NBT SBU SBT SBR Pass - By Project Trips Net New 8 4 3 PM TOTAL PROJECT TRAFFIC 8 4 3 PM TOTAL TRAFFIC 41 51 323 15 10 275 25 67 91 85 24 121 87

Alhambra Plaza and S Douglas Road

September 4, 2013

0.958

0.99

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR:

"AM EXISTING TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBL SBT SBR SBU AM Raw Turning Movements 224 8 142 13 21 29 148 848 7 12 1,114 90 Peak Season Correction Factor 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 AM EXISTING CONDITIONS 228 145 13 21 30 151 865 12 1,136 92 8 7 "PM EXISTING TRAFFIC" EBU EBL EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR EBT PM Raw Turning Movements 252 32 108 11 24 11 154 1.190 23 14 992 108 Peak Season Correction Factor 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 1.020 **PM EXISTING CONDITIONS** 257 33 110 11 24 11 157 1,214 23 14 1,012 110 "AM BACKGROUND TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR Years To Buildout 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 Yearly Growth Rate 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% AM BACKGROUND TRAFFIC GROWTH 9 6 35 0 46 0 6 1 1 1 0 4 AM NON-PROJECT TRAFFIC 237 151 14 22 31 157 900 1,182 96 8 7 12 "PM BACKGROUND TRAFFIC" EBU EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL SBT SBR Years To Buildout 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 Yearly Growth Rate 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% 1.0% PM BACKGROUND TRAFFIC GROWTH 10 0 0 49 41 4 1 4 1 6 1 1 PM NON-PROJECT TRAFFIC 267 34 114 11 25 11 163 1,263 24 15 1,053 114 "PROJECT DISTRUBUTION" LAND USE EBL EBT EBR WBU WBL WBT WBR NBU NBL NBT NBR SBU SBL TYPE EBU SBT SBR Pass-Bv Entering Distribution Exiting Net New 4.0% 9.0% Entering Distribution 4.0% 9.0% Exiting "AM PROJECT TRAFFIC" LAND USE WBT WBR NBU TYPE EBU EBL EBT EBR WBU WBL NBL NBT NBR SBU SBL SBT SBR Pass - By Project 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 Trips Net New 1 1 2 3 AM TOTAL PROJECT TRAFFIC 0 0 0 0 0 1 0 0 2 0 1 3 AM TOTAL TRAFFIC 237 8 151 14 22 32 157 901 14 1,185 96 7 "PM PROJECT TRAFFIC" LAND USE TYPE EBU EBR WBU WBL WBT WBR NBR SBL EBL EBT NBU NBL NBT SBU SBT SBR Pass - By Project Trips Net New 2 4 1 3 PM TOTAL PROJECT TRAFFIC 2 4 1 3 PM TOTAL TRAFFIC 267 34 114 11 25 13 163 1,267 24 16 1,056 114 

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR:

Minorca Avenue and S Douglas Road September 4, 2013 0.982 0.972

"AM EXISTIN	IG TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
AM Raw Turni	ng Movements		9		40						85	1,016				1,171	47
Peak Season Co	prrection Factor	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020
																	<u> </u>
AM EXISTING	CONDITIONS		9		41						87	1,036				1,194	48
"PM EXISTIN	-	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
PM Raw Turnii			79		92						40	1,404				1,027	25
Peak Season Co	prrection Factor	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020
PM EXISTING	CONDITIONS	r –		1					1	1							
PMEXISTING	CONDITIONS		81		94						41	1,432				1,048	26
"AM BACKGRO	UND TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Years To		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Yearly Gro		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
AM BACKGROUND		1.070	0	1.070	2	1.070	1.070	1.070	1.070	1.070	4	42	1.070	1.070	1.070	48	2
		1	Ŭ		-	1	1		1								
AM NON-PRO.	IECT TRAFFIC		9		43						91	1,078				1,242	50
"PM BACKGRO	-	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Years To		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Yearly Gro		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
PM BACKGROUND	TRAFFIC GROWTH		3		4						2	58				43	1
PM NON-PRO.						1	1										
PM NON-PRO			84		98						43	1,490				1,091	27
"PROJECT DIS																	
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Pass-By	Entering		EDL	EDI	EDK	WBU	WDL	WDI	WDR	NBU	50.0%	-50.0%	NDR	360	JDL	-50.0%	50.0%
Distribution	Exiting		50.0%		50.0%						50.0%	-30.0 %				-30.076	50.0 %
Net New	Entering		50.076		50.0 %						13.0%						18.0%
Distribution	Exiting		18.0%		13.0%						13.0 %						10.0 %
Distribution	Exiting		10.070		13.070												
"AM PROJEC	T TRAFFIC"																
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Trips	Net New		8		5						2						2
AM TOTAL PRO	JECT TRAFFIC		8		5						2	0				0	2
																	,ı
AM TOTAL	. TRAFFIC		17		48						93	1,078				1,242	52
"PM PROJEC																	
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By		2		2						2	-2				-2	2
Trips	Net New		7		4						6						9
PM TOTAL PRO	JECT TRAFFIC		9		6						8	-2				-2	11
DM TOTAL	TRAFFIC		02		404						54	4 490				4.090	20
PM TOTAL	INAFFIC		93		104						51	1,488				1,089	38

Alhambra Circle and Minorca Avenue April 24, 2014 0.926

0.983

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR:

"AM EXISTIN	IG TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
AM Raw Turni	ng Movements		6	35	102		31	31	8		78	42	110		17	253	25
Peak Season Co	prrection Factor	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010
AM EXISTING	CONDITIONS		6	35	103		31	31	8		79	42	111		17	256	25
	IG TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
PM Raw Turni	orrection Factor		2	35	83	1 0 1 0	88	61	17	1 0 1 0	64	86	76	1 9 1 9	10	204	6
Peak Season Co	Drrection Factor	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010
PM EXISTING	CONDITIONS		2	35	84		89	62	17		65	87	77		10	206	6
	UND TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	wвт	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
	Buildout	3	3	3	3	3	3	3	3	3	3	3	3	3 3	3	3	3
	owth Rate	1.0%	3	1.0%	3	3	1.0%	1.0%	3	3	3	1.0%	3	3 1.0%	3 1.0%	3	1.0%
	TRAFFIC GROWTH	1.070	0	1.070	3	1.070	1	1.070	0	1.070	2	1.070	3	1.070	1.070	8	1
		<u> </u>		<u> </u>		·	· ·	· · · ·				<u> </u>					
AM NON-PRO	JECT TRAFFIC		6	36	106		32	32	8		81	43	114		18	264	26
	UND TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
	Buildout	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
	owth Rate TRAFFIC GROWTH	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
PM BACKGROUND	TRAFFIC GROWTH	<u> </u>	0	1	3		3	2	1		2	3	2		0	6	0
PM NON-PRO	JECT TRAFFIC		2	36	87		92	64	18	<u>г</u>	67	90	79		10	212	6
"PROJECT DIS	STRUBUTION"																
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Pass-By	Entering																
Distribution	Exiting																
Net New	Entering			27.0%									27.0%		10.0%		
Distribution	Exiting						27.0%	27.0%	10.0%								
	CT TRAFFIC"							WDT				NET					
LAND USE	TYPE Pass - By	<b>EBU</b>	<b>EBL</b>	EBT	<b>EBR</b>	WBU 0	<b>WBL</b>	<b>WBT</b>	<b>WBR</b>	NBU 0	<b>NBL</b>	<b>NBT</b>	<b>NBR</b>	<b>SBU</b>	<b>SBL</b>	<b>SBT</b>	SBR 0
Project Trips	Net New	0	U	0	U	U	12	12	4	U	0	0	4	U	1	0	0
AM TOTAL PRO		<u> </u>	0	4	0		12	12	4	<u> </u>	0	0	4		1	0	0
ANTOTAL FRO	JECTINAITIC		U	4	U		12	12	4		U	0	4				•
AM TOTAL	TRAFFIC		6	40	106		44	44	12		81	43	118		19	264	26
"PM PROJEC	CT TRAFFIC"																
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By			└───					<u> </u>		L	└───				L	
Trips	Net New	—	<b> </b>	13			10	10	4	<u> </u>	└───	└───	14		5	└───	
PM TOTAL PRO	JECT TRAFFIC	I	<u> </u>	13			10	10	4		<u> </u>	<u> </u>	14		5	<u> </u>	
	TRAFFIC		2	49	87	1	102	74	22	1 1	67	90	93		15	212	6

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR: Alhambra Circle & Douglas Road/SW 37th Avenue April 24, 2014 0.862 0.863

"AM EXISTIN	IG TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	wвт	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
AM Raw Turni	ng Movements		60		15							1,129				1,204	264
	prrection Factor	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010
AM EXISTING	CONDITIONS		61		15							1,140				1,216	267
"PM EXISTIN	IG TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
PM Raw Turni	ng Movements		71		22							1,360				1,088	228
Peak Season Co	orrection Factor	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010	1.010
			r	1	r			1	1	r	r	r			1		
PM EXISTING	CONDITIONS		72		22							1,374				1,099	230
								WDT		NELL		NET		0.0011	0.01		
"AM BACKGRO	Buildout	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
	owth Rate	3	3 1.0%	3 1.0%	3 1.0%	3	3	3	3	3 1.0%	3 1.0%	3 1.0%	3	3	3	3	3
AM BACKGROUND		1.0%	1.0%	1.0%		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%		1.0%	1.0%	1.0%		1.0%
ANI DACKGROUND			2	I	0	I		I	I	I	I	35	I		I	37	8
AM NON-PRO	JECT TRAFFIC		63		15							1,175				1,253	275
																,	
"PM BACKGRO	UND TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Years To	Buildout	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Gr	owth Rate	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
PM BACKGROUND	TRAFFIC GROWTH		2		1							42				33	7
		1	1	1		1		1	1	1			1	1	1	1	
PM NON-PRO	JECT TRAFFIC		74		23							1,416				1,132	237
"PROJECT DIS								WDT				NET		0.511		0.D.T	
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Pass-By Distribution	Entering Exiting																
Net New	Entering															10.00/	10.0%
Distribution	Exiting		10.0%									18.0%				18.0%	10.0%
Distribution	Exiting		10.0%									16.0%					
"AM PROJEC	CT TRAFFIC"																
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Trips	Net New		4									8				2	1
AM TOTAL PRO	JECT TRAFFIC		4		0							8				2	1
AM TOTAL	_ TRAFFIC		67		15							1,183				1,255	276
"PM PROJEC																	
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By																<u> </u>
Trips	Net New		4									7				9	5
PM TOTAL PRO	JECT TRAFFIC		4									7				9	5
PM TOTAL	TRAFFIC		78		23					r –	r –	1,423				1,141	242
FWITUTAL			10		23					1	1	1,423				1,141	242

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR: Minorca Avenue and Project Driveway September 4, 2013 0.92 0.92

"AM EXISTING TR	AFFIC"	EBU	EBL	EBT <sup>(1)</sup>	EBR	WBU	WBL	WBT <sup>(1)</sup>	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
AM Raw Turning Mo	ovements			106				101									
Peak Season Correct		1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020
AM EXISTING CON	DITIONS			108				103									
"PM EXISTING TR		EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
PM Raw Turning Mo				146				116									
Peak Season Correct	ion Factor	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020
PM EXISTING CON	DITIONS			149				118									
"AM BACKGROUND	TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	wвт	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Years To Build		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Yearly Growth I		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
AM BACKGROUND TRAF				4				4									
				· ·													
AM NON-PROJECT	TRAFFIC			112				107									
"PM BACKGROUND		EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Years To Build		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Yearly Growth I		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
PM BACKGROUND TRAF	FIC GROWTH			6				5									
PM NON-PROJECT									1	1	1	1				r	r
PM NON-PROJECT	IRAFFIC			155				123									
"PROJECT DISTRUI																	
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Pass-By	Entering	EBU	EDL		EDK	WBU	100.0%	WDI	WDR	NBU	NDL	NDI	NDK	360	SDL	361	305
Distribution	Exiting						100.0%						100.0%				
Net New	Entering				64.0%		31.0%						100.0%				
Distribution	Exiting				64.0%		31.0%				64.0%		31.0%				
Distribution	Exiting										04.0%		31.0%				
"AM PROJECT TR	AFFIC"																
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Trips	Net New	v	v	Ť	9	Ť	4	Ŭ	Ť	Ŭ	28	Ť	13	Ÿ	Ŭ	Ť	Ť
AM TOTAL PROJECT				0	9		4	0			28		13			l	1
			1		-	1		-	1	1		1		1	1		
AM TOTAL TRA	FFIC			112	9		4	107			28		13				
"PM PROJECT TR																	
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
Project	Pass - By						4						4				
Trips	Net New				32		15				24		11				
PM TOTAL PROJECT	TRAFFIC				32		19				24		15				
PM TOTAL TRA	5510		1	155	32		19	123	1	1	24	1	15	1		r	r –

INTERSECTION: COUNT DATE: AM PEAK HOUR FACTOR: PM PEAK HOUR FACTOR: Galiano Street and Alley September 4, 2013 0.89 0.92

"AM EXISTIN	G TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT <sup>(1)</sup>	NBR	SBU	SBL	SBT <sup>(1)</sup>	SBR
AM Raw Turnir												300				148	
Peak Season Co	rrection Factor	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020
AM EXISTING	CONDITIONS											306				151	
"PM EXISTIN		EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
PM Raw Turnir												260				253	
Peak Season Co	rrection Factor	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020	1.020
PM EXISTING	CONDITIONS											265				258	
"AM BACKGRO	UND TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
		-			-		-	-			-						
					-			-			-						
					-			-			-						
TOTAL "VEST												0				0	
Years To	Buildout	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Yearly Gro		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%
AM BACKGROUND	TRAFFIC GROWTH											12				6	
AM NON-PROJ	ECT TRAFFIC											318				157	
	LOT INALLIO											510				137	
"PM BACKGRO	UND TRAFFIC"	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
					-			-			-						
		-															
		-															
TOTAL "VEST	ED" TRAFFIC											0				0	
	Bulldand																
Years To Yearly Gro		4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
PM BACKGROUND		1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0%	1.0 %	1.0%	1.0%	1.0%	1.0%	1.0 %	1.0%	1.0%	1.0%
																10	
PM NON-PROJ	ECT TRAFFIC											276				268	
	TRUBUTION																
"PROJECT DIS		EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR	SBU	SBL	SBT	SBR
LAND USE Pass-By	TYPE Entering	EBU	CDL	EDI	EDK	WBU	WDL	WDI	WDR	NBU	NDL		NDK	360	JDL	361	JDK
Distribution	Exiting																
Net New	Entering											18.0%	5.0%				
Distribution	Exiting								5.0%							7.0%	
									WBR	NBU	NBL	NBT	NBR	SBU	SBL	<b>0DT</b>	
"AM PROJEC		EDI	EDI	ЕРТ	CDD	\A/D11	W/DI				NBL					SBT	SBR
LAND USE	TYPE	EBU	EBL	EBT	EBR	WBU	WBL	WBI					NDI	360	<b>UDL</b>		
LAND USE Project	TYPE Pass - By	EBU	EBL	EBT	EBR	WBU	WBL	WBI						360		3	
LAND USE Project Trips	TYPE Pass - By Net New	EBU	EBL	EBT	EBR	WBU	WBL	WBI	2 2 2			3	1 1	380		3 3	
LAND USE Project Trips AM TOTAL PRO	TYPE Pass - By Net New JECT TRAFFIC	EBU	EBL	EBT	EBR	WBU	WBL	WBI	2 2			3 3	1 <b>1</b>	380		3	
LAND USE Project Trips	TYPE Pass - By Net New JECT TRAFFIC	EBU	EBL	EBT	EBR	WBU	WBL	WBI	2			3	1				
LAND USE Project Trips AM TOTAL PRO AM TOTAL	TYPE Pass - By Net New JECT TRAFFIC TRAFFIC	EBU	EBL	EBT	EBR	WBU	WBL	WBI	2 2			3 3	1 <b>1</b>			3	
LAND USE Project Trips AM TOTAL PRO AM TOTAL "PM PROJEC	TYPE Pass - By Net New JECT TRAFFIC TRAFFIC T TRAFFIC"								2 2 2			3 3 321	1 1 1			3 160	6PP
LAND USE Project Trips AM TOTAL PRO AM TOTAL "PM PROJEC LAND USE	TYPE Pass - By Net New JECT TRAFFIC TRAFFIC T TRAFFIC" TYPE	EBU	EBL	EBT		WBU			2 2 2		NBL	3 3	1 <b>1</b>	SBU	SBL	3	SBR
LAND USE Project Trips AM TOTAL PRO AM TOTAL PRO AM TOTAL "PM PROJEC LAND USE Project	TYPE Pass - By Net New JECT TRAFFIC TRAFFIC TRAFFIC" TYPE Pass - By								2 2 2 WBR			3 3 321 NBT	1 1 1 NBR			3 160 SBT	SBR
LAND USE Project Trips AM TOTAL PRO AM TOTAL "PM PROJEC LAND USE Project Trips	TYPE Pass - By Net New JECT TRAFFIC TRAFFIC TTRAFFIC" TYPE Pass - By Net New								2 2 2			3 3 321	1 1 1 NBR			3 160	SBR
LAND USE Project Trips AM TOTAL PRO AM TOTAL PRO AM TOTAL "PM PROJEC LAND USE Project	TYPE Pass - By Net New JECT TRAFFIC TRAFFIC TRAFFIC TYPE Pass - By Net New JECT TRAFFIC								2 2 2 WBR			3 3 321 NBT 9	1 1 1 NBR			3 160 SBT	SBR

APPENDIX G: Intersection Capacity Analyses **Existing Conditions** 

Intersection												
Intersection Delay, s/veh	16											
Intersection LOS	С											
Movement	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR
Vol, veh/h	0	0	4	3	0	70	191	116	0	73	35	110
Peak Hour Factor	0.92	0.88	0.88	0.88	0.92	0.88	0.88	0.88	0.92	0.88	0.88	0.88
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	5	3	0	80	217	132	0	83	40	125
Number of Lanes	0	0	1	1	0	0	1	0	0	0	1	0
Approach			EB			WB				NB		
Opposing Approach			WB			EB				SB		
Opposing Lanes			1			2				2		
Conflicting Approach Left			SB			NB				EB		
Conflicting Lanes Left			2			1				2		
Conflicting Approach Right			NB			SB				WB		
Conflicting Lanes Right			1			2				1		
HCM Control Delay			9.2			20.5				13.3		
HCMLOS			А			С				В		
Lane		NBLn1	EBLn1	FBI n2	WBLn1	SBLn1	SBLn2					
Vol Left, %		33%	0%	0%	19%	86%	0%					
Vol Thru, %		16%	100%	0%	51%	14%	0%					
Vol Right, %		50%	0%	100%	31%	0%	100%					
Sign Control		Stop	Stop	Stop	Stop	Stop	Stop					
Traffic Vol by Lane		218	4	3	377	114	78					
LT Vol		35	4	0	191	16	0					
Through Vol		110	0	3	116	0	78					
RT Vol		73	0	0	70	98	0					
Lane Flow Rate		248	5	3	428	130	89					
Geometry Grp		6	7	7	6	7	7					
Degree of Util (X)		0.414	0.008	0.006	0.686	0.242	0.137					
Departure Headway (Hd)		6.016	6.646	5.931	5.762	6.719	5.572					
Convergence, Y/N		Yes	Yes	Yes	Yes	Yes	Yes					
Сар		597	537	601	625	534	642					
Service Time		4.061	4.407	3.692	3.796	4.469	3.321					
HCM Lane V/C Ratio		0.415	0.009	0.005	0.685	0.243	0.139					
HCM Control Delay		13.3	9.5	8.7	20.5	11.6	9.2					
HCM Lane LOS		р	۸	۸	0	Р	۸					
HCM 95th-tile Q		B 2	A 0	A 0	C 5.4	B 0.9	A 0.5					

Intersection Intersection Delay, s/veh Intersection LOS					
Movement	SBU	SBL	SBT	SBR	
Vol, veh/h	0	98	16	78	
Peak Hour Factor	0.92	0.88	0.88	0.88	
Heavy Vehicles, %	2	2	2	2	
Mvmt Flow	0	111	18	89	
Number of Lanes	0	0	1	1	
Approach		SB			
Opposing Approach		NB			
Opposing Lanes		1			
Conflicting Approach Left		WB			
Conflicting Lanes Left		1			
Conflicting Approach Right		EB			
Conflicting Lanes Right		2			
HCM Control Delay		10.6			
HCM LOS		В			
Lane					

#### Timings 2: Galiano Street & Alhambra Plaza

	. ₹	٦	-	-	-	1	1	1	↓
Lane Group	EBU	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		3	<b>≜</b> ⊅		ፋጉ		4	ሻ	4
Volume (vph)	15	105	333	26	214	19	71	14	59
Turn Type	custom	pm+pt	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		1	5		2		4		8
Permitted Phases	1	5		2		4		8	
Detector Phase	1	1	5	2	2	4	4	8	8
Switch Phase									
Minimum Initial (s)	5.0	5.0	15.0	15.0	15.0	7.0	7.0	7.0	7.0
Minimum Split (s)	8.0	8.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Total Split (s)	8.0	8.0	58.0	50.0	50.0	32.0	32.0	32.0	32.0
Total Split (%)	8.9%	8.9%	64.4%	55.6%	55.6%	35.6%	35.6%	35.6%	35.6%
Yellow Time (s)	3.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.3	0.3	0.3	1.8	1.8	1.8	1.8
Lost Time Adjust (s)		0.0	0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		3.0	4.3		4.3		5.8	5.8	5.8
Lead/Lag	Lead	Lead		Lag	Lag				
Lead-Lag Optimize?	Yes	Yes		Yes	Yes				
Recall Mode	None	None	C-Min	C-Min	C-Min	None	None	None	None
Intersection Summary									

Intersection Summary

Cycle Length: 90 Actuated Cycle Length: 90

Offset: 0 (0%), Referenced to phase 2:WBTL and 5:EBTL, Start of Green

Natural Cycle: 50 Control Type: Actuated-Coordinated

Splits and Phases: 2: Galiano Street & Alhambra Plaza

	<b>₫</b> ø4
8 s 50 s	32 s
∞5 (R)	Ø8
58 s	32 s

## HCM Signalized Intersection Capacity Analysis 2: Galiano Street & Alhambra Plaza

	₫	۶	-	$\mathbf{r}$	4	-	×.	1	1	1	5	Ļ
Movement	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations		2	<b>≜</b> ⊅			4 Þ			4		<u>۲</u>	- î+
Volume (vph)	15	105	333	10	26	214	57	19	71	41	14	59
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Lane Util. Factor		1.00	0.95			0.95			1.00		1.00	1.00
Frt		1.00	1.00			0.97			0.96		1.00	0.97
Flt Protected		0.95	1.00			1.00			0.99		0.95	1.00
Satd. Flow (prot)		1770	3524			3422			1771		1770	1803
Flt Permitted		0.52	1.00			0.90			0.94		0.53	1.00
Satd. Flow (perm)		977	3524			3105			1671		992	1803
Peak-hour factor, PHF	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Adj. Flow (vph)	17	118	374	11	29	240	64	21	80	46	16	66
RTOR Reduction (vph)	0	0	1	0	0	16	0	0	23	0	0	13
Lane Group Flow (vph)	0	135	384	0	0	317	0	0	124	Ō	16	71
Turn Type	custom	pm+pt	NA	-	Perm	NA	-	Perm	NA	-	Perm	NA
Protected Phases	ouotonn	p pt	5			2			4			8
Permitted Phases	1	5	Ũ		2	-		4			8	Ũ
Actuated Green, G (s)		68.4	68.4		-	59.1			11.5		11.5	11.5
Effective Green, g (s)		68.4	68.4			59.1			11.5		11.5	11.5
Actuated g/C Ratio		0.76	0.76			0.66			0.13		0.13	0.13
Clearance Time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Vehicle Extension (s)		2.0	1.0			1.0			2.5		2.5	2.5
Lane Grp Cap (vph)		798	2678			2038			213		126	230
v/s Ratio Prot		c0.01	0.11			2000			210		120	0.04
v/s Ratio Perm		c0.12	0.11			0.10			c0.07		0.02	0.04
v/c Ratio		0.17	0.14			0.16			0.58		0.13	0.31
Uniform Delay, d1		2.9	2.9			5.9			37.0		34.8	35.6
Progression Factor		1.00	1.00			1.05			1.00		1.00	1.00
Incremental Delay, d2		0.0	0.1			0.2			3.4		0.3	0.6
Delay (s)		2.9	3.0			6.3			40.3		35.1	36.2
Level of Service		2.5 A	0.0 A			A			-10.0 D		D	00.2 D
Approach Delay (s)		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	3.0			6.3			40.3		D	36.0
Approach LOS			A			A			чо.о D			00.0 D
Intersection Summary												
HCM 2000 Control Delay			12.0	Н	CM 2000	Level of	Service		В			
HCM 2000 Volume to Capac	city ratio		0.24		•				-			
Actuated Cycle Length (s)	.,		90.0	S	um of los	t time (s)			13.1			
Intersection Capacity Utilizat	tion		51.0%		CU Level	( )	9		A			
Analysis Period (min)			15				-					

c Critical Lane Group

	,
	-
Maria	000
Movement	SBR
Lane Configurations	40
Volume (vph)	16
Ideal Flow (vphpl)	1900
Total Lost time (s)	
Lane Util. Factor	
Frt Fit Director at a d	
Fit Protected	
Satd. Flow (prot)	
Flt Permitted	
Satd. Flow (perm)	0.00
Peak-hour factor, PHF	0.89 18
Adj. Flow (vph)	18
RTOR Reduction (vph) Lane Group Flow (vph)	0
	0
Turn Type Protected Phases	
Protected Phases Permitted Phases	
Actuated Green, G (s)	
Effective Green, g (s)	
Actuated g/C Ratio	
Clearance Time (s)	
Vehicle Extension (s)	
Lane Grp Cap (vph)	
v/s Ratio Prot	
v/s Ratio Perm	
v/c Ratio	
Uniform Delay, d1	
Progression Factor	
Incremental Delay, d2	
Delay (s)	
Level of Service	
Approach Delay (s)	
Approach LOS	
Intersection Summary	
morsoolon ouninary	

#### Timings 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	٦	-	$\mathbf{i}$	+	1	1	5	ţ
Lane Group	EBL	EBT	EBR	WBT	NBL	NBT	SBL	SBT
Lane Configurations	1	र्भ	1	4î b	ሻ	<b>∱</b> î∌	ሻ	<b>≜</b> ⊅
Volume (vph)	228	8	145	21	151	865	12	1136
Turn Type	Split	NA	pm+ov	NA	pm+pt	NA	Perm	NA
Protected Phases	3	3	1	4	1	6		2
Permitted Phases			3		6		2	
Detector Phase	3	3	1	4	1	6	2	2
Switch Phase								
Minimum Initial (s)	7.0	7.0	5.0	7.0	5.0	7.0	7.0	7.0
Minimum Split (s)	22.8	22.8	8.0	25.0	8.0	32.9	32.9	32.9
Total Split (s)	36.0	36.0	8.0	29.0	8.0	115.0	107.0	107.0
Total Split (%)	20.0%	20.0%	4.4%	16.1%	4.4%	63.9%	59.4%	59.4%
Yellow Time (s)	4.0	4.0	3.0	4.0	3.0	4.0	4.0	4.0
All-Red Time (s)	0.8	0.8	0.0	0.8	0.0	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.8	4.8	3.0	4.8	3.0	5.9	5.9	5.9
Lead/Lag	Lead	Lead	Lead	Lag	Lead		Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Recall Mode	None	None	None	None	None	C-Min	C-Min	C-Min

Intersection Summary Cycle Length: 180 Actuated Cycle Length: 180 Offset: 21 (12%), Referenced to phase 2:SBTL and 6:NBTL, Start of Green Natural Cycle: 90

Control Type: Actuated-Coordinated

Splits and Phases: 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

<b>★</b> . ↓ <sub>2</sub> (R)	<b>▲</b> <sub>Ø3</sub>	<b>▼</b> ø4
8 s 107 s	36 s	29 s
<\$ <b>■ ↓ ■ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓</b>		
115 s		

# HCM Signalized Intersection Capacity Analysis 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	۶	-	$\mathbf{r}$	4	+	•	•	Ť	1	1	ţ	~
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	- ሻ	र्च	1		4î b		ሻ	<b>≜</b> ⊅		<u>۲</u>	<b>∱</b> ⊅	
Volume (vph)	228	8	145	13	21	30	151	865	7	12	1136	92
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Lane Util. Factor	0.95	0.95	1.00		0.95		1.00	0.95		1.00	0.95	
Frt	1.00	1.00	0.85		0.93		1.00	1.00		1.00	0.99	
Flt Protected	0.95	0.96	1.00		0.99		0.95	1.00		0.95	1.00	
Satd. Flow (prot)	1681	1691	1583		3260		1770	3535		1770	3499	
Flt Permitted	0.95	0.96	1.00		0.99		0.16	1.00		0.31	1.00	
Satd. Flow (perm)	1681	1691	1583		3260		297	3535		585	3499	
Peak-hour factor, PHF	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
Adj. Flow (vph)	238	8	151	14	22	31	157	901	7	12	1183	96
RTOR Reduction (vph)	0	0	123	0	30	0	0	0	0	0	3	0
Lane Group Flow (vph)	124	122	28	0	37	0	157	908	0	12	1276	0
Turn Type	Split	NA	pm+ov	Split	NA		pm+pt	NA		Perm	NA	
Protected Phases	3	3	. 1	4	4		1	6			2	
Permitted Phases			3				6			2		
Actuated Green, G (s)	18.1	18.1	33.5		7.7		138.7	138.7		120.3	120.3	
Effective Green, g (s)	18.1	18.1	33.5		7.7		138.7	138.7		120.3	120.3	
Actuated g/C Ratio	0.10	0.10	0.19		0.04		0.77	0.77		0.67	0.67	
Clearance Time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Vehicle Extension (s)	2.5	2.5	2.0		2.5		2.0	1.0		1.0	1.0	
Lane Grp Cap (vph)	169	170	294		139		354	2723		390	2338	
v/s Ratio Prot	c0.07	0.07	0.01		c0.01		c0.04	0.26			c0.36	
v/s Ratio Perm			0.01				0.30			0.02		
v/c Ratio	0.73	0.72	0.10		0.27		0.44	0.33		0.03	0.55	
Uniform Delay, d1	78.6	78.5	60.7		83.4		10.1	6.4		10.1	15.6	
Progression Factor	0.98	0.98	2.23		1.00		1.00	1.00		0.74	0.84	
Incremental Delay, d2	14.3	12.6	0.1		0.8		0.3	0.3		0.1	0.9	
Delay (s)	91.3	89.3	135.3		84.2		10.4	6.7		7.6	13.9	
Level of Service	F	F	F		F		В	Α		Α	В	
Approach Delay (s)		107.4			84.2			7.3			13.8	
Approach LOS		F			F			А			В	
Intersection Summary												
HCM 2000 Control Delay			26.2	Н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capa	icity ratio		0.54									
Actuated Cycle Length (s)			180.0		um of los				18.5			
Intersection Capacity Utiliza	ation		68.1%	IC	U Level	of Service	Э		С			
Analysis Period (min)			15									
c Critical Lane Group												

	٦	$\rightarrow$	1	1	Ļ
Lane Group	EBL	EBR	NBL	NBT	SBT
Lane Configurations	ሻ	1	ሻ	- <b>†</b> †	<b>≜</b> ⊅
Volume (vph)	9	41	87	1036	1194
Turn Type	Prot	Perm	pm+pt	NA	NA
Protected Phases	8		1	6	2
Permitted Phases		8	6		
Detector Phase	8	8	1	6	2
Switch Phase					
Minimum Initial (s)	9.0	9.0	5.0	16.0	16.0
Minimum Split (s)	20.0	20.0	9.9	20.9	20.9
Total Split (s)	53.0	53.0	22.0	127.0	105.0
Total Split (%)	29.4%	29.4%	12.2%	70.6%	58.3%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.9	0.9	0.9	0.9	0.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.9	4.9	4.9	4.9	4.9
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Recall Mode	None	None	None	C-Min	C-Min

Intersection Summary Cycle Length: 180 Actuated Cycle Length: 180 Offset: 27 (15%), Referenced to phase 2:SBT and 6:NBTL, Start of Green Natural Cycle: 60 Control Type: Actuated-Coordinated

Splits and Phases: 4: NW 37th Avenue/Douglas Road & Minorca Avenue



Movement         EBL         EBR         NBL         NBT         SBT         SBR           Lane Configurations         1         0		۶	$\mathbf{F}$	1	1	ţ	~	
Volume (veh/h)         9         41         87         1036         1194         48           Number         3         18         1         6         2         12           Initial Q (Qb), veh         0         0         0         0         0         0           Perding Bus, Adj         1.00         1.00         1.00         1.00         1.00           Adj Kor Rate, veh/h         9         42         89         1057         1218         49           Adj No, Ol Lanes         1         1         2         2         0         Peak Hour Factor         0.98         0.9	Movement	EBL	EBR	NBL	NBT	SBT	SBR	
Number         3         18         1         6         2         12           Initial Q (Qb), veh         0         0         0         0         0         0           Ped-Bike Ad(A_pDT)         1.00         1.00         1.00         1.00         1.00           Adj Sat Flow, veh/hn         186.3         186.3         186.3         186.3         186.3         186.3           Adj No of Lanes         1         1         2         2         0         Peak Hour Factor         0.98 </td <td>Lane Configurations</td> <td>ሻ</td> <td>1</td> <td>۳.</td> <td>- <b>†</b>†</td> <td><b>↑</b>1≽</td> <td></td> <td></td>	Lane Configurations	ሻ	1	۳.	- <b>†</b> †	<b>↑</b> 1≽		
Initial Q (Ob), veh 0 0 0 0 0 0 0 0 Ped-Bike Adj(A, pbT) 1.00 1.00 1.00 1.00 1.00 1.00 Adj Flow Rate, veh/h 1 166.3 166.3 166.3 166.3 190.0 Adj Flow Rate, veh/h 9 42 89 1057 1218 49 Adj No of Lanes 1 1 1 2 2 0 Peak Hour Factor 0.98 0.98 0.98 0.98 0.98 Percent Heavy Veh, % 2 2 2 2 2 2 2 Eq., veh/h 145 130 407 2737 2223 89 Arrive On Green 0.08 0.12 1.00 0.64 0.64 Saf Flow, veh/h/in 1774 1583 1774 3623 3661 139 Grp Volume(v), veh/h 1774 1583 1774 3623 3661 139 Grp Volume(v), veh/h 1774 1583 1774 3623 3661 139 Grp Volume(v), veh/h 1774 1583 1774 31057 621 646 Grg Sat Flow, veh/h 1774 1583 1774 3132 Cycle Q Clear(g_c), s 0.3 1.7 1.0 0.0 13.1 13.2 Cycle Q Clear(g_c), s 0.3 1.7 1.0 0.0 13.1 13.2 Cycle Q Clear(g_c), s 0.3 1.7 1.0 0.0 13.1 13.2 Cycle Q Clear(g_c), veh/h 1261 1125 749 6384 2617 2718 HOM Platon Ratio 1.00 1.00 0.00 Uniform Delay (d), siveh 28.7 29.3 4.4 0.0 6.7 6.7 Incr Delay (d), siveh 28.7 29.3 4.4 0.0 6.7 6.7 Incr Delay (d), siveh 28.7 29.3 4.4 0.0 6.7 6.7 Incr Delay (d), siveh 30.9 0.7 8.6 Approach Delay, siveh 30.9 0.7 8.6 Approach Delay, Siveh 30.9 0.7 8.6 Approach DS C C A A A A Approach Vol, veh/h 12 1 22 6 8 Phs Duration (G+Y+Rc), s 9.0 160.6 169.5 10.5 Charge Period (Y+Rc), s 4.90 00000 4.90 00001 4.9 Max Green Setting (Gmax), s 4.7 1.7 1.0 1.1 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 1.2 0.1 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Setting (Gmax), s 4.7 1.7 * 122.1 48.1 Max Green Sett	Volume (veh/h)		41	87	1036	1194		
Ped-Bike Adj(A, pbT)       1.00       1.00       1.00       1.00         Parking Bus, Adj       1.00       1.00       1.00       1.00       1.00         Adj Sat Flow, veh/hn       9       42       89       1057       1218       49         Adj No. of Lanes       1       1       2       2       0       Peak Hour Factor       0.98       0.71       737	Number	3	18	1	6	2	12	
Parking Bus, Adj       100       1.00       1.00       1.00       1.00       1.00         Adj Eav Riev, veh/h/in       186.3       186.3       186.3       186.3       190.0         Adj Flow Riev, veh/h       9       42       89       1057       1218       49         Adj Nov Alcanes       1       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2       3<	Initial Q (Qb), veh	0	0	0	0	0	0	
Adj Sař Flow, veľvh/ln       186.3       186.3       186.3       186.3       190.0         Adj No. of Lanes       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98         Cap, veh/h       145       130       407       2737       2223       89         Arrive On Green       0.08       0.08       0.12       1.00       0.64       0.64         Grp Voltme(v), veh/h       1774       1583       1774       1770       1770       1838         Grp Voltme(v), veh/h       9       42       89       1057       621       646         Grp Voltme(v), veh/h       9       42       89       1057       621       646         Grp Voltme(v), veh/h       9       42       89       1057       621       646         Grp Voltme(v), veh/h       100       1.00       1.01       1.00       0.08       1.13       1.22         Prop In Lane       1.00       1.00       1.00       1.00       1.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       2.03       3.03       1.00       1.00       1.00 <td>Ped-Bike Adj(A_pbT)</td> <td></td> <td>1.00</td> <td>1.00</td> <td></td> <td></td> <td>1.00</td> <td></td>	Ped-Bike Adj(A_pbT)		1.00	1.00			1.00	
Adj Flow Rate, veh/h       9       42       89       1057       1218       49         Adj No of Lanes       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98         Parcent Heavy Veh, %       2       2       2       2       2       2         Cap, veh/h       145       130       407       2737       2223       89         Arrive On Green       0.08       0.08       0.12       1.00       0.64       0.64         Sat Flow, veh/h       1774       1583       1774       1770       1770       1838         Ogs Sat Flow(s), veh/h       9       42       89       1057       621       646         Gr Sat Flow(s), veh/h       174       1583       1774       170       170       1838         Option Lane       1.00       1.00       1.00       1.01       1.02       0.06         Lane Grp Cap(c), veh/h       145       130       407       2737       1134       1178         V/C Ratio(X)       0.66       0.32       0.22       0.39       0.55       555         Avaii Cap(c, a), veh/h       1261       1	Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	
Adj No. of Lanes       1       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2 <th2< th="">       2       2       2<td>Adj Sat Flow, veh/h/ln</td><td>186.3</td><td>186.3</td><td>186.3</td><td>186.3</td><td>186.3</td><td>190.0</td><td></td></th2<>	Adj Sat Flow, veh/h/ln	186.3	186.3	186.3	186.3	186.3	190.0	
Paik Hour Factor         0.98         0.98         0.98         0.98         0.98           Percent Heavy Veh, %         2         3 <t< td=""><td>Adj Flow Rate, veh/h</td><td>9</td><td>42</td><td>89</td><td>1057</td><td>1218</td><td>49</td><td></td></t<>	Adj Flow Rate, veh/h	9	42	89	1057	1218	49	
Percent Heavy Veh, % 2 2 2 2 2 2 2 2 2 Cap, veh/h 145 130 407 2737 2223 89 Arrive On Green 0.08 0.02 0.08 0.12 1.00 0.64 0.64 Sat Flow, veh/h 1774 1583 1774 3632 3561 139 Grp Volume(v), veh/h 9 42 89 1057 621 646 Grp Sat Flow(s), veh/h/n 1774 1583 1774 1770 1770 1838 Q Serve(g.s), s 0.3 1.7 1.0 0.0 13.1 13.2 Cycle Q Clear(g_c), s 0.3 1.7 1.0 0.0 13.1 13.2 Cycle Q Clear(g_c), s 0.3 1.7 1.0 0.0 13.1 13.2 Prop In Lane 1.00 1.00 0.008 Lane Grp Cap(c), veh/h 145 130 407 2737 1134 1178 V/C Ratio(X) 0.06 0.32 0.22 0.39 0.55 0.55 Avail Cap(c_a), veh/h 1261 1125 749 6384 2617 2718 HCM Platon Ratio 1.00 1.00 2.00 1.00 1.00 Upstream Filter(I) 1.00 1.00 0.93 0.93 1.00 1.00 Uniform Delay (d), siveh 28.7 29.3 4.4 0.0 6.7 6.7 Incr Delay (d2), siveh 0.3 2.0 0.2 0.4 1.9 1.8 Initial Q Delay(d3), siveh 0.0 0.0 0.0 0.0 0.0 0.0 %ile Back07Q(50%), veh/h 51 1146 1267 Approach Vol, veh/h 51 1146 1267 Approach Vol, veh/h 51 146 146 1267 Approach Vol, veh/h 51 126 78.6 Approach Vol, veh/h 51 126 78.6 Approach Vol, veh/h 51 128 146 044 8.6 8.6 LnGrp Leay(d), siveh 30.9 0.7 8.6 Approach Vol, veh/h 51 122 68 8 Pris Duration (G+Y+Rc), s 9.0 160.6 169.5 10.5 C A A A A Timer 1 2 3 4 5 6 7 8 Assigned Phs 1 2 68 8 Pris Duration (G+Y+Rc), s 9.0 160.6 169.5 10.5 Change Period (Y+Rc), s 4.9000001 4.900004 4.900001 4.9 Max Green Setting (Gmax), s *17.1 *100.1 *122.1 48.1 Max Q Clear Time (g_c+I1), s 3.0 15.2 2.0 3.7 Green Ext Time (g_c,c), s 0.1 28.2 2.97 0.2 Intersection Summary HCM 2010 Ctrl Delay 54 HCM 2010 Ctrl Delay 54 HCM 2010 Ctrl Delay 54 HCM 2010 Ctrl Delay 54	Adj No. of Lanes	1	1	1	2	2	0	
Cap, veh/h       145       130       407       2737       2223       89         Arrive On Green       0.08       0.08       0.12       1.00       0.64       0.64         Sat Flow, veh/h       1774       1583       1774       3632       3561       139         Grp Volume(V), veh/h       9       42       89       1057       621       646         Grp Sat Flow(s), veh/h/ln       1774       1583       1774       170       1838         Q Serve(g.s), s       0.3       1.7       1.0       0.0       13.1       13.2         Cycle Q Clear(g.c), s       0.3       1.7       1.0       0.0       13.1       13.2         Prop In Lane       1.00       1.00       1.00       0.08       2.03.9       0.55       0.55         Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00       1.00         Uniform Delay (d), s/veh       0.8       2.0       0.2       0.4       1.9       1.8         Indri Delay (d), s/veh       2.8       9.3       1.4       0.0       6.7	Peak Hour Factor	0.98	0.98	0.98	0.98	0.98	0.98	
Cap, veh/h       145       130       407       2737       2223       89         Arrive On Green       0.08       0.08       0.12       1.00       0.64       0.64         Sat Flow, veh/h       1774       1583       1774       3632       3561       139         Grp Volume(V), veh/h       9       42       89       1057       621       646         Grp Volume(V), veh/h       1774       1583       1774       1770       1838         Q Serve(g_s), s       0.3       1.7       1.0       0.0       13.1       13.2         Cycle Q Clear(g_c), s       0.3       1.7       1.0       0.0       13.1       13.2         Prop In Lane       1.00       1.00       1.00       0.08       1.01       1.00         Lane Grp Cap(c), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00       1.00         Uniform Delay (d), siveh       0.3       2.0       0.2       0.4       1.9       1.8         Incr Delay (d2), siveh       0.3       2.0       0.2       0.4       1.9       1.8 <td>Percent Heavy Veh, %</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td></td>	Percent Heavy Veh, %	2	2	2	2	2	2	
Arrive On Green       0.08       0.08       0.12       1.00       0.64       0.64         Sat Flow, veh/h       1774       1583       1774       332       3561       139         Grp Volume(v), veh/h       9       42       89       1057       621       646         Grp Sat Flow(s), veh/h       1774       1583       1774       1770       138         Q Serve(g_s), s       0.3       1.7       1.0       0.0       13.1       13.2         Prop In Lane       1.00       1.00       0.008       Lane Grp Cap(c), veh/h       145       130       407       2737       1134       1178         V/C Ratio(X)       0.06       0.32       0.22       0.39       0.55       0.55         Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       2.00       2.00       1.00       1.00         Uniform Delay (d3), siveh       28       31.3       4.6       0.4       8.6       1.6         Indro Polay (d5), siveh       28       31.3 <td></td> <td>145</td> <td>130</td> <td>407</td> <td>2737</td> <td>2223</td> <td>89</td> <td></td>		145	130	407	2737	2223	89	
Grp Volume(v), veh/h       9       42       89       1057       621       646         Grp Sat Flow(s), veh/h/hln       1774       1583       1774       1770       1770       1838         Q Serve(g_s), s       0.3       1.7       1.0       0.0       13.1       13.2         Cycle Q Clear(g_c), s       0.3       1.7       1.0       0.0       13.1       13.2         Prop In Lane       1.00       1.00       1.00       0.08       Lane Grp Cap(c), veh/h       145       130       407       2737       1134       1178         V/C Ratio(X)       0.06       0.32       0.22       0.39       0.55       0.55       Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00       Upstram Filter(I)       1.00       1.00       0.00       1.00       1.00       Upstram Filter(I)       1.00 </td <td></td> <td>0.08</td> <td>0.08</td> <td>0.12</td> <td>1.00</td> <td>0.64</td> <td>0.64</td> <td></td>		0.08	0.08	0.12	1.00	0.64	0.64	
Grp Volume(v), veh/h       9       42       89       1057       621       646         Grp Sat Flow(s), veh/h/hln       1774       1583       1774       1770       1770       1338         Q Serve(g, s), s       0.3       1.7       1.0       0.0       13.1       13.2         Cycle Q Clear(g_c), s       0.3       1.7       1.0       0.0       13.1       13.2         Prop In Lane       1.00       1.00       1.00       0.08       Lane Grp Cap(c), veh/h       145       130       407       2737       1134       1178         V/C Ratio(X)       0.06       0.32       0.22       0.39       0.55       0.55       Axail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00       Upstram Filter(I)       1.00 <t< td=""><td>Sat Flow, veh/h</td><td>1774</td><td>1583</td><td>1774</td><td>3632</td><td>3561</td><td>139</td><td></td></t<>	Sat Flow, veh/h	1774	1583	1774	3632	3561	139	
Grp Sat Flow(s),veh/h/ln       1774       1583       1774       1770       1838         Q Serve(g_s), s       0.3       1.7       1.0       0.0       13.1       13.2         Cycle Q Clear(g_c), s       0.3       1.7       1.0       0.0       13.1       13.2         Prop In Lane       1.00       1.00       0.08       0.8       0.8         Lane Grp Cap(c), veh/h       145       130       407       2737       1134       1178         V/C Ratio(X)       0.06       0.32       0.22       0.39       0.55       0.55         Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.93       0.93       1.00       1.00         Uniform Delay (d), s/veh       0.3       2.0       2.0       1.00       1.00       1.00         Unror Delay (d), s/veh       0.3       2.0       0.4       0.1       7.0       7.2         LnGrp DOS       C       C       A       A       A       A         Approach LOS								
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$								
$\begin{array}{c c c c c c c c c c c c c c c c c c c $								
Prop In Lane       1.00       1.00       1.00       0.08         Lane Grp Cap(c), veh/h       145       130       407       2737       1134       1178         V/C Ratio(X)       0.06       0.32       0.22       0.39       0.55       0.55         Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       1.00       1.00       Upstream Filter(I)       1.00       1.00       0.93       0.93       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.93       0.93       1.00       1.00       Unform Delay (d), s/veh       0.8       1.00       1.00         Unifar Delay(d3), s/veh       0.3       2.0       0.2       0.4       1.9       1.8       1.11412       Delay(d3), s/veh       2.8       0.4       0.1       7.0       7.2       LnGrp Delay(d), s/veh       2.8       31.3       4.6       0.4       8.6       8.6         LnGrp Delay, s/veh       30.9       0.7       8.6       Approach Vol, veh/h       51       1146       1267         Approach LOS       C       A       A       A       A       A <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Lane Grp Cap(c), veh/h 145 130 407 2737 1134 1178 V/C Ratio(X) 0.06 0.32 0.22 0.39 0.55 0.55 Avail Cap(c_a), veh/h 1261 1125 749 6384 2617 2718 HCM Platoon Ratio 1.00 1.00 2.00 2.00 1.00 1.00 Upstream Filter(I) 1.00 1.00 0.93 0.93 1.00 1.00 Uniform Delay (d), s/veh 28.7 29.3 4.4 0.0 6.7 6.7 Incr Delay (d2), s/veh 0.3 2.0 0.2 0.4 1.9 1.8 Initial Q Delay(d3), s/veh 0.0 0.0 0.0 0.0 0.0 0.0 %ile BackOfQ(50%), veh/ln 0.2 0.8 0.4 0.1 7.0 7.2 LnGrp Delay(d), s/veh 28.9 31.3 4.6 0.4 8.6 8.6 LnGrp LOS C C A A A A Approach Vol, veh/h 51 1146 1267 Approach Delay, s/veh 30.9 0.7 8.6 Approach LOS C A A A A A Timer 1 2 3 4 5 6 7 8 Assigned Phs 1 2 6 8 Phs Duration (G+Y+Rc), s 9.0 160.6 169.5 10.5 Change Period (Y+Rc), s 4.5000004.9000001 * 4.900001 4.9 Max Green Setting (Gmax), s * 17.1 * 100.1 * 122.1 48.1 Max Q Clear Time (p_c), s 0.1 28.2 2.0 3.7 Green Ext Time (p_c), s 0.1 28.2 3.0 3.0 5.2 Green Ext Time (p_c), s 0.1 28.2 3.0 3.					010			
V/C Ratio(X)       0.06       0.32       0.22       0.39       0.55       0.55         Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.93       0.93       1.00       1.00         Uniform Delay (d), s/veh       28.7       29.3       4.4       0.0       6.7       6.7         Incr Delay (d2), s/veh       0.3       2.0       0.2       0.4       1.9       1.8         Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.8       0.4       0.1       7.0       7.2         LnGrp Delay(d),s/veh       28.9       31.3       4.6       0.4       8.6       8.6         Approach Vol, veh/h       51       1146       1267       Approach Delay, s/veh       30.9       0.7       8.6         Approach LOS       C       A       A       A       A       A         Timer       1       2       3       4       5       6<	•				2737	1134		
Avail Cap(c_a), veh/h       1261       1125       749       6384       2617       2718         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.93       0.93       1.00       1.00         Uniform Delay (d), s/veh       28.7       29.3       4.4       0.0       6.7       6.7         Incr Delay (d2), s/veh       0.3       2.0       0.2       0.4       1.9       1.8         Intrial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.8       0.4       0.1       7.0       7.2         LnGrp Delay(d),s/veh       28.9       31.3       4.6       0.4       8.6       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach LOS       C       A       A       A         Aproach LOS       C       A       A       A         Phs Duration (G+Y+Rc), s       9.0       160.6       169.5       10.5         Change Period (Y+Rc),								
HCM Platoon Ratio 1.00 1.00 2.00 2.00 1.00 1.00 1.00 Upstream Filter(I) 1.00 1.00 0.93 0.93 1.00 1.00 Uniform Delay (d), s/veh 28.7 29.3 4.4 0.0 6.7 6.7 Incr Delay (d), s/veh 0.3 2.0 0.2 0.4 1.9 1.8 Initial Q Delay(d3), s/veh 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.								
Upstream Filter(I)       1.00       1.00       0.93       0.93       1.00       1.00         Uniform Delay (d), s/veh       28.7       29.3       4.4       0.0       6.7       6.7         Incr Delay (d2), s/veh       0.3       2.0       0.2       0.4       1.9       1.8         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%), veh/ln       0.2       0.8       0.4       0.1       7.0       7.2         LnGrp Delay (d), s/veh       28.9       31.3       4.6       0.4       8.6       8.6         LnGrp DOS       C       C       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.5       10.2       2.0       3.7								
Uniform Delay (d), s/veh       28.7       29.3       4.4       0.0       6.7       6.7         Incr Delay (d2), s/veh       0.3       2.0       0.2       0.4       1.9       1.8         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%), veh/ln       0.2       0.4       0.1       7.0       7.2         LnGrp Delay(d), s/veh       28.9       31.3       4.6       0.4       8.6       8.6         LnGrp DOS       C       C       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       10.5       10.5       10.5         Change Period (Y+Rc), \$ 4.9000004.9000001       * 4.9000001       4.9       4.9       4.8.1       1         Max Green Setting (Gmax), \$ * 17.1       * 100.1       * 122.1       48.1								
Incr Delay (d2), s/veh       0.3       2.0       0.2       0.4       1.9       1.8         Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.8       0.4       0.1       7.0       7.2         LnGrp Delay(d),s/veh       28.9       31.3       4.6       0.4       8.6       8.6         Indrp LOS       C       C       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach LOS       C       A       A         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       10.5       10	,							
Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.8       0.4       0.1       7.0       7.2         LnGrp Delay(d),s/veh       28.9       31.3       4.6       0.4       8.6       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach Delay, s/veh       30.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       8         Phs Duration (G+Y+Rc), s       9.0       160.6       169.5       10.5       10.5         Change Period (Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       5.4       HCM 2010 Ctrl Delay       5.4         HCM 2010 LOS       A       A       A	• • • •							
%ile BackOfQ(50%),veh/ln       0.2       0.8       0.4       0.1       7.0       7.2         LnGrp Delay(d),s/veh       28.9       31.3       4.6       0.4       8.6       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach Delay, s/veh       30.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       9.0       10.5								
LnGrp Delay(d),s/veh       28.9       31.3       4.6       0.4       8.6       8.6         LnGrp LOS       C       C       A       A       A       A         Approach Vol, veh/h       51       1146       1267         Approach Delay, s/veh       30.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       9       <	• • •							
LnGrp LOS         C         C         A         A         A         A           Approach Vol, veh/h         51         1146         1267         Approach Delay, s/veh         30.9         0.7         8.6           Approach LOS         C         A         A         A         A           Timer         1         2         3         4         5         6         7         8           Assigned Phs         1         2         6         8         8         9         9.0         160.6         169.5         10.5         5         6         8         9         9.0         160.6         169.5         10.5         5         6         8         9         9         0.160.6         169.5         10.5         5         6         8         9         9         0         16         12.1         4.9         9         4.9         9         4.9         9         3.7         3.0         15.2         2.0         3.7         3.7         Green Ext Time (p_c), s         0.1         28.2         29.7         0.2         1         1         12.1         4.9         1         4.9         1         1         1.0         1.0         1.0	. ,							
Approach Vol, veh/h       51       1146       1267         Approach Delay, s/veh       30.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       9.0       160.6       169.5       10.5       10.5         Change Period (Y+Rc), s*       9.0       160.6       169.5       10.5       10.5       10.5         Change Period (Y+Rc), s*       9.0       160.6       122.1       48.1         Max Green Setting (Gmax), s*       17.1       100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       5.4       HCM 2010 Ctrl Delay       5.4         HCM 2010 LOS       A       A       A								
Approach Delay, s/veh       30.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       8       8         Phs Duration (G+Y+Rc), s       9.0       160.6       169.5       10.			<u> </u>					
Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.0       160.6       169.5       10.5         Change Period (Y+Rc), s* 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       5.4         HCM 2010 LOS       A       A								
Timer         1         2         3         4         5         6         7         8           Assigned Phs         1         2         6         8           Phs Duration (G+Y+Rc), s         9.0         160.6         169.5         10.5           Change Period (Y+Rc), s*         4.9000004.9000001         * 4.9000001         4.9           Max Green Setting (Gmax), s * 17.1         * 100.1         * 122.1         48.1           Max Q Clear Time (g_c+I1), s         3.0         15.2         2.0         3.7           Green Ext Time (p_c), s         0.1         28.2         29.7         0.2           Intersection Summary         5.4         HCM 2010 Ctrl Delay         5.4           HCM 2010 LOS         A         A         A								
Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.0       160.6       169.5       10.5         Change Period (Y+Rc), s* 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       5.4         HCM 2010 LOS       A		0	•	0			0	
Phs Duration (G+Y+Rc), s       9.0       160.6       169.5       10.5         Change Period (Y+Rc), s*       4.9000004.9000001       *       4.9000001       4.9         Max Green Setting (Gmax), s       *       17.1       *       10.1       *       122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7       3.7       Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       HCM 2010 Ctrl Delay       5.4       4       4       4		1		3	4	5		
Change Period (Y+Rc), \$ 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       5.4       4.9       4.9         HCM 2010 LOS       A       4.9       4.9	5	1						
Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       5.4         HCM 2010 LOS       A								
Max Q Clear Time (g_c+l1), s       3.0       15.2       2.0       3.7         Green Ext Time (p_c), s       0.1       28.2       29.7       0.2         Intersection Summary       HCM 2010 Ctrl Delay       5.4         HCM 2010 LOS       A       A						* 4.9		
Green Ext Time (p_c), s         0.1         28.2         29.7         0.2           Intersection Summary           HCM 2010 Ctrl Delay         5.4           HCM 2010 LOS         A								
Intersection Summary HCM 2010 Ctrl Delay 5.4 HCM 2010 LOS A								
HCM 2010 Ctrl Delay         5.4           HCM 2010 LOS         A	Green Ext Time (p_c), s	0.1	28.2				29.7	0.2
HCM 2010 LOS A	Intersection Summary							
HCM 2010 LOS A				5.4				
Notes								
	Notes							

\* HCM 2010 computational engine requires equal clearance times for the phases crossing the barrier.

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Existing\_AM.syn

HCM 2010 TWSC 5: Alhambra Circle & Minorca Avenue

Intersection											
Int Delay, s/veh	5.6										
Movement	EBL	EBT	EBR		WBL	WBT	WBR		NBL	NBT	NBR
Vol, veh/h	6	35	103		31	31	8		79	42	111
Conflicting Peds, #/hr	4	0	1		1	0	4		8	0	12
Sign Control	Stop	Stop	Stop		Stop	Stop	Stop		Free	Free	Free
RT Channelized	-	-	None		-	-	None		-	-	None
Storage Length	-	-	-		-	-	-		-	-	-
Veh in Median Storage, #	-	0	-		-	0	-		-	0	-
Grade, %	-	0	-		-	0	-		-	0	-
Peak Hour Factor	93	93	93		93	93	93		93	93	93
Heavy Vehicles, %	2	2	2		2	2	2		2	2	2
Mvmt Flow	6	38	111		33	33	9		85	45	119
Major/Minor	Minor2				Minor1				Major1		
Conflicting Flow All	629	667	305		682	622	121		306	0	0
Stage 1	329	329	505		279	279	121		300	0	0
Stage 2	329	338	-		403	343	-		-	-	-
Critical Hdwy	7.12	6.52	6.22		7.12	6.52	6.22		- 4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	0.22		6.12	5.52	0.22		4.12	-	-
Critical Hdwy Stg 2	6.12	5.52	-		6.12	5.52	-		-	-	-
Follow-up Hdwy	3.518	4.018	3.318		3.518	4.018	3.318		2.218	-	-
Pot Cap-1 Maneuver	395	380	735		364	403	930		1255	-	-
Stage 1	684	646	155		728	680	330		1200	-	-
Stage 2	709	641	-		624	637	-		-	-	-
Platoon blocked, %	109	041	-		024	037	-		-	-	-
Mov Cap-1 Maneuver	334	343	725		260	364	918		1242	-	-
Mov Cap-2 Maneuver	334	343	125		260	364	510		1242	-	-
Stage 1	630	634	-		200 670	626	-		-	-	-
-	608	590	-		484	625	-		-	-	-
Stage 2	000	590	-		404	025	-		-	-	-
Approach	EB				WB				NB		
HCM Control Delay, s	14.1				19.2				2.8		
HCM LOS	В				С						
		NOT					ODT	000			
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1		SBL	SBT	SBR			
Capacity (veh/h)	1242	-	-	549	328	1395	-	-			
HCM Lane V/C Ratio	0.068	-	-	0.282	0.229	0.013	-	-			
HCM Control Delay (s)	8.1	0	-	14.1	19.2	7.6	0	-			
HCM Lane LOS	A	А	-	В	С	A	A	-			
HCM 95th %tile Q(veh)	0.2	-	-	1.2	0.9	0	-	-			

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Existing\_AM.syn

#### Intersection

Int Delay, s/veh

Movement	SBL	SBT	SBR
Vol, veh/h	17	256	25
Conflicting Peds, #/hr	12	0	8
Sign Control	Free	Free	Free
RT Channelized	-	-	None
Storage Length	-	-	NULLE
Veh in Median Storage, #	-	0	-
Grade, %	-	0	-
	-		-
Peak Hour Factor	93	93	93
Heavy Vehicles, %	2	2	2
Mvmt Flow	18	275	27
Major/Minor	Major2		
Conflicting Flow All	169	0	0
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	4.12	-	-
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	_	-	-
Follow-up Hdwy	2.218	-	_
Pot Cap-1 Maneuver	1409	_	_
Stage 1	-	-	-
Stage 2	-	-	-
	-	-	-
Platoon blocked, %	4005	-	-
Mov Cap-1 Maneuver	1395	-	-
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-
Approach	SB		
HCM Control Delay, s	0.4		
HCM LOS			
Minor Long/Major Mumt			
Minor Lane/Major Mvmt			

NBL 0 0 Free - - 86 2 0 1724 - 4.14 - 2.22 363 -	NBT 1140 0 Free None - 0 0 86 2 1326 - - - - - - - - - - - - - - - - - - -				SBT 1216 0 Free - 0 0 86 2 1414 Major2 - - - - - - - - - - - - - - - - - - -	SBR 267 4 Free None - - - 86 2 310 0 - - - - - - - - - - - - - - - - - -	NEL 61 0 Stop - 0 0 0 86 2 71 Minor2 2232 1569 663 6.84 5.84 5.84 5.84 3.52 ~ 36	Stop None 0  862 17             
0 0 Free - - - - - - - - 86 2 0 - - - - - - - - - - - - - - - - - -	1140 0 Free None 0 0 86 2 1326				1216 0 Free - 0 0 86 2 1414	267 4 Free None - - - 86 2 310	61 0 Stop - 0 0 0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 3.52	15 0 Stop None 0 - - 86 2 17 862 - - 6.94 - - 3.32
0 Free - - - - - - - - - - - - - - - - - -	0 Free None 0 0 86 2 1326				0 Free - 0 0 86 2 1414	4 Free None - - 86 2 310	0 Stop 0 0 0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 5.84 3.52	0 Stop None 0 - - 86 2 17 - - - - 6.94 - - - 3.32
Free - - 86 2 0 ajor1 1724 - - 4.14 - 2.22	Free None 0 0 86 2 1326				Free 0 0 86 2 1414	Free None - - 86 2 310	Stop 0 0 0 0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 3.52	Stop None 0 - - 86 2 17 862 - - - - 6.94 - - 3.32
- - - - - - - - - - - - - - - - - - -	None 0 0 86 2 1326				- 0 86 2 1414	None - - 86 2 310 0	0 0 0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 3.52	None 0 - 86 2 17 862 - 6.94 - 3.32
- 86 2 0 ajor1 1724 - 4.14 - 2.22	0 0 86 2 1326				0 0 86 2 1414	- - 86 2 310	0 0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 3.52	0 - - 86 2 17 - - - - - - - - - - - - - - - - - -
86 2 0 1724 - 4.14 - 2.22	0 86 2 1326				0 0 86 2 1414	2 310 0	0 0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 3.52	- 86 2 17 862 - 6.94 - 3.32
86 2 0 1724 - 4.14 - 2.22	0 86 2 1326				0 86 2 1414	2 310 0	0 86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 3.52	2 17 862 - - 6.94 - 3.32
2 0 1724 - 4.14 - 2.22	86 2 1326				86 2 1414	2 310 0	86 2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 5.84 3.52	2 17 862 - - 6.94 - 3.32
2 0 1724 - 4.14 - 2.22	2 1326				2 1414	2 310 0	2 71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 5.84 3.52	2 17 862 - 6.94 - 3.32
0 ajor1 1724 - 4.14 - 2.22	1326				1414	310	71 <u>Minor2</u> 2232 1569 663 6.84 5.84 5.84 5.84 3.52	17 862 - 6.94 - 3.32
1724 - 4.14 - 2.22	0 - - - - - - - - - - -				<u>Major2</u> - - - - - - - -		2232 1569 663 6.84 5.84 5.84 3.52	862 - - 6.94 - 3.32 298
1724 - 4.14 - 2.22	0				<u>Major2</u> - - - - - - - - - -		2232 1569 663 6.84 5.84 5.84 3.52	- - 6.94 - 3.32
- 4.14 - 2.22	0 - - - - - - - -						1569 663 6.84 5.84 5.84 3.52	- - 6.94 - 3.32
- - 2.22							663 6.84 5.84 5.84 3.52	- - 3.32
- - 2.22						- - -	6.84 5.84 5.84 3.52	- - 3.32
- - 2.22	- - - -				-	-	5.84 5.84 3.52	- - 3.32
					- - -	- -	5.84 3.52	
	- - -				-	-	3.52	
	-				-	-		
363 - -	-				-		~ 36	298
-	-					-		
-					-	-	157	-
	-				-	-	474	-
	-				-	-		
363	-				-	-	~ 36	298
-	-				-	-	~ 36	-
-	-				-	-	157	-
-	-				-	-	474	-
NB					SB		NE	
0					0		\$ 559.3	
							F	
ELn1	NELn2	NBL	NBT	SBT	SBR			
36	298	363	-	-	-			
1.97	0.059	-	-	-	-			
692.5	17.8	0	-	-	-			
F	С	А	-	-	-			
7.8	0.2	0	-	-	-			
	0 ELn1 36 1.97 592.5 F 7.8	0 ELn1 NELn2 36 298 1.97 0.059 592.5 17.8 F C	0 <u>ELn1 NELn2 NBL</u> 36 298 363 1.97 0.059 - 592.5 17.8 0 F C A 7.8 0.2 0	0 <u>ELn1 NELn2 NBL NBT</u> 36 298 363 - 1.97 0.059 592.5 17.8 0 - F C A - 7.8 0.2 0 -	0 <u>ELn1 NELn2 NBL NBT SBT</u> 36 298 363 1.97 0.059 592.5 17.8 0 F C A 7.8 0.2 0	0 0 <u>ELn1 NELn2 NBL NBT SBT SBR</u> 36 298 363 1.97 0.059 592.5 17.8 0 F C A 7.8 0.2 0	0 0 <u>ELn1 NELn2 NBL NBT SBT SBR</u> 36 298 363 1.97 0.059 592.5 17.8 0 F C A 7.8 0.2 0	0 0 \$559.3 F <u>ELn1 NELn2 NBL NBT SBT SBR</u> 36 298 363 1.97 0.059 592.5 17.8 0 F C A 7.8 0.2 0

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Existing\_AM.syn

Intersection												
Intersection Delay, s/veh	16.5											
Intersection LOS	С											
Movement	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR
Vol, veh/h	0	5	58	56	0	101	174	106	0	8	49	99
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	5	63	61	0	110	189	115	0	9	53	108
Number of Lanes	0	0	1	1	0	0	1	0	0	0	1	0
Approach		EB				WB				NB		
Opposing Approach		WB				EB				SB		
Opposing Lanes		1				2				2		
Conflicting Approach Left		SB				NB				EB		
Conflicting Lanes Left		2				1				2		
Conflicting Approach Right		NB				SB				WB		
Conflicting Lanes Right		1				2				1		
HCM Control Delay		10.3				23.4				12.6		
HCM LOS		В				С				В		
Lane		NBLn1	EBLn1	EBLn2	WBLn1	SBLn1	SBLn2					
Vol Left, %		5%	8%	0%	27%	76%	0%					
Vol Thru, %		31%	92%	0%	46%	24%	0%					
Vol Right, %		63%	0%	100%	28%	0%	100%					
Sign Control		Stop	Stop	Stop	Stop	Stop	Stop					
Traffic Vol by Lane		156	63	56	381	183	143					
LT Vol		49	58	0	174	44	0					
Through Vol		99	0	56	106	0	143					
RT Vol		8	5	0	101	139	0					
Lane Flow Rate		170	68	61	414	199	155					
Geometry Grp		6	7	7	6	7	7					
Degree of Util (X)		0.308	0.131	0.104	0.714	0.384	0.253					
Departure Headway (Hd)		6.548	6.905	6.149	6.205	6.949	5.85					
Convergence, Y/N		Yes	Yes	Yes	Yes	Yes	Yes					
Cap		544	515	577	580	515	609					
Service Time		4.645	4.704	3.947	4.274	4.732	3.633					
HCM Lane V/C Ratio		0.313	0.132	0.106	0.714	0.386	0.255					
HCM Control Delay		12.6	10.8	9.7	23.4	14	10.6					
HCM Lane LOS		B	В	A	C	B	B					
HCM 95th-tile Q		1.3	0.4	0.3	5.8	1.8	1					

Intersection					
Intersection Delay, s/veh					
Intersection LOS					
Movement	SBU	SBL	SBT	SBR	
Vol, veh/h	0	139	44	143	
Peak Hour Factor	0.92	0.92	0.92	0.92	
Heavy Vehicles, %	2	2	2	2	
Mvmt Flow	0	151	48	155	
Number of Lanes	0	0	1	1	
Approach		SB			
Approach					
Opposing Approach		NB			
Opposing Lanes		WB			
Conflicting Approach Left Conflicting Lanes Left					
Conflicting Approach Right		EB			
Conflicting Lanes Right		2			
HCM Control Delay		2 12.5			
HCM LOS		12.5 B			
		D			
Lane					

#### Timings 2: Galiano Street & Alhambra Plaza

	5	٦	-	-	-	1	1	1	↓
Lane Group	EBU	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		1	A⊅		<b>≜</b> ⊅		4	ሻ	4
Volume (vph)	39	41	310	10	264	64	84	23	113
Turn Type	custom	pm+pt	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		1	5		2		4		8
Permitted Phases	1	5		2		4		8	
Detector Phase	1	1	5	2	2	4	4	8	8
Switch Phase									
Minimum Initial (s)	5.0	5.0	15.0	15.0	15.0	7.0	7.0	7.0	7.0
Minimum Split (s)	8.0	8.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Total Split (s)	8.0	8.0	52.0	44.0	44.0	38.0	38.0	38.0	38.0
Total Split (%)	8.9%	8.9%	57.8%	48.9%	48.9%	42.2%	42.2%	42.2%	42.2%
Yellow Time (s)	3.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.3	0.3	0.3	1.8	1.8	1.8	1.8
Lost Time Adjust (s)		0.0	0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		3.0	4.3		4.3		5.8	5.8	5.8
Lead/Lag	Lead	Lead		Lag	Lag				
Lead-Lag Optimize?	Yes	Yes		Yes	Yes				
Recall Mode	None	None	C-Min	C-Min	C-Min	None	None	None	None
Intersection Summary									

Intersection Summary

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 73 (81%), Referenced to phase 2:WBTL and 5:EBTL, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

	<b>™</b> ø4
8s <mark>44</mark> s	38 s
∞5 (R)	₹ ø8
52 s	38 s

## HCM Signalized Intersection Capacity Analysis 2: Galiano Street & Alhambra Plaza

	•	۶	-	*	4	Ļ	•	•	Ť	1	1	Ŧ
Movement	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations		2	<b>≜</b> †≱			<b>≜</b> †≱			<b>4</b> >		<u>۳</u>	ef 👘
Volume (vph)	39	41	310	14	10	264	24	64	84	82	23	113
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Lane Util. Factor		1.00	0.95			0.95			1.00		1.00	1.00
Frt		1.00	0.99			0.99			0.95		1.00	0.94
Flt Protected		0.95	1.00			1.00			0.99		0.95	1.00
Satd. Flow (prot)		1770	3517			3491			1749		1770	1744
Flt Permitted		0.53	1.00			0.94			0.65		0.46	1.00
Satd. Flow (perm)		980	3517			3294			1160		866	1744
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	42	45	337	15	11	287	26	70	91	89	25	123
RTOR Reduction (vph)	0	0	3	0	0	5	0	0	27	0	0	37
Lane Group Flow (vph)	0	87	349	0	0	319	0	0	223	0	25	177
Turn Type	custom	pm+pt	NA		Perm	NA		Perm	NA		Perm	NA
Protected Phases		1	5			2			4			8
Permitted Phases	1	5			2			4			8	
Actuated Green, G (s)		61.7	61.7			53.6			18.2		18.2	18.2
Effective Green, g (s)		61.7	61.7			53.6			18.2		18.2	18.2
Actuated g/C Ratio		0.69	0.69			0.60			0.20		0.20	0.20
Clearance Time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Vehicle Extension (s)		2.0	1.0			1.0			2.5		2.5	2.5
Lane Grp Cap (vph)		716	2411			1961			234		175	352
v/s Ratio Prot		0.01	c0.10									0.10
v/s Ratio Perm		0.08				c0.10			c0.19		0.03	
v/c Ratio		0.12	0.14			0.16			0.95		0.14	0.50
Uniform Delay, d1		4.7	4.9			8.1			35.5		29.5	31.9
Progression Factor		1.00	1.00			0.88			1.00		1.00	1.00
Incremental Delay, d2		0.0	0.1			0.2			45.4		0.3	0.8
Delay (s)		4.8	5.1			7.3			80.9		29.8	32.7
Level of Service		Α	А			Α			F		С	С
Approach Delay (s)			5.0			7.3			80.9			32.4
Approach LOS			А			А			F			С
Intersection Summary												
HCM 2000 Control Delay			26.0	Н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capac	ity ratio		0.35									
Actuated Cycle Length (s)			90.0	S	um of los	t time (s)			13.1			
Intersection Capacity Utilizat	ion		65.9%	IC	U Level	of Service	9		С			
Analysis Period (min)			15									

c Critical Lane Group

	,
	-
	000
Movement	SBR
Lane	<b>.</b> /
Volume (vph)	84
Ideal Flow (vphpl)	1900
Total Lost time (s)	
Lane Util. Factor	
Frt	
Flt Protected	
Satd. Flow (prot)	
Flt Permitted	
Satd. Flow (perm)	
Peak-hour factor, PHF	0.92
Adj. Flow (vph)	91
RTOR Reduction (vph)	0
Lane Group Flow (vph)	0
Turn Type	
Protected Phases	
Permitted Phases	
Actuated Green, G (s)	
Effective Green, g (s)	
Actuated g/C Ratio	
Clearance Time (s)	
Vehicle Extension (s)	
Lane Grp Cap (vph)	
v/s Ratio Prot	
v/s Ratio Perm	
v/c Ratio	
Uniform Delay, d1	
Progression Factor	
Incremental Delay, d2	
Delay (s)	
Level of Service	
Approach Delay (s) Approach LOS	
Intersection Summary	

#### Timings 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	٦	-	$\rightarrow$	-	1	1	1	Ŧ
Lane Group	EBL	EBT	EBR	WBT	NBL	NBT	SBL	SBT
Lane Configurations	ሻ	्र	1	ፋጉ	ሻ	<b>∱1</b> ≽	ሻ	<b>∱</b> î≽
Volume (vph)	257	33	110	24	157	1214	14	1012
Turn Type	Split	NA	pm+ov	NA	pm+pt	NA	Perm	NA
Protected Phases	3	3	1	4	1	6		2
Permitted Phases			3		6		2	
Detector Phase	3	3	1	4	1	6	2	2
Switch Phase								
Minimum Initial (s)	7.0	7.0	5.0	7.0	5.0	7.0	7.0	7.0
Minimum Split (s)	22.8	22.8	8.0	25.0	8.0	32.9	32.9	32.9
Total Split (s)	47.0	47.0	8.0	27.0	8.0	106.0	98.0	98.0
Total Split (%)	26.1%	26.1%	4.4%	15.0%	4.4%	58.9%	54.4%	54.4%
Yellow Time (s)	4.0	4.0	3.0	4.0	3.0	4.0	4.0	4.0
All-Red Time (s)	0.8	0.8	0.0	0.8	0.0	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.8	4.8	3.0	4.8	3.0	5.9	5.9	5.9
Lead/Lag	Lead	Lead	Lead	Lag	Lead		Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Recall Mode	None	None	None	None	None	C-Min	C-Min	C-Min

Intersection Summary Cycle Length: 180

Actuated Cycle Length: 180

Offset: 21 (12%), Referenced to phase 2:SBTL and 6:NBTL, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

Splits and Phases: 3: NW 37th Avenue/Douglas Road & Alhambra Plaza



# HCM Signalized Intersection Capacity Analysis 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	≯	-	$\mathbf{i}$	4	+	•	•	†	1	1	Ļ	~
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	<u>۳</u>	र्च	1		र्स कि		ኘ	<b>∱</b> ⊅		ሻ	<b>≜</b> ⊅	
Volume (vph)	257	33	110	11	24	11	157	1214	23	14	1012	110
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Lane Util. Factor	0.95	0.95	1.00		0.95		1.00	0.95		1.00	0.95	
Frt	1.00	1.00	0.85		0.96		1.00	1.00		1.00	0.99	
Flt Protected	0.95	0.96	1.00		0.99		0.95	1.00		0.95	1.00	
Satd. Flow (prot)	1681	1704	1583		3372		1770	3529		1770	3487	
Flt Permitted	0.95	0.96	1.00		0.99		0.20	1.00		0.22	1.00	
Satd. Flow (perm)	1681	1704	1583		3372		364	3529		416	3487	
Peak-hour factor, PHF	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Adj. Flow (vph)	260	33	111	11	24	11	159	1226	23	14	1022	111
RTOR Reduction (vph)	0	0	89	0	11	0	0	0	0	0	3	0
Lane Group Flow (vph)	146	147	22	0	35	0	159	1249	0	14	1130	0
Turn Type	Split	NA	pm+ov	Split	NA		pm+pt	NA		Perm	NA	
Protected Phases	.3	3	. 1	. 4	4			6			2	
Permitted Phases			3				6			2		
Actuated Green, G (s)	20.6	20.6	36.1		6.1		137.8	137.8		119.3	119.3	
Effective Green, g (s)	20.6	20.6	36.1		6.1		137.8	137.8		119.3	119.3	
Actuated g/C Ratio	0.11	0.11	0.20		0.03		0.77	0.77		0.66	0.66	
Clearance Time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Vehicle Extension (s)	2.5	2.5	2.0		2.5		2.0	1.0		1.0	1.0	
Lane Grp Cap (vph)	192	195	317		114		399	2701		275	2311	
v/s Ratio Prot	c0.09	0.09	0.01		c0.01		0.03	c0.35			c0.32	
v/s Ratio Perm			0.01				0.27			0.03		
v/c Ratio	0.76	0.75	0.07		0.31		0.40	0.46		0.05	0.49	
Uniform Delay, d1	77.3	77.2	58.3		84.9		8.5	7.7		10.6	15.1	
Progression Factor	0.99	0.99	1.97		1.00		1.00	1.00		0.73	0.76	
Incremental Delay, d2	15.3	14.3	0.0		1.1		0.2	0.6		0.3	0.7	
Delay (s)	91.7	90.6	115.0		86.0		8.8	8.2		8.0	12.2	
Level of Service	F	F	F		F		А	А		А	В	
Approach Delay (s)		97.7			86.0			8.3			12.1	
Approach LOS		F			F			Α			В	
Intersection Summary												
HCM 2000 Control Delay			23.0	н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capa	acity ratio		0.52		2 2000	_0.0101	2011100		Ŭ			
Actuated Cycle Length (s)			180.0	S	um of los	t time (c)			18.5			
Intersection Capacity Utiliz	ation		68.6%		CU Level				10.0 C			
Analysis Period (min)			15			0.00110	-		Ŭ			
c Critical Lane Group			.0									

	٦	$\mathbf{r}$	1	<b>†</b>	Ŧ
Lane Group	EBL	EBR	NBL	NBT	SBT
Lane Configurations	ľ	1	۲	<u></u>	A
Volume (vph)	81	94	41	1432	1048
Turn Type	Prot	Perm	pm+pt	NA	NA
Protected Phases	8		1	6	2
Permitted Phases		8	6		
Detector Phase	8	8	1	6	2
Switch Phase					
Minimum Initial (s)	4.0	4.0	4.0	4.0	4.0
Minimum Split (s)	20.0	20.0	8.9	20.0	20.0
Total Split (s)	43.0	43.0	22.0	137.0	115.0
Total Split (%)	23.9%	23.9%	12.2%	76.1%	63.9%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.9	0.9	0.9	0.9	0.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.9	4.9	4.9	4.9	4.9
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Recall Mode	None	None	None	C-Min	C-Min

Intersection Summary Cycle Length: 180 Actuated Cycle Length: 180 Offset: 52 (29%), Referenced to phase 2:SBT and 6:NBTL, Start of Green Natural Cycle: 55 Control Type: Actuated-Coordinated

Splits and Phases: 4: NW 37th Avenue/Douglas Road & Minorca Avenue


	≯	$\mathbf{F}$	•	Ť	ţ	<	
Movement	EBL	EBR	NBL	NBT	SBT	SBR	
Lane Configurations	ሻ	1	<u>۳</u>	- <b>††</b>	<b>∱</b> Ъ		
Volume (veh/h)	81	94	41	1432	1048	26	
Number	3	18	1	6	2	12	
nitial Q (Qb), veh	0	0	0	0	0	0	
Ped-Bike Adj(A_pbT)	1.00	1.00	1.00			1.00	
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	
Adj Sat Flow, veh/h/ln	186.3	186.3	186.3	186.3	186.3	190.0	
Adj Flow Rate, veh/h	84	97	42	1476	1080	27	
Adj No. of Lanes	1	1	1	2	2	0	
Peak Hour Factor	0.97	0.97	0.97	0.97	0.97	0.97	
Percent Heavy Veh, %	2	2	2	2	2	2	
Cap, veh/h	170	151	422	2736	2387	60	
Arrive On Green	0.10	0.10	0.06	1.00	0.68	0.68	
Sat Flow, veh/h	1774	1583	1774	3632	3622	88	
Grp Volume(v), veh/h	84	97	42	1476	542	565	
Grp Sat Flow(s),veh/h/ln	1774	1583	1774	1770	1770	1847	
Q Serve(g_s), s	3.4	4.4	0.5	0.0	10.7	10.7	
Cycle Q Clear(g_c), s	3.4	4.4	0.5	0.0	10.7	10.7	
Prop In Lane	1.00	1.00	1.00			0.05	
ane Grp Cap(c), veh/h	170	151	422	2736	1197	1249	
//C Ratio(X)	0.50	0.64	0.10	0.54	0.45	0.45	
Avail Cap(c_a), veh/h	905	808	773	6262	2610	2724	
HCM Platoon Ratio	1.00	1.00	2.00	2.00	1.00	1.00	
Jpstream Filter(I)	1.00	1.00	0.87	0.87	1.00	1.00	
Jniform Delay (d), s/veh	32.1	32.5	3.7	0.0	5.6	5.6	
ncr Delay (d2), s/veh	3.2	6.3	0.1	0.7	1.2	1.2	
nitial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	
%ile BackOfQ(50%),veh/In	1.8	2.2	0.2	0.3	5.5	5.8	
_nGrp Delay(d),s/veh	35.2	38.8	3.8	0.7	6.9	6.8	
_nGrp LOS	D	D	A	A	A	A	
Approach Vol, veh/h	181			1518	1107		
Approach Delay, s/veh	37.1			0.8	6.8		
Approach LOS	D			A.	A		
	1	2	ე			c	7 0
Fimer	<u> </u>	2	3	4	5	6	7 8
Assigned Phs	1	2				6	8
Phs Duration (G+Y+Rc), s	7.2	160.7			* 4 0	168.0	12.0
Change Period (Y+Rc), s* 4.9						000001	4.9
Max Green Setting (Gmax), s					* 132	.10001	38.1
Max Q Clear Time (g_c+l1), s Green Ext Time (p_c), s	5 2.5 0.0	12.7 37.8				2.0 40.3	6.4 0.9
ntersection Summary		-					
HCM 2010 Ctrl Delay			5.5				
HCM 2010 LOS			0.0 A				
Notes							

\* HCM 2010 computational engine requires equal clearance times for the phases crossing the barrier.

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Existing\_PM.syn

HCM 2010 TWSC 5: Alhambra Circle & Minorca Avenue

Int Delay, s/veh	7.4										
Movement	EBL	EBT	EBR		WBL	WBT	WBR		NBL	NBT	NBR
Vol, veh/h	2	35	84		89	62	17		65	87	77
Conflicting Peds, #/hr	2	0	4		4	0	2		12	0	4
Sign Control	Stop	Stop	Stop		Stop	Stop	Stop		Free	Free	Free
RT Channelized	-	-	None		-	-	None		-	-	None
Storage Length	-	-	-		-	-	-		-	-	-
Veh in Median Storage, #	-	0	-		-	0	-		-	0	-
Grade, %	-	0	-		-	0	-		-	0	-
Peak Hour Factor	98	98	98		98	98	98		98	98	98
Heavy Vehicles, %	2	2	2		2	2	2		2	2	2
Mvmt Flow	2	36	86		91	63	17		66	89	79
Major/Minor	Minor2				Minor1				Major1		
	543	542	229		563	506	144		220	0	0
Conflicting Flow All	238	542 238	229		265	265	144		220	0	0
Stage 1	230	238 304	-		205	205 241	-		-	-	-
Stage 2 Critical Hdwy	7.12	6.52	6.22		7.12	6.52	6.22		- 4.12	-	-
Critical Hdwy Stg 1	6.12	0.52 5.52	0.22		6.12	0.52 5.52	0.22		4.1Z	-	-
Critical Hdwy Stg 2	6.12	5.52	-		6.12	5.52	-		-	-	-
Follow-up Hdwy	3.518	4.018	3.318		3.518	4.018	3.318		2.218	-	-
Pot Cap-1 Maneuver	451	4.010	3.310 810		437	4.010	903		1349	-	-
Stage 1	765	708	010		740	689	303		1049	-	-
Stage 2	705	663	_		740	706	_		-	-	_
Platoon blocked, %	705	005			111	700				_	_
Mov Cap-1 Maneuver	370	416	799		343	437	891		1336	_	_
Mov Cap-2 Maneuver	370	416	100		343	437			-	_	_
Stage 1	721	700	_		697	649	_		_	_	_
Stage 2	584	624	-		592	698	-		-	-	-
Approach	EB				WB				NB		
HCM Control Delay, s	12.2				20.6				2.2		
HCM LOS	В				С						
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR			
Capacity (veh/h)	1336	-	-	622	400	1392	-	-			
HCM Lane V/C Ratio	0.05	-	-	0.199	0.429	0.007	-	-			
HCM Control Delay (s)	7.8	0	-	12.2	20.6	7.6	0	-			
HCM Lane LOS	7.0 A	Ă	-	B	20.0 C	A	Ă	-			
HCM 95th %tile Q(veh)	0.2	-	_	0.7	2.1	0	-				

#### Intersection

Int Delay, s/veh

Movement	SBL	SBT	SBR
Vol, veh/h	10	206	6
Conflicting Peds, #/hr	4	0	12
Sign Control	Free	Free	Free
RT Channelized	-	-	None
	-		NONE
Storage Length	-	-	-
Veh in Median Storage, #	-	0	-
Grade, %	-	0	-
Peak Hour Factor	98	98	98
Heavy Vehicles, %	2	2	2
Mvmt Flow	10	210	6
Major/Minor	Major2		
Conflicting Flow All	171	0	0
	171	0	0
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	4.12	-	-
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	2.218	-	-
Pot Cap-1 Maneuver	1406	-	-
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	1392	-	-
Mov Cap-2 Maneuver		-	-
Stage 1	_	-	-
Stage 2	-	_	_
Slage 2	-	-	-
Approach	SB		
HCM Control Delay, s	0.3		
HCM LOS			
Minor Long (Major Murat			
Minor Lane/Major Mvmt			

Intersection Int Delay, s/veh	21								
III Delay, Siven	21								
Movement	NBL	NBT				SBT	SBR	NEL	NER
Vol, veh/h	0	1374				1099	230	72	22
Conflicting Peds, #/hr	0	0				0	5	0	0
Sign Control	Free	Free				Free	Free	Stop	Stop
RT Channelized	-	None				-	None	-	None
Storage Length	-	-				-	-	0	0
Veh in Median Storage, #	-	0				0	-	0	-
Grade, %	-	0				0	-	0	-
Peak Hour Factor	86	86				86	86	86	86
Heavy Vehicles, %	2	2				2	2	2	2
Mvmt Flow	0	1598				1278	267	84	26
Major/Minor	Major1					Major2		Minor2	
Conflicting Flow All	1545	0				_	0	2211	773
Stage 1	-	-				-	-	1412	-
Stage 2	-	-				-	-	799	-
Critical Hdwy	4.14	-				-	-	6.84	6.94
Critical Hdwy Stg 1	-	-				-	-	5.84	-
Critical Hdwy Stg 2	-	-				-	-	5.84	-
Follow-up Hdwy	2.22	-				-	-	3.52	3.32
Pot Cap-1 Maneuver	426	-				-	-	~ 37	342
Stage 1	-	-				-	-	191	-
Stage 2	-	-				-	-	403	-
Platoon blocked, %		-				-	-		
Mov Cap-1 Maneuver	426	-				-	-	~ 37	342
Mov Cap-2 Maneuver	-	-				-	-	~ 37	-
Stage 1	-	-				-	-	191	-
Stage 2	-	-				-	-	403	-
Approach	NB					SB		NE	
HCM Control Delay, s	0					0		\$ 624.6	
HCM LOS	·					· ·		F	
Minor Lane/Major Mvmt	NELn1	NELn2	NBL	NBT	SBT	SBR			
Capacity (veh/h)	37	342	426	-	-	-			
HCM Lane V/C Ratio	2.263	0.075	-	-	-	-			
HCM Control Delay (s)	\$ 810.4	16.4	0	-	-	-			
HCM Lane LOS	φ 010.4 F	C	Ă	-	-	-			
HCM 95th %tile Q(veh)	9.2	0.2	0	-	-	-			
	0.2	0.2	v						
Notes	¢. Dalassassas	de 200-				nod *	All mains		
~: Volume exceeds capacity	\$: Delay excee	eus Juus	+: Com	putation	INOT Defi	nea ^:	All major vo	lume in platoon	

**Future Background Conditions** 

Intersection												
Intersection Delay, s/veh	17.2											
Intersection LOS	С											
Movement	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR
Vol, veh/h	0	0	4	3	0	73	199	121	0	76	36	114
Peak Hour Factor	0.92	0.88	0.88	0.88	0.92	0.88	0.88	0.88	0.92	0.88	0.88	0.88
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	0	5	3	0	83	226	137	0	86	41	130
Number of Lanes	0	0	1	1	0	0	1	0	0	0	1	0
Approach			EB			WB				NB		
Opposing Approach			WB			EB				SB		
Opposing Lanes			1			2				2		
Conflicting Approach Left			SB			NB				EB		
Conflicting Lanes Left			2			1				2		
Conflicting Approach Right			NB			SB				WB		
Conflicting Lanes Right			1			2				1		
HCM Control Delay			9.3			22.6				13.8		
HCMLOS			А			С				В		
Lane		NBLn1	EBLn1	FBI n2	WBLn1	SBLn1	SBLn2					
Vol Left, %		34%	0%	0%	19%	86%	0%					
Vol Thru, %		16%	100%	0%	51%	14%	0%					
Vol Right, %		50%	0%	100%	31%	0%	100%					
Sign Control		Stop	Stop	Stop	Stop	Stop	Stop					
Traffic Vol by Lane		226	4	3	393	119	81					
LT Vol		36	4	0	199	17	0					
Through Vol		114	0	3	121	0	81					
RT Vol		76	0	0	73	102	0					
Lane Flow Rate		257	5	3	447	135	92					
Geometry Grp		6	7	7	6	7	7					
Degree of Util (X)		0.436	0.009	0.006	0.722	0.256	0.145					
Departure Headway (Hd)		6.109	6.768	6.053	5.824	6.819	5.672					
Convergence, Y/N		Yes	Yes	Yes	Yes	Yes	Yes					
Сар		588	526	588	621	526	630					
Service Time		4.16	4.54	3.824	3.866	4.575	3.428					
HCM Lane V/C Ratio		0.437	0.01	0.005	0.72	0.257	0.146					
HCM Control Delay		13.8	9.6	8.9	22.6	11.9	9.4					
HCM Lane LOS		В 2.2	A	A	С	В	A					
HCM 95th-tile Q		2.2	0	0	6.1	1	0.5					

Intersection Intersection Delay, s/veh Intersection LOS					
Movement	SBU	SBL	SBT	SBR	
Vol, veh/h	0	102	17	81	
Peak Hour Factor	0.92	0.88	0.88	0.88	
Heavy Vehicles, %	2	2	2	2	
Mvmt Flow	0	116	19	92	
Number of Lanes	0	0	1	1	
Approach		SB			
Opposing Approach		NB			
Opposing Lanes		1			
Conflicting Approach Left		WB			
Conflicting Lanes Left		1			
Conflicting Approach Right		EB			
Conflicting Lanes Right		2			
HCM Control Delay		10.9			
HCM LOS		В			
Lane					

# Timings 2: Galiano Street & Alhambra Plaza

	5	٦	-	-	-	1	1	1	Ļ
Lane Group	EBU	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		3	<b>≜</b> ⊅		ፋጉ		4	ሻ	4
Volume (vph)	16	109	347	27	223	20	74	15	61
Turn Type	custom	pm+pt	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		1	5		2		4		8
Permitted Phases	1	5		2		4		8	
Detector Phase	1	1	5	2	2	4	4	8	8
Switch Phase									
Minimum Initial (s)	5.0	5.0	15.0	15.0	15.0	7.0	7.0	7.0	7.0
Minimum Split (s)	8.0	8.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Total Split (s)	8.0	8.0	58.0	50.0	50.0	32.0	32.0	32.0	32.0
Total Split (%)	8.9%	8.9%	64.4%	55.6%	55.6%	35.6%	35.6%	35.6%	35.6%
Yellow Time (s)	3.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.3	0.3	0.3	1.8	1.8	1.8	1.8
Lost Time Adjust (s)		0.0	0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		3.0	4.3		4.3		5.8	5.8	5.8
Lead/Lag	Lead	Lead		Lag	Lag				
Lead-Lag Optimize?	Yes	Yes		Yes	Yes				
Recall Mode	None	None	C-Min	C-Min	C-Min	None	None	None	None
Intersection Summary									

Intersection Summary

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 0 (0%), Referenced to phase 2:WBTL and 5:EBTL, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

	≪ <b>†</b> ø4
8 s 50 s	32 s
<u></u> ∞5 (R)	
58 s	32 s

# HCM Signalized Intersection Capacity Analysis 2: Galiano Street & Alhambra Plaza

	•	≯	+	*	4	Ļ	•	•	t	*	1	Ŧ
Movement	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations		2	<b>≜</b> †≱			et îr			<del>4</del> >		<u>۳</u>	eî 👘
Volume (vph)	16	109	347	10	27	223	59	20	74	43	15	61
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Lane Util. Factor		1.00	0.95			0.95			1.00		1.00	1.00
Frt		1.00	1.00			0.97			0.96		1.00	0.97
Flt Protected		0.95	1.00			1.00			0.99		0.95	1.00
Satd. Flow (prot)		1770	3525			3423			1771		1770	1802
Flt Permitted		0.52	1.00			0.90			0.94		0.52	1.00
Satd. Flow (perm)		963	3525			3098			1669		967	1802
Peak-hour factor, PHF	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Adj. Flow (vph)	18	122	390	11	30	251	66	22	83	48	17	69
RTOR Reduction (vph)	0	0	1	0	0	16	0	0	23	0	0	14
Lane Group Flow (vph)	0	140	400	0	0	331	0	0	130	0	17	74
Turn Type	custom	pm+pt	NA		Perm	NA		Perm	NA		Perm	NA
Protected Phases		1	5			2			4			8
Permitted Phases	1	5			2			4			8	
Actuated Green, G (s)		68.1	68.1			58.7			11.8		11.8	11.8
Effective Green, g (s)		68.1	68.1			58.7			11.8		11.8	11.8
Actuated g/C Ratio		0.76	0.76			0.65			0.13		0.13	0.13
Clearance Time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Vehicle Extension (s)		2.0	1.0			1.0			2.5		2.5	2.5
Lane Grp Cap (vph)		786	2667			2020			218		126	236
v/s Ratio Prot		c0.01	0.11									0.04
v/s Ratio Perm		c0.12				0.11			c0.08		0.02	
v/c Ratio		0.18	0.15			0.16			0.60		0.13	0.31
Uniform Delay, d1		3.0	3.0			6.1			36.9		34.6	35.4
Progression Factor		1.00	1.00			0.97			1.00		1.00	1.00
Incremental Delay, d2		0.0	0.1			0.2			3.7		0.4	0.6
Delay (s)		3.0	3.1			6.0			40.5		34.9	36.0
Level of Service		Α	А			А			D		С	D
Approach Delay (s)			3.1			6.0			40.5			35.8
Approach LOS			А			А			D			D
Intersection Summary												
HCM 2000 Control Delay			12.0	Н	CM 2000	Level of	Service		В			
HCM 2000 Volume to Capac	ity ratio		0.25									
Actuated Cycle Length (s)			90.0	S	um of los	t time (s)			13.1			
Intersection Capacity Utilizat	ion		51.3%	IC	CU Level	of Service	Э		Α			
Analysis Period (min)			15									

c Critical Lane Group

	4
Movement	SBR
Lane	
Volume (vph)	17
Ideal Flow (vphpl)	1900
Total Lost time (s) Lane Util. Factor	
Frt	
Flt Protected	
Satd. Flow (prot)	
Flt Permitted	
Satd. Flow (perm)	
Peak-hour factor, PHF	0.89
Adj. Flow (vph)	19
RTOR Reduction (vph)	0 0
Lane Group Flow (vph) Turn Type	0
Protected Phases	
Permitted Phases	
Actuated Green, G (s)	
Effective Green, g (s)	
Actuated g/C Ratio	
Clearance Time (s)	
Vehicle Extension (s)	
Lane Grp Cap (vph)	
v/s Ratio Prot	
v/s Ratio Perm v/c Ratio	
Uniform Delay, d1	
Progression Factor	
Incremental Delay, d2	
Delay (s)	
Level of Service	
Approach Delay (s)	
Approach LOS	
Intersection Summary	

#### Timings 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	≯	-	$\rightarrow$	+	1	1	1	Ļ
Lane Group	EBL	EBT	EBR	WBT	NBL	NBT	SBL	SBT
Lane Configurations	ሻ	र्भ	1	ፋጉ	ሻ	<b>∱</b> î≽	ሻ	<b>≜</b> ⊅
Volume (vph)	237	8	151	22	157	900	12	1182
Turn Type	Split	NA	pm+ov	NA	pm+pt	NA	Perm	NA
Protected Phases	3	3	1	4	1	6		2
Permitted Phases			3		6		2	
Detector Phase	3	3	1	4	1	6	2	2
Switch Phase								
Minimum Initial (s)	7.0	7.0	5.0	7.0	5.0	7.0	7.0	7.0
Minimum Split (s)	22.8	22.8	8.0	25.0	8.0	32.9	32.9	32.9
Total Split (s)	41.0	41.0	8.0	29.0	8.0	110.0	102.0	102.0
Total Split (%)	22.8%	22.8%	4.4%	16.1%	4.4%	61.1%	56.7%	56.7%
Yellow Time (s)	4.0	4.0	3.0	4.0	3.0	4.0	4.0	4.0
All-Red Time (s)	0.8	0.8	0.0	0.8	0.0	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.8	4.8	3.0	4.8	3.0	5.9	5.9	5.9
Lead/Lag	Lead	Lead	Lead	Lag	Lead		Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Recall Mode	None	None	None	None	None	C-Min	C-Min	C-Min

Intersection Summary Cycle Length: 180

Actuated Cycle Length: 180

Offset: 21 (12%), Referenced to phase 2:SBTL and 6:NBTL, Start of Green Natural Cycle: 100

Control Type: Actuated-Coordinated

Splits and Phases: 3: NW 37th Avenue/Douglas Road & Alhambra Plaza



# HCM Signalized Intersection Capacity Analysis 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	۶	-	$\mathbf{r}$	4	←	*	1	t	۲	1	Ļ	~
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	<del>ર્</del> ચ	1		ፋጉ		ሻ	<b>∱1</b> ≱		ሻ	At≯	
Volume (vph)	237	8	151	14	22	31	157	900	7	12	1182	96
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Lane Util. Factor	0.95	0.95	1.00		0.95		1.00	0.95		1.00	0.95	
Frt	1.00	1.00	0.85		0.93		1.00	1.00		1.00	0.99	
Flt Protected	0.95	0.96	1.00		0.99		0.95	1.00		0.95	1.00	
Satd. Flow (prot)	1681	1690	1583		3262		1770	3535		1770	3499	
Flt Permitted	0.95	0.96	1.00		0.99		0.14	1.00		0.30	1.00	
Satd. Flow (perm)	1681	1690	1583		3262		258	3535		564	3499	
Peak-hour factor, PHF	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
Adj. Flow (vph)	247	8	157	15	23	32	164	938	7	12	1231	100
RTOR Reduction (vph)	0	0	123	0	31	0	0	0	0	0	3	0
Lane Group Flow (vph)	128	127	34	0	39	0	164	945	0	12	1328	0
Turn Type	Split	NA	pm+ov	Split	NA		pm+pt	NA		Perm	NA	
Protected Phases	3	3	pin:01	4	4		2 pm·pt	6		1 Onn	2	
Permitted Phases	Ū	0	3	т	т		6	0		2	2	
Actuated Green, G (s)	18.6	18.6	38.7		7.8		138.1	138.1		115.0	115.0	
Effective Green, g (s)	18.6	18.6	38.7		7.8		138.1	138.1		115.0	115.0	
Actuated g/C Ratio	0.10	0.10	0.22		0.04		0.77	0.77		0.64	0.64	
Clearance Time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Vehicle Extension (s)	2.5	2.5	2.0		2.5		2.0	1.0		1.0	1.0	
Lane Grp Cap (vph)	173	174	340		141		366	2712		360	2235	
v/s Ratio Prot	c0.08	0.08	0.01		c0.01		c0.05	0.27		300	c0.38	
v/s Ratio Perm	0.00	0.00	0.01		CO.01		0.29	0.27		0.02	0.50	
v/c Ratio	0.74	0.73	0.01		0.28		0.29	0.35		0.02	0.59	
	0.74 78.4	78.3	56.7		0.20 83.4		12.6	0.35 6.7		12.0	18.9	
Uniform Delay, d1	0.99	0.99	1.62		03.4 1.00		12.0	1.00		0.83	0.91	
Progression Factor	0.99 14.4	13.3	0.0		0.8		0.3	0.4		0.03	1.1	
Incremental Delay, d2	91.8		0.0 91.7		0.0 84.2			0.4 7.0		0.2 10.1		
Delay (s)	91.0 F	90.6 F	91.7 F		04.2 F		12.9			IU.I B	18.3	
Level of Service	Г		Г		г 84.2		В	A Z O		D	B	
Approach Delay (s)		91.4						7.9			18.3	
Approach LOS		F			F			А			В	
Intersection Summary HCM 2000 Control Delay			26.2	Ц	CM 2000		Sonvico		С			
	oitu rotio		20.2 0.58	п		Level OI			U			
HCM 2000 Volume to Capa	uly ralio		0.58 180.0	0		ttime (c)			10 E			
Actuated Cycle Length (s)	tion				um of los CU Level (				18.5			
Intersection Capacity Utiliza	luon		70.1%	IC	U Level	DI SELVIC	e		С			
Analysis Period (min) c Critical Lane Group			15									

c Critical Lane Group

	٦	$\rightarrow$	•	1	Ļ
Lane Group	EBL	EBR	NBL	NBT	SBT
Lane Configurations	ሻ	1	ሻ	- <b>†</b> †	<b>≜</b> î≽
Volume (vph)	9	43	91	1078	1242
Turn Type	Prot	Perm	pm+pt	NA	NA
Protected Phases	8		1	6	2
Permitted Phases		8	6		
Detector Phase	8	8	1	6	2
Switch Phase					
Minimum Initial (s)	9.0	9.0	5.0	16.0	16.0
Minimum Split (s)	20.0	20.0	9.9	20.9	20.9
Total Split (s)	53.0	53.0	22.0	127.0	105.0
Total Split (%)	29.4%	29.4%	12.2%	70.6%	58.3%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.9	0.9	0.9	0.9	0.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.9	4.9	4.9	4.9	4.9
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Recall Mode	None	None	None	C-Min	C-Min
Intersection Summary					

Cycle Length: 180 Actuated Cycle Length: 180 Offset: 27 (15%), Referenced to phase 2:SBT and 6:NBTL, Start of Green Natural Cycle: 60 Control Type: Actuated-Coordinated

Splits and Phases: 4: NW 37th Avenue/Douglas Road & Minorca Avenue



Movement         EBL         EBR         NBL         NBT         SBT         SBR           Lane Configurations         1         0		≯	$\mathbf{r}$	1	1	ţ	~	
Volume (ven/h)         9         43         91         1078         1242         50           Number         3         18         1         6         2         12           Initial Q (Gb), veh         0         0         0         0         0         0           Perd-Bike Adj(A, pbT)         1.00         1.00         1.00         1.00         1.00           Parking Bus, Adj         1.00         1.00         1.00         1.00         1.00           Adj Row Rate, veh/h         9         44         93         1100         1267         51           Adj No of Lanes         1         1         2         2         0         Peak Hour Factor         0.98	Movement	EBL	EBR	NBL	NBT	SBT	SBR	
Number         3         18         1         6         2         12           Initial Q (Qb), veh         0         0         0         0         0         0           PedBike Adj(A_pDT)         1.00         1.00         1.00         1.00         1.00           Adj Sat Flow, veh/h/in         186.3         186.3         186.3         186.3         186.3         186.3           Adj Kov Atle, veh/h         9         44         93         1100         1267         51           Adj Ko of Lanes         1         1         2         2         0         Peak Hour Factor         0.98         0	Lane Configurations	<u>۲</u>	1	۳.	- <b>†</b> †	<b>↑</b> 1≽		
Initial Q(bb), veh Parking Bus, Adj Parking Bus, Adj Adj Row Lenes Adj Row Lenes Adj Row Rate, veh/h 186.3 190. 100 1267 51 Adj No of Lanes 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Volume (veh/h)	9	43	91	1078	1242	50	
Ped-Bine Adj(A, pbT)       1.00       1.00       1.00       1.00         Parking Bus, Adj       1.00       1.00       1.00       1.00       1.00         Adj Sat Flow, veh/hn       9       44       93       1100       1267       51         Adj No. of Lanes       1       1       2       2       0       Peak Hour Factor       0.98       0.71       0.01	Number	3	18	1	6	2	12	
Parking Bus, Adj       1.00       1.00       1.00       1.00       1.00       1.00         Adj Eav Riek, veh/h       186.3       186.3       186.3       190.0         Adj Flow Riek, veh/h       9       44       93       1100       1267       51         Adj Nov af Lanes       1       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2	Initial Q (Qb), veh	0	0	0	0	0	0	
Adj Saf Flow, veľvh/hln       186.3       186.3       186.3       186.3       190.0         Adj No. of Lanes       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98         Cap, veh/h       145       129       394       2767       2271       91         Arrive On Green       0.08       0.12       1.00       0.65       0.65         Grp Volume(v), weh/h       1774       1583       1774       1700       1838         Grp Volume(v), weh/h       9       1.0       0.0       1.4.3       1.4.3         Cycle Q. Clarg(c), s       0.3       1.9       1.0       0.44       3.3         Prop In Lane       1.00       1.00       1.00       0.08       1.4.3         Lane Grp Cap(c), veh/h       118       1060       712       6014       2465       2561         HCM Platoon Ratic       1.00       1.00       1.00       1.00       1.00       1.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       2.02       2.00       1.00       1.00       1.00       1.00         Upstream Filter(I)	Ped-Bike Adj(A_pbT)	1.00	1.00	1.00			1.00	
Adj Flow Rate, veh/h       9       44       93       1100       1267       51         Adj No of Lanes       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98         Parcent Heavy Veh, %       2       2       2       2       2       2       2       2         Cap, veh/h       145       129       394       2767       2271       91         Arrive On Green       0.08       0.08       0.12       1.00       0.65       0.55         Sat Flow, veh/h       1774       1583       1774       1770       1770       1838         Org Sat Flow(s), veh/h       9       44       93       100       0.0       14.3       14.3         Cycle Q Clear(g.c), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g.c), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g.c), s       0.3       1.9       3.0       0.0       1.0       0.06       0.0       0.0         Lane Gro Cap(c), veh/h       145       129       394       2767	Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	
Adj No. of Lanes       1       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2 </td <td>Adj Sat Flow, veh/h/ln</td> <td>186.3</td> <td>186.3</td> <td>186.3</td> <td>186.3</td> <td>186.3</td> <td>190.0</td> <td></td>	Adj Sat Flow, veh/h/ln	186.3	186.3	186.3	186.3	186.3	190.0	
Paik Hour Factor         0.98         0.98         0.98         0.98         0.98           Percent Heavy Veh, %         2         3 <t< td=""><td>Adj Flow Rate, veh/h</td><td>9</td><td>44</td><td>93</td><td>1100</td><td>1267</td><td>51</td><td></td></t<>	Adj Flow Rate, veh/h	9	44	93	1100	1267	51	
Percent Heavy Veh, %       2 <th2< th="">       2       <th2< th=""></th2<></th2<>	Adj No. of Lanes	1	1	1	2	2	0	
Cap, veh/h       145       129       394       2767       2271       91         Arrive On Green       0.08       0.08       0.12       1.00       0.65       0.65         Sat Flow, veh/h       1774       1583       1774       3632       3651       139         Grp Volume(V), veh/h       9       44       93       1100       646       672         Grp Sat Flow(s), veh/h/in       1774       1583       1774       1770       1838         Q Serve(g.s), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g.c), s       0.3       1.9       1.0       0.0       14.3       14.3         Prop In Lane       1.00       1.00       0.00       44.3       144.3       145         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Uniform Delay (d), siveh       0.3       2.2       0.2       0.4       1.9       1.9 <t< td=""><td>Peak Hour Factor</td><td>0.98</td><td>0.98</td><td>0.98</td><td>0.98</td><td>0.98</td><td>0.98</td><td></td></t<>	Peak Hour Factor	0.98	0.98	0.98	0.98	0.98	0.98	
Arrive On Green       0.08       0.08       0.12       1.00       0.65       0.65         Sat Flow, veh/h       1774       1583       1774       3362       3561       139         Grp Volume(v), veh/h       9       44       93       1100       646       672         Grp Sat Flow(s), veh/h/n       1774       1583       1774       1770       1538         Q Serve(g_s), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g_c), veh/h       145       129       394       2767       1159       1204         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       148       100       1.00       1.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.20       2.00       1.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       2.02       0.4       1.9       1.9       1.9         Initial Q Delay(d), siveh       0.3       2.2       0.2       7.4       7.7       1.0Grp Delay(d), siveh       32.9       0.7       8.6         Approach Vol, veh/h <td< td=""><td>Percent Heavy Veh, %</td><td>2</td><td>2</td><td>2</td><td>2</td><td>2</td><td>2</td><td></td></td<>	Percent Heavy Veh, %	2	2	2	2	2	2	
Arrive On Green       0.08       0.08       0.12       1.00       0.65       0.65         Sat Flow, veh/h       1774       1583       1774       3322       3561       139         Grp Volume(v), veh/h       9       44       93       1100       646       672         Grp Sat Flow(s), veh/h/n       1774       1783       1774       1770       1783         Q Serve(g_s), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(gc), s       0.3       1.9       1.0       0.0       14.3       14.3         Prop In Lane       1.00       1.00       0.08       14.3       14.3       14.3         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1188       1060       712       614       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       1.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), siveh       0.3       2.2       0.4       1.9       1.9       1.9      <	Cap, veh/h	145	129	394	2767	2271	91	
Grp Volume(v), veh/h       9       44       93       1100       646       672         Grp Sat Flow(s), veh/h/h/n       1774       1883       1774       1770       1770       1838         Q Serve(g_s), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g_c), s       0.3       1.9       1.0       0.0       14.3       14.3         Prop In Lane       1.00       1.00       1.00       0.08       Lane Grp Cap(c), veh/h       145       129       394       2767       1159       1204         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56       Axail Cap(c_a), veh/h       145       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       0.20       2.00       1.00       1.00       Upstram Filter(I)       1.00		0.08	0.08	0.12	1.00	0.65	0.65	
Grp Volume(v), veh/h       9       44       93       1100       646       672         Grp Sat Flow(s), veh/h/h/n       1774       1853       1774       1770       1770       1838         Q Serve(g, s), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g, c), s       0.3       1.9       1.0       0.0       14.3       14.3         Prop In Lane       1.00       1.00       0.00       14.3       14.3         Prop In Lane       1.00       1.00       0.08       Lane Grp Cap(c), veh/h       145       129       394       2767       1159       1204         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c, a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       1.00       1.00       1.00         Upstram Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d2), siveh       0.3       3.2       0.2       7.4       7.7         LnGrp Delay(d2), siveh       3.0       7.3       3	Sat Flow, veh/h	1774	1583	1774	3632	3561	139	
Grp Sat Flow(s),veh/h/ln       1774       1583       1774       1770       1838         Q Serve(g. s), s       0.3       1.9       1.0       0.0       14.3       14.3         Cycle Q Clear(g_c), s       0.3       1.9       1.0       0.0       14.3       14.3         Prop In Lane       1.00       1.00       0.08       14.3       14.3         Lane Grp Cap(c), veh/h       145       129       394       2767       1159       1204         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       0.00       1.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3), s/veh       0.3       0.2       0.2       7.4       7.7         LnGrp DOS       C       C       A       A       A         Approach Vol, veh/h       53 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>								
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$								
Cycle Q Clear(g_c), s       0.3       1.9       1.0       0.0       14.3       14.3         Prop In Lane       1.00       1.00       0.08       0.8         Lane Grp Cap(c), veh/h       145       129       394       2767       1159       1204         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d2), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%), veh/ln       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d), s/veh       32.9       0.7       8.6       Approach Vol, veh/h       53         Approach LOS       C       A       A       A       A         Aporoach Vol, veh/h <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
Prop In Lane       1.00       1.00       1.00       0.08         Lane Grp Cap(c), veh/h       145       129       394       2767       1159       1204         V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Unform Delay (d), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3), s/veh       0.3       2.2       0.2       7.4       7.7         LnGrp Delay(d), s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp Delay, s/veh       30.7       33.3       4.8       0.4       8.7       8.6         Approach Vol, veh/h       53       1193       1318       Approach Vol, veh/h       5.6         Approach LOS       C       A       A       A       A         Change Period (Y+Rc), s       9.1       16								
Lane Grp Cap(c), veh/h 145 129 394 2767 1159 1204 V/C Ratio(X) 0.06 0.34 0.24 0.40 0.56 0.56 Avail Cap(c_a), veh/h 1188 1060 712 6014 2465 2561 HCM Platoon Ratio 1.00 1.00 2.00 2.00 1.00 Upstream Filter(I) 1.00 1.00 0.92 0.92 1.00 1.00 Uniform Delay (d), s/veh 0.3 2.2 0.2 0.4 1.9 1.9 Initial Q Delay(d3), s/veh 0.0 0.0 0.0 0.0 0.0 0.0 %ile BackOfQ(50%), veh/ln 0.2 0.9 0.5 0.2 7.4 7.7 LnGrp Delay(d), s/veh 30.7 33.3 4.8 0.4 8.7 8.6 LnGrp LOS C C A A A A Approach Vol, veh/h 53 1193 1318 Approach Dolay, s/veh 32.9 0.7 8.6 Approach LOS C A A A A A Timer 1 2 3 4 5 6 7 8 Assigned Phs 1 2 6 8 Phs Duration (G+Y+Rc), s 9.1 160.1 169.2 10.8 Change Period (Y+Rc), s 4.5000004.9000001 * 4.900001 4.9 Max Green Setting (Gmax), s * 17.1 * 100.1 * 122.1 48.1 Max Q Clear Time (g_c+I1), s 3.0 16.3 2.0 3.9 Green Ext Time (g_c, s 0.1 30.8 32.9 0.2 Intersection Summary HCM 2010 Ctrl Delay 5.5 HCM 2010 Ctrl Delay 5.5 HCM 2010 Ctrl Delay 5.5 HCM 2010 LOS A								
V/C Ratio(X)       0.06       0.34       0.24       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       1.00       1.00       1.00         Uniform Delay (d), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%), veh/ln       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d), s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp Dolay, s/veh       30.7       33.3       4.8       0.4       8.7       8.6         Approach Vol, veh/h       53       1193       1318       138         Approach LOS       C       A       A       A         Pins Duration (G+Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       *100.1       * 122.1 <td< td=""><td></td><td></td><td></td><td></td><td>2767</td><td>1159</td><td></td><td></td></td<>					2767	1159		
Avail Cap(c_a), veh/h       1188       1060       712       6014       2465       2561         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       30.4       31.2       4.6       0.0       6.7       6.7         Incr Delay (d2), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d),s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       53       1193       1318         Approach LOS       C       A       A       A         Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8         Change Period (Y+Rc), s       9.1       160.1       169.2       10.8								
HCM Platoon Ratio 1.00 1.00 2.00 2.00 1.00 1.00 1.00 Upstream Filter(I) 1.00 1.00 0.92 0.92 1.00 1.00 Uniform Delay (d), s/veh 30.4 31.2 4.6 0.0 6.7 6.7 Incr Delay (d), s/veh 0.3 2.2 0.2 0.4 1.9 1.9 Initial Q Delay(d), s/veh 0.3 2.2 0.2 0.4 1.9 1.9 Initial Q Delay(d), s/veh 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.								
Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       30.4       31.2       4.6       0.0       6.7       6.7         Incr Delay (d2), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%), veh/In       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d), s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       53       1193       1318         Approach LOS       C       A       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8       10.8								
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$								
Incr Delay (d2), s/veh       0.3       2.2       0.2       0.4       1.9       1.9         Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d),s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       53       1193       1318         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       9       10.8       169.2       10.8         Change Period (Y+Rc), s       9.1       160.1       169.2       10.8       10.9       149.9         Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1       1       48.1       1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9       32.9       0.2         Intersection Summary       HCM 2010 Ctrl D								
Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d),s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       53       1193       1318         Approach Delay, s/veh       32.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       8         Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8       10.8         Change Period (Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9       4.9       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9       32.9       0.2         Intersection Summary       HCM 2010 Ctrl Delay       5.5       4       4       4       4	• • • •							
%ile BackOfQ(50%),veh/ln       0.2       0.9       0.5       0.2       7.4       7.7         LnGrp Delay(d),s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       53       1193       1318         Approach Delay, s/veh       32.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       9       10.8	• • •							
LnGrp Delay(d),s/veh       30.7       33.3       4.8       0.4       8.7       8.6         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       53       1193       1318         Approach Delay, s/veh       32.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       <	• • •							
LnGrp LOS         C         C         A         A         A         A           Approach Vol, veh/h         53         1193         1318         Approach Delay, s/veh         32.9         0.7         8.6           Approach LOS         C         A         A         A         A           Timer         1         2         3         4         5         6         7         8           Assigned Phs         1         2         3         4         5         6         7         8           Assigned Phs         1         2         6         8         8         9         9.1         160.1         169.2         10.8         10.8         14.9         4.9000001         4.9 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
Approach Vol, veh/h       53       1193       1318         Approach Delay, s/veh       32.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       8       9       9       10.7       10.7       8       8       8       9       9       10.7       8       6       8       8       9       9       10.7       8       8       8       9       9       10.8       10								
Approach Delay, s/veh       32.9       0.7       8.6         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       8       8       8         Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8       10.								
Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8         Change Period (Y+Rc), s* 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       5.5       HCM 2010 Ctrl Delay       5.5         HCM 2010 LOS       A       A								
Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8         Change Period (Y+Rc), s*       4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       5.5       HCM 2010 Ctrl Delay       5.5         HCM 2010 LOS       A       5.5								
Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8         Change Period (Y+Rc), s* 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       5.5       HCM 2010 Ctrl Delay       5.5         HCM 2010 LOS       A       A		1	0	2			<u>^</u>	7 0
Phs Duration (G+Y+Rc), s       9.1       160.1       169.2       10.8         Change Period (Y+Rc), s*       4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s       * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       5.5         HCM 2010 LOS       A		<u> </u>		3	4	5		
Change Period (Y+Rc), \$ 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       5.5       HCM 2010 LOS       A		1						
Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+l1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       HCM 2010 Ctrl Delay       5.5         HCM 2010 LOS       A								
Max Q Clear Time (g_c+l1), s       3.0       16.3       2.0       3.9         Green Ext Time (p_c), s       0.1       30.8       32.9       0.2         Intersection Summary       HCM 2010 Ctrl Delay       5.5         HCM 2010 LOS       A						* 4.9		
Green Ext Time (p_c), s         0.1         30.8         32.9         0.2           Intersection Summary         HCM 2010 Ctrl Delay         5.5         4           HCM 2010 LOS         A         A         A								
Intersection Summary       HCM 2010 Ctrl Delay     5.5       HCM 2010 LOS     A								
HCM 2010 Ctrl Delay         5.5           HCM 2010 LOS         A	Green Ext Time (p_c), s	0.1	30.8				32.9	0.2
HCM 2010 LOS A	Intersection Summary							
	HCM 2010 Ctrl Delay			5.5				
Notes	HCM 2010 LOS			А				
	Notes							

\* HCM 2010 computational engine requires equal clearance times for the phases crossing the barrier.

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Background\_AM.syn

HCM 2010 TWSC 5: Alhambra Circle & Minorca Avenue

Intersection											
Int Delay, s/veh	5.7										
Movement	EBL	EBT	EBR		WBL	WBT	WBR		NBL	NBT	NBR
Vol, veh/h	6	36	106		32	32	8		81	43	114
Conflicting Peds, #/hr	4	0	1		1	0	4		8	0	12
Sign Control	Stop	Stop	Stop		Stop	Stop	Stop		Free	Free	Free
RT Channelized	· -	-	None		-	-	None		-	-	None
Storage Length	-	-	-		-	-	-		-	-	-
Veh in Median Storage, #	-	0	-		-	0	-		-	0	-
Grade, %	-	0	-		-	0	-		-	0	-
Peak Hour Factor	93	93	93		93	93	93		93	93	93
Heavy Vehicles, %	2	2	2		2	2	2		2	2	2
Mvmt Flow	6	39	114		34	34	9		87	46	123
Major/Minor	Minor2				Minor1			Ν	/lajor1		
Conflicting Flow All	648	688	314		703	641	124	•	316	0	0
Stage 1	341	341			286	286	- 12		-	-	-
Stage 2	307	347	_		417	355	_		_	_	_
Critical Hdwy	7.12	6.52	6.22		7.12	6.52	6.22		4.12	_	_
Critical Hdwy Stg 1	6.12	5.52			6.12	5.52	-		-	-	_
Critical Hdwy Stg 2	6.12	5.52	-		6.12	5.52	-		-	-	_
Follow-up Hdwy	3.518	4.018	3.318		3.518	4.018	3.318		2.218	-	-
Pot Cap-1 Maneuver	383	369	726		352	393	927		1244	-	-
Stage 1	674	639	-		721	675	-		-	-	-
Stage 2	703	635	-		613	630	-		-	-	-
Platoon blocked, %					••••					-	-
Mov Cap-1 Maneuver	322	332	716		247	353	915		1232	-	-
Mov Cap-2 Maneuver	322	332	-		247	353	-			-	-
Stage 1	619	626	-		662	620	-		-	-	-
Stage 2	600	583	-		471	617	-		-	-	-
Approach	EB				WB				NB		
HCM Control Delay, s	14.5				20.2				2.8		
HCM LOS	B				20.2 C				2.0		
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR			
Capacity (veh/h)	1232	-	-	538	314	1390	-	-			
HCM Lane V/C Ratio	0.071	-	-	0.296	0.247	0.014	_	-			
HCM Control Delay (s)	8.1	0	_	14.5	20.2	7.6	0	-			
HCM Lane LOS	A	A	-	В	20.2 C	7.0 A	Â	-			
HCM 95th %tile Q(veh)	0.2	-	_	1.2	1	0	-	-			
	0.2			1.4	I	U					

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Background\_AM.syn

Intersection				 
Int Delay, s/veh				
Movement	SBL	SBT	SBR	
Vol, veh/h	18	264	26	 
Conflicting Peds, #/hr	12	0	8	
Sign Control	Free	Free	Free	
RT Channelized	-	-	None	
Storage Length	-	-	-	
Veh in Median Storage, #	-	0	-	
Grade, %	-	0	-	
Peak Hour Factor	93	93	93	
Heavy Vehicles, %	2	2	2	
Mvmt Flow	19	284	28	
Major/Minor	Major2			
Conflicting Flow All	173	0	0	 
Stage 1	-	-	-	
Stage 2	-	-	_	
Critical Hdwy	4.12	-	-	
Critical Hdwy Stg 1	-	-	-	
Critical Hdwy Stg 2	-	-	-	
Follow-up Hdwy	2.218	-	-	
Pot Cap-1 Maneuver	1404	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Platoon blocked, %		-	-	
Mov Cap-1 Maneuver	1390	-	-	
Mov Cap-2 Maneuver	-	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Approach	SB			
HCM Control Delay, s	0.4			
HCM LOS	0.4			
Minor Lane/Major Mvmt				

#### K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Background\_AM.syn

Intersection	40.0								
Int Delay, s/veh	18.6								
Movement	NBL	NBT				SBT	SBR	NEL	NER
Vol, veh/h	0	1175				1253	275	63	15
Conflicting Peds, #/hr	0	0				0	4	0	0
Sign Control	Free	Free				Free	Free	Stop	Stop
RT Channelized	-	None				-	None	-	None
Storage Length	-	-				-	-	0	0
Veh in Median Storage, #	-	0				0	-	0	-
Grade, %	-	0				0	-	0	-
Peak Hour Factor	86	86				86	86	86	86
Heavy Vehicles, %	2	2				2	2	2	2
Mvmt Flow	0	1366				1457	320	73	17
Major/Minor	Major1					Major2		Minor2	
Conflicting Flow All	1777	0					0	2300	888
Stage 1	-	-				-	-	1617	-
Stage 2	-	-				-	-	683	-
Critical Hdwy	4.14	-				-	-	6.84	6.94
Critical Hdwy Stg 1	-	-				-	-	5.84	-
Critical Hdwy Stg 2	-	-				-	-	5.84	-
Follow-up Hdwy	2.22	-				-	-	3.52	3.32
Pot Cap-1 Maneuver	346	-				-	-	~ 33	287
Stage 1	-	-				-	-	148	
Stage 2	-	-				-	-	463	-
Platoon blocked, %		-				-	-		
Mov Cap-1 Maneuver	346	-				-	-	~ 33	287
Mov Cap-2 Maneuver	-	-				-	-	~ 33	
Stage 1	-	-				-	-	148	-
Stage 2	-	-				-	-	463	-
Annasah						00			
Approach	NB					SB		NE CC1 0	
HCM Control Delay, s HCM LOS	0					0		\$ 664.2 F	
					007	055			
Minor Lane/Major Mvmt	NELn1	NELn2	NBL	NBT	SBT	SBR			
Capacity (veh/h)	33	287	346	-	-	-			
HCM Lane V/C Ratio	2.22	0.061	-	-	-	-			
HCM Control Delay (s)	\$ 817.9	18.4	0	-	-	-			
HCM Lane LOS	F	С	A	-	-	-			
HCM 95th %tile Q(veh)	8.3	0.2	0	-	-	-			
Notes							A11 ·		
~: Volume exceeds capacity	\$: Delay excee	eds 300s	+: Com	putation	Not Defi	ned *:	All major vo	olume in platoon	

Intersection												
Intersection Delay, s/veh	17.9											
Intersection LOS	С											
Movement	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR
Vol, veh/h	0	5	60	58	0	105	181	110	0	8	51	103
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	5	65	63	0	114	197	120	0	9	55	112
Number of Lanes	0	0	1	1	0	0	1	0	0	0	1	0
Approach		EB				WB				NB		
Opposing Approach		WB				EB				SB		
Opposing Lanes		1				2				2		
Conflicting Approach Left		SB				NB				EB		
Conflicting Lanes Left		2				1				2		
Conflicting Approach Right		NB				SB				WB		
Conflicting Lanes Right		1				2				1		
HCM Control Delay		10.5				26.3				13.1		
HCM LOS		В				D				В		
Lane		NBLn1	EBLn1		WBLn1	SBLn1	SBLn2					
Vol Left, %		5%	8%	0%	27%	76%	0%					
Vol Thru, %		31%	92%	0%	46%	24%	0%					
Vol Right, %		64%	0%	100%	28%	0%	100%					
Sign Control		Stop	Stop	Stop	Stop	Stop	Stop					
Traffic Vol by Lane		162	65	58	396	191	149					
LT Vol		51	60	0	181	46	0					
Through Vol		103	0	58	110	0	149					
RT Vol		8	5	0	105	145	0					
Lane Flow Rate		176	71	63	430	208	162					
Geometry Grp		6	7	7	6	7	7					
Degree of Util (X)		0.332	0.14	0.112	0.753	0.407	0.268					
Departure Headway (Hd)		6.79	7.154	6.397	6.298	7.17	6.069					
Convergence, Y/N		Yes	Yes	Yes	Yes	Yes	Yes					
Cap		532	504	563	568	504	596					
Service Time		4.797	4.865	4.108	4.389	4.87	3.769					
HCM Lane V/C Ratio		0.331	0.141	0.112	0.757	0.413	0.272					
HCM Control Delay		13.1	11	9.9	26.3	14.7	11					
HCM Lane LOS												
HCM 95th-tile Q		В 1.4	B 0.5	A 0.4	D 6.6	B 2	В 1.1					

Intersection Intersection Delay, s/veh					
Intersection LOS					
Movement	SBU	SBL	SBT	SBR	
Vol, veh/h	0	145	46	149	
Peak Hour Factor	0.92	0.92	0.92	0.92	
Heavy Vehicles, %	2	2	2	2	
Mvmt Flow	0	158	50	162	
Number of Lanes	0	0	1	1	
Approach		SB			
Opposing Approach		NB			
Opposing Lanes		1			
Conflicting Approach Left		WB			
Conflicting Lanes Left		1			
Conflicting Approach Right		EB			
Conflicting Lanes Right		2			
HCM Control Delay		13.1			
HCM LOS		В			
Lane					

# Timings 2: Galiano Street & Alhambra Plaza

	⊴	≯	-	-	-	1	1	1	↓
Lane Group	EBU	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		24	<b>≜</b> ⊅		<b>≜</b> ⊅		4	ሻ	eî 👘
Volume (vph)	41	43	323	10	275	67	87	24	118
Turn Type	custom	pm+pt	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		1	5		2		4		8
Permitted Phases	1	5		2		4		8	
Detector Phase	1	1	5	2	2	4	4	8	8
Switch Phase									
Minimum Initial (s)	5.0	5.0	15.0	15.0	15.0	7.0	7.0	7.0	7.0
Minimum Split (s)	8.0	8.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Total Split (s)	8.0	8.0	52.0	44.0	44.0	38.0	38.0	38.0	38.0
Total Split (%)	8.9%	8.9%	57.8%	48.9%	48.9%	42.2%	42.2%	42.2%	42.2%
Yellow Time (s)	3.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.3	0.3	0.3	1.8	1.8	1.8	1.8
Lost Time Adjust (s)		0.0	0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		3.0	4.3		4.3		5.8	5.8	5.8
Lead/Lag	Lead	Lead		Lag	Lag				
Lead-Lag Optimize?	Yes	Yes		Yes	Yes				
Recall Mode	None	None	C-Min	C-Min	C-Min	None	None	None	None
Intersection Summary									

Intersection Summary

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 73 (81%), Referenced to phase 2:WBTL and 5:EBTL, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

Splits and Phases:	2: Galiano Street & Alhambra Plaza
--------------------	------------------------------------

	<b>√</b> ø4
8s <mark>44</mark> s	38 s
∞5 (R)	₹ ø8
52 s	38 s

# HCM Signalized Intersection Capacity Analysis 2: Galiano Street & Alhambra Plaza

	<b>●</b>	٦	-	$\mathbf{i}$	•	-	×	1	1	1	1	ţ
Movement	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations		2	<b>≜</b> ⊅			<b>≜</b> ⊅			4		<u>۲</u>	ef 👘
Volume (vph)	41	43	323	15	10	275	25	67	87	85	24	118
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Lane Util. Factor		1.00	0.95			0.95			1.00		1.00	1.00
Frt		1.00	0.99			0.99			0.95		1.00	0.94
Flt Protected		0.95	1.00			1.00			0.99		0.95	1.00
Satd. Flow (prot)		1770	3516			3491			1749		1770	1744
Flt Permitted		0.52	1.00			0.94			0.64		0.46	1.00
Satd. Flow (perm)		967	3516			3294			1138		859	1744
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	45	47	351	16	11	299	27	73	95	92	26	128
RTOR Reduction (vph)	0	0	3	0	0	5	0	0	27	0	0	36
Lane Group Flow (vph)	0	92	364	0	0	332	0	0	233	0	26	187
Turn Type	custom	pm+pt	NA		Perm	NA		Perm	NA		Perm	NA
Protected Phases		1	5			2			4			8
Permitted Phases	1	5			2			4			8	
Actuated Green, G (s)		61.0	61.0			52.7			18.9		18.9	18.9
Effective Green, g (s)		61.0	61.0			52.7			18.9		18.9	18.9
Actuated g/C Ratio		0.68	0.68			0.59			0.21		0.21	0.21
Clearance Time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Vehicle Extension (s)		2.0	1.0			1.0			2.5		2.5	2.5
Lane Grp Cap (vph)		702	2383			1928			238		180	366
v/s Ratio Prot		0.01	c0.10									0.11
v/s Ratio Perm		0.08				c0.10			c0.20		0.03	
v/c Ratio		0.13	0.15			0.17			0.98		0.14	0.51
Uniform Delay, d1		5.0	5.2			8.6			35.4		29.0	31.5
Progression Factor		1.00	1.00			0.87			1.00		1.00	1.00
Incremental Delay, d2		0.0	0.1			0.2			51.9		0.3	0.9
Delay (s)		5.0	5.3			7.7			87.3		29.2	32.4
Level of Service		Α	А			А			F		С	С
Approach Delay (s)			5.3			7.7			87.3			32.0
Approach LOS			А			А			F			С
Intersection Summary												
HCM 2000 Control Delay			27.3	Н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capac	city ratio		0.37									
Actuated Cycle Length (s)			90.0	S	um of los	t time (s)			13.1			
Intersection Capacity Utilizat	ion		66.8%	IC	CU Level	of Service	9		С			
Analysis Period (min)			15									
Intersection Capacity Utilizat	ion		66.8%				9					

c Critical Lane Group

Movement	SBR
Lane Configurations Volume (vph) Ideal Flow (vphpl) Total Lost time (s)	87 1900
Lane Util. Factor Frt Flt Protected Satd. Flow (prot)	
Flt Permitted Satd. Flow (perm)	
Peak-hour factor, PHF Adj. Flow (vph) RTOR Reduction (vph)	0.92 95 0
Lane Group Flow (vph)	0
Turn Type Protected Phases	
Permitted Phases Actuated Green, G (s)	
Effective Green, g (s) Actuated g/C Ratio Clearance Time (s)	
Vehicle Extension (s)	
Lane Grp Cap (vph) v/s Ratio Prot v/s Ratio Perm v/c Ratio	
Uniform Delay, d1 Progression Factor Incremental Delay, d2	
Delay (s) Level of Service Approach Delay (s) Approach LOS	
Intersection Summary	

#### Timings 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	≯	-	$\rightarrow$	+	1	1	1	Ļ
Lane Group	EBL	EBT	EBR	WBT	NBL	NBT	SBL	SBT
Lane Configurations	ሻ	र्भ	1	ፋጉ	ሻ	<b>≜</b> ⊅	ሻ	<b>≜</b> ⊅
Volume (vph)	267	34	114	25	163	1263	15	1053
Turn Type	Split	NA	pm+ov	NA	pm+pt	NA	Perm	NA
Protected Phases	3	3	1	4	1	6		2
Permitted Phases			3		6		2	
Detector Phase	3	3	1	4	1	6	2	2
Switch Phase								
Minimum Initial (s)	7.0	7.0	5.0	7.0	5.0	7.0	7.0	7.0
Minimum Split (s)	22.8	22.8	8.0	25.0	8.0	32.9	32.9	32.9
Total Split (s)	53.0	53.0	8.0	27.0	8.0	100.0	92.0	92.0
Total Split (%)	29.4%	29.4%	4.4%	15.0%	4.4%	55.6%	51.1%	51.1%
Yellow Time (s)	4.0	4.0	3.0	4.0	3.0	4.0	4.0	4.0
All-Red Time (s)	0.8	0.8	0.0	0.8	0.0	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.8	4.8	3.0	4.8	3.0	5.9	5.9	5.9
Lead/Lag	Lead	Lead	Lead	Lag	Lead		Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Recall Mode	None	None	None	None	None	C-Min	C-Min	C-Min

Intersection Summary

Cycle Length: 180 Actuated Cycle Length: 180

Offset: 21 (12%), Referenced to phase 2:SBTL and 6:NBTL, Start of Green

Natural Cycle: 90

Control Type: Actuated-Coordinated

Splits and Phases: 3: NW 37th Avenue/Douglas Road & Alhambra Plaza



# HCM Signalized Intersection Capacity Analysis 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	≯	-	$\mathbf{r}$	4	+	•	•	t	1	1	ţ	~
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	<u>۳</u>	र्च	1		4 Þ		- ሽ	<b>≜</b> ⊅		<u>۲</u>	<b>≜</b> ⊅	
Volume (vph)	267	34	114	11	25	11	163	1263	24	15	1053	114
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Lane Util. Factor	0.95	0.95	1.00		0.95		1.00	0.95		1.00	0.95	
Frt	1.00	1.00	0.85		0.96		1.00	1.00		1.00	0.99	
Flt Protected	0.95	0.96	1.00		0.99		0.95	1.00		0.95	1.00	
Satd. Flow (prot)	1681	1703	1583		3375		1770	3529		1770	3487	
Flt Permitted	0.95	0.96	1.00		0.99		0.17	1.00		0.21	1.00	
Satd. Flow (perm)	1681	1703	1583		3375		325	3529		395	3487	
Peak-hour factor, PHF	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Adj. Flow (vph)	270	34	115	11	25	11	165	1276	24	15	1064	115
RTOR Reduction (vph)	0	0	89	0	11	0	0	0	0	0	3	0
Lane Group Flow (vph)	151	153	26	0	36	0	165	1300	0	15	1176	0
Turn Type	Split	NA	pm+ov	Split	NA		pm+pt	NA		Perm	NA	
Protected Phases	3	3	1	4	4		1	6			2	
Permitted Phases			3				6			2		
Actuated Green, G (s)	21.2	21.2	41.4		6.1		137.2	137.2		114.0	114.0	
Effective Green, g (s)	21.2	21.2	41.4		6.1		137.2	137.2		114.0	114.0	
Actuated g/C Ratio	0.12	0.12	0.23		0.03		0.76	0.76		0.63	0.63	
Clearance Time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Vehicle Extension (s)	2.5	2.5	2.0		2.5		2.0	1.0		1.0	1.0	
Lane Grp Cap (vph)	197	200	364		114		409	2689		250	2208	
v/s Ratio Prot	0.09	c0.09	0.01		c0.01		0.05	c0.37			c0.34	
v/s Ratio Perm			0.01				0.26			0.04		
v/c Ratio	0.77	0.77	0.07		0.32		0.40	0.48		0.06	0.53	
Uniform Delay, d1	77.0	77.0	54.3		84.9		10.1	8.1		12.6	18.3	
Progression Factor	1.01	1.01	1.43		1.00		1.00	1.00		0.70	0.78	
Incremental Delay, d2	15.3	15.0	0.0		1.2		0.2	0.6		0.4	0.9	
Delay (s)	93.0	92.9	77.6		86.1		10.3	8.7		9.2	15.0	
Level of Service	F	F	Е		F		В	А		Α	В	
Approach Delay (s)		88.7			86.1			8.9			15.0	
Approach LOS		F			F			А			В	
Intersection Summary												
HCM 2000 Control Delay			23.1	Н	CM 2000	Level of	Service		С			_
HCM 2000 Volume to Capac	ity ratio		0.55									
Actuated Cycle Length (s)			180.0	S	um of los	t time (s)			18.5			
Intersection Capacity Utilizat	ion		70.3%	IC	U Level	of Service	Э		С			
Analysis Period (min)			15									
c Critical Lane Group												

	≯	$\mathbf{r}$	1	1	Ŧ
Lane Group	EBL	EBR	NBL	NBT	SBT
Lane Configurations	ሻ	1	ሻ	- <b>†</b> †	<b>≜</b> î≽
Volume (vph)	84	98	43	1490	1091
Turn Type	Prot	Perm	pm+pt	NA	NA
Protected Phases	8		1	6	2
Permitted Phases		8	6		
Detector Phase	8	8	1	6	2
Switch Phase					
Minimum Initial (s)	4.0	4.0	4.0	4.0	4.0
Minimum Split (s)	20.0	20.0	8.9	20.0	20.0
Total Split (s)	43.0	43.0	22.0	137.0	115.0
Total Split (%)	23.9%	23.9%	12.2%	76.1%	63.9%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.9	0.9	0.9	0.9	0.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.9	4.9	4.9	4.9	4.9
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Recall Mode	None	None	None	C-Min	C-Min
Intersection Summary					

Cycle Length: 180 Actuated Cycle Length: 180 Offset: 52 (29%), Referenced to phase 2:SBT and 6:NBTL, Start of Green Natural Cycle: 55 Control Type: Actuated-Coordinated

Splits and Phases: 4: NW 37th Avenue/Douglas Road & Minorca Avenue



Movement         EBL         EBR           Lane Configurations         Image: Configurations         Image: Configurations         Image: Configurations           Volume (veh/h)         84         98           Number         3         18           Initial Q (Qb), veh         0         0           Ped-Bike Adj(A_pbT)         1.00         1.00           Adj Sat Flow, veh/h         187         101           Adj Sat Flow, veh/h         87         101           Adj No. of Lanes         1         1           Peak Hour Factor         0.97         0.97           Percent Heavy Veh, %         2         2           Cap, veh/h         172         153           Arrive On Green         0.10         0.10           Sat Flow, veh/h         1774         1583           Grp Volume(v), veh/h         87         101           Grp Sat Flow(s), veh/h/ln         1774         1583           Q Serve(g_s), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Prop In Lane         1.00         1.00           Lane Grp Cap(c), veh/h         172 <th>•</th> <th>•</th> <th>1</th> <th>ţ</th> <th>~</th> <th></th>	•	•	1	ţ	~	
Volume (veh/h)       84       98         Number       3       18         Initial Q (Qb), veh       0       0         Ped-Bike Adj(A_pbT)       1.00       1.00         Adj Sat Flow, veh/h/ln       186.3       186.3         Adj Flow Rate, veh/h       87       101         Adj No. of Lanes       1       1         Peak Hour Factor       0.97       0.97         Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green       0.10       0.10         Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Cycle Q Clear(g_c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Upstream Filter(I)       1.00       1.00         Uniform Delay (d), s/veh       3.4.7       4.9         Incr Delay (d2),	NBL	NBL	NBT	SBT	SBR	
Number       3       18         Initial Q (Qb), veh       0       0         Ped-Bike Adj(A_pbT)       1.00       1.00         Adj Sat Flow, veh/h/ln       186.3       186.3         Adj Flow Rate, veh/h       87       101         Adj No. of Lanes       1       1         Peak Hour Factor       0.97       0.97         Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green       0.10       0.10         Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Cycle Q Clear(g_c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Upstream Filter(I)       1.00       1.00         Unofrom Delay (d), s/veh       3.4.4       34.9         Incr Delay (d2), s/veh       3.3       6.7         Indit	ሻ	٦	- 11	<b>≜</b> ⊅		
Initial Q (Qb), veh       0       0         Ped-Bike Adj(A_pbT)       1.00       1.00         Parking Bus, Adj       1.00       1.00         Adj Sat Flow, veh/h/ln       186.3       186.3         Adj Flow Rate, veh/h       87       101         Adj No. of Lanes       1       1         Peak Hour Factor       0.97       0.97         Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green       0.10       0.10         Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s), veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Prop In Lane       1.00       1.00         Lane Grp Cap(c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       1.00       1.00         Upstream Filter	43	43	1490	1091	27	
Ped-Bike Adj(A_pbT)       1.00       1.00         Parking Bus, Adj       1.00       1.00         Adj Sat Flow, veh/h/ln       186.3       186.3         Adj Flow Rate, veh/h       87       101         Adj No. of Lanes       1       1         Peak Hour Factor       0.97       0.97         Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green       0.10       0.10         Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Prop In Lane       1.00       1.00         Lane Grp Cap(c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Upstream Filter(I)       1.00       1.00         Uniform Delay (d2), s/veh       3.3       6.7         Indrip Delay(d3), s/veh       0.0       0.0	1	1	6	2	12	
Parking Bus, Adj       1.00       1.00         Adj Sat Flow, veh/h/ln       186.3       186.3         Adj Flow Rate, veh/h       87       101         Adj No. of Lanes       1       1         Peak Hour Factor       0.97       0.97         Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green       0.10       0.10         Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Cycle Q Clear(g_c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Uniform Delay (d), s/veh       3.4.4       34.9         Incr Delay (d2), s/veh       3.3       6.7         Initial Q Delay(d3), s/veh       0.0       0.0         Wile BackOfQ(50%), veh/ln       2.0       2.4         LnGrp Delay       0.5/veh       39.8 <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td></td>	0	0	0	0	0	
Parking Bus, Adj       1.00       1.00         Adj Sat Flow, veh/h/ln       186.3       186.3         Adj Flow Rate, veh/h       87       101         Adj No. of Lanes       1       1         Peak Hour Factor       0.97       0.97         Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green       0.10       0.10         Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Cycle Q Clear(g_c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Uniform Delay (d), s/veh       3.4.4       34.9         Incr Delay (d2), s/veh       3.3       6.7         Initial Q Delay(d3), s/veh       0.0       0.0         Wile BackOfQ(50%), veh/ln       2.0       2.4         LnGrp Delay       0.5/veh       39.8 <td>1.00</td> <td>1.00</td> <td></td> <td></td> <td>1.00</td> <td></td>	1.00	1.00			1.00	
Adj Flow Rate, veh/h87101Adj No. of Lanes11Peak Hour Factor $0.97$ Percent Heavy Veh, %2Cap, veh/h $172$ Arrive On Green $0.10$ $0.10$ $0.10$ Sat Flow, veh/h $1774$ 1583Grp Volume(v), veh/h $87$ Marrive On Green $0.10$ Sat Flow, veh/h $1774$ 1583Q Serve(g_s), s $3.7$ 4.9Cycle Q Clear(g_c), s $3.7$ 4.9Cycle Q Clear(g_c), s $3.7$ 4.9Cycle Q Clear(g_c), veh/h $172$ 153V/C Ratio(X) $0.51$ Avail Cap(c_a), veh/h $844$ 753HCM Platoon Ratio $1.00$ Upstream Filter(I) $1.00$ 1.00 $1.00$ Uniform Delay (d), s/veh $34.4$ 34.4 $34.9$ Incr Delay (d2), s/veh $3.3$ 6.7 $0.0$ Mitial Q Delay(d3), s/veh $0.0$ $0.0$ $0.0$ $%$ le BackOfQ(50%), veh/ln $2.0$ $2.4$ $2.4$ LnGrp Delay(d), s/veh $39.8$ Approach LOSDD $1$ Timer1 $1$ $2$ Assigned Phs1 $2$ $2$ Phs Duration (G+Y+Rc), s* $7.4$ $160.0$ $160.0$ Change Period (Y+Rc), s* $4.9000004.9000001$ Max Green Setting (Gmax), s* $17.1$ Max Q Clear Time (p_c), s<	1.00	1.00	1.00	1.00	1.00	
Adj No. of Lanes       1       1         Peak Hour Factor $0.97$ $0.97$ Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green $0.10$ $0.10$ Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s $3.7$ $4.9$ Cycle Q Clear(g_c), s $3.7$ $4.9$ Cycle Q Clear(g_c), veh/h $172$ $153$ V/C Ratio(X) $0.51$ $0.66$ Avail Cap(c_a), veh/h $844$ $753$ HCM Platoon Ratio $1.00$ $1.00$ Jpstream Filter(I) $1.00$ $1.00$ Jniform Delay (d), s/veh $34.4$ $34.9$ ncr Delay (d2), s/veh $3.3$ $6.7$ nitial Q Delay(d3),s/veh $0.0$ $0.0$ Wile BackOfQ(50%),veh/ln $2.0$ $2.4$ _nGrp Delay(d), s/veh $39.8$ Approach LOS         Approach LOS       D       D         Timer       1<	186.3	186.3	186.3	186.3	190.0	
Peak Hour Factor $0.97$ $0.97$ Percent Heavy Veh, %       2       2         Cap, veh/h       172       153         Arrive On Green $0.10$ $0.10$ Sat Flow, veh/h       1774       1583         Grp Volume(v), veh/h       87       101         Grp Sat Flow(s), veh/h/ln       1774       1583         Q Serve(g_s), s $3.7$ $4.9$ Cycle Q Clear(g_c), s $3.7$ $4.9$ Cycle Q Clear(g_c), veh/h       172       153         V/C Ratio(X) $0.51$ $0.66$ Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio $1.00$ $1.00$ Upstream Filter(I) $1.00$ $1.00$ Uniform Delay (d), s/veh $34.4$ $34.9$ Incr Delay (d2), s/veh $3.3$ $6.7$ Initial Q Delay(d3), s/veh $0.0$ $0.0$ Wile BackOfQ(50%), veh/ln $2.0$ $2.4$ LnGrp Delay(d), s/veh $37.6$ $41.6$ LnGrp LOS       D       D         Approach LOS       D       D         Timer       1       2	44	44	1536	1125	28	
Percent Heavy Veh, %         2         2           Cap, veh/h         172         153           Arrive On Green         0.10         0.10           Sat Flow, veh/h         1774         1583           Grp Volume(v), veh/h         87         101           Grp Sat Flow(s), veh/h         1774         1583           Q Serve(g_s), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Prop In Lane         1.00         1.00           Lane Grp Cap(c), veh/h         172         153           V/C Ratio(X)         0.51         0.66           Avail Cap(c_a), veh/h         844         753           HCM Platoon Ratio         1.00         1.00           Upstream Filter(I)         1.00         1.00           Uniform Delay (d), s/veh         34.4         34.9           Incr Delay (d2), s/veh         3.3         6.7           Initial Q Delay(d3),s/veh         0.0         0.0           %ile BackOfQ(50%),veh/ln         2.0         2.4           LnGrp Delay(d),s/veh         37.6         41.6           LnGrp LOS         D         D           Approach LOS         D         D	1	1	2	2	0	
Cap, veh/h172153Arrive On Green0.100.10Sat Flow, veh/h17741583Grp Volume(v), veh/h87101Grp Sat Flow(s),veh/h/ln17741583Q Serve(g_s), s3.74.9Cycle Q Clear(g_c), s3.74.9Prop In Lane1.001.00Lane Grp Cap(c), veh/h172153V/C Ratio(X)0.510.66Avail Cap(c_a), veh/h844753HCM Platoon Ratio1.001.00Jpstream Filter(I)1.001.00Jniform Delay (d), s/veh34.434.9ncr Delay (d2), s/veh3.36.7nitial Q Delay(d3),s/veh0.00.0%ile BackOfQ(50%),veh/ln2.02.4_nGrp Delay(d),s/veh37.641.6_nGrp LOSDDDDDApproach LOSDDChange Period (Y+Rc), s* 4.9000004.9000001Max Green Setting (Gmax), s * 17.1Max Q Clear Time (g_c+I1), s2.513.7Green Ext Time (p_c), s0.041.5ntersection Summary	0.97	0.97	0.97	0.97	0.97	
Arrive On Green0.100.10Sat Flow, veh/h17741583Grp Volume(v), veh/h87101Grp Sat Flow(s), veh/h/ln17741583Q Serve(g_s), s3.74.9Cycle Q Clear(g_c), s3.74.9Cycle Q Clear(g_c), s3.74.9Prop In Lane1.001.00.ane Grp Cap(c), veh/h172153//C Ratio(X)0.510.66Avail Cap(c_a), veh/h844753HCM Platoon Ratio1.001.00Jpstream Filter(I)1.001.00Juiform Delay (d), s/veh34.434.9ncr Delay (d2), s/veh3.36.7nitial Q Delay(d3), s/veh0.00.0%ile BackOfQ(50%), veh/ln2.02.4.nGrp Delay(d), s/veh37.641.6.nGrp LOSDDApproach LOSDDFimer12Assigned Phs12Phs Duration (G+Y+Rc), s* 4.9000004.9000001Max Green Setting (Gmax), s* 17.1* 110.1Max Q Clear Time (g_c+I1), s2.513.7Green Ext Time (p_c), s0.041.5ntersection Summary	2	2	2	2	2	
Arrive On Green0.100.10Sat Flow, veh/h17741583Grp Volume(v), veh/h87101Grp Sat Flow(s), veh/h/ln17741583Q Serve(g_s), s3.74.9Cycle Q Clear(g_c), s3.74.9Cycle Q Clear(g_c), s3.74.9Prop In Lane1.001.00_ane Grp Cap(c), veh/h172153//C Ratio(X)0.510.66Avail Cap(c_a), veh/h844753HCM Platoon Ratio1.001.00Jpstream Filter(I)1.001.00Juiform Delay (d), s/veh34.434.9ncr Delay (d2), s/veh3.36.7nitial Q Delay(d3), s/veh3.36.7nitial Q Delay(d3), s/veh3.36.7nitial Q Delay(d3), s/veh3.67.6Approach Vol, veh/h188Approach LOSDDFimer12Assigned Phs12Phs Duration (G+Y+Rc), s*7.4160.0Change Period (Y+Rc), s*4.9000004.9000001Max Green Setting (Gmax), s*17.1* 110.1Max Q Clear Time (g_c+I1), s2.513.7Green Ext Time (p_c), s0.041.5ntersection Summary	409	409	2764	2430	60	
Grp Volume(v), veh/h         87         101           Grp Sat Flow(s),veh/h/ln         1774         1583           Q Serve(g_s), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Prop In Lane         1.00         1.00           Lane Grp Cap(c), veh/h         172         153           V/C Ratio(X)         0.51         0.66           Avail Cap(c_a), veh/h         844         753           HCM Platoon Ratio         1.00         1.00           Upstream Filter(I)         1.00         1.00           Uniform Delay (d), s/veh         34.4         34.9           Incr Delay (d2), s/veh         3.3         6.7           Initial Q Delay(d3),s/veh         0.0         0.0           %ile BackOfQ(50%),veh/ln         2.0         2.4           LnGrp Delay(d),s/veh         37.6         41.6           LnGrp LOS         D         D           Approach LOS         D         D           Timer         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s*	0.06	0.06	1.00	0.69	0.69	
Grp Volume(v), veh/h         87         101           Grp Sat Flow(s),veh/h/ln         1774         1583           Q Serve(g_s), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Cycle Q Clear(g_c), s         3.7         4.9           Prop In Lane         1.00         1.00           _ane Grp Cap(c), veh/h         172         153           V/C Ratio(X)         0.51         0.66           Avail Cap(c_a), veh/h         844         753           HCM Platoon Ratio         1.00         1.00           Jpstream Filter(I)         1.00         1.00           Jiform Delay (d), s/veh         34.4         34.9           ncr Delay (d2), s/veh         3.3         6.7           nitial Q Delay(d3),s/veh         0.0         0.0           %ile BackOfQ(50%),veh/ln         2.0         2.4           _nGrp Delay(d),s/veh         37.6         41.6           _nGrp LOS         D         D           Approach Vol, veh/h         188           Approach LOS         D         D           Timer         1         2           Assigned Phs         1         2           Phs Duration (G	1774		3632	3622	88	
Grp Sat Flow(s),veh/h/ln       1774       1583         Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Prop In Lane       1.00       1.00         Lane Grp Cap(c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Upstream Filter(I)       1.00       1.00         Uniform Delay (d), s/veh       34.4       34.9         Incr Delay (d2), s/veh       3.3       6.7         Initial Q Delay(d3),s/veh       0.0       0.0         %ile BackOfQ(50%),veh/ln       2.0       2.4         LnGrp Delay(d),s/veh       37.6       41.6         LnGrp LOS       D       D         Approach Vol, veh/h       188         Approach LOS       D         Timer       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s* 4.9000004.9000001       Max Green Setting (Gmax), s* 17.1       * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7         Green Ext Time (p_c), s       0.0       41.5	44		1536	564	589	
Q Serve(g_s), s       3.7       4.9         Cycle Q Clear(g_c), s       3.7       4.9         Prop In Lane       1.00       1.00         _ane Grp Cap(c), veh/h       172       153         V/C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jniform Delay (d), s/veh       34.4       34.9         ncr Delay (d2), s/veh       3.3       6.7         nitial Q Delay(d3), s/veh       0.0       0.0         %ile BackOfQ(50%), veh/ln       2.0       2.4         _nGrp Delay(d), s/veh       37.6       41.6         _nGrp LOS       D       D         Approach Vol, veh/h       188         Approach LOS       D         Timer       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s* 4.9000004.9000001       Max Green Setting (Gmax), s * 17.1 * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7         Green Ext Time (p_c), s       0.0       41.5	1774		1770	1770	1847	
Cycle Q Clear(g_c), s       3.7       4.9         Prop In Lane       1.00       1.00         _ane Grp Cap(c), veh/h       172       153         //C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jniform Delay (d), s/veh       34.4       34.9         ncr Delay (d2), s/veh       3.3       6.7         nitial Q Delay(d3), s/veh       0.0       0.0         %ile BackOfQ(50%), veh/ln       2.0       2.4         _nGrp Delay(d), s/veh       37.6       41.6         _nGrp LOS       D       D       D         Approach Vol, veh/h       188       Approach Delay, s/veh       39.8         Approach LOS       D       D       D         Timer       1       2       Phs Duration (G+Y+Rc), s* 4.9000004.9000001       Max Green Setting (Gmax), s * 17.1 * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7       Green Ext Time (p_c), s       0.0       41.5	0.5		0.0	11.7	11.7	
Prop In Lane       1.00       1.00         Lane Grp Cap(c), veh/h       172       153         //C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jniform Delay (d), s/veh       34.4       34.9         ncr Delay (d2), s/veh       3.3       6.7         nitial Q Delay(d3), s/veh       0.0       0.0         %ile BackOfQ(50%), veh/ln       2.0       2.4         _nGrp Delay(d), s/veh       37.6       41.6         _nGrp LOS       D       D         Approach Vol, veh/h       188       Approach LOS         Approach LOS       D       D         Timer       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s* 7.4       160.0         Change Period (Y+Rc), s* 4.9000004.9000001       Max Green Setting (Gmax), s* 17.1       * 110.1         Max Q Clear Time (p_c), s       0.0       41.5       1.5         ntersection Summary       0.0       41.5	0.5		0.0	11.7	11.7	
Lane Grp Cap(c), veh/h       172       153         //C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jniform Delay (d), s/veh       34.4       34.9         ncr Delay (d2), s/veh       3.3       6.7         nitial Q Delay(d3),s/veh       0.0       0.0         %ile BackOfQ(50%),veh/ln       2.0       2.4         .nGrp Delay(d),s/veh       37.6       41.6         .nGrp LOS       D       D         Approach Vol, veh/h       188         Approach LOS       D         Fimer       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s* 4.9000004.9000001       Max Green Setting (Gmax), s* 17.1       * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7         Green Ext Time (p_c), s       0.0       41.5	1.00				0.05	
//C Ratio(X)       0.51       0.66         Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jniform Delay (d), s/veh       34.4       34.9         ncr Delay (d2), s/veh       3.3       6.7         nitial Q Delay(d3),s/veh       0.0       0.0         %ile BackOfQ(50%),veh/ln       2.0       2.4         _nGrp Delay(d),s/veh       37.6       41.6         _nGrp Delay(d),s/veh       37.6       41.6         _nGrp LOS       D       D         Approach Vol, veh/h       188         Approach LOS       D         Fimer       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s*       7.4       160.0         Change Period (Y+Rc), s*       4.9000004.9000001         Max Green Setting (Gmax), s*       17.1       * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7         Green Ext Time (p_c), s       0.0       41.5	409		2764	1218	1272	
Avail Cap(c_a), veh/h       844       753         HCM Platoon Ratio       1.00       1.00         Jpstream Filter(I)       1.00       1.00         Jniform Delay (d), s/veh       34.4       34.9         ncr Delay (d2), s/veh       3.3       6.7         nitial Q Delay(d3), s/veh       0.0       0.0         %ile BackOfQ(50%), veh/ln       2.0       2.4         _nGrp Delay(d), s/veh       37.6       41.6         _nGrp Delay(d), s/veh       37.6       41.6         _nGrp Delay(d), s/veh       37.6       41.6         _nGrp Delay(d), s/veh       39.8       Approach Vol, veh/h         Approach Delay, s/veh       39.8       Approach LOS         Approach LOS       D       D         Fimer       1       2         Assigned Phs       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s* 4.9000004.9000001       Max Green Setting (Gmax), s* 17.1       * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7         Green Ext Time (p_c), s       0.0       41.5         ntersection Summary       11.5	0.11		0.56	0.46	0.46	
HCM Platoon Ratio1.001.00Jpstream Filter(I)1.001.00Jpstream Filter(I)1.001.00Jniform Delay (d), s/veh34.434.9ncr Delay (d2), s/veh3.36.7nitial Q Delay(d3),s/veh0.00.0%ile BackOfQ(50%),veh/In2.02.4_nGrp Delay(d),s/veh37.641.6_nGrp LOSDDApproach Vol, veh/h188Approach Delay, s/veh39.8Approach LOSDTimer12Assigned Phs1Phs Duration (G+Y+Rc), s* 7.4160.0Change Period (Y+Rc), s* 4.9000004.9000001Max Green Setting (Gmax), s* 17.1* 110.1Max Q Clear Time (g_c+I1), s2.513.7Green Ext Time (p_c), s0.041.5ntersection Summary	732		5838	2433	2540	
Jpstream Filter(I)1.001.00Jniform Delay (d), s/veh $34.4$ $34.9$ ncr Delay (d2), s/veh $3.3$ $6.7$ nitial Q Delay(d3), s/veh $0.0$ $0.0$ %ile BackOfQ(50%), veh/ln $2.0$ $2.4$ _nGrp Delay(d), s/veh $37.6$ $41.6$ _nGrp Delay(d), s/veh $37.6$ $41.6$ _nGrp LOSDDApproach Vol, veh/h $188$ Approach Delay, s/veh $39.8$ Approach LOSDTimer12Assigned Phs12Phs Duration (G+Y+Rc), s $7.4$ 160.0Change Period (Y+Rc), s* 4.9000004.9000001Max Green Setting (Gmax), s * 17.1 * 110.1Max Q Clear Time (g_c+I1), s $2.5$ 13.7Green Ext Time (p_c), s $0.0$ 41.5ntersection Summary	2.00		2.00	1.00	1.00	
Uniform Delay (d), s/veh         34.4         34.9           Incr Delay (d2), s/veh         3.3         6.7           Initial Q Delay(d3),s/veh         0.0         0.0           %ile BackOfQ(50%),veh/In         2.0         2.4           LnGrp Delay(d),s/veh         37.6         41.6           LnGrp Delay(d),s/veh         37.6         41.6           LnGrp LOS         D         D           Approach Vol, veh/h         188           Approach Delay, s/veh         39.8           Approach LOS         D           Timer         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s * 17.1 * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5	0.85		0.85	1.00	1.00	
Incr Delay (d2), s/veh3.36.7Initial Q Delay(d3), s/veh0.00.0%ile BackOfQ(50%), veh/ln2.02.4LnGrp Delay(d), s/veh37.641.6LnGrp Delay(d), s/veh37.641.6LnGrp LOSDDApproach Vol, veh/h188Approach Delay, s/veh39.8Approach LOSDTimer12Assigned Phs1Phs Duration (G+Y+Rc), s7.4Change Period (Y+Rc), s* 4.9000004.9000001Max Green Setting (Gmax), s* 17.1* 110.1Max Q Clear Time (g_c+I1), s2.513.7Green Ext Time (p_c), s0.041.5Intersection Summary11	3.8		0.0	5.7	5.7	
Initial Q Delay(d3),s/veh         0.0         0.0           %ile BackOfQ(50%),veh/ln         2.0         2.4           LnGrp Delay(d),s/veh         37.6         41.6           LnGrp Delay(d),s/veh         37.6         41.6           LnGrp Delay(d),s/veh         37.6         41.6           Approach Vol, veh/h         188         Approach Delay, s/veh         39.8           Approach LOS         D         D         D           Timer         1         2         Assigned Phs         1         2           Assigned Phs         1         2         Phs Duration (G+Y+Rc), s*         7.4         160.0           Change Period (Y+Rc), s*         7.4         160.0         Change Period (Y+Rc), s*         1.2           Max Green Setting (Gmax), s*         17.1         * 110.1         Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5         Intersection Summary	0.1		0.7	1.3	1.2	
%ile BackOfQ(50%),veh/ln       2.0       2.4         LnGrp Delay(d),s/veh       37.6       41.6         LnGrp LOS       D       D         Approach Vol, veh/h       188         Approach Delay, s/veh       39.8         Approach LOS       D         Timer       1       2         Assigned Phs       1       2         Assigned Phs       1       2         Phs Duration (G+Y+Rc), s*       7.4       160.0         Change Period (Y+Rc), s*       4.9000004.9000001         Max Green Setting (Gmax), s*       17.1       * 110.1         Max Q Clear Time (g_c+I1), s       2.5       13.7         Green Ext Time (p_c), s       0.0       41.5         Intersection Summary       1.5       1.5	0.0		0.0	0.0	0.0	
LnGrp Delay(d),s/veh         37.6         41.6           LnGrp LOS         D         D           Approach Vol, veh/h         188           Approach Delay, s/veh         39.8           Approach LOS         D           Timer         1           Assigned Phs         1           Phs Duration (G+Y+Rc), s         7.4           Change Period (Y+Rc), s*         4.9000004.9000001           Max Green Setting (Gmax), s         *17.1           Max Q Clear Time (g_c+I1), s         2.5           Green Ext Time (p_c), s         0.0           Attriane         0.0	0.2		0.3	6.1	6.3	
LnGrp LOS         D         D           Approach Vol, veh/h         188           Approach Delay, s/veh         39.8           Approach LOS         D           Timer         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s * 17.1         * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5           Intersection Summary         1.5	3.9		0.7	7.0	6.9	
Approach Vol, veh/h         188           Approach Delay, s/veh         39.8           Approach LOS         D           Timer         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s * 17.1         * 110.1           Max Green Setting (Gmax), s         s.         13.7         Green Ext Time (p_c), s         0.0         41.5           ntersection Summary         160.0         10.0         10.0         10.0         10.0	A		A	A	A	
Approach Delay, s/veh         39.8           Approach LOS         D           Timer         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s * 17.1         * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5           ntersection Summary         1         1			1580	1153	71	
Approach LOS         D           Timer         1         2           Assigned Phs         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s * 17.1         * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5           ntersection Summary         1         1			0.8	6.9		
Timer         1         2           Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s         *17.1         * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7         Green Ext Time (p_c), s         0.0         41.5           ntersection Summary         1         1         1         1         1			A	0.0 A		
Assigned Phs         1         2           Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s* 17.1         * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5           ntersection Summary         1         1	•	•				
Phs Duration (G+Y+Rc), s         7.4         160.0           Change Period (Y+Rc), s* 4.9000004.9000001         Max Green Setting (Gmax), s* 17.1         * 110.1           Max Q Clear Time (g_c+I1), s         2.5         13.7           Green Ext Time (p_c), s         0.0         41.5           ntersection Summary         10.0         10.0	3	3	4	5	6	7 8
Change Period (Y+Rc), \$ 4.9000004.9000001         Max Green Setting (Gmax), s * 17.1 * 110.1         Max Q Clear Time (g_c+I1), s 2.5 13.7         Green Ext Time (p_c), s 0.0 41.5         ntersection Summary					6	8
Max Green Setting (Gmax), s * 17.1 * 110.1Max Q Clear Time (g_c+11), s 2.5 13.7Green Ext Time (p_c), s 0.0 41.5ntersection Summary				± 4 •	167.4	12.6
Max Q Clear Time (g_c+l1), s2.513.7Green Ext Time (p_c), s0.041.5ntersection Summary					000001	4.9
Green Ext Time (p_c), s 0.0 41.5 ntersection Summary				* 132	2.10001	38.1
ntersection Summary					2.0	6.9
					45.0	0.9
	5.7	5.7				
HCM 2010 LOS	А	А				
Notes						

\* HCM 2010 computational engine requires equal clearance times for the phases crossing the barrier.

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Background\_PM.syn

HCM 2010 TWSC 5: Alhambra Circle & Minorca Avenue

Int Delay, s/veh	7.8										
Movement	EBL	EBT	EBR		WBL	WBT	WBR	1	NBL	NBT	NBR
Vol, veh/h	2	36	87		92	64	18		67	90	79
Conflicting Peds, #/hr	2	0	4		4	0	2		12	0	4
Sign Control	Stop	Stop	Stop		Stop	Stop	Stop	F	ree	Free	Free
RT Channelized	-	-	None		-	-	None		-	-	None
Storage Length	-	-	-		-	-	-		-	-	-
Veh in Median Storage, #	-	0	-		-	0	-		-	0	-
Grade, %	-	0	-		-	0	-		-	0	-
Peak Hour Factor	98	98	98		98	98	98		98	98	98
Heavy Vehicles, %	2	2	2		2	2	2		2	2	2
Mvmt Flow	2	37	89		94	65	18		68	92	81
Major/Minor	Minor2				Minor1			Ма	jor1		
Conflicting Flow All	559	557	235		580	520	148		226	0	0
Stage 1	244	244	200		273	273	140		220	0	0
Stage 2	315	313			307	247			_		_
Critical Hdwy	7.12	6.52	6.22		7.12	6.52	6.22		4.12		_
Critical Hdwy Stg 1	6.12	5.52	0.22		6.12	5.52	0.22	•	T. 12	_	_
Critical Hdwy Stg 2	6.12	5.52	_		6.12	5.52	_		_	_	_
Follow-up Hdwy	3.518	4.018	3.318		3.518	4.018	3.318	2	218	_	_
Pot Cap-1 Maneuver	440	439	804		426	461	899		342	_	_
Stage 1	760	704	-00		733	684	-	I		_	_
Stage 2	696	657	-		703	702	-		_	-	-
Platoon blocked, %					100					-	-
Mov Cap-1 Maneuver	357	408	793		331	428	887	1	329	-	-
Mov Cap-2 Maneuver	357	408	-		331	428	-	•		-	-
Stage 1	714	696	-		689	643	_		-	-	-
Stage 2	572	617	-		581	694	-		-	-	-
Approach	EB				WB				NB		
Approach											
HCM Control Delay, s HCM LOS	12.4 B				21.8 C				2.2		
	D				Ũ						
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR			
Capacity (veh/h)	1329	-	-	614	389	1386	-	-			
HCM Lane V/C Ratio	0.051	-	-	0.208	0.456	0.007	-	-			
HCM Control Delay (s)	7.9	0	-	12.4	21.8	7.6	0	-			
HCM Lane LOS	Α	А	-	В	С	А	А	-			
HCM 95th %tile Q(veh)	0.2	-	-	0.8	2.3	0	-	-			

Intersection				
Int Delay, s/veh				
Movement	SBL	SBT	SBR	
Vol, veh/h	10	212	6	
Conflicting Peds, #/hr	4	0	12	
Sign Control	Free	Free	Free	
RT Channelized	-	-	None	
Storage Length	-	-	-	
Veh in Median Storage, #	-	0	-	
Grade, %	-	0	-	
Peak Hour Factor	98	98	98	
Heavy Vehicles, %	2	2	2	
Mvmt Flow	10	216	6	
Major/Minor	Major2			
Conflicting Flow All	176	0	0	
Stage 1	-	-	-	
Stage 2	-	-	-	
Critical Hdwy	4.12	-	-	
Critical Hdwy Stg 1	-	-	-	
Critical Hdwy Stg 2	-	-	-	
Follow-up Hdwy	2.218	-	-	
Pot Cap-1 Maneuver	1400	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Platoon blocked, %		-	-	
Mov Cap-1 Maneuver	1386	-	-	
Mov Cap-2 Maneuver	-	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Approach	SB			
HCM Control Delay, s	0.3			
HCM LOS				
Minor Lane/Major Mvmt				

Intersection	04.4								
Int Delay, s/veh	24.4								
Movement	NBL	NBT				SBT	SBR	NEL	NER
Vol, veh/h	0	1416				1132	237	74	23
Conflicting Peds, #/hr	0	0				0	5	0	0
Sign Control	Free	Free				Free	Free	Stop	Stop
RT Channelized	-	None				-	None	-	None
Storage Length	-	-				-	-	0	0
Veh in Median Storage, #	-	0				0	-	0	-
Grade, %	-	0				0	-	0	-
Peak Hour Factor	86	86				86	86	86	86
Heavy Vehicles, %	2	2				2	2	2	2
Mvmt Flow	0	1647				1316	276	86	27
Major/Minor	Major1					Major2		Minor2	
Conflicting Flow All	1592	0				-	0	2277	796
Stage 1	-	-				_	-	1454	
Stage 2	-	_				_	_	823	_
Critical Hdwy	4.14	_				_	_	6.84	6.94
Critical Hdwy Stg 1		_				_	_	5.84	0.04
Critical Hdwy Stg 2	-	_				_	_	5.84	_
Follow-up Hdwy	2.22	_				_	_	3.52	3.32
Pot Cap-1 Maneuver	408					_		~ 34	330
Stage 1	400					_		181	000
Stage 2	_	_				-	-	392	_
Platoon blocked, %						_		552	_
Mov Cap-1 Maneuver	408					_		~ 34	330
Mov Cap-2 Maneuver	400	_				-	-	~ 34	000
Stage 1	-	-				-	-	181	-
Stage 2	-	-				-	-	392	-
Stage 2	-	-				-	-	552	-
Approach	NB					SB		NE	
HCM Control Delay, s HCM LOS	0					0		\$ 724.5 F	
								·	
Minor Lane/Major Mvmt	NELn1	NELn2	NBL	NBT	SBT	SBR			
Capacity (veh/h)	34	330	408	-	-	-			
HCM Lane V/C Ratio	2.531	0.081	-	-	-	-			
HCM Control Delay (s)	\$ 944.4	16.9	0	-	-	-			
HCM Lane LOS	F	С	A	-	-	-			
HCM 95th %tile Q(veh)	9.8	0.3	0	-	-	-			
Notes ~: Volume exceeds capacity	\$: Delay excee	ade 300e	±. Co~	putation		ned *·	All major w	olume in platoon	
· · · · · · · · · · · · · · · · · · ·	φ. Delay excee	505 2005	T. CON	iputation	NUL Dell	neu .			

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Background\_PM.syn

**Future Total Conditions** 

Intersection												
Intersection Delay, s/veh	17.8											
Intersection LOS	С											
Movement	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR
Vol, veh/h	0	1	4	3	0	75	199	124	0	76	36	114
Peak Hour Factor	0.92	0.88	0.88	0.88	0.92	0.88	0.88	0.88	0.92	0.88	0.88	0.88
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	1	5	3	0	85	226	141	0	86	41	130
Number of Lanes	0	0	1	1	0	0	1	0	0	0	1	0
Approach		EB				WB				NB		
Opposing Approach		WB				EB				SB		
Opposing Lanes		1				2				2		
Conflicting Approach Left		SB				NB				EB		
Conflicting Lanes Left		2				1				2		
Conflicting Approach Right		NB				SB				WB		
Conflicting Lanes Right		1				2				1		
HCM Control Delay		9.5				23.6				14		
HCMLOS		А				С				В		
Lane		NBLn1	EBLn1	EDI p2	WBLn1	SBLn1	SBLn2					
Lanc				EDLIIZ	VVDLIII	SDLIII	ODLIIZ					
		34%	20%	0%	19%	83%	0%					
Vol Left, % Vol Thru, %												
Vol Left, %		34%	20%	0%	19%	83%	0%					
Vol Left, % Vol Thru, %		34% 16%	20% 80%	0% 0%	19% 50%	83% 17%	0% 0%					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane		34% 16% 50% Stop 226	20% 80% 0%	0% 0% 100%	19% 50% 31%	83% 17% 0% Stop 127	0% 0% 100%					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol		34% 16% 50% Stop 226 36	20% 80% 0% Stop	0% 0% 100% Stop	19% 50% 31% Stop 398 199	83% 17% 0% Stop	0% 0% 100% Stop 85 0					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane		34% 16% 50% Stop 226 36 114	20% 80% 0% Stop 5 4 0	0% 0% 100% Stop 3 0 3	19% 50% 31% Stop 398 199 124	83% 17% 0% Stop 127 22 0	0% 0% 100% Stop 85 0 85					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol		34% 16% 50% Stop 226 36 114 76	20% 80% 0% Stop 5 4 0 1	0% 0% 100% Stop 3 0 3 0	19% 50% 31% Stop 398 199 124 75	83% 17% 0% Stop 127 22 0 105	0% 0% 100% Stop 85 0 85 0					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate		34% 16% 50% Stop 226 36 114 76 257	20% 80% 0% Stop 5 4 0 1 6	0% 0% 100% Stop 3 0 3 0 3 0 3	19% 50% 31% Stop 398 199 124 75 452	83% 17% 0% Stop 127 22 0 105 144	0% 0% 100% Stop 85 0 85 0 97					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp		34% 16% 50% Stop 226 36 114 76 257 6	20% 80% 0% Stop 5 4 0 1 6 7	0% 0% 100% Stop 3 0 3 0 3 7	19% 50% 31% Stop 398 199 124 75 452 6	83% 17% 0% Stop 127 22 0 105 144 7	0% 0% 100% Stop 85 0 85 0 97 7					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X)		34% 16% 50% Stop 226 36 114 76 257 6 0.44	20% 80% 0% Stop 5 4 0 1 6 7 0.011	0% 0% 100% Stop 3 0 3 0 3 7 0.006	19% 50% 31% Stop 398 199 124 75 452 6 0.737	83% 17% 0% Stop 127 22 0 105 144 7 0.274	0% 0% 100% Stop 85 0 85 0 97 7 0.153					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd)		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942	0% 0% 100% Stop 3 0 3 7 0.006 6.124	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845	0% 0% 100% Stop 85 0 85 0 97 7 0.153 5.713					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd) Convergence, Y/N		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168 Yes	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942 Yes	0% 0% 100% Stop 3 0 3 0 3 7 0.006 6.124 Yes	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869 Yes	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845 Yes	0% 0% 100% Stop 85 0 85 0 97 7 0.153 5.713 Yes					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd) Convergence, Y/N Cap		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168 Yes 583	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942 Yes 513	0% 0% 100% Stop 3 0 3 0 3 7 0.006 6.124 Yes 581	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869 Yes 615	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845 Yes 524	0% 0% 100% Stop 85 0 85 0 97 7 0.153 5.713 Yes 625					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd) Convergence, Y/N Cap Service Time		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168 Yes 583 4.221	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942 Yes 513 4.718	0% 0% 100% Stop 3 0 3 7 0.006 6.124 Yes 581 3.899	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869 Yes 615 3.909	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845 Yes 524 4.602	0% 0% 100% Stop 85 0 85 0 97 7 0.153 5.713 5.713 Yes 625 3.47					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd) Convergence, Y/N Cap Service Time HCM Lane V/C Ratio		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168 Yes 583 4.221 0.441	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942 Yes 513 4.718 0.012	0% 0% 100% Stop 3 0 3 0 3 7 0.006 6.124 Yes 581 3.899 0.005	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869 Yes 615 3.909 0.735	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845 Yes 524 4.602 0.275	0% 0% 100% Stop 85 0 85 0 97 7 0.153 5.713 Yes 625 3.47 0.155					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd) Convergence, Y/N Cap Service Time HCM Lane V/C Ratio HCM Control Delay		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168 Yes 583 4.221 0.441 14	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942 Yes 513 4.718 0.012 9.8	0% 0% 100% Stop 3 0 3 7 0.006 6.124 Yes 581 3.899 0.005 8.9	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869 Yes 615 3.909 0.735 23.6	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845 Yes 524 4.602 0.275 12.2	0% 0% 100% 85 0 85 0 97 7 0.153 5.713 Yes 625 3.47 0.155 9.5					
Vol Left, % Vol Thru, % Vol Right, % Sign Control Traffic Vol by Lane LT Vol Through Vol RT Vol Lane Flow Rate Geometry Grp Degree of Util (X) Departure Headway (Hd) Convergence, Y/N Cap Service Time HCM Lane V/C Ratio		34% 16% 50% Stop 226 36 114 76 257 6 0.44 6.168 Yes 583 4.221 0.441	20% 80% 0% Stop 5 4 0 1 6 7 0.011 6.942 Yes 513 4.718 0.012	0% 0% 100% Stop 3 0 3 0 3 7 0.006 6.124 Yes 581 3.899 0.005	19% 50% 31% Stop 398 199 124 75 452 6 0.737 5.869 Yes 615 3.909 0.735	83% 17% 0% Stop 127 22 0 105 144 7 0.274 6.845 Yes 524 4.602 0.275	0% 0% 100% Stop 85 0 85 0 97 7 0.153 5.713 Yes 625 3.47 0.155					

Intersection Intersection Delay, s/veh Intersection LOS					
Movement	SBU	SBL	SBT	SBR	
Vol, veh/h	0	105	22	85	
Peak Hour Factor	0.92	0.88	0.88	0.88	
Heavy Vehicles, %	2	2	2	2	
Mvmt Flow	0	119	25	97	
Number of Lanes	0	0	1	1	
Approach		SB			
Opposing Approach		NB			
Opposing Lanes		1			
Conflicting Approach Left		WB			
Conflicting Lanes Left		1			
Conflicting Approach Right		EB			
Conflicting Lanes Right		2			
HCM Control Delay		11.1			
HCM LOS		В			
Lane					

# Timings 2: Galiano Street & Alhambra Plaza

	⊴	٦	-	4	-	1	1	1	ŧ
Lane Group	EBU	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		3	<b>≜</b> ⊅		ፋጉ		4	ሻ	4
Volume (vph)	16	111	347	27	223	20	75	15	64
Turn Type	custom	pm+pt	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		1	5		2		4		8
Permitted Phases	1	5		2		4		8	
Detector Phase	1	1	5	2	2	4	4	8	8
Switch Phase									
Minimum Initial (s)	5.0	5.0	15.0	15.0	15.0	7.0	7.0	7.0	7.0
Minimum Split (s)	8.0	8.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Total Split (s)	8.0	8.0	58.0	50.0	50.0	32.0	32.0	32.0	32.0
Total Split (%)	8.9%	8.9%	64.4%	55.6%	55.6%	35.6%	35.6%	35.6%	35.6%
Yellow Time (s)	3.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.3	0.3	0.3	1.8	1.8	1.8	1.8
Lost Time Adjust (s)		0.0	0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		3.0	4.3		4.3		5.8	5.8	5.8
Lead/Lag	Lead	Lead		Lag	Lag				
Lead-Lag Optimize?	Yes	Yes		Yes	Yes				
Recall Mode	None	None	C-Min	C-Min	C-Min	None	None	None	None
Intersection Summarv									

Intersection Summary

Cycle Length: 90 Actuated Cycle Length: 90

Offset: 0 (0%), Referenced to phase 2:WBTL and 5:EBTL, Start of Green Natural Cycle: 50

Control Type: Actuated-Coordinated

Splits and Phases:	2: Galiano Street & Alhambra Plaza
--------------------	------------------------------------

	≪ <b>†</b> ø4
8 s 50 s	32 s
<u></u> ∞5 (R)	
58 s	32 s

# HCM Signalized Intersection Capacity Analysis 2: Galiano Street & Alhambra Plaza

	4	۶	-	*	4	Ļ	•	≺	Ť	1	1	Ŧ
Movement	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations		2	<b>≜</b> †≱			4 Þ			- <b>4</b> >		<u>۳</u>	ef 👘
Volume (vph)	16	111	347	10	27	223	59	20	75	43	15	64
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Lane Util. Factor		1.00	0.95			0.95			1.00		1.00	1.00
Frt		1.00	1.00			0.97			0.96		1.00	0.97
Flt Protected		0.95	1.00			1.00			0.99		0.95	1.00
Satd. Flow (prot)		1770	3525			3423			1772		1770	1804
Flt Permitted		0.52	1.00			0.90			0.94		0.52	1.00
Satd. Flow (perm)		963	3525			3098			1670		964	1804
Peak-hour factor, PHF	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Adj. Flow (vph)	18	125	390	11	30	251	66	22	84	48	17	72
RTOR Reduction (vph)	0	0	1	0	0	16	0	0	23	0	0	13
Lane Group Flow (vph)	0	143	400	0	0	331	0	0	131	0	17	78
Turn Type	custom	pm+pt	NA		Perm	NA		Perm	NA		Perm	NA
Protected Phases		· 1	5			2			4			8
Permitted Phases	1	5			2			4			8	
Actuated Green, G (s)		68.0	68.0			58.5			11.9		11.9	11.9
Effective Green, g (s)		68.0	68.0			58.5			11.9		11.9	11.9
Actuated g/C Ratio		0.76	0.76			0.65			0.13		0.13	0.13
Clearance Time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Vehicle Extension (s)		2.0	1.0			1.0			2.5		2.5	2.5
Lane Grp Cap (vph)		785	2663			2013			220		127	238
v/s Ratio Prot		c0.01	0.11									0.04
v/s Ratio Perm		c0.12				0.11			c0.08		0.02	
v/c Ratio		0.18	0.15			0.16			0.60		0.13	0.33
Uniform Delay, d1		3.0	3.0			6.2			36.8		34.5	35.4
Progression Factor		1.00	1.00			0.96			1.00		1.00	1.00
Incremental Delay, d2		0.0	0.1			0.2			3.6		0.4	0.6
Delay (s)		3.0	3.2			6.1			40.4		34.8	36.0
Level of Service		A	Α			Α			D		С	D
Approach Delay (s)			3.1			6.1			40.4			35.8
Approach LOS			A			Α			D			D
Intersection Summary												
HCM 2000 Control Delay			12.1	Н	CM 2000	Level of	Service		В			
HCM 2000 Volume to Capac	ity ratio		0.25									
Actuated Cycle Length (s)			90.0	S	um of los	t time (s)			13.1			
Intersection Capacity Utilizat	ion		51.3%	IC	U Level	of Service	9		Α			
Analysis Period (min)			15									

c Critical Lane Group

Movement	SBR
Lane	
Volume (vph)	17
Ideal Flow (vphpl) Total Lost time (s)	1900
Lane Util. Factor	
Frt	
Flt Protected	
Satd. Flow (prot)	
Flt Permitted	
Satd. Flow (perm)	0.00
Peak-hour factor, PHF	0.89 19
Adj. Flow (vph) RTOR Reduction (vph)	0
Lane Group Flow (vph)	0
Turn Type	-
Protected Phases	
Permitted Phases	
Actuated Green, G (s)	
Effective Green, g (s)	
Actuated g/C Ratio Clearance Time (s)	
Vehicle Extension (s)	
Lane Grp Cap (vph)	
v/s Ratio Prot	
v/s Ratio Perm	
v/c Ratio	
Uniform Delay, d1	
Progression Factor	
Incremental Delay, d2	
Delay (s) Level of Service	
Approach Delay (s)	
Approach LOS	
Intersection Summary	
mensection ourninally	

#### Timings 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	≯	-	$\rightarrow$	-	1	1	1	↓
Lane Group	EBL	EBT	EBR	WBT	NBL	NBT	SBL	SBT
Lane Configurations	ሻ	र्भ	1	4 î b	ሻ	<b>∱</b> ⊅	ሻ	<b>≜</b> ⊅
Volume (vph)	237	8	151	22	157	901	14	1185
Turn Type	Split	NA	pm+ov	NA	pm+pt	NA	Perm	NA
Protected Phases	3	3	1	4	1	6		2
Permitted Phases			3		6		2	
Detector Phase	3	3	1	4	1	6	2	2
Switch Phase								
Minimum Initial (s)	7.0	7.0	5.0	7.0	5.0	7.0	7.0	7.0
Minimum Split (s)	22.8	22.8	8.0	25.0	8.0	32.9	32.9	32.9
Total Split (s)	41.0	41.0	8.0	29.0	8.0	110.0	102.0	102.0
Total Split (%)	22.8%	22.8%	4.4%	16.1%	4.4%	61.1%	56.7%	56.7%
Yellow Time (s)	4.0	4.0	3.0	4.0	3.0	4.0	4.0	4.0
All-Red Time (s)	0.8	0.8	0.0	0.8	0.0	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.8	4.8	3.0	4.8	3.0	5.9	5.9	5.9
Lead/Lag	Lead	Lead	Lead	Lag	Lead		Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Recall Mode	None	None	None	None	None	C-Min	C-Min	C-Min

Intersection Summary Cycle Length: 180 Actuated Cycle Length: 180 Offset: 21 (12%), Referenced to phase 2:SBTL and 6:NBTL, Start of Green Natural Cycle: 100 Control Type: Actuated-Coordinated

Splits and Phases: 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

<b>↓ ↓</b> <i>ø</i> 2 (R)	<b>Å</b> ø3		<b>▼</b> ø4	
8 s 102 s	41 s	1	29 s	
≪ <b>1</b>				
110 s				
## HCM Signalized Intersection Capacity Analysis 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	۶	-	*	4	+	•	•	1	1	1	ţ	~
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	्रभ	1		ፋት		<u>۲</u>	<b>∱</b> ⊅		<u>۲</u>	<b>≜</b> ⊅	
Volume (vph)	237	8	151	14	22	32	157	901	7	14	1185	96
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Lane Util. Factor	0.95	0.95	1.00		0.95		1.00	0.95		1.00	0.95	
Frt	1.00	1.00	0.85		0.93		1.00	1.00		1.00	0.99	
Flt Protected	0.95	0.96	1.00		0.99		0.95	1.00		0.95	1.00	
Satd. Flow (prot)	1681	1690	1583		3258		1770	3535		1770	3499	
Flt Permitted	0.95	0.96	1.00		0.99		0.14	1.00		0.30	1.00	
Satd. Flow (perm)	1681	1690	1583		3258		256	3535		563	3499	
Peak-hour factor, PHF	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
Adj. Flow (vph)	247	8	157	15	23	33	164	939	7	15	1234	100
RTOR Reduction (vph)	0	0	123	0	32	0	0	0	0	0	3	0
Lane Group Flow (vph)	128	127	34	0	39	0	164	946	0	15	1331	0
Turn Type	Split	NA	pm+ov	Split	NA		pm+pt	NA		Perm	NA	
Protected Phases	3	3	. 1	. 4	4			6			2	
Permitted Phases			3				6			2		
Actuated Green, G (s)	18.6	18.6	38.9		7.8		138.1	138.1		114.8	114.8	
Effective Green, g (s)	18.6	18.6	38.9		7.8		138.1	138.1		114.8	114.8	
Actuated g/C Ratio	0.10	0.10	0.22		0.04		0.77	0.77		0.64	0.64	
Clearance Time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Vehicle Extension (s)	2.5	2.5	2.0		2.5		2.0	1.0		1.0	1.0	
Lane Grp Cap (vph)	173	174	342		141		367	2712		359	2231	
v/s Ratio Prot	c0.08	0.08	0.01		c0.01		c0.05	0.27			c0.38	
v/s Ratio Perm			0.01				0.29			0.03		
v/c Ratio	0.74	0.73	0.10		0.28		0.45	0.35		0.04	0.60	
Uniform Delay, d1	78.4	78.3	56.5		83.4		12.7	6.7		12.1	19.1	
Progression Factor	0.99	0.99	1.62		1.00		1.00	1.00		0.82	0.91	
Incremental Delay, d2	14.4	13.3	0.0		0.8		0.3	0.4		0.2	1.1	
Delay (s)	91.9	90.7	91.4		84.2		13.0	7.0		10.1	18.4	
Level of Service	F	F	F		F		В	Α		В	В	
Approach Delay (s)		91.3			84.2			7.9			18.3	
Approach LOS		F			F			Α			В	
Intersection Summary												
HCM 2000 Control Delay			26.2	Н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capa	city ratio		0.58									
Actuated Cycle Length (s)			180.0	S	um of los	t time (s)			18.5			
Intersection Capacity Utiliza	tion		70.2%	IC	U Level	of Service	е		С			
Analysis Period (min)			15									
c Critical Lane Group												

	≯	$\mathbf{r}$	•	1	Ļ
Lane Group	EBL	EBR	NBL	NBT	SBT
Lane Configurations	۲	1	1	<u></u>	<b>∱</b> î≽
Volume (vph)	17	48	93	1078	1242
Turn Type	Prot	Perm	pm+pt	NA	NA
Protected Phases	8		1	6	2
Permitted Phases		8	6		
Detector Phase	8	8	1	6	2
Switch Phase					
Minimum Initial (s)	9.0	9.0	5.0	16.0	16.0
Minimum Split (s)	20.0	20.0	9.9	20.9	20.9
Total Split (s)	53.0	53.0	22.0	127.0	105.0
Total Split (%)	29.4%	29.4%	12.2%	70.6%	58.3%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.9	0.9	0.9	0.9	0.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.9	4.9	4.9	4.9	4.9
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Recall Mode	None	None	None	C-Min	C-Min
Intersection Summary					

Cycle Length: 180 Actuated Cycle Length: 180 Offset: 27 (15%), Referenced to phase 2:SBT and 6:NBTL, Start of Green Natural Cycle: 60 Control Type: Actuated-Coordinated

Splits and Phases: 4: NW 37th Avenue/Douglas Road & Minorca Avenue



Movement         EBL         EBR         NBL         NBT         SBT         SBR           Lane Configurations         1         2         1         1         1         0		≯	$\mathbf{r}$	1	1	Ŧ	1	
Volume (veh/h)         17         48         93         1078         1242         52           Number         3         18         1         6         2         12           Initial Q (Ob), veh         0         0         0         0         0           Pad-Bike Adji(A_pbT)         1.00         1.00         1.00         1.00           Parking Bus, Adj         1.00         1.00         1.00         1.00           Adj Row Rate, veh/h         17         49         95         1100         1267         53           Adj No, of Lanes         1         1         2         2         0         Peak Hour Factor         0.98         141 <th>Movement</th> <th>EBL</th> <th>EBR</th> <th>NBL</th> <th>NBT</th> <th>SBT</th> <th>SBR</th> <th></th>	Movement	EBL	EBR	NBL	NBT	SBT	SBR	
Number         3         16         1         6         2         12           Initial Q (Qb), veh         0 </td <td>Lane Configurations</td> <td><u>۳</u></td> <td>1</td> <td><u>۲</u></td> <td>- <b>††</b></td> <td>- <b>†</b>1&gt;</td> <td></td> <td></td>	Lane Configurations	<u>۳</u>	1	<u>۲</u>	- <b>††</b>	- <b>†</b> 1>		
Initial Q(bL), veh       0       0       0       0       0       0       0       0         Ped-Bike Adj(A, pbT)       1.00       1.00       1.00       1.00       1.00       1.00       1.00         Adj Staf Flow, veh/h1n       186.3       186.3       186.3       186.3       190.0         Adj No. of Lanes       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2       1	Volume (veh/h)	17	48	93	1078	1242	52	
Ped-Bike Adj(A, pbT)       1.00       1.00       1.00       1.00       1.00         Parking Bus, Adj       1.00       1.00       1.00       1.00       1.00       1.00         Adj Sta Flow, veh/hln       17       49       95       1100       1267       53         Adj No. of Lanes       1       1       1       2       0       Peak Hour Factor       0.98	Number	3	18	1	6	2	12	
Parking Bus, Agi       1.00       1.00       1.00       1.00       1.00       1.00         Adj Sat Flow, velvh/nin       186.3       186.3       186.3       186.3       190.0         Adj Flow Rate, velvh       1       14       9       95       1100       1267       53         Adj No of Lanes       1       1       1       2       2       0       Peak Hour Factor       0.98       0.98       0.98       0.98       Peaker Hour Factor       0.98       0.98       0.98       0.98       0.98       Percent Heavy Veh, %       2	Initial Q (Qb), veh	0	0	0	0	0	0	
Adj Sař Flow, veľvíh/ln       186.3       186.3       186.3       186.3       190.0         Adj No of Lanes       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98         Cap, veh/h       161       144       387       2744       2250       94         Arrive On Green       0.09       0.09       0.12       1.00       0.65       0.65         Sat Flow, veh/h       1774       1583       1774       3632       3555       145         Grp Volume(v), veh/h       1774       1583       1774       1700       1837         Q Serve(g_s), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       0.00       0.08       Lane Grp Cap(c), veh/h       111       1.00       14.8       14.8       V/CR atic(X)       0.11       0.24       0.20       0.00       0.08         Lane Grp Cap(c), veh/h       161       144       387       2744       1150       1194       V/C Ratic(X)       0.11       0.24       0.20       0.00       0.00       0.00       0.00       0.00       0.00	Ped-Bike Adj(A_pbT)	1.00	1.00	1.00			1.00	
Adj Riow Rate, veh/h       17       49       95       1100       1267       53         Adj No of Lanes       1       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2       2       2       2       2       2       2       2         Cap, veh/h       161       144       387       2744       2250       94         Arrive On Green       0.09       0.012       10.0       6.65       6.5         Sat Flow, veh/h       1774       1583       1774       3632       3555       145         Grp Volume(v), veh/h       1774       1583       1774       1770       1770       1837       Q       Q       2       2       2       2         Q Serve(g.s), s       0.6       2.1       1.1       0.0       14.8       14.8       2       2       1100       14.8       14.8         Open Lane       0.0       100       100       0.00       0.08       Lane Gro Cap(c), veh/h       161       144       387       2744       150       1194       2512       HC	Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	
Adj No. of Lanes       1       1       1       2       2       0         Peak Hour Factor       0.98       0.98       0.98       0.98       0.98       0.98       0.98         Percent Heavy Veh, %       2 </td <td>Adj Sat Flow, veh/h/ln</td> <td>186.3</td> <td>186.3</td> <td>186.3</td> <td>186.3</td> <td>186.3</td> <td>190.0</td> <td></td>	Adj Sat Flow, veh/h/ln	186.3	186.3	186.3	186.3	186.3	190.0	
Peak Hour Factor         0.98         0.98         0.98         0.98         0.98         0.98           Percent Heavy Veh, %         2	Adj Flow Rate, veh/h	17	49	95	1100	1267	53	
Percent Heavy Veh, %       2	Adj No. of Lanes	1	1	1	2	2	0	
Cap, veh/h       161       144       387       2744       2250       94         Arrive On Green       0.09       0.90       0.12       1.00       0.65       0.65         Sat Flow, veh/h       1774       1563       1774       3632       3555       145         Grp Valume(V), veh/h       1774       1563       1774       1770       1837         Q Serve(g_s), s       0.6       2.1       1.1       0.0       14.8       14.8         Cycle Q Clear(g_c), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       0.08       1194       V/C Ratio(X)       0.11       0.34       0.25       0.40       0.66         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56       4/44       1100       1.00	Peak Hour Factor	0.98	0.98	0.98	0.98	0.98	0.98	
Arrive On Green         0.09         0.09         0.12         1.00         0.65         0.65           Sat Flow, veh/h         1774         1583         1774         3555         145           Grp Volume(v), veh/h         17         49         95         1100         647         673           Grp Sat Flow(s), veh/h/ln         1774         1583         1774         1770         1837           Q Serve(g_s), s         0.6         2.1         1.1         0.0         14.8         14.8           Cycle Q Clear(g_c), s         0.6         2.1         1.1         0.0         1937           Q Serve(g_s), s         0.6         2.1         1.1         0.0         14.8         14.8           Cycle Q Clear(g_c), veh/h         161         144         387         2744         1150         1194           V/C Ratio(X)         0.11         0.34         0.25         0.40         0.56         0.56           Avail Cap(c_a), veh/h         1165         1040         698         5902         2419         2512           HCM Platoon Ratio         1.00         1.00         2.00         2.00         1.00         1.00           Upstream Filter(I)         1.00	Percent Heavy Veh, %	2	2	2	2	2	2	
Arrive On Green         0.09         0.09         0.12         1.00         0.65         0.65           Sat Flow, veh/h         1774         1583         1774         3555         145           Grp Volume(v), veh/h         17         49         95         1100         647         673           Grp Sat Flow(s), veh/h1n         1774         1583         1774         1770         1837           Q Serve(g_s), s         0.6         2.1         1.1         0.0         14.8         14.8           Cycle Q Clear(g_c), s         0.6         2.1         1.1         0.0         14.8         14.8           Prop In Lane         1.00         1.00         1.00         0.08         Lane Grp Cap(c), veh/h         161         144         387         2744         1150         1194           V/C Ratio(X)         0.11         0.34         0.25         0.40         0.56         0.56           Avail Cap(c_a), veh/h         1165         1040         698         5902         2419         2512         HCM Platoon Ratio         1.00         1.00         1.00         1.00         1.00         1.00         1.00         1.00         1.00         1.00         1.00         1.00         1.00	-	161	144	387	2744	2250	94	
Grp Volume(v), veh/h       17       49       95       1100       647       673         Grp Sat Flow(s), veh/h/ln       1774       1583       1774       1770       1837         Q Serve(g_s), s       0.6       2.1       1.1       0.0       14.8       14.8         Cycle Q Clear(g_c), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       0.08       111       0.44       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(C_a), veh/h       1161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(C_a), veh/h       1161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(C_a), veh/h       110       1.00       1.00       2.00       1.00       1.00         Uniform Delay (d), s/veh       30.6       31.2       4.8       0.0       1.01       1.		0.09	0.09	0.12	1.00	0.65	0.65	
Grp Volume(v), veh/h       17       49       95       1100       647       673         Grp Sat Flow(s), veh/h/ln       1774       1583       1774       1770       1837         Q Serve(g_s), s       0.6       2.1       1.1       0.0       14.8       14.8         Cycle Q Clear(g_c), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       1.00       0.08       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(C_a), veh/h       1161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(C_a), veh/h       1161       144       387       2744       1150       1194         U/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(C_a), veh/h       1105       1.00       1.00       1.00       1.00       1.00       1.00         Uniform Delay (d), si/veh       30.6       31.2       4.8       0.0       0.0       1.00	Sat Flow, veh/h		1583	1774	3632	3555	145	
Grp Sat Flow(s), veh/h/ln       1774       1583       1774       1770       1837         Q Serve(g, s), s       0.6       2.1       1.1       0.0       14.8       14.8         Cycle Q Clear(g_c), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       0.08       111       0.34       0.25       0.40       0.56       0.56         Avail Cap(c_a), veh/h       161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1161       104       088       5902       2419       2512         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       30.6       31.2       4.8       0.0       7.1       7.1         Incr Delay (d), s/veh       31.0       0.5       0.2       7.6       7.9       1.6         LnGrp Delay (d), s/veh       32.6       0.8       9.0 <td></td> <td></td> <td></td> <td></td> <td>1100</td> <td></td> <td></td> <td></td>					1100			
Q Serve(g_s), s       0.6       2.1       1.1       0.0       14.8       14.8         Cycle Q Clear(g_c), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       1.00       0.08       0.08         Lane Grp Cap(c), veh/h       161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1165       1040       698       5902       2419       2512         HCM Platoon Ratio       1.00       1.00       2.00       1.00       1.00       Upstream Filter(I)       1.00       1.00       9.92         Initral Q Delay(d), s/veh       0.4       2.0       0.2       0.4       2.0       1.9         Initial Q Delay(d), s/veh       0.6       1.0       0.0       0.0       0.0       0.0         More pole S       C       C       A       A       A       A         Approach Vol, veh/h       66       1195       1320       Approach Vol, veh/h       66       8         Phs Duration (G+Y+Rc), s       9.2       159.3       168.5 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Cycle Q Clear(g_c), s       0.6       2.1       1.1       0.0       14.8       14.8         Prop In Lane       1.00       1.00       0.08         Lane Grp Cap(c), veh/h       161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1165       1040       698       5902       2419       2512         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       0.4       2.0       0.2       1.4       2.0       1.9         Initial Q Delay(d3), s/veh       0.4       2.0       0.2       7.6       7.9         LnGrp Delay (d), s/veh       31.0       0.5       0.2       7.6       7.9         LnGrp Delay (d), s/veh       32.6       0.8       9.0       Approach LOS       C       A       A         Approach LOS       C       A       A       A       A       A       A         Assigned Phs       1 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Prop In Lane       1.00       1.00       1.00       0.08         Lane Grp Cap(c), veh/h       161       144       387       2744       1150       1194         V/C Ratio(X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1165       1040       698       5902       2419       2512         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.22       0.4       2.0       1.9         Initial Q Delay(d), s/veh       0.4       2.0       0.2       7.6       7.9         LnGrp Delay(d), s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp Delay(d), s/veh       32.6       0.8       9.0       1.2       6       8       8								
Lane Grp Cap(c), veh/h 161 144 387 2744 1150 1194 V/C Ratio(X) 0.11 0.34 0.25 0.40 0.56 0.56 Avail Cap(c_a), veh/h 1165 1040 698 5902 2419 2512 HCM Platoon Ratio 1.00 1.00 2.00 2.00 1.00 1.00 Upstream Filter(I) 1.00 1.00 0.92 0.92 1.00 1.00 Uniform Delay (d), s/veh 30.6 31.2 4.8 0.0 7.1 7.1 Incr Delay (d2), s/veh 0.4 2.0 0.2 0.4 2.0 1.9 Initial Q Delay(d3), s/veh 0.0 0.0 0.0 0.0 0.0 0.0 %ile BackOfQ(50%), veh/ln 0.3 1.0 0.5 0.2 7.6 7.9 LnGrp Delay(d), s/veh 31.0 33.2 5.1 0.4 9.1 9.0 LnGrp Delay(d), s/veh 32.6 0.8 9.0 Approach Dol, veh/h 66 1195 1320 Approach LOS C C A A A A A Arbon A A Approach LOS C A A A A A Arbon A A Assigned Phs 1 2 6 8 Assigned Phs 1 2 6 8 Phs Duration (G+Y+Rc), \$ 9.2 159.3 168.5 11.5 Change Period (Y+Rc), \$ 4.9000001 4.9 Max Green Setting (Gmax), \$ * 17.1 * 100.1 * 122.1 48.1 Max Q Clear Time (p_c), \$ 0.1 30.8 33.0 0.3 Intersection Summary HCM 2010 Ctrl Delay 5.8 HCM 2010 LOS A						-		
V/C Ratio (X)       0.11       0.34       0.25       0.40       0.56       0.56         Avail Cap(c_a), veh/h       1165       1040       698       5902       2419       2512         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       30.6       31.2       4.8       0.0       7.1       7.1         Incr Delay (d2), s/veh       0.4       2.0       0.2       0.4       2.0       1.9         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0       0.0         Kile BackOfQ(50%), veh/ln       0.3       1.0       0.5       0.2       7.6       7.9         LnGrp Delay(d), s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp Delay, s/veh       32.6       0.8       9.0         Approach LOS       C       A       A       A         Pis Duration (G+Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       *100.1       * 122.1       48.1     <	•				2744	1150		
Avail Cap(c_a), veh/h       1165       1040       698       5902       2419       2512         HCM Platoon Ratio       1.00       1.00       2.00       2.00       1.00       1.00         Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       30.6       31.2       4.8       0.0       7.1       7.1         Incr Delay (d2), s/veh       0.4       2.0       0.2       0.4       2.0       1.9         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0         Mile BackOfQ(50%), veh/ln       0.3       1.0       0.5       0.2       7.6       7.9         LnGrp Delay(d), s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp Delay(d), s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp Delay(d), s/veh       32.6       0.8       9.0       9.0       4.0       4.0       4.0         Approach LOS       C       A       A       A       A       4.0       4.0         Max Green Seting (Grax), s * 17.1 * 100.1       * 122.1       48.1       4.0								
HCM Plation Ratio 1.00 1.00 2.00 2.00 1.00 1.00 1.00 Upstream Filter(I) 1.00 1.00 0.92 0.92 1.00 1.00 Uniform Delay (d), s/veh 30.6 31.2 4.8 0.0 7.1 7.1 Incr Delay (d), s/veh 0.4 2.0 0.2 0.4 2.0 1.9 Initial Q Delay(d3), s/veh 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.	. ,							
Upstream Filter(I)       1.00       1.00       0.92       0.92       1.00       1.00         Uniform Delay (d), s/veh       30.6       31.2       4.8       0.0       7.1       7.1         Incr Delay (d2), s/veh       0.4       2.0       0.2       0.4       2.0       1.9         Initial Q Delay(d3), s/veh       0.0       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%), veh/ln       0.3       1.0       0.5       0.2       7.6       7.9         LnGrp Delay(d), s/veh       31.0       0.3       2.5.1       0.4       9.1       9.0         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       66       1195       1320         Approach LOS       C       A       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       Phosucation (G+Y+Rc), s       9.2       159.3       168.5       11.5         Change Period (Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9       Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1								
Uniform Delay (d), s/veh $30.6$ $31.2$ $4.8$ $0.0$ $7.1$ $7.1$ Incr Delay (d2), s/veh $0.4$ $2.0$ $0.2$ $0.4$ $2.0$ $1.9$ Initial Q Delay(d3), s/veh $0.0$ $0.0$ $0.0$ $0.0$ $0.0$ %ile BackOfQ(50%), veh/ln $0.3$ $1.0$ $0.5$ $0.2$ $7.6$ $7.9$ LnGrp Delay(d), s/veh $31.0$ $33.2$ $5.1$ $0.4$ $9.1$ $9.0$ LnGrp DOS       C       C       A       A       A         Approach Vol, veh/h $66$ $1195$ $1320$ Approach LOS       C       A       A         Timer       1       2 $3$ $4$ $5$ $6$ $7$ Assigned Phs       1       2 $6$ $8$ $7$ $8$ Assigned Phs       1       2 $6$ $8$ $7$ $8$ Assigned Phs       1       2 $6$ $8$ $7$ $8$ Max Green Setting (Gmax), s $17.1$ $*100.1$ $*122.1$ $48.1$ <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Incr Delay (d2), s/veh       0.4       2.0       0.2       0.4       2.0       1.9         Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.3       1.0       0.5       0.2       7.6       7.9         LnGrp Delay(d),s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp DOS       C       C       A       A       A         Approach Vol, veh/h       66       1195       1320         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Initial Q Delay(d3),s/veh       0.0       0.0       0.0       0.0       0.0         %ile BackOfQ(50%),veh/ln       0.3       1.0       0.5       0.2       7.6       7.9         LnGrp Delay(d),s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       66       1195       1320         Approach Delay, s/veh       32.6       0.8       9.0         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       9       9       9       9       9       9       9       9       9       9       9       9       9       15       15       15       15       168.5       11.5       5       11.5       5       168.5       11.5       168.5       11.5       14       9       9       33.0       0.3       168.5       11.5       14       100.1       * 122.1       48.1       48.1       48.1       48.1       48.1	• • • •							
%ile BackOfQ(50%),veh/ln       0.3       1.0       0.5       0.2       7.6       7.9         LnGrp Delay(d),s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp LOS       C       C       A       A       A         Approach Vol, veh/h       66       1195       1320         Approach Delay, s/veh       32.6       0.8       9.0         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       9       9       9       168.5       11.5       15       15       15       168.5       11.5       15       168.5       11.5       15       168.5       11.5       16       122.1       48.1       48.1       49       48       49       49       49       49       49       49       49       49 <td>• • •</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	• • •							
LnGrp Delay(d),s/veh       31.0       33.2       5.1       0.4       9.1       9.0         LnGrp LOS       C       C       A       A       A       A         Approach Vol, veh/h       66       1195       1320         Approach Delay, s/veh       32.6       0.8       9.0         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       8       9       <	• • •							
LnGrp LOS         C         C         A         A         A         A           Approach Vol, veh/h         66         1195         1320         Approach Delay, s/veh         32.6         0.8         9.0           Approach LOS         C         A         A         A         A           Timer         1         2         3         4         5         6         7         8           Assigned Phs         1         2         6         8         8         9 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
Approach Vol, veh/h       66       1195       1320         Approach Delay, s/veh       32.6       0.8       9.0         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       9								
Approach Delay, s/veh       32.6       0.8       9.0         Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8       9.0         Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.2       159.3       168.5       11.5         Change Period (Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.1       16.8       2.0       4.1         Green Ext Time (p_c), s       0.1       30.8       33.0       0.3         Intersection Summary       5.8       A       A								
Approach LOS       C       A       A         Timer       1       2       3       4       5       6       7       8         Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.2       159.3       168.5       11.5         Change Period (Y+Rc), s* 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.1       16.8       2.0       4.1         Green Ext Time (p_c), s       0.1       30.8       33.0       0.3         Intersection Summary       5.8            HCM 2010 LOS       A	••							
Timer         1         2         3         4         5         6         7         8           Assigned Phs         1         2         6         8           Phs Duration (G+Y+Rc), s         9.2         159.3         168.5         11.5           Change Period (Y+Rc), s*         4.9000004.9000001         * 4.9000001         4.9           Max Green Setting (Gmax), s * 17.1         * 100.1         * 122.1         48.1           Max Q Clear Time (g_c+I1), s         3.1         16.8         2.0         4.1           Green Ext Time (p_c), s         0.1         30.8         33.0         0.3           Intersection Summary         5.8         HCM 2010 Ctrl Delay         5.8           HCM 2010 LOS         A         A         A								
Assigned Phs       1       2       6       8         Phs Duration (G+Y+Rc), s       9.2       159.3       168.5       11.5         Change Period (Y+Rc), s* 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.1       16.8       2.0       4.1         Green Ext Time (p_c), s       0.1       30.8       33.0       0.3         Intersection Summary       5.8            HCM 2010 LOS       A			0	n			~	7 0
Phs Duration (G+Y+Rc), s       9.2       159.3       168.5       11.5         Change Period (Y+Rc), s' 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s       * 17.1       * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.1       16.8       2.0       4.1         Green Ext Time (p_c), s       0.1       30.8       33.0       0.3         Intersection Summary       5.8         HCM 2010 LOS       A				3	4	5		
Change Period (Y+Rc), \$ 4.9000004.9000001       * 4.9000001       4.9         Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.1       16.8       2.0       4.1         Green Ext Time (p_c), s       0.1       30.8       33.0       0.3         Intersection Summary       5.8       4       4         HCM 2010 LOS       A       4       4		1	_				•	
Max Green Setting (Gmax), s * 17.1 * 100.1       * 122.1       48.1         Max Q Clear Time (g_c+I1), s       3.1       16.8       2.0       4.1         Green Ext Time (p_c), s       0.1       30.8       33.0       0.3         Intersection Summary         HCM 2010 Ctrl Delay       5.8         HCM 2010 LOS       A						* 1 0		
Max Q Clear Time (g_c+l1), s         3.1         16.8         2.0         4.1           Green Ext Time (p_c), s         0.1         30.8         33.0         0.3           Intersection Summary         HCM 2010 Ctrl Delay         5.8         4           HCM 2010 LOS         A         A         4								
Green Ext Time (p_c), s         0.1         30.8         33.0         0.3           Intersection Summary         HCM 2010 Ctrl Delay         5.8         4           HCM 2010 LOS         A         A         A								
Intersection Summary HCM 2010 Ctrl Delay 5.8 HCM 2010 LOS A								
HCM 2010 Ctrl Delay         5.8           HCM 2010 LOS         A	Green Ext Time (p_c), s	0.1	30.8				33.0	0.3
HCM 2010 Ctrl Delay         5.8           HCM 2010 LOS         A	Intersection Summary							
HCM 2010 LOS A				5.8				
	,							
Notes								

\* HCM 2010 computational engine requires equal clearance times for the phases crossing the barrier.

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Total\_AM.syn

HCM 2010 TWSC 5: Alhambra Circle & Minorca Avenue

Intersection Int Delay, s/veh	6.6										
Int Boldy, or ton	0.0										
Movement	EBL	EBT	EBR		WBL	WBT	WBR		NBL	NBT	NBR
Vol, veh/h	6	40	106		44	44	12		81	43	118
Conflicting Peds, #/hr	4	0	1		1	0	4		8	0	12
Sign Control	Stop	Stop	Stop		Stop	Stop	Stop		Free	Free	Free
RT Channelized	-	-	None		-	-	None		-	-	None
Storage Length	-	-	-		-	-	-		-	-	-
Veh in Median Storage, #	-	0	-		-	0	-		-	0	-
Grade, %	-	0	-		-	0	-		-	0	-
Peak Hour Factor	93	93	93		93	93	93		93	93	93
Heavy Vehicles, %	2	2	2		2	2	2		2	2	2
Mvmt Flow	6	43	114		47	47	13		87	46	127
Major/Minor	Minor2				Minor1				Major1		
Conflicting Flow All	661	694	314		709	645	126		316	0	0
Stage 1	343	343	-		288	288	-		-	-	-
Stage 2	318	351	-		421	357	-		-	-	-
Critical Hdwy	7.12	6.52	6.22		7.12	6.52	6.22		4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-		6.12	5.52	-		-	-	-
Critical Hdwy Stg 2	6.12	5.52	-		6.12	5.52	-		-	-	-
Follow-up Hdwy	3.518	4.018	3.318		3.518	4.018	3.318		2.218	-	-
Pot Cap-1 Maneuver	376	366	726		349	391	924		1244	-	-
Stage 1	672	637	-		720	674	-		-	-	-
Stage 2	693	632	-		610	628	-		-	-	-
Platoon blocked, %										-	-
Mov Cap-1 Maneuver	304	329	716		242	351	912		1232	-	-
Mov Cap-2 Maneuver	304	329	-		242	351	-		-	-	-
Stage 1	617	623	-		661	619	-		-	-	-
Stage 2	575	580	-		464	615	-		-	-	-
Approach	EB				WB				NB		
HCM Control Delay, s	14.9				22.5				2.7		
HCM LOS	В				22.5 C				2.1		
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR			
Capacity (veh/h)	1232	-	-	525	312	1385	-	-			
HCM Lane V/C Ratio	0.071	-	-	0.311	0.345	0.015	-	-			
HCM Control Delay (s)	8.1	0	-	14.9	22.5	7.6	0	-			
HCM Lane LOS	A	А	-	В	С	А	А	-			
HCM 95th %tile Q(veh)	0.2	-	-	1.3	1.5	0	-	-			

Intersection				
Int Delay, s/veh				
Movement	SBL	SBT	SBR	
Vol, veh/h	19	264	26	
Conflicting Peds, #/hr	12	0	8	
Sign Control	Free	Free	Free	
RT Channelized	-	-	None	
Storage Length	-	-	-	
Veh in Median Storage, #	-	0	-	
Grade, %	-	0	-	
Peak Hour Factor	93	93	93	
Heavy Vehicles, %	2	2	2	
Mvmt Flow	20	284	28	
-			-	
Major/Minor	Major2			
Conflicting Flow All	177	0	0	
Stage 1	-	-	-	
Stage 2	-	-	-	
Critical Hdwy	4.12	-	-	
Critical Hdwy Stg 1	-	-	-	
Critical Hdwy Stg 2	-	-	-	
Follow-up Hdwy	2.218	-	-	
Pot Cap-1 Maneuver	1399	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Platoon blocked, %		-	-	
Mov Cap-1 Maneuver	1385	-	-	
Mov Cap-2 Maneuver	-	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Approach	SB			
HCM Control Delay, s	0.5			
	0.0			

Minor Lane/Major Mvmt

Int Delay, s/veh	22.1								
Movement	NBL	NBT				SBT	SBR	NEL	NEF
Vol, veh/h	0	1183				1255	276	67	<u>ואבר</u> 1
Conflicting Peds, #/hr	0	0				1255	4	0	(
Sign Control	Free	Free				Free	Free	Stop	Stop
RT Channelized	-	None				-	None	Stop	None
Storage Length	-	NULLE					NONE	0	
Veh in Median Storage, #	-	0				-0	-	0	(
Grade, %	-	0				0	-	0	
Peak Hour Factor	86	86				86	86	86	86
Heavy Vehicles, %	2	2				2	2	2	
Mvmt Flow	2	1376				1459	321	78	1
	0	1370				1459	321	78	1
Major/Minor	Major1					Major2		Minor2	
Conflicting Flow All	1780	0				-	0	2308	890
Stage 1	-	-				-	_	1620	
Stage 2	-	-				-	-	688	
Critical Hdwy	4.14	-				-	-	6.84	6.94
Critical Hdwy Stg 1	-	-				-	-	5.84	
Critical Hdwy Stg 2	-	-				-	-	5.84	
Follow-up Hdwy	2.22	-				-	-	3.52	3.32
Pot Cap-1 Maneuver	345	-				-	-	~ 32	286
Stage 1	-	-				-	-	147	-
Stage 2	-	-				-	-	460	
Platoon blocked, %		-				-	-		
Mov Cap-1 Maneuver	345	-				-	-	~ 32	286
Mov Cap-2 Maneuver	-	-				-	-	~ 32	
Stage 1	-	-				-	_	147	
Stage 2	-	-				-	_	460	
otago L								100	
Approach	NB					SB		NE	
HCM Control Delay, s	0					0		\$ 752.8	
HCM LOS								F	
Minor Lano/Major Mymt	NELn1	NELn2	NBL	NBT	SBT	SBR			
Minor Lane/Major Mvmt					SDI				
Capacity (veh/h)	32	286	345	-	-	-			
HCM Lane V/C Ratio	2.435	0.061	-	-	-	-			
HCM Control Delay (s)	\$ 917.2	18.4	0	-	-	-			
HCM Lane LOS	F	С	A	-	-	-			
HCM 95th %tile Q(veh)	9	0.2	0	-	-	-			
Notes ~: Volume exceeds capacity	\$: Delay excee			putation					

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Total\_AM.syn

HCM 2010 TWSC 7: Project Driveway & Minorca Avenue

Int Delay, s/veh	1.6							
Movement		EBT	EBR		WBL	WBT	NBL	NBR
Vol, veh/h		112	9		4	107	28	13
Conflicting Peds, #/hr		0	0		0	0	0	0
Sign Control		Free	Free		Free	Free	Stop	Stop
RT Channelized		-	None		-	None	-	None
Storage Length		-	-		-	-	0	-
Veh in Median Storage, #		0	-		-	0	0	-
Grade, %		0	-		-	0	0	-
Peak Hour Factor		92	92		92	92	92	92
Heavy Vehicles, %		2	2		2	2	2	2
Mvmt Flow		122	10		4	116	30	14
Major/Minor		Major1		Ν	1ajor2		Minor1	
Conflicting Flow All		0	0		132	0	252	127
Stage 1		-	-		-	-	127	121
Stage 2		_	_		_	_	125	-
Critical Hdwy		_	_		4.12	_	6.42	6.22
Critical Hdwy Stg 1		_	_		-	_	5.42	0.22
Critical Hdwy Stg 2		_	_		_	_	5.42	_
Follow-up Hdwy		_	_		2.218	_	3.518	3.318
Pot Cap-1 Maneuver		_	_		1453	_	737	923
Stage 1		_	_			_	899	520
Stage 2		_	_		_	_	901	_
Platoon blocked, %		_	_			_	501	
Mov Cap-1 Maneuver			_		1453		735	923
Mov Cap-2 Maneuver		-	-		1400	-	735	520
Stage 1		-	-		-	-	899	
-		-	-		-	-	898	-
Stage 2		-	-		-	-	090	-
Approach		EB			WB		NB	
HCM Control Delay, s		0			0.3		9.9	
HCM LOS							A	
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT			
Capacity (veh/h)	786	-	-	1453	-			
HCM Lane V/C Ratio	0.057	-	-	0.003	-			
HCM Control Delay (s)	9.9	-	-	7.5	0			
HCM Lane LOS	А	-	-	А	А			
HCM 95th %tile Q(veh)	0.2	-	-	0	-			

Movement         WBL         WBR         NBL         NBR         SEL         SER           Lane Configurations         I		4	*_	٦	1	$\searrow$	$\mathbf{i}$		
Volume (veh/h)         0         2         321         1         0         160           Sign Control         Stop         Free         Stop         0%         0%         0%         0%         0%         0%         Peak Hour Factor         0.89         0.80         0.89         0.80         0.99         0.90         0.90         0.91         0.10         0.10         0.10         0.10         0.10         0.10         1.1         C2, stage 2 conf vol         vC2, stage 2 conf vol <td>Movement</td> <td>WBL</td> <td>WBR</td> <td>NBL</td> <td>NBR</td> <td>SEL</td> <td>SER</td> <td></td> <td></td>	Movement	WBL	WBR	NBL	NBR	SEL	SER		
Sign Control         Stop         Free         Free         Free           Grade         0%         0%         0%         0%         0%         0%           Peak Hour Factor         0.89         0.89         0.89         0.89         0.89         0.89           Hourly flow rate (vph)         0         2         361         1         0         180           Pedestrians         Lane Width (ft)         Walking Speed (ft/s)         Persent Blockage         None         None           Walking Speed (ft/s)         Persent Blockage         None         None         None         None           Median type         None         None         None         None         None         None           VC1, stage 1 conf vol         170         pX, platon unblocked         0.99         0.99         vC, conflicting volume         451         361         362           VC1, stage 1 conf vol         VC1, unblocked vol         444         353         354         100         100         100         100         Grade         102         103         1193         1193         1193         1193         1193         1193         1193         1193         1193         1193         1193         1193	Lane Configurations		1						
Grade         0%         0%         0%         0%           Peak Hour Factor         0.89         0.89         0.89         0.89         0.89           Houry flow rate (vph)         0         2         361         1         0         180           Pedestrians         Lane Width (ft)         Walking Speed (ft/s)         Percent Blockage         Right tum flare (veh)         10         180           Median type         None         None         None         None         Median type         VC, conflicting volume         451         361         362           VC1, stage 1 conf vol         VC2, conflicting volume         451         361         362         VC1, stage 1 conf vol         VC2, stage 2 conf vol         VC4, unblocked vol         444         353         354         S54         S55         S54         S55         S54         S55         S54         S55         S54         S55         S54         S55         S55         S56         S65         S65         S65         S65         S65         S65         S65			2		1		160		
Peak Hour Factor         0.89         0.89         0.89         0.89         0.89         0.89           Houry flow rate (vph)         0         2         361         1         0         180           Pedestrians         Lane Width (ft)         Waking Speed (ft/s)         Percent Blockage         Right tum flare (veh)         None         None         None           Median storage veh)         Upstream signal (ft)         170         pX, platoon unblocked         0.99         0.99         vC2, conflicting volume         451         361         362           VC1, stage 1 conf vol         VC2, stage 2 conf vol         VC2, stage 2 conf vol         VC2, stage (s)         1100         100           CK capacity (veh/h)         535         3.3         2.2         2         0         9           Direction, Lane #         WB 1         NB 1         SE 1         SE 2         VClume Kight         2         1         0         1193         Direction, Lane #         WB 1         NB 1									
Hourly flow rate (vph)       0       2       361       1       0       180         Pedestrians       Lane Width (ft)       Walking Speed (ft/s)       Percent Blockage       None       None       None         Percent Blockage       Right turn flare (veh)       Median type       None       None       None         Median type       None       None       None       None       None         VC, conflicting volume       451       361       362       VC, conflicting volume       451         VC, conflicting volume       451       361       362       VC, stage 1 conf vol       VC, unblocked vol       444       353       354         VC, stage 2 conf vol       VCu, unblocked vol       444       353       354       C. Stage (s)       If (s)       100       CM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2       Volume Erit       0       0       0       0       0         Volume Right       2       1       0       0       0       0       0       0       0       0       0       0       0       0       0       0       0       0       0       0	Grade								
Pedestrians         Lane Width (ft)         Walking Speed (ft/s)         Percent Blockage         Right turn flare (veh)         Median type       None         Median type       None         Walking Speed (ft/s)         Percent Blockage         Right turn flare (veh)         Median type       None         Median type       0.99         Upstream signal (ft)       170         pX, platoon unblocked       0.99         vC, conflicting volume       451         VC1, stage 1 conf vol       VC2, stage 2 conf vol         vC2, stage 2 conf vol       VCU, unblocked vol         VC2, stage 2 conf vol       VCU, unblocked vol         VC2, stage (s)       6.8         tf (s)       5.3         go queue free %       100         100       100         Molume Left       0         0       0         Volume Total       2         363       1700         Volume to Capacity       0.0         Volume to Capacity       0.0         Control Delay (s)       10.7       0.0         Control Delay (s)       10.7       0.0         Lane LOS <td></td> <td>0.89</td> <td></td> <td></td> <td>0.89</td> <td>0.89</td> <td></td> <td></td> <td></td>		0.89			0.89	0.89			
Lane Width (ft)         Walking Speed (ft/s)         Percent Blockage         Right tum flare (veh)         Median storage veh)         Upstream signal (ft)       170         PX, platoon unblocked       0.99       0.99         vC1, stage 1 conf vol       vC2, stage 2 conf vol         vC2, stage 2 conf vol       vC4, unblocked vol         vC1, stage 1 conf vol       vC4, unblocked vol         vC2, stage 2 conf vol       vC4, unblocked vol         vC2, stage 2 conf vol       vC4, unblocked vol         vC4, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1         tC, stage 2 conf vol       vC4       vC4       vC4         vC3 unblocked vol       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Right       2       1       0       0         cSH       639       1700       1700       Volume tot Capacity       0.0         Volume Loft       0       0 <td< td=""><td></td><td>0</td><td>2</td><td>361</td><td>1</td><td>0</td><td>180</td><td></td><td></td></td<>		0	2	361	1	0	180		
Walking Speed (ft/s)       Percent Blockage         Right tum flare (veh)       None       None         Median type       None       None         Upstream signal (ft)       170         pX, platoon unblocked       0.99       0.99         vC, conflicting volume       451       361         vC2, stage 1 conf vol       vC2, stage 2 conf vol       vC2, stage 2 conf vol         vC2, stage 2 conf vol       vC1, stage 1 conf vol       vC2, stage 2 conf vol         vC2, stage (s)       6.8       6.9       4.1         tC, single (s)       6.8       6.9       4.1         tC, single (s)       100       100       100         cd capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Right       2       1       0       0       0         CSH       639       1700       1700       1700       1700         Volume Right       2       1       0       0       0       0         Control Delay (s)       10.7       0.0       0.0       0.0       1.1									
Percent Blockage         None         None         None           Right turn flare (veh)         Median type         None         None           Wedian type (veh)         170         PX. platoon unblocked         0.99         0.99           Upstream signal (ft)         170         PX. platoon unblocked         0.99         0.99           vC, conflicting volume         451         361         362         VC. conflicting volume         451           vC2, stage 1 conf vol         VC2, stage 2 conf vol           vC1, stage (s)         6.8         6.9         4.1         C. 2 stage (s)         E         E           tF (s)         3.5         3.3         2.2         P0 queue free %         100         100         100           cd capacity (veh/h)         539         639         1193         E         E         E           Volume Total         2         362         90         90         O         O         SE 1         SE 2           Volume Total         2         362         90         90         O         O         SE 1         SE 2           Volume Eot         0         0         0 <td>( )</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	( )								
Right turn flare (veh)       None       None       None         Median type       None       None       None         Median storage veh)       Upstream signal (ft)       170         DyX, platoon unblocked       0.99       0.99       0.99         vC, conflicting volume       451       361       362         vC1, stage 1 conf vol       vC2, stage 2 conf vol       vC4, unblocked vol       444         VC3, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1         tC, 2 stage 2 conf vol       vC4, unblocked vol       444         VC3, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1         tC, 2 stage (s)       tf (s)       3.5       3.3       2.2         p0 queue free %       100       100       100       control 0.0       control 0.0         Direction, Lane #       WB 1       NB 1       SE 1       SE 2       Volume Control       2       362       90       90         Volume Total       2       362       90       90       00       0       control S       Control Non       0.0       0.0       Control 0.0 <td>• • • • •</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>	• • • • •								
Median type         None         None           Median storage veh)         170           Upstream signal (ft)         170           pX, platoon unblocked         0.99         0.99           vC, conflicting volume         451         361         362           vC1, stage 1 conf vol         vC2, stage 2 conf vol         vC2, stage 2 conf vol         vC2, unblocked vol         444           VC1, sigle (s)         6.8         6.9         4.1         tC, 2 stage (s)         tF (s)           tF (s)         3.5         3.3         2.2         p0 queue free %         100         100           p0 queue free %         100         100         100         100         conflocting volume 4.11           Direction, Lane #         WB 1         NB 1         SE 1         SE 2         Volume Total         2         362         90         90           Volume Edt         0 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>									
Median storage veh)       170         Upstream signal (ft)       170         pX, platoon unblocked       0.99       0.99         vC, conflicting volume       451       361       362         vC1, stage 1 conf vol       vC2, stage 2 conf vol       vC2, stage 2 conf vol       vC2, stage 2 conf vol         vC2, stage 2 conf vol       444       353       354         vC, single (s)       6.8       6.9       4.1         tC, 2 stage (s)       tf (s)       3.5       3.3       2.2         p0 queue free %       100       100       100       100         cM capacity (veh/h)       539       639       1193       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Right       2       1       0       0         cSH       639       1700       1700       Volume K         Volume Right       2       1       0       0         Control Delay (s)       10.7       0.0       0.0       0.0         Control Delay (s)       10.7       0.0       0.0       0.0         Lane LOS       B	,								
Upstream signal (ft)         170           pX, platoon unblocked         0.99         0.99         0.99           vCi, conflicting volume         451         361         362           vC1, stage 1 conf vol         vC2, stage 2 conf vol         vC4, unblocked vol         444         353         354           tC, single (s)         6.8         6.9         4.1         tC, 2 stage (s)         tF (s)         3.5         3.3         2.2           p0 queue free %         100         100         100         constant         co				None		None			
pX, platoon unblocked       0.99       0.99       0.99         vC, conflicting volume       451       361       362         vC1, stage 1 conf vol       vC2, stage 2 conf vol       vC4, unblocked vol       444         vC2, stage 2 conf vol       vC4, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1       100       100         tC, 2 stage (s)       tF (s)       3.5       3.3       2.2       22         p0 queue free %       100       100       100       100         cM capacity (veh/h)       539       639       1193       193         Direction, Lane #       WB 1       NB 1       SE 2       Volume Total       2       362       90       90         Volume Total       2       362       90       90       0 </td <td></td> <td></td> <td></td> <td>470</td> <td></td> <td></td> <td></td> <td></td> <td></td>				470					
vC, conflicting volume       451       361       362         vC1, stage 1 conf vol       vC2, stage 2 conf vol       vCu, unblocked vol       444         vC0, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1         tC, 2 stage (s)       t       t       t         tF (s)       3.5       3.3       2.2         p0 queue free %       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Total       2       362       90       90         Volume toft       0       0       0       0         cSH       639       1700       1700       1700         Volume to Capacity       0.00       0.1       0.0       0.0         Control Delay (s)       10.7       0.0       0.0       0.0         Lane LOS       B        Approach LOS       B         Average Delay       0.0       10.0       10.0       A         Intersection Cap		0.00	0.00	170		0.00			
vC1, stage 1 conf vol       vC2, stage 2 conf vol         vCu, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1         tC, 2 stage (s)       t       t       t         tF (s)       3.5       3.3       2.2         p0 queue free %       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Total       2       1       0       0         volume Right       2       1       0       0         cSH       639       1700       1700       1700         Volume to Capacity       0.00       0.21       0.05       0.05         Queue Length 95th (ft)       0       0       0       0         Queue Longt (s)       10.7       0.0       0.0       0.0         Lane LOS       B       Approach LOS       B       Intersection Summary         Average Delay       0.0       0.0       10.0       10.0         Intersection Capacity Utilization									
vC2, stage 2 conf vol       vCu, unblocked vol       444       353       354         tC, single (s)       6.8       6.9       4.1         tC, 2 stage (s)       tF (s)       3.5       3.3       2.2         p0 queue free %       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Total       2       362       90       90         Volume Total       2       362       90       90         Volume Total       2       10       0       0         cSH       639       1700       1700       1700         Volume to Capacity       0.00       0.21       0.05       Queue Length 95th (ft)       0       0         Control Delay (s)       10.7       0.0       0.0       0.0       Lane LOS       B         Approach LOS       B       Intersection Summary       0.0       ICU Level of Service       A		451	301			362			
vCu, unblocked vol         444         353         354           tC, single (s)         6.8         6.9         4.1           tC, 2 stage (s)									
tC, single (s)       6.8       6.9       4.1         tC, 2 stage (s)       10       100       100         tF (s)       3.5       3.3       2.2         p0 queue free %       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Left       0       0       0       0         Volume Right       2       1       0       0       0         cSH       639       1700       1700       1700       1700         Volume to Capacity       0.00       0.21       0.05       0.05         Queue Length 95th (ft)       0       0       0       0         Queue LoS       B       Approach Delay (s)       10.7       0.0       0.0         Approach LOS       B       Intersection Summary       0.0       ICU Level of Service       A		111	353			354			
tC, 2 stage (s)       10       3.5       3.3       2.2         p0 queue free %       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Left       0       0       0       0         Volume Right       2       1       0       0         cSH       639       1700       1700       1700         Volume to Capacity       0.00       0.21       0.05       0.05         Queue Length 95th (ft)       0       0       0       0         Control Delay (s)       10.7       0.0       0.0       100         Lane LOS       B       Approach Delay (s)       10.7       0.0       0.0         Intersection Summary       0.0       11.2%       ICU Level of Service       A									
tF (s)       3.5       3.3       2.2         p0 queue free %       100       100       100         cM capacity (veh/h)       539       639       1193         Direction, Lane #       WB 1       NB 1       SE 1       SE 2         Volume Total       2       362       90       90         Volume Left       0       0       0       0         Volume Right       2       1       0       0         cSH       639       1700       1700       1700         Volume to Capacity       0.00       0.21       0.05       0.05         Queue Length 95th (ft)       0       0       0       0         Control Delay (s)       10.7       0.0       0.0       0.0         Lane LOS       B       Approach LOS       B       Intersection Summary         Average Delay       0.0       0.0       10.0       10.0         Intersection Capacity Utilization       21.2%       ICU Level of Service       A		0.0	0.5			4.1			
p0 queue free %         100         100         100           cM capacity (veh/h)         539         639         1193           Direction, Lane #         WB 1         NB 1         SE 1         SE 2           Volume Total         2         362         90         90           Volume Left         0         0         0         0           Volume Right         2         1         0         0           Volume Right         2         1         0         0           Volume Right         2         1         0         0           Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0         0           Queue Length 95th (ft)         0         0         0.0         0.0         0.0           Lane LOS         B         B         Approach LOS         B         Intersection Summary           Average Delay         0.0         0.0         10.7         0.0         A           Intersection Capacity Utilization         21.2%         ICU Level of Service         A		35	33			22			
CM capacity (veh/h)         539         639         1193           Direction, Lane #         WB 1         NB 1         SE 1         SE 2           Volume Total         2         362         90         90           Volume Left         0         0         0         0           Volume Right         2         1         0         0           Volume Right         2         1         0         0           Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0         0.0           Lane LOS         B         Approach LOS         B         Intersection Summary         Average Delay         0.0           Intersection Capacity Utilization         21.2%         ICU Level of Service         A									
Direction, Lane #         WB 1         NB 1         SE 1         SE 2           Volume Total         2         362         90         90           Volume Left         0         0         0         0           Volume Right         2         1         0         0           cSH         639         1700         1700         1700           Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0           Lane LOS         B         Approach Delay (s)         10.7         0.0         0.0           Intersection Summary         Average Delay         0.0         ICU Level of Service         A									
Volume Total         2         362         90         90           Volume Left         0         0         0         0           Volume Right         2         1         0         0           cSH         639         1700         1700         1700           Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0           Lane LOS         B         Approach Delay (s)         10.7         0.0         0.0           Approach LOS         B         Intersection Summary         0.0         0.0         0.0           Intersection Capacity Utilization         21.2%         ICU Level of Service         A					SE 0	1100			
Volume Left         0         0         0           Volume Right         2         1         0         0           cSH         639         1700         1700         1700           Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0           Lane LOS         B         Approach Delay (s)         10.7         0.0         0.0           Approach LOS         B									
Volume Right         2         1         0         0           cSH         639         1700         1700         1700           Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0           Lane LOS         B         Approach Delay (s)         10.7         0.0         0.0           Intersection Summary         0.0         0.0         ICU Level of Service         A									
cSH       639       1700       1700       1700         Volume to Capacity       0.00       0.21       0.05       0.05         Queue Length 95th (ft)       0       0       0       0         Control Delay (s)       10.7       0.0       0.0       0.0         Lane LOS       B       Approach Delay (s)       10.7       0.0       0.0         Approach LOS       B       Intersection Summary       0.0       10.0         Intersection Capacity Utilization       21.2%       ICU Level of Service       A									
Volume to Capacity         0.00         0.21         0.05         0.05           Queue Length 95th (ft)         0         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0         0           Lane LOS         B         Approach Delay (s)         10.7         0.0         0.0         0           Approach LOS         B         Intersection Summary         0.0         0.0         0.0           Intersection Capacity Utilization         21.2%         ICU Level of Service         A									
Queue Length 95th (ft)         0         0         0         0           Control Delay (s)         10.7         0.0         0.0         0.0           Lane LOS         B         Approach Delay (s)         10.7         0.0         0.0           Approach LOS         B         Intersection Summary         0.0         0.0         ICU Level of Service         A									
Control Delay (s)       10.7       0.0       0.0       0.0         Lane LOS       B       Approach Delay (s)       10.7       0.0       0.0         Approach Delay (s)       10.7       0.0       0.0       0.0         Approach LOS       B       Intersection Summary       0.0         Intersection Capacity Utilization       21.2%       ICU Level of Service       A									
Lane LOS     B       Approach Delay (s)     10.7       0.0     0.0       Approach LOS     B       Intersection Summary       Average Delay     0.0       Intersection Capacity Utilization     21.2%       ICU Level of Service     A									
Approach Delay (s)       10.7       0.0       0.0         Approach LOS       B       Intersection Summary         Intersection Summary       0.0         Intersection Capacity Utilization       21.2%       ICU Level of Service									
Approach LOS     B       Intersection Summary     0.0       Average Delay     0.0       Intersection Capacity Utilization     21.2%       ICU Level of Service     A			0.0	0.0					
Average Delay     0.0       Intersection Capacity Utilization     21.2%       ICU Level of Service     A									
Average Delay     0.0       Intersection Capacity Utilization     21.2%       ICU Level of Service     A	Intersection Summary								
Intersection Capacity Utilization 21.2% ICU Level of Service A				0.0					
Analysis Daried (min) 15		ation		21.2%	IC	U Level o	of Service	А	
	Analysis Period (min)			15					

Intersection												
Intersection Delay, s/veh	19.1											
Intersection LOS	С											
Movement	EBU	EBL	EBT	EBR	WBU	WBL	WBT	WBR	NBU	NBL	NBT	NBR
Vol, veh/h	0	10	60	58	0	107	181	119	0	8	51	103
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	0	11	65	63	0	116	197	129	0	9	55	112
Number of Lanes	0	0	1	1	0	0	1	0	0	0	1	0
Approach		EB				WB				NB		
Opposing Approach		WB				EB				SB		
Opposing Lanes		1				2				2		
Conflicting Approach Left		SB				NB				EB		
Conflicting Lanes Left		2				1				2		
Conflicting Approach Right		NB				SB				WB		
Conflicting Lanes Right		1				2				1		
HCM Control Delay		10.8				28.7				13.4		
HCM LOS		В				D				В		
Lane		NBLn1	EBLn1	EBLn2	WBLn1	SBLn1	SBLn2					
Vol Left, %		5%	14%	0%	26%	75%	0%					
Vol Thru, %		31%	86%	0%	44%	25%	0%					
Vol Right, %		64%	0%	100%	29%	0%	100%					
Sign Control		Stop	Stop	Stop	Stop	Stop	Stop					
Traffic Vol by Lane		162	70	58	407	198	152					
		51	60	0	181	50	0					
Through Vol		103	0	58	119	0	152					
RT Vol		8	10	0	107	148	0					
Lane Flow Rate		176	76 7	63 7	442	215 7	165					
Geometry Grp Degree of Util (X)		6 0.338	0.154	0.114	6 0.78	0.433	7 0.282					
Departure Headway (Hd)		6.906	7.278	6.487	6.463	7.237	0.202 6.141					
Convergence, Y/N		Yes	Yes	Yes	Yes	Yes	Yes					
Convergence, 1/10 Cap		523	494	553	562	499	587					
Service Time		4.927	5.011	4.219	4.463	4.953	3.857					
HCM Lane V/C Ratio		0.337	0.154	0.114	0.786	0.431	0.281					
HCM Control Delay		13.4	11.3	10.1	28.7	15.4	11.3					
HCM Lane LOS		В	B	В	D	C	В					
HCM 95th-tile Q		1.5	0.5	0.4	7.2	2.2	1.2					

Intersection Intersection Delay, s/veh Intersection LOS					
Movement	SBU	SBL	SBT	SBR	
Vol, veh/h	0	148	50	152	
Peak Hour Factor	0.92	0.92	0.92	0.92	
Heavy Vehicles, %	2	2	2	2	
Mvmt Flow	0	161	54	165	
Number of Lanes	0	0	1	1	
Approach		SB			
Opposing Approach		NB			
Opposing Lanes		1			
Conflicting Approach Left		WB			
Conflicting Lanes Left		1			
Conflicting Approach Right		EB			
Conflicting Lanes Right		2			
HCM Control Delay		13.6			
HCM LOS		В			
Lane					

## Timings 2: Galiano Street & Alhambra Plaza

	_	٦	-	-	-	1	1	1	Ŧ
Lane Group	EBU	EBL	EBT	WBL	WBT	NBL	NBT	SBL	SBT
Lane Configurations		24	<b>≜</b> ⊅		<b>≜</b> ⊅		4	ሻ	ef 👘
Volume (vph)	41	51	323	10	275	67	91	24	121
Turn Type	custom	pm+pt	NA	Perm	NA	Perm	NA	Perm	NA
Protected Phases		1	5		2		4		8
Permitted Phases	1	5		2		4		8	
Detector Phase	1	1	5	2	2	4	4	8	8
Switch Phase									
Minimum Initial (s)	5.0	5.0	15.0	15.0	15.0	7.0	7.0	7.0	7.0
Minimum Split (s)	8.0	8.0	20.0	20.0	20.0	20.0	20.0	20.0	20.0
Total Split (s)	8.0	8.0	52.0	44.0	44.0	38.0	38.0	38.0	38.0
Total Split (%)	8.9%	8.9%	57.8%	48.9%	48.9%	42.2%	42.2%	42.2%	42.2%
Yellow Time (s)	3.0	3.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.0	0.0	0.3	0.3	0.3	1.8	1.8	1.8	1.8
Lost Time Adjust (s)		0.0	0.0		0.0		0.0	0.0	0.0
Total Lost Time (s)		3.0	4.3		4.3		5.8	5.8	5.8
Lead/Lag	Lead	Lead		Lag	Lag				
Lead-Lag Optimize?	Yes	Yes		Yes	Yes				
Recall Mode	None	None	C-Min	C-Min	C-Min	None	None	None	None
Intersection Summary									

Intersection Summary

Cycle Length: 90 Actuated Cycle Length: 90

Offset: 73 (81%), Referenced to phase 2:WBTL and 5:EBTL, Start of Green

Natural Cycle: 50

Control Type: Actuated-Coordinated

Splits and Phases: 2: Galiano Street & Alhambra Plaza

	<b>√1</b> ø4
8s <mark>44</mark> s	38 s
ø5 (R) <b>₩</b>	₩ø8
52 s	38 s

## HCM Signalized Intersection Capacity Analysis 2: Galiano Street & Alhambra Plaza

	1	٦	-	$\mathbf{r}$	4	+	×	•	1	1	1	Ŧ
Movement	EBU	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT
Lane Configurations		1	<b>∱1</b> ≱			<b>∱</b> î≽			4		ሻ	4Î
Volume (vph)	41	51	323	15	10	275	25	67	91	85	24	121
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Lane Util. Factor		1.00	0.95			0.95			1.00		1.00	1.00
Frt		1.00	0.99			0.99			0.95		1.00	0.94
Flt Protected		0.95	1.00			1.00			0.99		0.95	1.00
Satd. Flow (prot)		1770	3516			3491			1751		1770	1746
FIt Permitted		0.52	1.00			0.94			0.64		0.46	1.00
Satd. Flow (perm)		967	3516			3294			1130		852	1746
Peak-hour factor, PHF	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92	0.92
Adj. Flow (vph)	45	55	351	16	11	299	27	73	99	92	26	132
RTOR Reduction (vph)	0	0	3	0	0	5	0	0	26	0	0	35
Lane Group Flow (vph)	0	100	364	0	0	332	0	0	238	0	26	192
Turn Type	custom	pm+pt	NA		Perm	NA		Perm	NA		Perm	NA
Protected Phases		1	5			2			4			8
Permitted Phases	1	5			2			4			8	
Actuated Green, G (s)		60.8	60.8			52.4			19.1		19.1	19.1
Effective Green, g (s)		60.8	60.8			52.4			19.1		19.1	19.1
Actuated g/C Ratio		0.68	0.68			0.58			0.21		0.21	0.21
Clearance Time (s)		3.0	4.3			4.3			5.8		5.8	5.8
Vehicle Extension (s)		2.0	1.0			1.0			2.5		2.5	2.5
Lane Grp Cap (vph)		701	2375			1917			239		180	370
v/s Ratio Prot		0.01	c0.10									0.11
v/s Ratio Perm		0.09				c0.10			c0.21		0.03	
v/c Ratio		0.14	0.15			0.17			1.00		0.14	0.52
Uniform Delay, d1		5.1	5.3			8.7			35.4		28.8	31.4
Progression Factor		1.00	1.00			0.87			1.00		1.00	1.00
Incremental Delay, d2		0.0	0.1			0.2			56.7		0.3	0.9
Delay (s)		5.1	5.4			7.8			92.1		29.1	32.3
Level of Service		А	А			А			F		С	С
Approach Delay (s)			5.4			7.8			92.1			32.0
Approach LOS			А			А			F			С
Intersection Summary												
HCM 2000 Control Delay			28.4	Н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capaci	ity ratio		0.38									
Actuated Cycle Length (s)			90.0	S	um of los	t time (s)			13.1			
Intersection Capacity Utilizati	on		67.2%		CU Level		e		С			
Analysis Period (min)			15									

c Critical Lane Group

	,
	-
Movement	SBR
Lane	
Volume (vph)	87
Ideal Flow (vphpl)	1900
Total Lost time (s)	1900
Lane Util. Factor	
Frt	
Flt Protected	
Satd. Flow (prot)	
Flt Permitted	
Satd. Flow (perm)	
Peak-hour factor, PHF	0.92
Adj. Flow (vph)	95
RTOR Reduction (vph)	0
Lane Group Flow (vph)	0
Turn Type	
Protected Phases	
Permitted Phases	
Actuated Green, G (s)	
Effective Green, g (s)	
Actuated g/C Ratio	
Clearance Time (s)	
Vehicle Extension (s)	
Lane Grp Cap (vph)	
v/s Ratio Prot	
v/s Ratio Perm	
v/c Ratio	
Uniform Delay, d1	
Progression Factor	
Incremental Delay, d2 Delay (s)	
Level of Service	
Approach Delay (s)	
Approach LOS	
Intersection Summary	

### Timings 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

.

	٦	-	$\rightarrow$	-	1	1	1	Ŧ
Lane Group	EBL	EBT	EBR	WBT	NBL	NBT	SBL	SBT
Lane Configurations	ሻ	र्भ	1	ፋጉ	ሻ	<b>≜</b> ⊅	ሻ	<b>≜</b> ⊅
Volume (vph)	267	34	114	25	163	1267	16	1056
Turn Type	Split	NA	pm+ov	NA	pm+pt	NA	Perm	NA
Protected Phases	3	3	1	4	1	6		2
Permitted Phases			3		6		2	
Detector Phase	3	3	1	4	1	6	2	2
Switch Phase								
Minimum Initial (s)	7.0	7.0	5.0	7.0	5.0	7.0	7.0	7.0
Minimum Split (s)	22.8	22.8	8.0	25.0	8.0	32.9	32.9	32.9
Total Split (s)	53.0	53.0	8.0	27.0	8.0	100.0	92.0	92.0
Total Split (%)	29.4%	29.4%	4.4%	15.0%	4.4%	55.6%	51.1%	51.1%
Yellow Time (s)	4.0	4.0	3.0	4.0	3.0	4.0	4.0	4.0
All-Red Time (s)	0.8	0.8	0.0	0.8	0.0	1.9	1.9	1.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.8	4.8	3.0	4.8	3.0	5.9	5.9	5.9
Lead/Lag	Lead	Lead	Lead	Lag	Lead		Lag	Lag
Lead-Lag Optimize?	Yes	Yes	Yes	Yes	Yes		Yes	Yes
Recall Mode	None	None	None	None	None	C-Min	C-Min	C-Min

Intersection Summary

Cycle Length: 180 Actuated Cycle Length: 180

Offset: 21 (12%), Referenced to phase 2:SBTL and 6:NBTL, Start of Green Natural Cycle: 90

Control Type: Actuated-Coordinated

Splits and Phases: 3: NW 37th Avenue/Douglas Road & Alhambra Plaza



## HCM Signalized Intersection Capacity Analysis 3: NW 37th Avenue/Douglas Road & Alhambra Plaza

	٨	-	$\mathbf{i}$	•	+	•	1	1	1	1	Ļ	~
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	<u>۲</u>	र्च	1		đ îr		<u>۲</u>	<b>∱</b> ⊅		- ከ	<b>≜</b> ⊅	
Volume (vph)	267	34	114	11	25	13	163	1267	24	16	1056	114
Ideal Flow (vphpl)	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900	1900
Total Lost time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Lane Util. Factor	0.95	0.95	1.00		0.95		1.00	0.95		1.00	0.95	
Frt	1.00	1.00	0.85		0.96		1.00	1.00		1.00	0.99	
Flt Protected	0.95	0.96	1.00		0.99		0.95	1.00		0.95	1.00	
Satd. Flow (prot)	1681	1703	1583		3361		1770	3529		1770	3488	
Flt Permitted	0.95	0.96	1.00		0.99		0.17	1.00		0.21	1.00	
Satd. Flow (perm)	1681	1703	1583		3361		323	3529		394	3488	
Peak-hour factor, PHF	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99	0.99
Adj. Flow (vph)	270	34	115	11	25	13	165	1280	24	16	1067	115
RTOR Reduction (vph)	0	0	88	0	13	0	0	0	0	0	3	0
Lane Group Flow (vph)	151	153	27	0	36	0	165	1304	0	16	1179	0
Turn Type	Split	NA	pm+ov	Split	NA		pm+pt	NA		Perm	NA	
Protected Phases	3	3	1	4	4		1	6			2	
Permitted Phases			3				6			2		
Actuated Green, G (s)	21.2	21.2	41.6		6.1		137.2	137.2		113.8	113.8	
Effective Green, g (s)	21.2	21.2	41.6		6.1		137.2	137.2		113.8	113.8	
Actuated g/C Ratio	0.12	0.12	0.23		0.03		0.76	0.76		0.63	0.63	
Clearance Time (s)	4.8	4.8	3.0		4.8		3.0	5.9		5.9	5.9	
Vehicle Extension (s)	2.5	2.5	2.0		2.5		2.0	1.0		1.0	1.0	
Lane Grp Cap (vph)	197	200	365		113		410	2689		249	2205	
v/s Ratio Prot	0.09	c0.09	0.01		c0.01		0.05	c0.37			c0.34	
v/s Ratio Perm			0.01				0.26			0.04		
v/c Ratio	0.77	0.77	0.07		0.32		0.40	0.48		0.06	0.53	
Uniform Delay, d1	77.0	77.0	54.1		84.9		10.1	8.1		12.7	18.4	
Progression Factor	1.01	1.01	1.45		1.00		1.00	1.00		0.69	0.76	
Incremental Delay, d2	15.3	15.0	0.0		1.2		0.2	0.6		0.5	0.9	
Delay (s)	93.1	92.8	78.3		86.1		10.4	8.7		9.2	14.9	
Level of Service	F	F	E		F		В	Α		A	В	
Approach Delay (s)		88.9			86.1			8.9			14.8	
Approach LOS		F			F			A			В	
Intersection Summary												
HCM 2000 Control Delay			23.1	Н	CM 2000	Level of	Service		С			
HCM 2000 Volume to Capac	city ratio		0.55									
Actuated Cycle Length (s)			180.0	S	um of los	t time (s)			18.5			
Intersection Capacity Utilizat	tion		70.4%	IC	CU Level	of Servic	e		С			
Analysis Period (min)			15									
c Critical Lane Group												

c Critical Lane Group

	≯	$\rightarrow$	1	1	Ļ
Lane Group	EBL	EBR	NBL	NBT	SBT
Lane Configurations	1	1	٦	<u></u>	<b>∱</b> ⊅
Volume (vph)	93	104	51	1488	1089
Turn Type	Prot	Perm	pm+pt	NA	NA
Protected Phases	8		1	6	2
Permitted Phases		8	6		
Detector Phase	8	8	1	6	2
Switch Phase					
Minimum Initial (s)	4.0	4.0	4.0	4.0	4.0
Minimum Split (s)	20.0	20.0	8.9	20.0	20.0
Total Split (s)	43.0	43.0	22.0	137.0	115.0
Total Split (%)	23.9%	23.9%	12.2%	76.1%	63.9%
Yellow Time (s)	4.0	4.0	4.0	4.0	4.0
All-Red Time (s)	0.9	0.9	0.9	0.9	0.9
Lost Time Adjust (s)	0.0	0.0	0.0	0.0	0.0
Total Lost Time (s)	4.9	4.9	4.9	4.9	4.9
Lead/Lag			Lead		Lag
Lead-Lag Optimize?			Yes		Yes
Recall Mode	None	None	None	C-Min	C-Min
Intersection Summary					

Cycle Length: 180 Actuated Cycle Length: 180 Offset: 52 (29%), Referenced to phase 2:SBT and 6:NBTL, Start of Green Natural Cycle: 60 Control Type: Actuated-Coordinated

Splits and Phases: 4: NW 37th Avenue/Douglas Road & Minorca Avenue



Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	EBL 93 3 0 1.00 1.00 1.00 186.3 96 1 0.97 2 179 0.10 1774 96 1774	EBR 104 18 0 1.00 1.00 186.3 107 1 0.97 2 160 0.10 1583	NBL 51 1 0 1.00 1.00 186.3 53 1 0.97 2 406 0.07	NBT ↑↑ 1488 6 0 1.00 186.3 1534 2 0.97 2 2756	SBT ↑↑ 1089 2 0 1.00 186.3 1123 2 0.97 2	SBR 38 12 0 1.00 1.00 1.00 190.0 39 0 0.97				
Volume (veh/h) Number Initial Q (Qb), veh Ped-Bike Adj(A_pbT) Parking Bus, Adj Adj Sat Flow, veh/h/In Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green <u>Sat Flow, veh/h</u> Grp Volume(v), veh/h	93 3 0 1.00 1.00 186.3 96 1 0.97 2 179 0.10 1774 96 1774	104 18 0 1.00 186.3 107 1 0.97 2 160 0.10 1583	51 1 0 1.00 1.00 186.3 53 1 0.97 2 406	1488 6 0 1.00 186.3 1534 2 0.97 2	1089 2 0 1.00 186.3 1123 2 0.97	12 0 1.00 190.0 39 0 0.97				
Number Initial Q (Qb), veh Ped-Bike Adj(A_pbT) Parking Bus, Adj Adj Sat Flow, veh/h/ln Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	3 0 1.00 186.3 96 1 0.97 2 179 0.10 <u>1774</u> 96 1774	18 0 1.00 186.3 107 1 0.97 2 160 0.10 1583	1 0 1.00 186.3 53 1 0.97 2 406	6 0 1.00 186.3 1534 2 0.97 2	2 0 1.00 186.3 1123 2 0.97	12 0 1.00 190.0 39 0 0.97				
Initial Q (Qb), veh Ped-Bike Adj(A_pbT) Parking Bus, Adj Adj Sat Flow, veh/h/In Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	0 1.00 1.00 186.3 96 1 0.97 2 179 0.10 <u>1774</u> 96 1774	0 1.00 186.3 107 1 0.97 2 160 0.10 1583	0 1.00 186.3 53 1 0.97 2 406	0 1.00 186.3 1534 2 0.97 2	0 1.00 186.3 1123 2 0.97	0 1.00 1.00 190.0 39 0 0.97				
Ped-Bike Adj(A_pbT) Parking Bus, Adj Adj Sat Flow, veh/h/In Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	1.00 1.00 186.3 96 1 0.97 2 179 0.10 1774 96 1774	1.00 1.00 186.3 107 1 0.97 2 160 0.10 1583	1.00 1.00 186.3 53 1 0.97 2 406	1.00 186.3 1534 2 0.97 2	1.00 186.3 1123 2 0.97	1.00 1.00 190.0 39 0 0.97				
Parking Bus, Adj Adj Sat Flow, veh/h/ln Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	1.00 186.3 96 1 0.97 2 179 0.10 1774 96 1774	1.00 186.3 107 1 0.97 2 160 0.10 1583	1.00 186.3 53 1 0.97 2 406	186.3 1534 2 0.97 2	186.3 1123 2 0.97	1.00 190.0 39 0 0.97				
Adj Sat Flow, veh/h/ln Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	186.3 96 1 0.97 2 179 0.10 <u>1774</u> 96 1774	186.3 107 1 0.97 2 160 0.10 1583	186.3 53 1 0.97 2 406	186.3 1534 2 0.97 2	186.3 1123 2 0.97	190.0 39 0 0.97				
Adj Flow Rate, veh/h Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	96 1 0.97 2 179 0.10 1774 96 1774	107 1 0.97 2 160 0.10 1583	53 1 0.97 2 406	1534 2 0.97 2	1123 2 0.97	39 0 0.97				
Adj No. of Lanes Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	1 0.97 2 179 0.10 1774 96 1774	1 0.97 2 160 0.10 1583	1 0.97 2 406	2 0.97 2	2 0.97	0 0.97				
Peak Hour Factor Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	0.97 2 179 0.10 <u>1774</u> 96 1774	0.97 2 160 0.10 1583	0.97 2 406	0.97 2	0.97	0.97				
Percent Heavy Veh, % Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	2 179 0.10 <u>1774</u> 96 1774	2 160 0.10 1583	2 406	2						
Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	179 0.10 <u>1774</u> 96 1774	160 0.10 1583	406		2	_				
Cap, veh/h Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	0.10 <u>1774</u> 96 1774	0.10 1583		2756		2				
Arrive On Green Sat Flow, veh/h Grp Volume(v), veh/h	1774 96 1774	1583	0.07		2389	83				
Grp Volume(v), veh/h	96 1774			1.00	0.68	0.68				
Grp Volume(v), veh/h	96 1774		1774	3632	3583	121				
	1774	107	53	1534	569	593				
		1583	1774	1770	1770	1841				
Q Serve(g_s), s	4.2	5.3	0.6	0.0	12.2	12.2				
Cycle Q Clear(g_c), s	4.2	5.3	0.6	0.0	12.2	12.2				
Prop In Lane	1.00	1.00	1.00			0.07				
ane Grp Cap(c), veh/h	179	160	406	2756	1211	1260				
//C Ratio(X)	0.54	0.67	0.13	0.56	0.47	0.47				
Avail Cap(c_a), veh/h	828	739	717	5729	2387	2484				
HCM Platoon Ratio	1.00	1.00	2.00	2.00	1.00	1.00				
Jpstream Filter(I)	1.00	1.00	0.85	0.85	1.00	1.00				
Jniform Delay (d), s/veh	34.9	35.4	4.0	0.0	6.0	6.0				
ncr Delay (d2), s/veh	3.5	6.7	0.1	0.7	1.3	1.3				
nitial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0				
%ile BackOfQ(50%),veh/ln	2.2	2.6	0.3	0.3	6.3	6.5				
InGrp Delay(d),s/veh	38.4	42.0	4.1	0.3	7.3	7.3				
InGrp LOS	50.4 D	μ2.0 D	A	0.7 A	7.5 A	7.5 A				
	203	D	~	1587	1162					
Approach Vol, veh/h	203 40.3			0.8	7.3					
Approach Delay, s/veh	40.3 D									
Approach LOS	D			А	A					
imer	1	2	3	4	5	6	7	8		
Assigned Phs	1	2				6		8		
Phs Duration (G+Y+Rc), s	7.7	159.2				166.9		13.1		
Change Period (Y+Rc), s* 4.900						000001		4.9		
/lax Green Setting (Gmax), s *	* 17.1	* 110.1			* 132	2.10001		38.1		
/lax Q Clear Time (g_c+l1), s	2.6	14.2				2.0		7.3		
Green Ext Time (p_c), s	0.1	41.6				45.3		1.0		
ntersection Summary										
ICM 2010 Ctrl Delay			6.1							
ICM 2010 LOS			A							
			Л							

\* HCM 2010 computational engine requires equal clearance times for the phases crossing the barrier.

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Total\_PM.syn

HCM 2010 TWSC 5: Alhambra Circle & Minorca Avenue

Intersection											
Int Delay, s/veh	9.2										
	50									NET	
Movement	EBL	EBT	EBR		WBL	WBT	WBR	NE		NBT	NBR
Vol, veh/h	2	49	87		102	74	22		57	90	93
Conflicting Peds, #/hr	2	0	4		4	0	2		12	_ 0	_ 4
Sign Control	Stop	Stop	Stop		Stop	Stop	Stop	Fre	ee	Free	Free
RT Channelized	-	-	None		-	-	None		-	-	None
Storage Length	-	-	-		-	-	-		-	-	-
Veh in Median Storage, #	-	0	-		-	0	-		-	0	-
Grade, %	-	0	-		-	0	-		-	0	-
Peak Hour Factor	98	98	98		98	98	98		98	98	98
Heavy Vehicles, %	2	2	2		2	2	2		2	2	2
Mvmt Flow	2	50	89		104	76	22	t	58	92	95
Major/Minor	Minor2				Minor1			Majo	r1		
Conflicting Flow All	583	581	235		603	537	155		26	0	0
Stage 1	254	254			280	280	-		_	-	-
Stage 2	329	327	-		323	257	-		-	-	-
Critical Hdwy	7.12	6.52	6.22		7.12	6.52	6.22	4.1	12	-	-
Critical Hdwy Stg 1	6.12	5.52	-		6.12	5.52	-		-	-	-
Critical Hdwy Stg 2	6.12	5.52	-		6.12	5.52	-		-	-	-
Follow-up Hdwy	3.518	4.018	3.318		3.518	4.018	3.318	2.2	18	-	-
Pot Cap-1 Maneuver	424	425	804		411	450	891	134		-	-
Stage 1	750	697	-		727	679	-		-	-	-
Stage 2	684	648	-		689	695	-		-	-	-
Platoon blocked, %										-	-
Mov Cap-1 Maneuver	333	393	793		308	416	879	132	29	-	-
Mov Cap-2 Maneuver	333	393	-		308	416	-		-	-	-
Stage 1	704	686	-		683	637	-		-	-	-
Stage 2	548	608	-		554	684	-		-	-	-
Approach	ГР							N	חו		
Approach	EB				WB				IB		
HCM Control Delay, s	13.3				25.7			2	.1		
HCM LOS	В				D						
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR			
Capacity (veh/h)	1329	-	-	574	371	1369	-	-			
HCM Lane V/C Ratio	0.051	-	-	0.245	0.545	0.011	-	-			
HCM Control Delay (s)	7.9	0	-	13.3	25.7	7.7	0	-			
HCM Lane LOS	А	А	-	В	D	А	А	-			
HCM 95th %tile Q(veh)	0.2	-	-	1	3.1	0	-	-			

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Total\_PM.syn

Intersection				
Int Delay, s/veh				
•				
Movement	SBL	SBT	SBR	
Vol, veh/h	15	212	6	
Conflicting Peds, #/hr	4	0	12	
Sign Control	Free	Free	Free	
RT Channelized	-	-	None	
Storage Length	-	-	-	
Veh in Median Storage, #	-	0	-	
Grade, %	-	0 0	-	
Peak Hour Factor	98	98	98	
Heavy Vehicles, %	2	2	2	
Mvmt Flow	15	216	6	
			Ŭ	
	Maine			
Major/Minor	Major2			
Conflicting Flow All	191	0	0	
Stage 1	-	-	-	
Stage 2	-	-	-	
Critical Hdwy	4.12	-	-	
Critical Hdwy Stg 1	-	-	-	
Critical Hdwy Stg 2	-	-	-	
Follow-up Hdwy	2.218	-	-	
Pot Cap-1 Maneuver	1383	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Platoon blocked, %		-	-	
Mov Cap-1 Maneuver	1369	-	-	
Mov Cap-2 Maneuver	-	-	-	
Stage 1	-	-	-	
Stage 2	-	-	-	
Approach	SB			
Approach	0.5			
HCM Control Delay, s	0.5			
HCM LOS				
Minor Long/Major Mumt				
Minor Lane/Major Mvmt				

K:\FTL\_TPTO\043581000-100 Alahambra Circle\calc\Synchro\04-29-2014\Updated PSF\Total\_PM.syn

Intersection									
Int Delay, s/veh	28.2								
Movement	NBL	NBT				SBT	SBR	NEL	NER
Vol, veh/h	0	1423				1141	242	78	23
Conflicting Peds, #/hr	0	0				0	5	0	0
Sign Control	Free	Free				Free	Free	Stop	Stop
RT Channelized	-	None				-	None	-	None
Storage Length	-	-				-	-	0	0
Veh in Median Storage, #	-	0				0	-	0	-
Grade, %	-	0				0	-	0	-
Peak Hour Factor	86	86				86	86	86	86
Heavy Vehicles, %	2	2				2	2	2	2
Mvmt Flow	0	1655				1327	281	91	27
Major/Minor	Major1					Major2		Minor2	
Conflicting Flow All	1608	0					0	2294	804
Stage 1	-	-				-	-	1467	-
Stage 2	-	-				-	-	827	_
Critical Hdwy	4.14	-				-	-	6.84	6.94
Critical Hdwy Stg 1	-	-				-	-	5.84	-
Critical Hdwy Stg 2	-	-				-	-	5.84	-
Follow-up Hdwy	2.22	-				-	-	3.52	3.32
Pot Cap-1 Maneuver	402	-				-	-	~ 33	326
Stage 1		-				-	-	178	
Stage 2	-	-				-	-	390	-
Platoon blocked, %		-				-	-		
Mov Cap-1 Maneuver	402	-				-	-	~ 33	326
Mov Cap-2 Maneuver	-	-				-	-	~ 33	
Stage 1	-	-				-	-	178	-
Stage 2	-	-				-	-	390	-
Approach	NB					SB		NE	
HCM Control Delay, s	0					0		\$ 811.4	
HCM LOS								F	
Minor Lane/Major Mvmt	NELn1	NELn2	NBL	NBT	SBT	SBR			
Capacity (veh/h)	33	326	402	-	-	-			
HCM Lane V/C Ratio	2.748	0.082	-	-	-	-			
HCM Control Delay (s)	\$ 1045.7	17	0	-	-	-			
HCM Lane LOS	F	С	А	-	-	-			
HCM 95th %tile Q(veh)	10.5	0.3	0	-	-	-			
Notes									
~: Volume exceeds capacity	\$: Delay excee	eds 300s	+: Com	putation	Not Defi	ined *:	All major vo	olume in platoon	

HCM 2010 TWSC 7: Project Driveway & Minorca Avenue

Int Delay, s/veh	1.5							
Movement		EBT	EBR		WBL	WBT	NBL	NBF
Vol, veh/h		155	32		19	123	24	15
Conflicting Peds, #/hr		0	0		0	0	0	C
Sign Control		Free	Free		Free	Free	Stop	Stop
RT Channelized		-	None		-	None	-	None
Storage Length		-	-		-	-	0	-
Veh in Median Storage, #		0	-		-	0	0	-
Grade, %		0	-		-	0	0	-
Peak Hour Factor		92	92		92	92	92	92
Heavy Vehicles, %		2	2		2	2	2	2
Mvmt Flow		168	35		21	134	26	16
Major/Minor		Major1		1	Major2		Minor1	
Conflicting Flow All		0	0		203	0	361	186
Stage 1		-	-		200	-	186	100
Stage 2		_	_		_	_	175	-
Critical Hdwy		_	_		4.12	_	6.42	6.22
Critical Hdwy Stg 1		_	_		-	_	5.42	0.22
Critical Hdwy Stg 2		_	_		_	_	5.42	-
Follow-up Hdwy		_	_		2.218	_	3.518	3.318
Pot Cap-1 Maneuver		_	_		1369	_	638	856
Stage 1		_	_		-	_	846	
Stage 2		_	_		_	_	855	-
Platoon blocked, %		_	_			_	000	
Mov Cap-1 Maneuver		_	_		1369	_	627	856
Mov Cap-2 Maneuver		_	_		-	_	627	
Stage 1		_	_		_	_	846	
Stage 2		-	-		-	-	840	
Approach		EB			WB		NB	
HCM Control Delay, s		0			1		10.5	
HCM LOS		Ū			·		B	
Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT			
Capacity (veh/h)	699	-	-	1369	-			
HCM Lane V/C Ratio	0.061	-	-	0.015	-			
HCM Control Delay (s)	10.5	-	-	7.7	0			
HCM Lane LOS	В	-	-	A	Â			
HCM 95th %tile Q(veh)	0.2	-	-	0	-			

	4	*	٦	1	$\searrow$	$\mathbf{i}$		
Movement	WBL	WBR	NBL	NBR	SEL	SER		
Lane Configurations		1	۰Y			11		
Volume (veh/h)	0	2	285	3	0	271		
Sign Control	Stop		Free		Free			
Grade	0%		0%		0%			
Peak Hour Factor	0.92	0.92	0.92	0.92	0.92	0.92		
Hourly flow rate (vph)	0	2	310	3	0	295		
Pedestrians								
Lane Width (ft)								
Walking Speed (ft/s)								
Percent Blockage								
Right turn flare (veh)								
Median type			None		None			
Median storage veh)								
Upstream signal (ft)			161					
pX, platoon unblocked								
vC, conflicting volume	459	311			313			
vC1, stage 1 conf vol								
vC2, stage 2 conf vol								
vCu, unblocked vol	459	311			313			
tC, single (s)	6.8	6.9			4.1			
tC, 2 stage (s)								
tF (s)	3.5	3.3			2.2			
p0 queue free %	100	100			100			
cM capacity (veh/h)	531	684			1244			
Direction, Lane #	WB 1	NB 1	SE 1	SE 2				
Volume Total	2	313	147	147				
Volume Left	0	0	0	0				
Volume Right	2	3	0	0				
cSH	684	1700	1700	1700				
Volume to Capacity	0.00	0.18	0.09	0.09				
Queue Length 95th (ft)	0	0	0	0				
Control Delay (s)	10.3	0.0	0.0	0.0				
Lane LOS	B	~ ~	0.0					
Approach Delay (s)	10.3	0.0	0.0					
Approach LOS	В							
Intersection Summary								
Average Delay			0.0					
Intersection Capacity Utilizati								
Analysis Period (min)	on		19.3% 15	IC	U Level o	of Service	А	



#### CITY OF CORAL GABLES, FLORIDA

#### ORDINANCE NO. 2854

AN ORDINANCE VACATING PORTION OF ALLEY RUNNING EAST/WEST WHICH IS BOUNDED ON THE EAST BY THE SOUTHERLY PROLONGATION OF THE EAST LINE OF LOT 15 AND IS BOUNDED ON THE WEST BY THE SOUTHERLY PROLONGATION OF THE WEST LINE OF LOT 7; AND ALL OF THAT PORTION OF THE ALLEY RUNNING NORTH/SOUTH WHICH IS BOUNDED ON THE NORTH BY THE EASTERLY PROLONGATION OF THE NORTH LINE OF LOT 11 AND BOUNDED ON THE SOUTH BY THE EAS-TERLY PROLONGATION OF THE SOUTH LINE OF LOT 11, ALL IN BLOCK 22 OF THE "REVISED PLAT OF CORAL GABLES SECTION L", ACCOR-DING TO THE PLAT THEREOF AS RECORDED IN PLAT BOOK 8 AT PAGE 85 OF THE PUBLIC RECORDS OF DADE COUNTY, FLORIDA; PROVIDING FOR SUBSTITUTE EASEMENT FOR ALLEY PURPOSES; SETTING FORTH TERMS AND CONDITIONS; PROVIDING EFFECTIVE DATE THIRTY DAYS FROM JUNE 27, 1989; AND REPEALING ALL ORDINANCES INCONSIS-TENT HEREWITH.

WHEREAS, the purpose of this ordinance is to vacate a portion of alley running East/West and all of that portion of alley running North/South lying in Block 22 of the "Revised Plat of Coral Gables Section L", more particularly described hereinafter in Section 1; to provide for substitute easement for public alley purposes as described in Section 2, and

WHEREAS, the Street and Alley Vacation Committee at a meeting held on May 4, 1989, recommended the vacation of such alley, and

ABE6:27

WHEREAS, the City Commission held a public hearing on May 23, 1989, to consider the vacation of said alley at which hearing all interested persons were afforded the opportunity to be heard, and

WHEREAS, it is felt that the vacation of said alley and the provisions of the substitute easement are in the interest of public health, safety, order, convenience, comfort, prosperity and general welfare,

NOW, THEREFORE, BE IT ORDAINED BY THE COMMISSION OF THE CITY OF CORAL GABLES:

SECTION 1. That a portion of alley running East/West which is bounded on the East by the Southerly prolongation of the East line of Lot 15 and is bounded on the West by the Southerly prolongations of the West line of Lot 7, and all of that portion of alley running North/South which is bounded on the North by the Easterly prolongation of the North line of Lot 11 and bounded on the South by the Easterly prolongation of the South line of Lot 11, all in Block 22, of the "Revised Plat of Coral Gables Section L" (Minorca Avenue and Douglas Road) shall be and it is hereby vacated, abandoned and discontinued for the purpose for which it was dedicated to public use subject to the terms and conditions as set forth hereinafter.

SECTION 2. That the Owner of record, by proper instrument, shall grant an easement to the City of Coral Gables and any and all applicable utility companies for substitute alley purposes to be used for utility purposes including storm and sanitary sewers and for use as a passageway for City vehicles and the general public. Said easement being legally described as follows:

> Begin at the Southwest corner of Lot 7, Block 22, of the "REVISED PLAT OF CORAL GABLES SECTION L" according to the plat thereof as recorded in Plat Book 8 at Page 85 of the Public Records of Dade County, Florida; thence run North 50' 03' 53" East for a distance of 23.01 feet to a point; thence run North 10' 08' 25" East along a line parallel with the West line of said Lot 7 for a distance of 107.00 feet more or less to a Point of Intersection with the North line of said Lot 7, said point being a point on a circular curve concave to the North; thence run along said circular curve to the left having a radius of 290.18 feet through a central angle of 03' 57' 51" for an arc distance of 20.08 feet, and a chord which bears South

> > Page 1 of 3, Ord. No. 2854

84' 44' 25" East to a point on a line; thence run South 10' 08' 26" West along a line parallel with the West line of said Lot 7 for a distance of 140.45 feet to a Point of Intersection with the South right-of-way line of the 20 feet East-West Alley in said Block 22; thence run South 89' 59' 20" West along the South right-of-way line of the said 20 feet East-West Alley for a distance of 35.32 feet to a Point of Intersection with the Southerly projection of the West line of said Lot 7; thence run North 10' 08' 26" East for a distance of 20.32 feet to the Point of Beginning; containing 3,236 square feet, more or less.

SECTION 3. That the easement described hereinabove in Section 2 shall be constructed in accordance with the specifications of the Public Works Department of the City of Coral Gables and the plans for such construction shall be submitted to and shall be subject to approval by the Public Works Department. The permits and inspections for such construction shall be handled in the same manner as the paving for streets and alleys.

SECTION 4. That the City of Coral Gables shall have the right to exercise the same control over the easement described hereinabove in Section 2 as if the same were a dedicated alley and the acceptance and approval of such easement shall in no way relieve the applicant from complying with any and all regulations pertaining to alleys including but not limited to the building, zoning and other applicable regulations.

SECTION 5. That the easement described hereinabove in Section 2 shall at all times be kept free and clear of any and all encroachments and obstructions, including but not limited to motor vehicles, trucks, trailers, debris, stoops, waste containers, and the like, and the City shall have the authority to monitor and enforce the same.

SECTION 6. That a vertical clearance of nineteen (19) feet extending the full length and width of the easement shall be provided above the easement described hereinabove in Section 2. That the Owner shall be able to construct foundations and footings underneath the roadway to be constructed in the easement area, provided that such footings and foundations do not interfere with any storm and sanitary sewers to be installed in the easement area.

SECTION 7. When and if required by the Public Works Department, the easement described hereinabove in Section 2 shall be provided with lighting fixtures which will provide an average level of illumination of two (2) footcandles of lighting over all of the area of the easement, but at no point shall there be less than one (1) footcandle of light. The cost of installing and maintaining the lighting fixtures and lights shall be borne by the applicant. Should the applicant fail to maintain the lighting system to the level of proper illumination and should the applicant fail to correct such deficiency within a period of thirty (30) days upon notification by the City, then the City Manager shall proceed to have such condition remedied and the cost thereof shall be a lien against the property to the same extent and character as are the liens for special assessments or improvements and with the same penalties and with the same rights of collection, foreclosure, sale and forfeiture as obtained in the case of liens for special improvements.

SECTION 8. That the Owner shall be held responsible for the maintenance and repair of the easement described hereinabove in Section 2 and should the Public Works Department, upon inspection, determine that the easement is in disrepair, it shall notify the Owner and if the Owner fails to repair said easement within a period of thirty (30) days, then the City Manager shall proceed to have such condition remedied and the cost thereof shall be a lien against the property to the same extent and character as are the liens for special assessments or improvements and with the same penalties and with the same rights of collection, foreclosure, sale and forfeiture as obtained in the case of liens for special improvements.

SECTION 9. That the costs of removal and/or relocation of any and all utilities, including storm and sanitary sewers, installation of any required drainage facilities, removal of curbs or abandoned concrete approaches and sidewalks, removal of any structures and the paving and construction of the substitute easement hereinabove described shall be borne by the applicant, whose action necessitates such expense.

Page 2 of 3, Ord. No. 2854

SECTION 10. That the use of the vacated property shall be limited to the same uses as to which the adjacent properties are zoned.

SECTION 11. That the reversionary rights to the portion of the alley vacated shall revert to the owners abutting on each side of the vacated alley.

SECTION 12. That the vacation of the alley shall not become effective until such time as all the existing buildings adjacent to the vacated alley have been removed and the substitute easement is conveyed and a foundation permit required for the associated project is granted.

SECTION 13. That this ordinance shall become void if said foundation permits lapse prior to the commencement of construction.

SECTION 14. That the vacation of the alley shall not become effective until such time as the seven (7) conditions - as outlined in the Preliminary Design Review Committee's Minutes of Special Meeting of Wednesday, June 7, 1989 - are met. These conditions are as follows:

- Re-study the proposed service court.
   Improve visibility of traffic entering and exiting parking ramps. Reexamine proximity of entrance/exit of parking ramp on Minorca Avenue and the wall and setback at Galiano Street parking access.
- 3. Conform building facade modifications to the Mediterranean bonus requirements as reviewed and approved by the Board of Architects.
- 4. Study by applicant of the possibility of retaining and incorporating key elements of the art deco Southern Bell Building into the new development, preferably in the proposed park.
- 5. Provide a pedestrian crosswalk across Alhambra Plaza, between the main entrances of the existing Alhambra development and the proposed project.
- 6. Provision by applicant of traffic studies by David Plummer and
- Associates prepared for the proposed development. 7. That handicapped access throughout the development be indicated on the plans, and that it meet Code requirements.

SECTION 15. That the City of Coral Gables, within thirty (30) days after the requirements of this ordinance have been satisfied, shall issue a certificate of recordable form, confirming that the requirements of the ordinance have been satisfied and that the vacation of the alley has become effective.

SECTION 16. That this ordinance shall become effective thirty (30) days from June 27, 1989.

SECTION 17. That all ordinances or parts of ordinances inconsistent or in conflict herewith shall be and they are hereby repealed insofar as there is conflict or inconsistency.

PASSED AND ADOPTED THIS TWENTY-SEVENTH DAY OF JUNE, A. D., 1989

BEORGE M. CORRIGAN MAYOR

ATTEST:

VIRGINIA L. PAUL CITY CLERK

193

2 . 1



Prepared by Planning Division on April 18, 2014 and revised on May 30, 2014 Review based on plans dated 05.16.14

### Existing designations and site data:

Category	Site Info
Property address	100 Alhambra Circle
Property legal description	Lots 3 - 40, including portions of alleys, Block 22, Section "L"
Total site area (sq. ft.)	142,305 sq. ft.*
Existing property uses	Commercial building and surface parking lot
Existing Comprehensive Plan Future Land Use Map designation(s)	Commercial High-Rise Intensity
Proposed Comprehensive Plan Future Land Use Map designation(s)	No change proposed
Existing Zoning Map designation(s)	C; Commercial District
Proposed Zoning Map designation(s)	No change proposed
Eligible to utilize Mixed Use District (MXD) provisions	Eligible to utilize Individual MXD Building provisions
Within Central Business District (CBD)	Yes
Within Mediterranean Architectural District (citywide)	Yes
Within Coral Gables Redevelopment Infill District (GRID) (Traffic Concurrency Exemption Zone)	Yes
Restrictive Covenant	Restrictive Covenant required in Lieu of a Unity of Title.

\*As per Miami-Dade County Property Appraiser website.

Category	Site Info
Total site area (sq. ft.)	142,305 sq. ft.*
Floor area ratio (FAR) permitted – Maximum 3.0 FAR (without Mediterranean bonus)	426,915 sq. ft.
Floor area ratio (FAR) permitted – Maximum 3.5 FAR (with Mediterranean bonus)	498,068 sq. ft.
Floor area ratio (FAR) proposed	3.37 FAR; 480,000 sq. ft.
Building height (feet) permitted	190'-6" with Mediterranean Bonus
Building height (feet) proposed	190'-0"

\*As per Miami-Dade County Property Appraiser website.

Note: The review provided herein is not a comprehensive analysis and is intended only to identify concerns at the Development Review Committee (DRC) level in order to inform the applicant of any changes that may be necessary to allow further review of the application to proceed.

## Zoning Code Analysis:

Zoning Code Section	Reference/Provision	Required/Provided
Sec. 3-206.E.1	All buildings or structures located in Districts shall be constructed or erected upon a building site containing at least one (1) platted lot and such building site shall have a minimum	Complies.
Sec. 3-401	street frontage of fifty (50) feet. Conditional Uses	Requires conditional use review and approval by the Planning and Zoning Board and City Commission.
Article 3. Division 5. F	Planned Area Development	
Sec. 3-502.A	Uses permitted. Unless approved as a mixed use development, the uses permitted within a PAD shall be those uses specified and permitted within the underlying District in which the PAD is located.	Complies.
Sec. 3-502.C.1	Minimum site area. The minimum site area required for a PAD shall be not less than one (1) acre for residentially or commercially designated property.	Complies.
Sec. 3-502.C.2	Configuration of lands. The parcel of land for which the application is made for a PAD shall be a contiguous unified parcel with sufficient width and depth to accommodate the proposed use. The minimum lot width shall be two hundred (200) feet and minimum lot depth shall be one hundred (100) feet.	Complies.
Sec. 3-502.C.3	Floor area ratio for a PAD. The floor area ratio for a PAD shall conform to the requirements for each intended use in the underlying zoning districts; provided, however, that the total combined floor area ratio for all uses within the PAD shall be allowed to be distributed throughout the PAD.	Complies.
Sec. 3-502.C.4	Density for multi-family dwellings and overnight accommodations. The density requirements for multi-family dwellings and overnight accommodations shall be in accordance with the provisions of the applicable zoning district.	Complies. No residential density limitations for individual MXD projects located within the CBD.
Sec. 3-502.C.5	Transfer of density within a PAD. The density within a PAD may be permitted to be transferred throughout the development site provided that such transfer is not intrusive on abutting single family residential areas.	Complies.
Sec. 3-502.C.6	Landscaped open space. The minimum landscaped open space required for a PAD shall be not less than twenty (20%) percent of the PAD site. Landscaped or urban	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	open space which is located on elevated portions of the site may	
Sec. 3-502.C.7	count toward this requirement. Height of buildings. The maximum height of any building in a PAD shall conform to the provisions of the underlying zoning district.	Complies.
Sec. 3-502.C.8.a	Architectural relief and elements (i.e. windows, cornice lines, etc.) shall be provided on all sides of buildings, similar to the architectural features provided on the front façade.	Approved by the Board of Architects on 05/08/2014.
Sec. 3-502.C.8.b	Facades in excess of one hundred and fifty (150) feet in length shall incorporate design features such as: staggering of the façade, use of architectural elements such as kiosks, overhangs, arcades, etc.	Approved by the Board of Architects on 05/08/2014.
Sec. 3-502.C.8.c	Parking garages shall include architectural treatments compatible with buildings and structures which occupy the same street.	Approved by the Board of Architects on 05/08/2014.
Sec. 3-502.C.8.d	Where necessary and appropriate to enhance public pedestrian access, no block face shall have a length greater than two hundred and fifty (250) feet without a public pedestrian passageway or alley providing through access.	Complies.
Sec. 3-502.C.8.e	All buildings, except accessory buildings, shall have their main pedestrian entrance oriented towards the front or side property line.	Complies.
Sec. 3-502.C.9	Perimeter and transition. Any part of the perimeter of a PAD which fronts on an existing street or open space shall be so designed as to complement and harmonize with adjacent land uses with respect to scale, density, setback, bulk, height, landscaping and screening. Properties which are adjacent to residentially zoned or used land shall be limited to a maximum height of forty five (45) feet within one hundred (100) feet of the adjacent right-of-way.	Complies.
Sec. 3-502.C.10	Minimum street frontage; building site requirement, number of buildings per site, lot coverage and all setbacks. There shall be no specified minimum requirements for street frontage, building sites, number of buildings within the development, or lot coverage.	Complies.
Sec. 3-502.C.11	Platting and/or replatting of development site. Nothing contained herein shall be construed as	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	requiring the platting and/or	
	replatting of a development site for a	
	PAD provided, however, that the	
	Planning and Zoning Board and City	
	Commission may require the platting	
	or replatting of the development site	
	when it determines that the platting	
	or replatting would be in the best	
	interest of the community.	
Sec. 3-502.C.12	Facing of buildings. Nothing in this	Complies.
	Division shall be construed as	
	prohibiting a building in a PAD from	
	facing upon a private street when	
	such buildings are shown to have	
	adequate access in a manner which	
	is consistent with the purposes and	
	objectives of these regulations and	
	such private street has been	
	recommended for approval by the	
	Planning and Zoning Board and	
Sec. 3-502.C.13	approved by the City Commission. Off-street parking and off-street	Complian
Sec. 3-502.C.13		Complies.
	loading standards and requirements.	Cubicat to annual butha Diagning and Zaning
	The off-street parking and off-street	Subject to approval by the Planning and Zoning
	loading standards and requirements	Board and City Commission.
	for a PAD shall conform to the	
	requirements of the applicable	
	zoning district. Off-street parking for	
	bicycles shall be provided as may be	
	required by the Planning and Zoning	
	Board and approved by the City	
	Commission. Where the parking for	
	the development is to be located	
	within a common parking area or a	
	parking garage, a restrictive	
	covenant shall be filed reserving	
	within the parking area or the parking	
	garage the required off-street	
	parking for each individual building	
	and/or use and such off-street	
	parking spaces shall be allocated	
	proportionately.	
Sec. 3-502.C.14	Boats and recreational vehicle,	To be regulated by Code Enforcement.
	parking. No boats and/or recreational	
	vehicles shall be parked on the	
	premises of a PAD unless such boats	
	and/or recreational vehicles are	
	located within an enclosed garage.	
Sec. 3-502.C.15	Accessory uses and structures. Uses	Complies.
	and structures which are customarily	Compiloo
	accessory and clearly incidental to	
	permitted uses and structures are	
	permitted in a PAD subject to the	
	provisions of Article 5, Division 1.	
	Any use permissible as a principal	
	use may be permitted as an	
	accessory use, subject to limitations	
	and requirements applying to the	

Zoning Code Section	Reference/Provision	Required/Provided
	principal use.	
Sec. 3-502.C.16	Signs. The number, size, character,	To be determined.
	location and orientation of signs and	
	lighting for signs for a PAD shall be in	PAD signage shall be in accordance with Article 5,
	accordance with Article 5, Division 19.	Division 19.
Sec. 3-502.C.17	Refuse and service areas. Refuse	Complies.
	and service areas for a PAD shall be	
	so designed, located, landscaped and	
	screened and the manner and timing	
	of refuse collection and deliveries, shipment or other service activities so	
	arranged as to minimize impact on	
	adjacent or nearby properties or	
	adjoining public ways, and to not	
	impede circulation patterns.	
Sec. 3-502.C.18	Minimum design and construction	Substitute alley easement is subject to review
	standards for private streets and	and approval by Public Works.
	drainage systems. The minimum	
	design and construction standards	
	for private streets in a PAD shall	
	meet the same standards as	
	required for public streets as	
	required by the Public Works	
	Department of the City of Coral	
	Gables. The minimum construction	
	standards for drainage systems shall	
	be in accordance with the Florida	
0 0 500 0 40	Building Code.	
Sec. 3-502.C.19	Ownership of PAD. All land included	To be determined.
	within a PAD shall be owned by the	
	applicant requesting approval of such development, whether that applicant	
	be an individual, partnership or	
	corporation, or groups of individuals,	
	partnerships or corporations. The	
	applicant shall present proof of the	
	unified control of the entire area	
	within the proposed PAD and shall	
	submit an agreement stating that if	
	the owner(s) proceeds with the	
	proposed development they will:	
	a. Develop the property in	
	accordance with:	
	i. The final development plan	
	approved by the City	
	Commission for the area.	
	ii. Regulations existing when the	
	PAD ordinance is adopted.	
	<li>iii. Such other conditions or modifications as may be</li>	
	attached to the approval of the	
	special-use permit for the	
	construction of such PAD.	
	b. Provide agreements and	
	declarations of restrictive	
	covenants acceptable to the City	

Zoning Code Section	Reference/Provision	Required/Provided
	Commission for completion of the development in accordance with	
	the final development plan as well	
	as for the continuing operation	
	and maintenance of such areas,	
	functions and facilities as are not to be provided, operated or	
	maintained at general public	
	expense.	
	c. Bind the successors and assigns	
	in title to any commitments made	
	under the provisions of the	
	approved PAD.	
Sec. 3-502.C.20	Compatibility with historic landmarks.	Not applicable.
	Where an historic landmark exists	
	within the site of a PAD the	
	development shall be required to be	
	so designed as to insure compatibility with the historic landmark.	
Sec. 3-502.C.21	Easements. The City Commission	Complies.
060. 0-002.0.21	may, as a condition of PAD approval,	Complies.
	require that suitable areas for	City Commission reserves the right to impose
	easements be set aside, dedicated	conditions of approval as deemed necessary.
	and/or improved for the installation of	
	public utilities and purposes which	
	include, but shall not be limited to	
	water, gas, telephone, electric power,	
	sewer, drainage, public access,	
	ingress, egress, and other public purposes which may be deemed	
	necessary by the City Commission.	
Sec. 3-502.C.22	Installation of utilities. All utilities	Complies.
	within a PAD including but not limited	p
	to telephone, electrical systems and	
	television cables shall be installed	
	underground.	
Sec. 3-502.C.23	Mixed-uses within a PAD. A PAD	Complies.
	may be so designed as to include	
	the establishment of complementary and compatible combinations of	
	office, hotel, multi-family and retail	
	uses which shall be oriented to the	
	development as well as the district in	
	which the development is located.	
Sec. 3-502.C.24	Common areas for PADs. Any	To be determined.
	common areas established for the	
	PAD shall be subject to the following:	
	a. The applicant shall establish a	
	property owner's association for	
	the ownership and maintenance	
	of all common areas, including	
	open space, recreational facilities,	
	private streets, etc. Such	
	association shall not be dissolved	
	nor shall it dispose of any	
	common areas by sale or	

Zoning Code Section	Reference/Provision	Required/Provided
	otherwise (except to an organization conceived and established to own and maintain the common areas), however, the conditions of transfer shall conform to the Development Plan.	
	b. Membership in the association shall be mandatory for each property owner in the PAD and any successive purchaser that has a right of enjoyment of the common areas.	
	<ul> <li>c. The association shall be responsible for liability insurance, local taxes, and the maintenance of the property.</li> </ul>	
	d. Property owners that have a right of enjoyment of the common areas shall pay their pro rata share of the cost, or the assessment levied by the association shall become a lien on the property.	
	e. In the event that the association established to own and maintain commons areas or any successor organization, shall at any time after the establishment of the PAD fail to maintain the common areas in reasonable order and condition in accordance with the Development Plan, the City Commission may serve written notice upon such association and/or the owners of the PAD and hold a public hearing. If deficiencies of maintenance are not corrected within thirty (30) days after such notice and hearing the City Commission shall call upon any public or private agency to maintain the common areas for a period of one year. When the City Commission determines that the subject organization is not prepared or able to maintain the common areas such public or private agency shall continue maintenance for yearly periods.	
	<ul> <li>f. The cost of such maintenance by such agency shall be assessed proportionally against the</li> </ul>	

Zoning Code Section	Reference/Provision	Required/Provided
	properties within the PAD that have a right of enjoyment of the common areas and shall become a lien on said properties.	
	g. Land utilized for such common areas shall be restricted by appropriate legal instrument satisfactory to the City Attorney as common areas in perpetuity in accordance with the provisions of Article 5, Division 23. Such instrument shall be recorded in the Public Records of Dade County and shall be binding upon	
	the developer, property owners association, successors, and assigns and shall constitute a covenant running with the land.	
Sec. 3-502.D	Exemptions to PAD minimum development standards for configuration of land requirements. Exemptions to minimum development standards may be considered for Assisted Living Facilities (ALF) and/or Affordable Housing Facilities that would allow parcels of land to be noncontiguous as prescribed herein. These exemptions shall only be available to PAD developments that satisfy all of the following criteria:	Not applicable.
	1. The project demonstrates that it would result in beneficial effects, serve important public interests, and not result in significant adverse impacts to the environment, residential areas, public services and facilities, or the desired character of an area.	
	2. A minimum of seventy five (75%) percent of the total gross square footage of all buildings and ancillary ALF support uses (including square footage of recreational areas, support services, mechanical, etc) is dedicated as an assisted living facility and/or affordable housing facility.	
	<ol> <li>A maximum of two (2) noncontiguous parcels may be combined.</li> </ol>	
	4. The two (2) noncontiguous	

Zoning Code Section	Reference/Provision	Required/Provided
	<ul> <li>properties have the following designations:</li> <li>a. Commercial land use designation(s) and commercial zoning designation(s); or</li> <li>b. Industrial land use designation and industrial zoning designation.</li> </ul>	
	5. The proposed noncontiguous parcels are within one hundred and twenty (120) feet of one another. Such distance shall be measured by a straight line between the closest property lines of the properties.	
	ment plan – General requirements.	
Sec. 3-502.D.1	Professional services required: plans for buildings or structures within a Planned Area Development shall be prepared by a registered Architect with the assistance of a registered Engineer and a registered Landscape Architect, all being qualified under the laws of the State of Florida to prepare such plans.	Complies.
Sec. 3-502.D.2	Legal description of site: should the legal description of the site for a Planned Area Development contain a metes and bounds description, such description shall be prepared by a registered land surveyor. The legal description shall be accompanied by a map at a scale suitable for reproduction for advertising for public hearing, showing exact location of the development.	Complies.
Sec. 3-502.D.3	Development proposal: the Development Plan shall consist of a map or map series and any technical reports and supporting data necessary to substantiate, describe or aid the Development Plan. The plans for the development proposal shall include the following written and graphic materials:	See review provided below.
Sec. 3-502.D.3.a	<ul> <li>Site condition map: site condition map or map series indicating the following: <ol> <li>Title of Planned Area</li> <li>Development and name of the owner(s) and developer.</li> </ol> </li> <li>Scale, date, north arrow and the relationship of the site to such external facilities as highways, roads, streets, residential areas, shopping areas and cultural</li> </ul>	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	<ul> <li>complexes.</li> <li>iii. Boundaries of the subject property, all existing streets, buildings, water courses, easements, section lines and other important physical features within the proposed project. Other information on physical features affecting the proposed project as may be required.</li> <li>iv. Existing contour lines at one foot intervals. Datum shall be National Geodetic Vertical Datum (N.G.V.D.) (if required by City Staff).</li> <li>v. The location of all existing storm drainage, water, sewer, electric, telephone and other utility provisions.</li> </ul>	
Sec. 3-502.D.3.b	Plan of pedestrian and vehicular circulation showing the location and proposed circulation system of arterial, collector, local and private streets, including driveways, service areas, loading areas and points of access to existing public rights-of- way and indicating the width, typical sections and street names. The applicant is encouraged to submit one (1) or more companion proposals for a pedestrian system, transit system or other alternative for the movement of persons by means other than privately owned automobiles.	Complies.
Sec. 3-502.D.3.c	Exterior facade elevations (if deemed appropriate or necessary by City Staff) of all proposed buildings to be located on the development site.	Complies.
Sec. 3-502.D.3.d	Isometrics or perspective and/or massing model(s) (if deemed appropriate or necessary by City Staff) of the proposed development.	Complies.
Sec. 3-502.D.3.e	Map of existing land use.	Complies.
Sec. 3-502.D.3.f	Existing and proposed lot(s) lines and/or property lines.	Complies.
Sec. 3-502.D.3.g	Master site planA general plan for the use of all lands within the proposed Planned Area Development. The plan shall serve as the generalized zoning for the development and shall guide the location of permissible uses and structures. Such plan shall show the general location, function and extent of all components or units of the plan, indicating the proposed gross	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	floor area and/or floor area ratio of all existing and proposed buildings, structures and other improvements including maximum heights, types and number of dwelling units, landscaped open space provisions such as parks, passive or scenic	
	areas, common areas, leisure time facilities, and areas of public or quasi-public institutional uses.	
Sec. 3-502.D.3.h	Location and size of all existing and	To be determined.
	proposed signs.	PAD signage shall be in accordance with Article 5, Division 19.
Sec. 3-502.D.3.i	Existing and proposed utility systems including sanitary sewers, storm sewers and/or storm water drainage system and water, electric, gas and telephone lines. The applicant shall submit a statement indicating what proposed arrangements have been made with appropriate agencies for the provision of needed utilities to and within the Planned Area Development including, water supply, sewer, storm drainage collection and disposal, electric power, gas, and telephone.	To be provided if required by Public Works.
Sec. 3-502.D.3.j	General landscape plan indicating the proposed treatment of materials used for public, private and common open spaces and treatment of the perimeter of the development including buffering techniques such as screening, berms and walls, significant landscape features or areas shall be noted as shall the provisions for same.	Complies.
Sec. 3-502.D.3.k	Description of adjacent land areas, including land uses, zoning, densities, circulation systems, public facilities, and unique natural features of the landscape.	Complies.
Sec. 3-502.D.3.I	Proposed easements for utilities, including water, power, telephone, storm sewer, sanitary sewer and fire lanes showing dimensions and use.	Complies.
Sec. 3-502.D.3.m	Location of proposed off-street parking. Smaller developments (as determined by the Planning Director) shall also be required to include stall size, aisle widths, location of attendant spaces, number of spaces by use, number of standard and compact spaces.	Complies.
Sec. 3-502.D.3.n	Location and designation of historic landmarks located within the development site which have been	Not applicable.
Zoning Code Section	Reference/Provision	Required/Provided
------------------------	---	--
	approved as provided within the Zoning Code or notation of those structures which may be worthy of	
Sec. 3-502.D.3.o	historic designation. Certified survey showing property	Complies.
	boundary, existing buildings and their dimensions, setbacks from streets, (public and private) and property lines, easements, streets, alleys, topographical data, water areas, unique natural features, existing vegetation and all trees with an upright trunk of either nine (9) or more inches in circumference (as measured at the narrowest point below four and one-half (4½) feet above ground level) or twelve (12) or more feet in height (if required by City Staff).	
Sec. 3-502.D.3.p	Proposed development schedule indicating the appropriate date when construction of the development can be expected to begin and be completed, including initiation and completion dates of separate phases of a phased development and the proposed schedule for the construction and improvement of common areas within said phases, including any auxiliary and/or accessory buildings and required parking.	To be provided. Include in City Commission application submittal package a phasing plan (see Overall Site Plan; Sheet A-06) with projected construction initiation and completion dates.
Sec. 3-502.D.3.q	Location and designation of proposed traffic regulation devices within the development.	Complies.
Sec. 3-502.D.3.r	<ul> <li>Statistical information including: <ol> <li>Total square footage and/or acreage of the development site.</li> <li>Maximum building coverage expressed as a percentage of the development site area.</li> </ol> </li> <li>The land area (expressed as a percent of the total site area) devoted to: <ul> <li>(a)Landscaped open space; and</li> <li>(b)Common areas usable for recreation or leisure purposes.</li> </ul> </li> </ul>	Complies.
Sec. 3-502.D.3.s	Copies of any covenants, easements and/or agreements required by this section or any other ordinance and/or regulations for the Planned Area Development.	Complies.
Article 3. Development		
Sec. 3-1201	Abandonment and Vacation of Non- Fee Interests.	Substitute alley easement is subject to review and approval by Public Works.
Sec. 3-2001	Art in Public Places.	Requires review by Economic Sustainability.

Zoning Code Section	Reference/Provision	Required/Provided
Section 4-201. Mixed	Use District (MXD)	
Sec. 4-201.A.7.e.i.	MXD development permitted within (C) Commercial and (I) Industrial Districts only.	Complies.
D. Performance Standa		
Sec. 4-201.D.2	Minimum site area for an MXD project/building. Twenty-thousand (20,000) square	Complies.
	feet.	
Sec. 4-201.D.4	Lot coverage.	Complies.
Sec. 4-201.D.5	No minimum or maximum.	Complies.
	Mixed use percentages. Provide min. 8% total sq. ft., or entire ground floor, whichever is greater, as ground floor uses.	Complies.
E. Building regulations		
Sec. 4-201.E.2	Encroachments for balconies, awnings, etc. Subject to applicable regulations.	To be determined at review of final drawings.
Sec. 4-201.E.4	Floors. No minimum or maximum required.	Complies.
Sec. 4-201.E.5	Floor-to-floor height. The minimum floor-to-floor height shall be permitted as regulated per the Building Code.	Floor-to-floor height to be approved by the Building Official.
Sec. 4-201.E.7	Heights of architectural elements, etc.	Complies.
	<ul> <li>The maximum allowable height(s), subject to satisfying Article 3, Division 4, Conditional Uses, of architectural elements, spires, bell towers, elevator housings or similar non-habitable structures for the following underlying zoning designations and uses may be granted as follows:</li> <li>Commercial Limited District: Up to and including 15 feet.</li> <li>Industrial and Commercial</li> </ul>	
	<ul><li>Districts: Up to and including 25 feet.</li><li>Manufacturing uses: Up to and including 10 feet.</li></ul>	
Sec. 4-201.E.9	Number of buildings per site. No minimum or maximum required.	Complies.
Sec. 4-201.E.10	Ground floor building frontage on primary streets. Minimum 50% of the linear ground floor building frontage shall include retail sales and service, office, or restaurant or public realm	Complies.
Sec. 4-201.E.11	land area uses. Ground floor building frontage on	Complies.
060. 4-201.E.11		Complies.

Reference/Provision	Required/Provided
secondary streets. Minimum 40% of the linear ground floor building	
service, office, or restaurant or public	
Retail frontage on alleys. No	Complies.
Residential density. Up to a	Complies.
except for properties in the Central Business District (CBD) and the North and South Industrial Mixed Use Districts. There shall be no density limitations in the CBD and the North and South Industrial Mixed Use Districts.	No residential density limitations for individual MXD projects located within the CBD.
Setbacks (buildings). Front: Up to 45 feet in height: None. If	Complies.
<ul> <li>Side: Interior side: None.</li> <li>Side street: 15 feet.</li> <li>Rear: Abutting a dedicated alley or street: None. No abutting alley or street: 10 feet.</li> <li>Balconies: Cantilevered open balconies may project into the required setback areas a maximum of 6 feet.</li> <li>Applicants and property owners desiring to develop pursuant to these regulations may not seek a variance for relief or reduction in building setbacks. Reductions are only permitted subject to the below listed regulations.</li> </ul>	Mediterranean Bonus provisions permit reduction of setbacks to zero (0) feet.
Setback reductions and vertical building stepbacks. Reduction in setbacks. Setbacks may be reduced subject to the following standards: Minimum percentage of open space. A minimum of 50% of the total ground floor square footage received from the setback reduction is provided as publicly accessible street level open space and landscape area on the private property. The open space is subject to the following: • Types of open space. Types of open space shall be in the form of courtyards, plazas, arcades/loggias, pedestrian pass- throughs and open atriums adjacent/contiguous to the adjacent rights-of-way.	Complies.
	<ul> <li>secondary streets. Minimum 40% of the linear ground floor building frontage shall include retail sales and service, office, or restaurant or public realm land area uses.</li> <li>Retail frontage on alleys. No minimum or maximum required.</li> <li>Residential density. Up to a maximum of 125 units per acre except for properties in the Central Business District (CBD) and the North and South Industrial Mixed Use Districts. There shall be no density limitations in the CBD and the North and South Industrial Mixed Use Districts.</li> <li>Setbacks (buildings).</li> <li>Front: Up to 45 feet in height: None. If over 45 feet in height: 10 feet.</li> <li>Side street: 15 feet.</li> <li>Rear: Abutting a dedicated alley or street: None. No abutting alley or street: 10 feet.</li> <li>Balconies: Cantilevered open balconies may project into the required setback areas a maximum of 6 feet.</li> <li>Applicants and property owners desiring to develop pursuant to these regulations may not seek a variance for relief or reduction in building setbacks. Reductions are only permitted subject to the below listed regulations.</li> <li>Setback reductions and vertical building stepbacks.</li> <li>Reduction in setbacks. Setbacks may be reduced subject to the following standards: Minimum percentage of open space. A minimum of 50% of the total ground floor square footage received from the setback reduction is provided as publicly accessible street level open space and landscape area on the private property. The open space is subject to the following:</li> <li>Types of open space. Types of open space shall be in the form of courtyards, plazas, arcades/loggias, pedestrian pass- throughs and open atriums adjacent/contiguous to the</li> </ul>

Zoning Code Section	Reference/Provision	Required/Provided
	(i.e., plazas) shall be 500 square	
	feet.	
	<ul> <li>Include both hard and softscape</li> </ul>	
	landscape improvements and pedestrian amenities.	
	<ul> <li>Vertical volume. As a minimum</li> </ul>	
	include a vertical volume of space	
	equal from street level to the first	
	floor height or a minimum of 13	
	feet. Additional height may be recommended.	
	<ul> <li>Restaurant seating. This area may</li> </ul>	
	be used for outdoor restaurant	
	seating subject to approval as	
	provided for in these regulations.	
	Vertical building stepbacks. A	
	vertical building stepback of a	
	minimum of 10 feet shall be provided at a maximum height of	
	45 feet on all façades. Additional	
	vertical building stepbacks may be	
	required by City Architect and	
	Board of Architects to further	
	reduce the potential impacts of the	
F. Design regulations.	building bulk and mass.	
Sec. 4-201.F.2	Architectural relief and elements	Complies.
	shall be provided on all sides of	Complicat
	buildings and include similar	
	architectural features as to those	
	provided on the front façade. No	
	blank walls shall be permitted unless required pursuant to applicable Fire	
	and Life Safety Code requirements.	
Sec. 4-201.F.3	Building support services. All	Complies.
	mechanical, electrical and other	
	associated support service areas	
	shall be located entirely within the structure.	
Sec. 4-201.F.4	Facades in excess of 150 feet in	Approved by the Board of Architects on
	length, shall incorporate design	05/08/2014.
	features with the use of, but not	
	limited to the following items:	
	<ul> <li>(a) Breaks, stepbacks or variations in bulk/massing at a minimum of</li> </ul>	
	100 foot intervals.	
	(b) Use of architectural relief and	
	elements.	
Sec. 4-201.F.5	Lighting (street). Decorative street	Complies.
	lighting shall be provided and located	
	on all streets/rights-of-way subject to the following:	
	<ul> <li>Light fixtures/poles up to thirty-five</li> </ul>	
	(35) feet in height.	
	Subject to all other applicable City	
	code provisions.	
Sec. 4-201.F.6	Lighting (building). External	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	illumination and lighting of buildings shall require Planning Department and Planning and Zoning Board review and recommendation with approval of the City Commission.	Subject to review and recommendation by the Planning and Zoning Board and approval by the City Commission.
Sec. 4-201.F.7	Lighting (landscaping). Lighting in the form of uplighting of landscaping is encouraged.	Complies.
Sec. 4-201.F.8	Outdoor storage. The storage of materials, goods, merchandise, and equipment for the purpose of display and/or sales outside the confines of any buildings or structures is prohibited.	To be regulated by Code Enforcement.
Sec. 4-201.F.9	Overhead doors. Overhead doors shall not face or be directed towards residential properties and/or adjacent rights-of-way abutting residentially zoned properties.	Complies.
Sec. 4-201.F.10	<ul> <li>Paver treatments. Paver treatments shall be included in the following locations:</li> <li>Driveway entrances.</li> <li>Crosswalks.</li> <li>Sidewalks. Minimum of 25% of paving surface.</li> </ul>	Complies.
Sec. 4-201.F.11	Parking garages. Parking garages shall include exterior architectural treatments compatible with buildings or structures which occupy the same development and/or street.	Approved by the Board of Architects on 05/08/2014.
Sec. 4-201.F.12	Pedestrian access orientation. All buildings, except accessory buildings, shall have their main pedestrian entrance or entrances oriented towards the front property line.	Complies.
Sec. 4-201.F.13	Pedestrian amenities. Pedestrian amenities shall be provided on both private property and/or public open spaces including but not limited to the following: benches, information kiosks, lighting, bike racks, refuse containers, sidewalk pavement treatments, statuary, street crosswalk paver treatments, wall mounted fountains, water fountains and other similar water features. All pedestrian amenities shall be permanently secured to the ground surface. Above amenities shall be consistent in design and form with the applicable City Public Realm Design Manual.	Complies.
Sec. 4-201.F.14	Pedestrian design features for building frontages (street level only). On any front property line or primary	Approved by the Board of Architects on 05/08/2014.

Zoning Code Section	Reference/Provision	Required/Provided
	street, where an adjoining pedestrian	
	sidewalk is located, the following	
	design features shall be included:	
	<ul> <li>Display windows or retail display area;</li> </ul>	
	<ul> <li>Landscaping; and/or,</li> </ul>	
	<ul> <li>Architectural building design</li> </ul>	
	features.	
	The intent is to create pedestrian	
	and shopper interest, preclude	
	inappropriate or inharmonious	
	design, preclude blank walls of	
	building faces, and prohibit windows	
	from being permanently obstructed.	
Sec. 4-201.F.15	Pedestrian pass-throughs/paseo.	Approved by the Board of Architects on
	Pedestrian pass-throughs shall be	05/08/2014.
	provided for each 250 linear feet or	
	fraction thereof of building frontage	
	provided on the primary street. The	
	pass through shall be subject to the	
	following: <ul> <li>Minimum of 10 feet in width.</li> </ul>	
	<ul> <li>Include pedestrian amenities as defined herein.</li> </ul>	
	In lieu of providing one (1) pass	
	through of ten (10) feet every two	
	hundred and fifty (250) feet of	
	building frontage, two (2) pass-	
	throughs can be combined to provide	
	one (1), twenty (20) foot wide pass-	
	through.	
Sec. 4-201.F.16	Porte-cocheres. Porte-cocheres are	Not applicable.
	prohibited on front property line or	
	primary street.	
Sec. 4-201.F.17	Rooftop screening. All mechanical,	Approved by the Board of Architects on
	electrical, cellular antennas and	05/08/2014.
	other similar roof top building support	
	services shall be entirely screened	
	from public view subject to the	
	discretion and approval from the	
	Board of Architects for design and	
	screening material. Landscaping	
	may be used as a screening material at the discretion of the Board of	
	Architects.	
G. Landscaping.		
Sec. 4-201.G.1	Landscape open space requirements	See review provided under Article 5, Division 11
000.1201.0.1	are satisfied pursuant to the rights-	below.
	of-way planting requirements listed	5000.
	in Article 5, Division 11.	
H. Parking/vehicle stor		
Sec. 4-201.H.1	Bicycle storage. To encourage the	Complies.
	use of bicycles a minimum of one 10	·
	foot bicycle rack for each 250	
	parking spaces or fraction thereof	
	shall be provided. The location shall	
	be convenient to users and shall be	
	subject to review as a part of the site	

Zoning Code Section	Reference/Provision	Required/Provided
	plan review.	
Sec. 4-201.H.2	Boats and recreational vehicles, or similar accessory vehicles. These vehicles shall be parked and/or stored within an enclosed garage, area or structure.	To be regulated by Code Enforcement.
Sec. 4-201.H.3	Raised curbing. Six (6) inch raised curbing shall be provided on all streets abutting this use. Curb cuts and ramps for handicapped access shall also be provided at all street intersections and points of pedestrian crossing.	To be reviewed and approved by Public Works.
Sec. 4-201.H.4	Loading/unloading areas. Off-street loading standards and requirements shall conform to the requirements as set forth in Article 5, Division 14. All loading/unloading areas and/or facilities shall be within fully enclosed areas with overhead doors. Overhead doors shall remain closed when not in use and after hours.	Complies.
Sec. 4-201.H.6	On-street parking. On-street parking must be provided on both sides of the street on all primary streets, unless encroachments for arcades/loggias are requested. Evaluation as to the amount of on-street parking provided shall be evaluated on a case-by- case basis. On-street parking shall not be included as satisfying the required parking requirements. On-street parking is encouraged on alleys. Removal of on-street parking shall be subject to compensation to the City based upon established City provisions.	To be approved by Parking, Public Service and Public Works.
Sec. 4-201.H.7	Parking garages. Ground floor parking that is located and fronting on a primary street is prohibited. Ground floor parking is permitted on secondary streets and shall be fully enclosed within the structure and shall be surrounded by retail uses. Ground floor parking is permitted on alley frontages. Parking facilities shall accommodate pedestrian access to all adjacent	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	streets and alleys.	
Sec. 4-201.H.8	Parking space limitations. Restricting	Complies.
	and/or assignment of off-street	
	parking spaces for individual tenant	
	or users with the use of signage,	
	pavement markings, etc., are permitted.	
Sec. 4-201.H.9	Residential uses. Off-street parking	Complies.
2000. 1 201.11.0	requirements shall conform to the	
	requirements as set forth in Article 5,	
	Division 14.	
Sec. 4-201.H.10	Surface parking areas. Surface	Complies.
	parking lots and/or similar vehicle	
	use areas are prohibited to front on	
0 4 004 11 44	primary streets.	
Sec. 4-201.H.11	Valet parking areas. If valet parking	Valet parking, if utilized, must be located entirely
	is desired, the valet parking drop-off areas shall be provided on private	on private property and is prohibited from parking in any proposed tandem parking spaces.
	property. Tandem and/or stacking of	in any proposed tandem parking spaces.
	parking are prohibited.	
I. Sanitation and servi		
Sec. 4-201.I.1	General. In accordance with Article	To be reviewed and approved by Public Service.
	5, Division 17.	
J. Signs.		
Sec. 4-201.J.1	General. In accordance with Article	To be determined.
	5, Division 19.	PAD signage shall be in accordance with Article 5,
		Division 19.
K. Streets and alleys.	•	
Sec. 4-201.K.1	Streets and alleys. Property owner(s)	Substitute alley easement is subject to review
	may request the vacation and/or	and approval by Public Works.
	abandonment of a public right-of-way	
	subject to the criteria and procedure in Article 3, Division 12.	
Sec. 4-201.K.2	Driveways.	Complies.
0ec. 4-201.N.2	Diveways.	Complies.
	Vehicular access to parking garages	
	shall be from a side street or alley.	
	Vehicular egress/ingress, including	
	but not limited to driveways, service	
	drives, drive-throughs, etc., may be	
	permitted from a primary street and	
	shall be evaluated as part of site	
	plan review based upon the project	
	design in relation to existing	
	surrounding circulation. Valet access points are exempt from these	
	provisions.	
	Vehicular entrances for drive-through	
	facilities, garage entrances, service	
	bays and loading/unloading facilities	
	should be consolidated into one (1)	
	curb cut to reduce the amount of	
	vehicular penetration into pedestrian sidewalks and adjoining rights-of-way.	
Sec. 4-201.K.3	Sidewalks and adjoining rights-or-way.	Complias
Sec. 4-201.K.3	Sidewalks.	Complies.

Zoning Code Section	Reference/Provision	Required/Provided
	Pedestrian pathways and/or sidewalks shall connect to one another to form a continuous pedestrian network from parking garage entrances, parking areas, primary and secondary pedestrian entrances, etc. Wherever possible pathways shall be separated from vehicular traffic.	
	Sidewalks shall be located on both sides of all streets with a minimum of four (4) foot unobstructed clear area. The clear area shall be unobstructed by utility poles, fire hydrants, benches, trash receptacles, newspaper stands, light poles, planter boxes, telephone booths or other similar temporary or permanent structures (traffic signage shall be exempt from the above regulations).	
	Sidewalks at points of street intersections or pedestrian crossing shall be sloped in such a manner as to accommodate handicapped access with the use of two (2) curb cuts and/or ramps at each street intersection.	
L. Utilities.		
Sec. 4-201.L.1	Underground utilities. All utilities shall be installed underground in accordance with the provisions of Article 5, Division 22.	To be reviewed and approved by Public Works.
Sec. 4-201.L.2	Above ground utilities. Above ground, façade, roof, mechanical and electrical facilities shall be appropriately screened to entirely hide the facility in accordance with the provisions of Article 5, Divisions 11 and 18. Screening materials may include landscaping, walls, fencing, etc., to achieve one hundred (100%) percent opacity. Approval of type of screening shall be determined at time of site plan review.	To be determined. Need to show all proposed utilities and mechanical equipment with required screening. Determination requires full-size set of plans for review.
M. Miscellaneous.	· · ·	
Sec. 4-201.M.1	Configuration of land. The parcel proposed for development shall be a contiguous unified parcel with sufficient width and depth to accommodate the proposed uses. Public rights-of-way or other public lands shall not be considered as a separation.	Complies.
Sec. 4-201.M.2	Easements. The City may, as a condition of approval, require that	Substitute alley easement is subject to review and approval by Public Works.

Zoning Code Section	Reference/Provision	Required/Provided
	suitable areas for easements be set aside, dedicated and/or improved for	City Commission may require additional
	the installation of public utilities and	conditions of approval as deemed necessary.
	purposes which include, but shall not	
	be limited to water, gas, telephone,	
	electric power, sewer, drainage,	
	public access, ingress, egress, open	
	space, recreation and other public	
	purposes which may be deemed necessary by the City Commission.	
Sec. 4-201.M.3	Encroachments into public rights-of-	To be reviewed and approved by Public Works.
	way. Any encroachments,	
	construction and penetration into the	
	rights-of-way shall be subject to the	
	following: <ul> <li>The property owners shall be</li> </ul>	
	responsible for all maintenance of	
	all encroachments and/or property	
	of all surrounding public rights-of-	
	way, including but not limited to	
	the following: landscaping (hard	
	and softscape); benches; trash	
	receptacles; irrigation; kiosks;	
	plazas; open spaces; recreational	
	facilities; private streets, etc.	
	subject to all the provisions for	
	which the development was	
	approved as may be amended.	
	The property owners shall be responsible for liability insurance	
	responsible for liability insurance, local taxes, and the maintenance	
	of the encroachment and/or	
	property.	
Sec. 4-201.M.4	Live work units.	Not applicable.
	Each live work unit, including the	
	garage (if applicable), shall be	
	separated by walls from other live	
	work units or other uses in the	
	building, and shall have the ability	
	to construct separate entrances to	
	each use in the future.	
Sec. 4-201.M.6	Transfer of density and floor area	Complies.
	ratio within the site plan. The density	
	and floor area ratio may be	
	transferred throughout the	
Section 4 202 Comm	contiguous unified parcel.	
Section 4-302. Comm	. ,	To be reviewed and approved by Zening when
Sec. 4-302.B	Permitted uses.	To be reviewed and approved by Zoning when obtaining certificate of use permits.
Sec. 4-302.C	Conditional uses.	To be reviewed and approved by Zoning when obtaining certificate of use permits.
Sec. 4-302.D	Performance standards.	Proposed mixed-use building must comply with
		Performance Standards for mixed-use
		developments in overlay district. See review
		provided under "Section 4-201. Mixed Use
		District (MXD)" above.

Zoning Code Section	Reference/Provision	Required/Provided	
Sec. 4-302.D.7. Additio	Sec. 4-302.D.7. Additional standards for mixed-use development.		
Sec. 4-302.D.7.a	Mix of uses. In order to encourage	Complies.	
	the creative mix of uses, all mixed-		
	use developments shall have at least eight (8%) percent or the entire		
	ground floor of retail commercial		
	and/or office uses. The remaining		
	portions of the building may be uses		
	permitted in the underlying zoning		
	designations.		
Sec. 4-302.D.7.b	Floor area ratio. When multiple	Complies.	
	uses are incorporated into a		
	development of four (4) or more		
	stories in height, the floor area ratio		
	(FAR) for each use shall be individually determined and the		
	highest of the individual FAR shall be		
	applied to the entire development.		
Sec. 4-302.D.7.c	Ground floor treatment. Ground floor	Approved by the Board of Architects on	
	treatment for all Mixed-Use	05/08/2014.	
	development shall be pedestrian		
	oriented, and shall detail the percent		
	glazing to solids, pedestrian-oriented		
	landscaping and other features when		
	submitting to the Board of Architects and Planning and Zoning Board.		
Article 5 – Developme			
•	t Standards. Division 11. Landscaping		
Sec. 5-1104.A	See Zoning Code Sec. 5-1104.A for	Compliance required at time of final plan	
	general requirements that are applicable to all rights-of-way and	submittal.	
	private properties within the City.		
Section 5-1105. Landso			
Sec. 5-1105.A	Public rights-of-way. Must comply	Requires review and approval by Public Service	
	with items 1 thru 6 of Zoning Code	and Public Works.	
	Section 5-1105.A.		
Sec. 5-1105.C	Other properties. Must comply with	Requires review and approval by Public Service	
	items 1 thru 3 of Zoning Code	and Public Works.	
Article C. Development	Section 5-1105.C.	ing and Driveryou Deguinements	
Sec. 5-1402.A	t Standards. Division 14. Parking, Loadi Dimensions and configuration of	To be determined.	
3ec. 5-1402.A	parking spaces.	To be determined.	
		Compliance required at time of final plan	
	1. Required parking space	submittal.	
	dimensions:		
	a. Parallel parking spaces: 9		
	feet by 22 feet.		
	b. Angled parking spaces: 8 <sup>1</sup> / <sub>2</sub>		
	feet by 18 feet.		
	<ul> <li>c. Disabled parking spaces shall be dimensioned in accordance</li> </ul>		
	with Chapter 11 of the Florida		
	Building Code.		
	-		
	2. Wheel stops and curbing. Precast		
	concrete wheel stops or curbing		
	shall be provided for all angled	Bage 22	

Zoning Code Section	Reference/Provision	Required/Provided
	parking spaces that abut a sidewalk such that cars are curbed at 16 ½ feet. The balance of the required depth of the parking spaces between the wheel stop or curb and the sidewalk shall be clear of obstructions.	
	3. Required aisle widths. Minimum required aisle widths for two-way aisles: 22 feet.	
Sec. 5-1402.B	Dimensions of loading spaces. Loading spaces shall be at least 10 feet wide by 25 feet long, and shall provide at least 14 feet of vertical clearance.	To be determined. Compliance required at time of final plan submittal.
Sec. 5-1406.A	<ol> <li>General.</li> <li>All triangles of visibility that are required by this Section shall be kept clear of visual obstructions between a height of 2½ feet and 8 feet above the established grade.</li> <li>Visibility triangles for driveways and intersections that are not included in this section shall be provided in accordance with the standards set out in the Miami-Dada County Code</li> </ol>	Complies.
Sec. 5-1409.B	Dade County Code. Calculation of parking requirements. (List parking requirements for each proposed use as specified in Zoning Code Section 5-1409. Amount of	Complies. See Sheet A-0.5.1 for parking calculations.
Sec. 5-1410.A	required parking) Tandem spaces. Tandem spaces are permitted as required parking; provided each set of tandem parking spaces are assigned to an individual	Not applicable.
Sec. 5-1410.B.2	<ul> <li>unit within the building.</li> <li>Vertical parking lifts may utilize the following maximum percentages to satisfy required parking spaces, calculated at two (2) parking spaces per lift, within a building:</li> <li>a. Twenty percent (20%) of the first fifty (50) parking spaces; and,</li> <li>b. Ten percent (10%) from fifty-one (51) spaces to two-hundred (200) spaces; and</li> <li>c. Five (5%) percent thereafter.</li> <li>Vertical parking lift systems shall be limited to two-levels/decks and each lift shall be controlled exclusively by one (1) tenant/unit</li> </ul>	Not applicable.





Attachment

#### MIAMI DAILY BUSINESS REVIEW

Published Daily except Saturday, Sunday and Legal Holidays Miami, Miami-Dade County, Florida

#### STATE OF FLORIDA COUNTY OF MIAMI-DADE:

Before the undersigned authority personally appeared M. ZALDIVAR, who on oath says that he or she is the LEGAL CLERK, Legal Notices of the Miami Daily Business Review f/k/a Miami Review, a daily (except Saturday, Sunday and Legal Holidays) newspaper, published at Miami in Miami-Dade County, Florida; that the attached copy of advertisement, being a Legal Advertisement of Notice in the matter of

CITY OF CORAL GABLES LOCAL PLANNING AGENCY (LPA) PUBLIC HEARING - JUNE 11, 2014

in the XXXX Court. was published in said newspaper in the issues of

05/30/2014

Affiant further says that the said Miami Daily Business Review is a newspaper published at Miami in said Miami-Dade County, Florida and that the said newspaper has heretofore been continuously published in said Miami-Dade County, Florida, each day (except Saturday, Sunday and Legal Holidays) and has been entered as second class mail matter at the post office in Miami in said Miami-Dade County, Florida, for a period of one year next preceding the first publication of the attached copy of advertisement; and affiant further says that he or she has neither paid nor promised any person, firm or corporation any discount, rebate, commission or refund for the purpose of securing this advertisement for publication in the said newspaper,

Sworn to and subscriber be e me th

A.D. 30

(SEAL)

M. ZALDIVAR personally known to me



#### CITY OF CORAL GABLES, FLORIDA NOTICE OF PUBLIC HEARING

City Public	Local Planning Agency (LPA)/
Hearing	Planning and Zoning Board
Dates/Times	Wednesday, June 11, 2014, 6:00 - 9:00 p.m.
Location	City Commission Chambers, City Hall, 405 Biltmore Way, Coral Gables, Florida, 33134

PUBLIC NOTICE is hereby given that the City of Coral Gables, Florida, Local Planning Agency (LPA)/ Planning and Zoning Board (PZB) will conduct Public Hearings on the following:

Items 1 and 2 are related.

- 1. An Ordinance of the City Commission of Coral Gables, Florida requesting review of a Planned Area Development (PAD) pursuant to Zoning Code Article 3, "Development Review", Division 5, "Planned Area Development (PAD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for severability, repealer, codification, and an effective date. (Legal description on file at the City)
- 2. A Resolution of the City Commission of Coral Gables, Florida requesting mixed use site plan review pursuant to Zoning Code Article 4, "Zoning Districts", Division 2, "Overlay and Special Purpose Districts", Section 4-201, "Mixed Use District (MXD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for an effective date. (Legal description on file at the City)
- 3. An Ordinance of the City Commission of Coral Gables, Florida providing for text amendments to the City of Coral Gables Official Zoning Code, Article 3, "Development Review", Division 10, "Transfer of Development Rights (TDR)", by expanding the area for qualifying TDR sending sites to include historically designated properties within a Multi-Family 2 (MF2) District located in the area north of the Central business District (CBD) bounded by, SW 8th Street (north), Navarre Avenue (south), Douglas Road (east) and LeJeune Road (west); providing for severability, repealer, codification and an effective date.
- 4. An Ordinance of the City Commission of Coral Gables, Florida, repealing Sections 101-20, 101-21, 101-22, 101-23, 101-24, 101-25 And 101-26 of Article II, Development Review Committee, of Chapter 101, Administration And Enforcement, of the Coral Gables Code of Ordinances in its entirety; and Division 8 of Article 2. Decision Making



and Administrative Bodies, of the Official Zoning Code of Coral Gables in its entirety; providing for a new Division 8, of Article 2, Official Zoning Code of Coral Gables, by updating, revising and codifying Development Review Committee (DRC) procedures and review requirements as originally established in Ordinance No. 2003-45; providing for severability, repealer, codification and an effective date.

All interested parties are invited to attend and participate. Upon recommendation by the Board, the applications will be scheduled for City Commission consideration. Please visit the City webpage at www.coralgables.com to view information concerning the applications. The complete applications are on file and available for examination during business hours at the Planning and Zoning Division, 427 Biltmore Way, Suite 201, Coral Gables, Florida, 33134. Questions and written comments can be directed to the Planning Division at planning@ coralgables.com (FAX: 305.460.5327) or 305.460.5211.

Ramon Trias Director of Planning and Zoning Planning & Zoning Division

City of Coral Gables, Florida

Any person, who acts as a lobbyist pursuant to the City of Coral Gables Any person, who acts as a topoyist pursuant to the City of Coral Gables Ordinance No. 2006-11, as amended, must register with the City Clerk prior to engaging in lobbying activities before City Staff, Boards, Committees or City Commission. A copy of the Ordinance is available in the Office of the City Clerk, City Hall. If a person decides to appeal any decision made by a Board. Committee or City Commission with respect decision made by a Board, Committee or City Commission with respect to any matter considered at a meeting or hearing, that person will need to ensure that a verbatim record of the proceedings is made, which record includes the testimony and evidence upon which the appeal is to be based (F.S. 286.0105). Any meeting may be opened and continued and, under certain circumstances, additional legal notice will not be provided. Any person requiring special accommodations for participation in the proceedings or the materials in accessible format should contact Walter Carlson, Assistant City Planner at 305.460.5211, no less than three working days prior to the meeting. All meetings are telecast live on Coral Gables TV Channel 77.

14-3-171/2291396M

5/30

			Attachment	
	Court	of Coral Gables esy Public ng Notice 2014		
Applica	ant:	USRE Holdings, LLC		
Application:		Conditional Use Review of a Planned Area Development (PAD) and Mixed Use (MXD) Site Plan Review		
Property: Columbus Center (1 Alhambra Plaza and 100 Alhambra Circle)		mbra Plaza and 100		
Public Hearing - Date/Time/		Planning and Zoning Board/ Local Planning Agency, June 11, 2014, 6:00 – 9:00 p.m., City Commission Chambers, City Hall,		
Location: 405 Biltmore Way, Coral Gables, Florida, 33134			ables, Florida, 33134	

**PUBLIC NOTICE** is hereby given that the City of Coral Gables, Florida, Planning and Zoning Board (PZB)/Local Planning Agency (LPA) will conduct a Public Hearing on June 11, 2014 on the following applications at the Coral Gables City Commission Chambers, City Hall, 405 Biltmore Way, Coral Gables, Florida:

- 1. An Ordinance of the City Commission of Coral Gables, Florida requesting review of a Planned Area Development (PAD) pursuant to Zoning Code Article 3, "Development Review", Division 5, "Planned Area Development (PAD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for severability, repealer, codification and an effective date. (Legal description on file at the City)
- 2. A Resolution of the City Commission of Coral Gables, Florida requesting mixed use site plan review pursuant to Zoning Code Article 4, "Zoning Districts", Division 2, "Overlay and Special Purpose Districts", Section 4-201, "Mixed Use District (MXD)", for the construction of the second phase of the existing commercial project referred to as the "Columbus Center" on the property legally described as Lots 3-40 and portions of alleyway, Block 22, Section L (100 Alhambra Circle and 1 Alhambra Plaza), Coral Gables, Florida; including required conditions; providing for an effective date. (Legal description on file at the City)

All interested parties are invited to attend and participate. Upon recommendation by the Board, the application will be scheduled for City Commission consideration. Please visit the City webpage at <u>www.coralgables.com</u> to view information concerning the application. The complete application is on file and available for examination during business hours at the Planning Division, 427 Biltmore Way, Suite 201, Coral Gables, Florida, 33134. Questions and written comments regarding the application can be directed to the Planning Division at planning@coralgables.com, FAX: 305.460.5327 or 305.460.5211. Please forward to other interested parties.

Sincerely,

City of Coral Gables, Florida